



# AU-004



## Indoor Network Horn Speaker

Clear Sound • Recessed Mount • ONVIF • PoE • Pre-recorded Messages • Schedule Trigger

### Technical Specifications

#### Product Information

Model	AU-004
Rated Impedance	8 ohm
Average Min. Power	15 W
Frequency Ranges	500-2KHZ +/-10dB 400-12KHZ +/-20dB
Max. SPL 1W / 1M	96 dB
Microphone	50Hz-20kHz at 1Pa, 50cm distance, SPL 115dB at 1kHz

#### Network

SIP Support	RFC 3261
Interface	WAN: RJ-45x1, 10/100Mbps Fast Ethernet port
Supported Protocols	SIP, ONVIF, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Audio Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall

#### VSS Integration

Two-way Communication	Supported
Automatic Trigger Audio Clips	Supported

#### General

Casing	Metal
Power	PoE or 12-24V
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Dimensions	200 x 90 mm
Weight	1 kg
Certifications	CE, FCC, VCCI, BSMI