


CC8370-HV Fisheye Network Camera USER'S Manual

3MP • WDR Pro • 3DNR • 180° Panoramic Vlew • IK10 • IP66 • SNV



Rev. 1.0

Table of Contents

| Revision History 3 Read Before Use 4 Package Contents 4 Symbols and Statements in this Document. 4 Physical Description 5 Repeater Model (IBS367-R/RT) Cascade Connections 7 Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using Web Browsers 22 Using 3CPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > Homepage layout 38 System > Parameters 43 System > Parameters 43 System > Parameters 43 System > Parameters 44 Media > Video 61 Media > Video 62 Media > Video 63 Metria > Accessitings 69 | Overview | 3 |
|--|--|-----|
| Package Contents 4 Symbols and Statements in this Document. 4 Physical Description 5 Repeater Model (IB3367-R/RT) Cascade Connections 7 Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using QFP-compatible Mobile Devices 22 Using 3GPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Logs 41 Media > Image 44 Media > Image 48 Media > Logs 69 Network > Streaming protocols 77 Network > Streaming protocols 77 </td <td>Revision History</td> <td>3</td> | Revision History | 3 |
| Symbols and Statements in this Document. 4 Physical Description 5 Repeater Model (IB8367-R/RT) Cascade Connections 7 Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using RTSP Players 22 Using RTSP Players 22 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 System > General settings 36 System > Logs 36 System > Logs 36 System > Logs 41 System > Naintenance 44 Media > Image 48 Media > Udeo 61 Media > Video 62 Media > Video 68 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Streaming protocols | Read Before Use | 4 |
| Physical Description 5 Repeater Model (IBB367-R/RT) Cascade Connections 7 Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 22 Using GPP-compatible Mobile Devices 23 Using VVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > Ceneral settings 36 System > Logs 36 System > Logs 31 System > Logs 41 Media > Image 43 Media > Video 61 Media > Video 62 Media > Video 62 Media > Video 63 Network > Shreaming protocols 77 Network > Shreaming protocols <t< td=""><td>Package Contents</td><td>4</td></t<> | Package Contents | 4 |
| Repeater Model (IB8367-R/RT) Cascade Connections 7 Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using XTSP Players 22 Using XTSP Players 22 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Logs 41 System > Logs 41 System > Parameters 43 System > Maintenance 44 Media > Video 68 Metwick > Streaming protocols 77 Network > Streaming protocols 77 <td< td=""><td>•</td><td></td></td<> | • | |
| Hardware Installation 9 Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Foccus 18 Accessing the Network Camera 19 Using Web Browsers 22 Using GTSP Players 22 Using GTSP Players 22 Using GTSP Players 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Logs 41 System > Naintenance 44 Media > Image 48 Media > Video 61 Media > Video 62 Media > Video 62 Media > Video 63 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Streaming protocols 87 PT2 > PT2 settings 100 Event > Vent settings 65 OPT2 > | Physical Description | 5 |
| Network Deployment 13 Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using GTSP Players 22 Using 3GPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Homepage layout 38 System > Parameters 43 System > Maintenance 44 Media > Udeo 61 Media > Video 62 Media > Video 63 Network > General settings 69 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Seneral settings 69 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Streaming protocols 77 Network | Repeater Model (IB8367-R/RT) Cascade Connections | 7 |
| Software Installation 16 Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using STSP Players 22 Using 3GPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Homepage layout 38 System > Maintenance 41 Media > Inage 43 Media > Video 61 Media > Video 61 Media > Video 61 Media > Audio 68 Network > Sther Picker K Transfer Protocol over SSL) 88 Security > User accounts 87 Security > Vacess List 95 PTZ > PTZ settings 104 Applications > Motion detection 118 Applications > Motion detection 122 Applications > Audio detection 122 Ap | Hardware Installation | 9 |
| Ready to Use 17 Auto Focus 18 Accessing the Network Camera 19 Using Web Browsers 19 Using RTSP Players 22 Using 3GPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Homepage layout 38 System > Parameters 41 Media > Image 48 Media > Video 61 Media > Video 61 Media > Video 62 Media > Video 61 Media > Video 61 Media > System / SIMP (Simple Network Management Protocol) 86 Security > User accounts 87 Security > Marcess List 95 PTZ > PTZ settings 100 Event settings 104 Applications > Molio detection 118 Applications > Molio detection 122 Applications > VAIO PC | Network Deployment | 13 |
| Auto Focus18Accessing the Network Camera19Using Web Browsers19Using RTSP Players22Using 3GP-compatible Mobile Devices23Using VIVOTEK Recording Software24Main Page25Client Settings30Configuration35System > Homepage layout38System > Homepage layout38System > Logs41System > Naintenance44Media > Image43Media > Image61Media > Video61Media > Video62Media > Video62Media > Video62Media > Video62Media > Video62Media > Audio.68Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > Loses List95PTZ > PTZ settings100Event settings.100Event settings100Event settings104Applications > OL and DO121Applications > VAIDP (VIVOTEK Application Development Platform)123Applications > Nation detection123Applications > Nation detection123Applications > Nation detection123Applications > Nation detection123Applications > Nation Settings127 | Software Installation | |
| Accessing the Network Camera 19 Using Web Browsers 19 Using RTSP Players 22 Using 3GPP-compatible Mobile Devices 23 Using VIVOTEK Recording Software 24 Main Page 25 Client Settings 30 Configuration 35 System > General settings 36 System > Homepage layout 38 System > Homepage layout 38 System > Parameters 41 System > Maintenance 44 Media > Video 61 Media > Video 61 Media > Video 62 Media > Video 64 Media > Video 64 Media > Video 64 Media > Video 64 Media > Nueo 62 Media > Nueo 62 Media > Nueo 64 Media > Video 64 Media > Nueo 64 Media > Nueo 68 Network > Streaming protocols 77 Network > Streaming protocols 77 Network > Streaming protocol | Ready to Use | 17 |
| Using Web Browsers19Using RTSP Players.22Using 3GPP-compatible Mobile Devices23Using VIVOTEK Recording Software24Main Page.25Client Settings30Configuration35System > General settings36System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video61Media > Audio68Network > General settings69Network > Streaming protocols77Network > Streaming protocols77Network > SIMP (Simple Network Management Protocol)86Security > HTTPS (Hypertext Transfer Protocol over SSL)85Security > Access List95PTZ > PTZ settings100Event settings100Event settings104Applications > D1 and DO21Applications > Audio detection122Applications > Audio detection123Applications > NADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Auto Focus | 18 |
| Using RTSP Players22Using 3GPP-compatible Mobile Devices23Using VIVOTEK Recording Software24Main Page25Client Settings30Configuration35System > General settings36System > Logs41System > Logs41System > Parameters43System > Maintenance44Media > Video61Media > Video62Media > Video68Network > General settings69Network > Straming protocols77Network > SINP (Simple Network Management Protocol)86Security > HTTPS (Hypertext Transfer Protocol over SSL)87Security > Access List95PTZ > PTZ settings100Event settings104Applications > Motion detection122Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Accessing the Network Camera | |
| Using 3GPP-compatible Mobile Devices.23Using VIVOTEK Recording Software24Main Page25Client Settings30Configuration35System > Homepage layout38System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Video68Network > General settings69Network > Streaming protocols77Network > Streaming protocols77Network > Streaming protocols77Network > Streaming protocols87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event settings100Event settings104Applications > Motion detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Using Web Browsers | 19 |
| Using VIVOTEK Recording Software24Main Page25Client Settings30Configuration35System > General settings36System > Homepage layout38System > Parameters41System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Video62Metwork > General settings69Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Motion detection118Applications > Land DO121Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Using RTSP Players | 22 |
| Main Page25Client Settings30Configuration35System > General settings36System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Audio68Network > General settings69Network > Streaming protocols77Network > Streaming protocols77Network > Streaming protocols77Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings100Applications > Motion detection118Applications > Liand DO121Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Using 3GPP-compatible Mobile Devices | 23 |
| Client Settings30Configuration35System > General settings36System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Lions > Motion detection118Applications > DI and DO121Applications > Audio detection122Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Using VIVOTEK Recording Software | 24 |
| Configuration35System > General settings36System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Video62Media > Video68Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Notion detection118Applications > Ind DO121Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Main Page | |
| System > General settings36System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Video68Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Ettings104Applications > DI and DO121Applications > Natio detection122Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Client Settings | |
| System > Homepage layout38System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Motion detection118Applications > I and DO121Applications > Audio detection122Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Configuration | |
| System > Logs41System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > Streaming protocols77Network > SIMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | System > General settings | 36 |
| System > Parameters43System > Maintenance44Media > Image48Media > Video61Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > SIMP (Simple Network Management Protocol)86Security > User accounts87Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Notion detection118Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | System > Homepage layout | |
| System > Maintenance.44Media > Image48Media > Video61Media > Video62Media > Audio.68Network > General settings.69Network > Streaming protocols77Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings.104Applications > Motion detection118Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | System > Logs | 41 |
| Media > Image48Media > Video61Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | System > Parameters | 43 |
| Media > Video61Media > Video62Media > Audio68Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings.104Applications > Motion detection118Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | System > Maintenance | 44 |
| Media > Video | Media > Image | 48 |
| Media > Audio68Network > General settings.69Network > Streaming protocols.77Network > SNMP (Simple Network Management Protocol).86Security > User accounts.87Security > HTTPS (Hypertext Transfer Protocol over SSL).88Security > Access List.95PTZ > PTZ settings.100Event > Event settings104Applications > Motion detection118Applications > DI and DO.121Applications > Tampering detection.123Applications > VADP (VIVOTEK Application Development Platform).125Recording > Recording settings.127 | Media > Video | 61 |
| Network > General settings69Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings.104Applications > Motion detection118Applications > DI and DO121Applications > Tampering detection122Applications > NADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Media > Video | 62 |
| Network > Streaming protocols77Network > SNMP (Simple Network Management Protocol)86Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Motion detection118Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Media > Audio | 68 |
| Network > SNMP (Simple Network Management Protocol).86Security > User accounts.87Security > HTTPS (Hypertext Transfer Protocol over SSL).88Security > Access List.95PTZ > PTZ settings.100Event > Event settings.104Applications > Motion detection.118Applications > DI and DO.121Applications > Tampering detection.122Applications > Audio detection.123Applications > VADP (VIVOTEK Application Development Platform).125Recording > Recording settings.127 | Network > General settings | 69 |
| Security > User accounts87Security > HTTPS (Hypertext Transfer Protocol over SSL)88Security > Access List95PTZ > PTZ settings100Event > Event settings104Applications > Motion detection118Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Network > Streaming protocols | 77 |
| Security > HTTPS (Hypertext Transfer Protocol over SSL).88Security > Access List.95PTZ > PTZ settings.100Event > Event settings104Applications > Motion detection118Applications > DI and DO.121Applications > Tampering detection.122Applications > Audio detection.123Applications > VADP (VIVOTEK Application Development Platform).125Recording > Recording settings.127 | Network > SNMP (Simple Network Management Protocol) | 86 |
| Security > Access List.95PTZ > PTZ settings.100Event > Event settings104Applications > Motion detection118Applications > DI and DO.121Applications > Tampering detection.122Applications > Audio detection.123Applications > VADP (VIVOTEK Application Development Platform).125Recording > Recording settings.127 | Security > User accounts | 87 |
| PTZ > PTZ settings100Event > Event settings104Applications > Motion detection118Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Security > HTTPS (Hypertext Transfer Protocol over SSL) | |
| Event > Event settings.104Applications > Motion detection.118Applications > DI and DO121Applications > Tampering detection122Applications > Audio detection123Applications > VADP (VIVOTEK Application Development Platform)125Recording > Recording settings127 | Security > Access List | 95 |
| Applications > Motion detection 118 Applications > DI and DO 121 Applications > Tampering detection 122 Applications > Audio detection 123 Applications > VADP (VIVOTEK Application Development Platform) 125 Recording > Recording settings 127 | PTZ > PTZ settings | |
| Applications > DI and DO 121 Applications > Tampering detection 122 Applications > Audio detection 123 Applications > VADP (VIVOTEK Application Development Platform) 125 Recording > Recording settings 127 | Event > Event settings | 104 |
| Applications > Tampering detection 122 Applications > Audio detection 123 Applications > VADP (VIVOTEK Application Development Platform) 125 Recording > Recording settings 127 | Applications > Motion detection | 118 |
| Applications > Audio detection 123 Applications > VADP (VIVOTEK Application Development Platform) 125 Recording > Recording settings 127 | Applications > DI and DO | 121 |
| Applications > VADP (VIVOTEK Application Development Platform) | Applications > Tampering detection | 122 |
| Recording > Recording settings | Applications > Audio detection | 123 |
| | Applications > VADP (VIVOTEK Application Development Platform) | 125 |
| Local storage > SD card management | Recording > Recording settings | 127 |
| | Local storage > SD card management | 132 |

| Local storage > Content management | |
|-------------------------------------|-----|
| Appendix | |
| URL Commands for the Network Camera | 136 |
| Technical Specifications | |
| Technology License Notice | |
| Electromagnetic Compatibility (EMC) | 230 |

Overview

VIVOTEK's CC8370-HV is a vandal-proof cube network camera offering up to 30 fps at 3-Megapixel resolution. Its compact size makes it an ideal choice for boutique, department and convenience stores. With the unique hang-proof design and inconspicuous appearance, the CC8370-HV is also ideal for schools, police stations and prisons.

The CC8370-HV can view at a wide angle of 180 degrees, providing complete video security with no dead angles. Featuring with WDR Pro, the camera captures both the dark and bright areas of an image and combines the differences to create a highly realistic representation of the original scene, and with SNV technology, it makes high-quality full-color surveillance video possible under low-light conditions. These features enable the camera to provide video quality nearing the capabilities of the human eye. The unique mounting design facilitates easy installation on a wall or desktop in order to capture faces at eye level. A built-in microphone which records sound within a 5 meter radius further increases the level of surveillance.

The CC8370-HV also supports the industry-standard H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. Together with the ST7501 multi-lingual 32-channel recording software, users can simply and quickly set up an easy-to-use IP surveillance system.

Revision History

Rev. 1.0: Initial release.

Read Before Use

The use of surveillance devices may be prohibited by law in your country. The Network Camera is not only a high-performance web-ready camera but can also be part of a flexible surveillance system. It is the user's responsibility to ensure that the operation of such devices is legal before installing this unit for its intended use.

It is important to first verify that all contents received are complete according to the Package Contents listed below. Take note of the warnings in the Quick Installation Guide before the Network Camera is installed; then carefully read and follow the instructions in the Installation chapter to avoid damage due to faulty assembly and installation. This also ensures the product is used properly as intended.

The Network Camera is a network device and its use should be straightforward for those who have basic networking knowledge. It is designed for various applications including video sharing, general security/surveillance, etc. The Configuration chapter suggests ways to best utilize the Network Camera and ensure proper operations. For creative and professional developers, the URL Commands of the Network Camera section serves as a helpful reference to customizing existing homepages or integrating with the current web server.

Package Contents

- CC8370-HV
- Dessicant bag, screw packs
- Waterproof Ethernet cable housing
- Mount bracket for junction box
- Quick Installation Guide & alignment sticker

Symbols and Statements in this Document



INFORMATION: provides important messages or advices that might help prevent inconvenient or problem situations.



NOTE: Notices provide guidance or advices that are related to the functional integrity of the machine.



Tips: Tips are useful information that helps enhance or facilitae an installation, function, or process.




WARNING! or IMPORTANT!: These statements indicate situations that can be dangerous or hazardous to the machine or you.



Electrical Hazard: This statement appears when high voltage electrical hazards might occur to an operator.


Physical Description

Internal View




Hardware Installation


1. Jot down the camera's MAC address for later reference. This is important if you have multiple cameras at different installation sites.




2. Attach the alignment sticker to a preferred location. Drill a cabling hole and the pilot holes for the mounting screws. You can then hammer in the plastic anchors.




3. Open the top cover by loosening the anti-tamper screws.




4. Install a MicroSD card (if local storage is preferred). Replace the desiccant bag to ensure the camera is not damaged by moisture.




- 5. When connecting the LAN cable, use the cable housing to make sure the connections are waterproof.
- 5-1. Pass an Ethernet cable (without the RJ45 connector) through the seal dome, rubber seal, and the cable gland body.
- 5-2. When done, use a crimping clamp to connect the wires to an RJ45 connector.




5-3. Route the cable through the cabling hole. Connect the Ethernet connector. Install the waterproof housing with a seal ring. Tighten up the connector.



6. Secure the camera to wall using the included screws.







7. Install the top cover by fastening the anti-tamper screws.

- Optional configuration

You can also mount the camera to a 1-7/8" single gang box. Secure a mounting plate to the gang box using the included pan head screws, and then install the camera to the mounting plate as shown below.




You can loosen the retention screws on the sides of lens module to tilt the shooting angle if the need should arise.



8. Install the "Installation Wizard 2" software utility that can be found on VIVOTEK's website.




- 9. The program will search for VIVOTEK Video Receivers, Video Servers or Network Cameras on the same LAN.
- 10. Double-click on the camera's MAC address to open a browser management session with the camera.
- 11. With a live view is displayed on your laptop, check the live view to ensure the image is in focus.



LED Definitions

| | ltem | LED status | Description |
|-------------|------|--|---|
| LED | 1 | Steady Red | Powered and system booting, or network failed |
| D | | Red LED off | Power off |
| fir | | Green LED off | Network is disconnected |
| Definitions | 2 | Steady Red and Green LED blinks every 1 sec. | Connected to network |
| ้ร | 3 | Green LED blinks every 1 sec. and RED LED blinks consecutively every 0.15 sec. | Upgrading firmware |
| | 4 | Green and RED blink every 0.15 sec, Green and RED light on, then blink again. | Restoring defaults |
| | 5 | RED LED is on, Green LED blinks and RED LED is constantly on. | Status after a reset (network connected) |
| | | Green and RED LEDs are constantly on. | Status after a reset (network disconnected) |

Hardware Reset



Reset Button

The reset button is used to reset the system or restore the factory default settings. Sometimes resetting the system can return the camera to normal operation. If the system problems remain after reset, restore the factory settings and install again.

<u>Reset</u>: Press the recessed reset button. Wait for the Network Camera to reboot.

<u>Restore</u>: Press and hold the reset button until the status LED rapidly blinks. Note that all settings will be restored to factory default. Upon successful restore, the status LED will blink green and red during normal operation.

SD/SDHC/SDXC Card Capacity


This network camera is compliant with **SD/SDHC 16GB / 8GB / 32GB / 64GB** and other preceding standard SD cards.

Network Deployment

General Connection (PoE)


When using a PoE-enabled switch

The Network Camera is PoE-compliant, allowing transmission of power and data via a single Ethernet cable. Follow the below illustration to connect the Network Camera to a PoE-enabled switch via Ethernet cable.



When using a non-PoE switch

Use a PoE power injector (optional) to connect between the Network Camera and a non-PoE switch.



DOTE:


1. The camera is only to be connected to PoE networks without routing to outside plants.

2. For PoE connection, use only UL listed I.T.E. with PoE output.

Internet connection via a router

Before setting up the Network Camera over the Internet, make sure you have a router and follow the steps below.

 Connect your Network Camera behind a router, the Internet environment is illustrated below. Regarding how to obtain your IP address, please refer to Software Installation on page 16 for details.



- 2. In this case, if the Local Area Network (LAN) IP address of your Network Camera is 192.168.0.3, please forward the following ports for the Network Camera on the router.
 - HTTP port: default is 80
 - RTSP port: default is 554
 - RTP port for video: default is 5556
 - RTCP port for video: default is 5557

If you have changed the port numbers on the Network page, please open the ports accordingly on your router. For information on how to forward ports on the router, please refer to your router's user's manual.

3. Find out the public IP address of your router provided by your ISP (Internet Service Provider). Use the public IP and the secondary HTTP port to access the Network Camera from the Internet. Please refer to Network Type on page 70 for details.

Internet connection with static IP

Choose this connection type if you are required to use a static IP for the Network Camera. Please refer to LAN setting on page 69 for details.

Internet connection via PPPoE (Point-to-Point over Ethernet)

Choose this connection type if you are connected to the Internet via a DSL Line. Please refer to PPPoE on page 70 for details.

Configure the router, virtual server or firewall, so that the router can forward any data coming into a preconfigured port number to a network camera on the private network, and allow data from the camera to be transmitted to the outside of the network over the same path.

| From | Forward to |
|---------------------|-----------------|
| 122.146.57.120:8000 | 192.168.2.10:80 |
| 122.146.57.120:8001 | 192.168.2.11:80 |
| | |

When properly configured, you can access a camera behind the router using the HTTP request such as follows: http://122.146.57.120:8000

If you change the port numbers on the Network configuration page, please open the ports accordingly on your router. For example, you can open a management session with your router to configure access through the router to the camera within your local network. Please consult your network administrator for router configuration if you have troubles with the configuration.

For more information with network configuration options (such as that of streaming ports), please refer to Configuration > Network Settings. VIVOTEK also provides the automatic port forwarding feature as an NAT traversal function with the precondition that your router must support the UPnP port forwarding feature.

| | Network > General settings |
|---------------------|--|
| System | Network type Port |
| Media | * LAN |
| Network | Get IP address automatically |
| General settings | Use fixed P address. |
| Streaming protocols | Enable UPnP presentation |
| DOMS | P Enable UPhP port forwarding |
| QoS | O PPPoE |
| SNMP | Enable Pv6 |
| Security | The device is configuring now. Your browser will reconnect IPv6 informy to http://192.168.4.140.80/ |
| PTZ | Manually If the connection fails, please manually enter the above P address in your browser. |
| Event | Save |

Software Installation

Installation Wizard 2 (IW2), a software included in the product CD, helps you set up your Network Camera on the LAN.


1. Install IW2 under the Software Utility directory from the software CD. Double-click the IW2 shortcut on your desktop to launch the program.



2. The program will conduct an analysis of your network environment. After your network environment is analyzed, please click **Next** to continue the program.

| 🗣 Installation Winnel 2 - Referrit Environment Analysis 🛛 🔀 | 🖷 Inshilletina Winnel I - Retweek Type 🛛 🛞 |
|--|---|
| Installation Wizard 2 | Installation Wizard 2 |
| The wizard is analyzing your network environment. Please walt a moment. | Your network environment was analyzed as below. Private DHCP |
| | Cable/DSL modem Router |
| Ett | Est |

- 3. The program will search for all VIVOTEK network devices on the same LAN.
- 4. After a brief search, the installer window will prompt. Click on the MAC and model name that matches the one printed on the product label. You can then double-click on the address to open a management session with the Network Camera.



Ready to Use

- 1. A browser session with the Network Camera should prompt as shown below.
- 2. You should be able to see live video from your camera. You may also install the 32-channel recording software from the software CD in a deployment consisting of multiple cameras. For its installation details, please refer to its related documents.





- 1. If you forget the root (administrator) password for the camera, you can restore the camera defaults by pressing the reset button for longer than 5 seconds.
- 2. If DHCP is enabled in your network, and the camera cannot be accessed, run the IW2 utility to search the network. If the camera has been configured with fixed IP that does not comply with your local network, you may see its default IP 169.254.x.x. If you still cannot find the camera, you can restore the camera to its factory defaults.
- 3. If you change your network parameters, e.g., added a connection to a LAN card, re-start the IW2 utility.

Accessing the Network Camera


This chapter explains how to access the Network Camera through web browsers, RTSP players, 3GPP-compatible mobile devices, and VIVOTEK recording software.

Using Web Browsers

Use Installation Wizard 2 (IW2) to access the Network Cameras on LAN.


If your network environment is not a LAN, follow these steps to access the Network Camera:

- 1. Launch your web browser (e.g., Microsoft[®] Internet Explorer or Mozilla Firefox).
- 2. Enter the IP address of the Network Camera in the address field. Press Enter.
- 3. Live video will be displayed in your web browser.
- 4. If it is the first time installing the VIVOTEK network camera, an information bar will prompt as shown below. Follow the instructions to install the required plug-in on your computer.




NOTE:

► For Mozilla Firefox or Chrome users, your browser will use Quick Time to stream the live video. If you don't have Quick Time on your computer, please download it first, then launch the web browser.



- By default, the Network Camera is not password-protected. To prevent unauthorized access, it is highly recommended to set a password for the Network Camera. For more information about how to enable password protection, please refer to Security on page 87.
- If you see a dialog box indicating that your security settings prohibit running ActiveX[®] Controls, please enable the ActiveX[®] Controls for your browser.
- 1. Choose Tools > Internet Options > Security > Custom Level.



2. Look for Download signed ActiveX[®] controls; select Enable or Prompt. Click **OK**.

| Security Settings | ? 🗙 |
|--|----------|
| Settings: | |
| ActiveX controls and plug-ins Download signed ActiveX controls Disable Enable Prompt | |
| | ife N |
| Reset custom settings | |
| | |
| | |

3. Refresh your web browser, then install the ActiveX[®] control. Follow the instructions to complete installation.


- Currently the Network Camera utilizes 32-bit ActiveX plugin. You CAN NOT open a management/view session with the camera using a 64-bit IE browser.
- If you encounter this problem, try execute the lexplore.exe program from C:\Windows\ SysWOW64. A 32-bit version of IE browser will be installed.
- On Windows 7, the 32-bit explorer browser can be accessed from here: C:\Program Files (x86)\Internet Explorer\iexplore.exe
- If you open a web session from the IW2 utility, a 32-bit IE browser will be opened.




- 1. The onscreen Java control can malfunction under the following situations: A PC connects to different cameras that are using the same IP address (or the same camera running different firmware versions). Removing your browser cookies will solve this problem.
- 2. If you encounter problems with displaying the configuration menus or UI items, try disable the Compatibility View on IE8 or IE9.



You may also press the F12 key to open the developer tools utility, and then change the Browser Mode to the genuine IE8 or IE9 mode.



In the event of plug-in compatibility issues, you may try to uninstall the plug-in that was
previously installed.



Using RTSP Players

To view the streaming media using RTSP players, you can use one of the following players that support RTSP streaming.



Quick Time Player

VLC media player

- 1. Launch the RTSP player.
- 2. Choose File > Open URL. A URL dialog box will pop up.
- 3. The address format is rtsp://<ip address>:<rtsp port>/<RTSP streaming access name for stream1 or stream2>

As most ISPs and players only allow RTSP streaming through port number 554, please set the RTSP port to 554. For more information, please refer to RTSP Streaming on page 78. For example:

| Open URL | | | |
|--------------------------|-----------|----|--------|
| Enter an Internet URL to | o open: | | |
| rtsp://192.168.5.151 | /live.sdp | | ~ |
| | | ОК | Cancel |

4. The live video will be displayed in your player.

For more information on how to configure the RTSP access name, please refer to RTSP Streaming on page 78 for details.



Using 3GPP-compatible Mobile Devices

To view the streaming media through 3GPP-compatible mobile devices, make sure the Network Camera can be accessed over the Internet. For more information on how to set up the Network Camera over the Internet, please refer to Setup the Network Camera over the Internet on page 13.

To utilize this feature, please check the following settings on your Network Camera:

- 1. Because most players on 3GPP mobile phones do not support RTSP authentication, make sure the authentication mode of RTSP streaming is set to disable. For more information, please refer to RTSP Streaming on page 78.
- 2. As the the bandwidth on 3G networks is limited, you will not be able to use a large video size. Please set the video streaming parameters as listed below.

For more information, please refer to Stream settings on page 61.

| Video Mode | H.264 |
|-----------------------------------|-----------|
| Frame size | 176 x 144 |
| Maximum frame rate | 5 fps |
| Intra frame period | 1S |
| Video quality (Constant bit rate) | 40kbps |

- 3. As most ISPs and players only allow RTSP streaming through port number 554, please set the RTSP port to 554. For more information, please refer to RTSP Streaming on page 78.
- 4. Launch the player on the 3GPP-compatible mobile devices (e.g., Quick Time).
- 5. Type the following URL commands into the player. The address format is rtsp://<public ip address of your camera>:<rtsp port>/<RTSP streaming access name for stream # with small frame size and frame rate>. For example:

| Open URL | | × |
|------------------------------------|----|--------|
| Enter an Internet URL to open: | | |
| rtsp://192.168.4.147:554/live2jsdp | | • |
| | ОК | Cancel |

You can configure Stream #2 into the suggested stream settings as listed above for live viewing on a mobile device.

Using VIVOTEK Recording Software

The product software CD also contains an ST7501 recording software, allowing simultaneous monitoring and video recording for multiple Network Cameras. Please install the recording software; then launch the program to add the Network Camera to the Channel list. For detailed information about how to use the recording software, please refer to the user's manual of the software or download it from http://www.vivotek.com.



Main Page

This chapter explains the layout of the main page. It is composed of the following sections: VIVOTEK INC. Logo, Host Name, Camera Control Area, Configuration Area, Menu, and Live Video Window.



VIVOTEK INC. Logo

Click this logo to visit the VIVOTEK website.

Host Name

The host name can be customized to fit your needs. The name can be changed especially there are many cameras in your surveillance deployment. For more information, please refer to System on page 36.

Camera Control Area

<u>Video Stream</u>: This Network Camera supports multiple streams (streams 1 and 2) simultaneously. You can select any of them for live viewing. For more information about multiple streams, please refer to page 61 for detailed information.

<u>Manual Trigger</u>: Click to enable/disable an event trigger manually. Please configure an event setting on the Application page before you enable this function. A total of 3 event configuration can be configured. For more information about event setting, please refer to page 103. If you want to hide this item on the homepage, please go to **Configuration> System > Homepage Layout > General settings > Customized button** to deselect the "show manual trigger button" checkbox.

Configuration Area

<u>Client Settings</u>: Click this button to access the client setting page. For more information, please refer to Client Settings on page 30.

<u>Configuration</u>: Click this button to access the configuration page of the Network Camera. It is suggested that a password be applied to the Network Camera so that only the administrator can configure the Network Camera. For more information, please refer to Configuration on page 35.

Language: Click this button to choose a language for the user interface. Language options are available in: English, Deutsch, Español, Français, Italiano, 日本語, Português, 簡体中文, and 繁體中文. Please note that you can also change a language on the Configuration page; please refer to page 35.

Hide Button

You can click the hide button to hide or display the control panel.

Resize Buttons

E Auto E 100% E 50% E 25% .

Click the Auto button, the video cell will resize automatically to fit the monitor. Click 100% is to display the original homepage size. Click 50% is to resize the homepage to 50% of its original size. Click 25% is to resize the homepage to 25% of its original size.

Live Video Window

The following window is displayed when the video mode is set to H.264: H.264 Protocol and Media Options



<u>Video Title</u>: The video title can be configured. For more information, please refer to Video Settings on page 48.


<u>H.264 Protocol and Media Options</u>: The transmission protocol and media options for H.264 video streaming. For further configuration, please refer to Client Settings on page 30.

<u>Time</u>: Display the current time. For further configuration, please refer to Media > Image > Genral settings on page 48.

<u>Title and Time</u>: The video title and time can be stamped on the streaming video. For further configuration, please refer to Media > Image > General settings on page 53.

<u>PTZ Panel</u>: This Network Camera supports "digital" (e-PTZ) pan/tilt/zoom control, which allows roaming a smaller view frame within a large view frame. Please refer to PTZ settiings on page 100 for detailed information.

<u>Global View</u>: Click on this item to display the Global View window. The Global View window contains a full view image (the largest frame size of the captured video) and a floating frame (the viewing region of the current video stream). The floating frame allows users to control the e-PTZ function (Electronic Pan/ Tilt/Zoom). For more information about e-PTZ operation, please refer to E-PTZ Operation on page 100. For more information about to set up the viewing region of the current video stream, please refer to page 100.




Note that the PTZ buttons on the panel are not operational unless you are showing only a portion of the full image. If the live view window is displaying the full view, the PTZ buttons are not functional.

<u>Video Control Buttons</u>: Depending on the Network Camera model and Network Camera configuration, some buttons may not be available.

Snapshot: Click this button to capture and save still images. The captured images will be displayed in a pop-up window. Right-click the image and choose **Save Picture As** to save it in JPEG (*.jpg) or BMP (*.bmp) format.

Digital Zoom: Click and uncheck "Disable digital zoom" to enable the zoom operation. The navigation screen indicates the part of the image being magnified. To control the zoom level, drag the slider bar. To move to a different area you want to magnify, drag the navigation screen.



Pause: Pause the transmission of the streaming media. The button becomes the Resume button after clicking the Pause button.

Stop: Stop the transmission of the streaming media. Click the Resume button to continue transmission.

Start MP4 Recording: Click this button to record video clips in MP4 file format to your computer. Press the Stop MP4 Recording button to end recording. When you exit the web browser, video recording stops accordingly. To specify the storage destination and file name, please refer to MP4 Saving Options on page 31 for details.

Volume: When the Mute function is not activated, move the slider bar to adjust the volume on the local computer.

Mute: Turn off the volume on the local computer. The button becomes the Mudio On button after clicking the Mute button.

We mute: Turn off the Mic volume on the local computer. The button becomes the Mic On button after clicking the Mute button.

E Full Screen: Click this button to switch to full screen mode. Press the "Esc" key to switch back to normal mode.



- 1. For a megapixel camera, it is recommended to use monitors of the 24" size or larger, and are capable of 1600x1200 or better resolutions.
- 2. Below are the defaults for Audio settings:

For cameras that come with built-in microphone: **Not Muted.** For cameras that come without built-in microphone: **Muted.**



■ The following window is displayed when the video mode is set to MJPEG:

<u>Video Title</u>: The video title can be configured. For more information, please refer to Media > Image on page 53.

<u>Time</u>: Display the current time. For more information, please refer to Media > Image on page 53.

<u>Title and Time</u>: Video title and time can be stamped on the streaming video. For more information, please refer to Media > Image on page 53.

<u>Video Control Buttons</u>: Depending on the Network Camera model and Network Camera configuration, some buttons may not be available.

Snapshot: Click this button to capture and save still images. The captured images will be displayed in a pop-up window. Right-click the image and choose **Save Picture As** to save it in JPEG (*.jpg) or BMP (*.bmp) format.

Digital Zoom: Click and uncheck "Disable digital zoom" to enable the zoom operation. The navigation screen indicates the part of the image being magnified. To control the zoom level, drag the slider bar. To move to a different area you want to magnify, drag the navigation screen.

| Disable digital ptz | and the second sec |
|---------------------|--|
| Zoom Factor: | 100% |
| 100% | 400% |

Start MP4 Recording: Click this button to record video clips in MP4 file format to your computer. Press the Stop MP4 Recording button to end recording. When you exit the web browser, video recording stops accordingly. To specify the storage destination and file name, please refer to MP4 Saving Options on page 31 for details.

E Full Screen: Click this button to switch to full screen mode. Press the "Esc" key to switch back to normal mode.

Client Settings

This chapter explains how to select the stream transmission mode and saving options on the local computer. When completed with the settings on this page, click **Save** on the page bottom to enable the settings.

H.264 Media Options

| _ | H.264 media options |
|---|---------------------|
| | Mdeo and audio |
| | O Mdeo only |
| | ○ Audio only |

Select to stream video or audio data or both. This is enabled only when the video mode is set to H.264.

H.264 Protocol Options

| H.264 Protocol Options |
|----------------------------|
| O UDP Unicast |
| O UDP Multicast |
| ⊙ TCP |
| Онттр |
| |

Depending on your network environment, there are four transmission modes of H.264 streaming:

<u>UDP unicast</u>: This protocol allows for more real-time audio and video streams. However, network packets may be lost due to network burst traffic and images may be broken. Activate UDP connection when occasions require time-sensitive responses and the video quality is less important. Note that each unicast client connecting to the server takes up additional bandwidth and the Network Camera allows up to ten simultaneous accesses.

<u>UDP multicast</u>: This protocol allows multicast-enabled routers to forward network packets to all clients requesting streaming media. This helps to reduce the network transmission load of the Network Camera while serving multiple clients at the same time. Note that to utilize this feature, the Network Camera must be configured to enable multicast streaming at the same time. For more information, please refer to RTSP Streaming on page 78.

<u>TCP</u>: This protocol guarantees the complete delivery of streaming data and thus provides better video quality. The downside of this protocol is that its real-time effect is not as good as that of the UDP protocol.

<u>HTTP</u>: This protocol allows the same quality as TCP protocol without needing to open specific ports for streaming under some network environments. Users inside a firewall can utilize this protocol to allow streaming data through.

MP4 Saving Options

| MP4 saving opt | ions — | |
|------------------------------------|--------------------------|--------|
| Folder: | C:\Record | Browse |
| File name prefix: | CLIP | |
| ✓ Add date and | time suffix to file name | |

Users can record live video as they are watching it by clicking Start MP4 Recording on the main page. Here, you can specify the storage destination and file name.

<u>Folder</u>: Specify a storage destination on your PC for the recorded video files. The location can be changed.

<u>File name prefix</u>: Enter the text that will be appended to the front of the video file name. A specified folder will be automatically created on your local hard disk.

Add date and time suffix to the file name: Select this option to append the date and time to the end of the file name.



Local Streaming Buffer Time

| Γ | Local | l streaming buffer time | |
|---|-------|-------------------------|--|
| | 0 | Millisecond | |
| | | | |

Save

Due to the unsteady bandwidth flow, the live streaming may lag and not be very smoothly. If you enable this option, the live streaming will be stored temporarily on your PC's cache memory for a few seconds before being played on the live viewing window. This will help you see the streaming more smoothly. If you enter 3,000 Millisecond, the streaming will delay for 3 seconds.

Joystick settings

Enable Joystick

Connect a joystick to a USB port on your management computer. Supported by the plug-in (Microsoft's DirectX), once the plug-in for the web console is loaded, it will automatically detect if there is any joystick on the computer. The joystick should work properly without installing any other driver or software.

Then you can begin to configure the joystick settings of connected devices. Please follow the instructions below to enable joystick settings.

- 1. Select a detected joystick, if there are multiple, from the Selected joystick menu. If your joystick is not detected, if may be defective.
- 2. Click Calibrate or Configure buttons to configure the joystick-related settings.

| Joystick settings | | |
|--------------------------------|-------------------|------|
| Selected joystick: Macally Air | Stick | |
| Calibrate | Configure buttons | |
| | | Save |



- If you want to assign Preset actions to your joystick, the preset locations should be configured in advance in the Configuration > PTZ page.
- If your joystick is not working properly, it may need to be calibrated. Click the Calibrate button
 to open the Game Controllers window located in Microsoft Windows control panel and follow the
 instructions for trouble shooting.
- The joystick will appear in the Game Controllers list in the Windows Control panel. If you want to
 check out for your devices, go to the following page: Start -> Control Panel -> Game Controllers.

| Game Controllers | ? 🗙 |
|---|------------------------|
| These settings help you configure the game co your computer. | ntrollers installed on |
| | Status |
| CH PRODUCTS IP DESKTOP CONTROLLER | OK |
| Add Remove | Properties |
| Advanced | Troubleshoot |
| | |

Buttons Configuration

In the Button Configuration window, the left column shows the actions you can assign, and the right column shows the functional buttons and assigned actions. The number of buttons may differ from different joysticks.

Please follow the steps below to configure your joystick buttons:

1. Choosing one of the actions and click **Assign** will pop up a dialog. Then you can assign this action to a button by pressing the joystick button or select it from the drop-down list. For example: Assign **Home** (move to home position) to Button 1.

| Suttons Configuration | | | | × |
|--|----------------------------------|--|---------|--|
| Assigned Actions | | | | |
| Actions | | Buttons | Assigne | ed Actions |
| Home Zoom In | ^ | Button1 Button2 | | |
| Zoom Out | 🕙 "B | lome" | | |
| Focus Pris Patrol Preset Page Up Page Down Record to AVI Snapshot Auto Naming | sele But But But But | tton1 tton2 tton3 tton5 | | o assign to "Home" or list below. |
| Assign Clear Selected | But But But But | :ton6 :ton7 :ton8 :ton9 :ton10 :ton11 :ton12 | | <u>Q</u> K <u>C</u> ancel <u>Q</u> K <u>C</u> ancel |

2. Click **OK** to confirm the configuration.

| 🧟 Buttons Confi | guration |
|---|--|
| | s |
| Actions | ▼ "Home" |
| Home Zoom In Coom Out Focus Fo | select the button from the list below. Button1 Click "Ok" to assign "" to button1 |
| | <u>Q</u> K <u>C</u> ancel |

Buttons Configuration

Click the **Configure Buttons** button, a window will prompt as shown below. Please follow the steps below to configure your joystick buttons:

1. Select a button number from the Button # pull-down menu.


| / http:// | /192.16 | 8.6.231/setup/configure_b | | |
|---|--------------------|---------------------------|------------------------|--|
| http://192.168.6.231/setup/configure_buttons.html | | | | |
| >Joys | tick | Settings | | |
| Actions | : Togg | e play/pause 💌 | | |
| Button: | 1 ▼ 1 2 3 | Assigned Actions | Assign Delete OK | |
| 1 | 4 | Full Screen | | |
| 2 | 5 6 | Stop | | |
| 3 | 7 | Zoom in | | |
| 4 | 8 9 | 2001111 | | |
| 5 | 10 | Patrol | | |
| 6 | 11 12 | Toggle play/pause | | |
| 7 | | | | |
| 8 | | | | |
| 9 | | | | |
| 10 | | | | |
| 11 | | | | |
| 12 | | Snapshot | | |
| | | | | |
| \mid 🙆 網際紛 | | 保護模式: 關閉 🛛 🖓 🖓 | 👻 🔍 100% 👻 🔬 | |



If you are not sure of the locations of each button, use the **Properties** window in the **Game Controllers** utility.

| | and the state of the second se |
|---|--|
| | Settings Tex |
| 11 x1 These satings half parcool gas the game consider incident or parc range on Incident game constants | Ted for gave contains. The consider is not functioning properly, thing works so relation it is realisated, by the Selfrey page Avec |
| Consten States Missely ArDick OK | KARE /V ARE 1 M. BANNY Page of View Hat |
| Add. Ferrore Prigettes | •••• |
| | OK Canad Canad |

2. Select a corresponding action, such as Patrol or Preset#.



3. Click the **Assign** button to assign an action to the button. You can delete an association by selecting a button number, and then click the **Delete** button.

Repeat the process until you are done with the configuration of all preferred actions.

The buttons you define should appear on the button list accordingly.

 Please remember to click the Save button on the Client settings page to preserver your settings.

Configuration

Click **Configuration** on the main page to enter the camera setting pages. Note that only Administrators can access the configuration page.

VIVOTEK provides an easy-to-use user interface that helps you set up your network camera with minimal effort. In order to simplify the user interface, detailed information will be hidden unless you click on the function item. When you click on the first sub-item, the detailed information for the first sub-item will be displayed; when you click on the second sub-item, the detailed information for the second sub-item will be displayed and that of the first sub-item will be hidden.

The following is the interface of the main page:

| Y VIVOTEK | | | | | | | |
|------------------|---|--|--|--|--|--|--|
| WWW.VIVOTIK.COM | Home Client settings Configuration Language | | | | | | |
| | System > General settings | | | | | | |
| System | SystemNavigation Area | | | | | | |
| General settings | Host name: Mega-Pixel Network Camera | | | | | | |
| Homepage layout | Turn off the LED indicator | | | | | | |
| Parameters | System time | | | | | | |
| Maintenance | Time zone: GMT+08:00 Beijing, Chonqqinq, Honq Konq, Kuala Lumpur, Sinqapore, Taipei 🗨 | | | | | | |
| Media | Note: You can upload your daylight saving time rules on <u>Maintenance</u> page or use the camera default value. | | | | | | |
| Network | Keep current date and time | | | | | | |
| Security | Synchronize with computer time | | | | | | |
| РТΖ | Manual | | | | | | |
| Event | Automatic | | | | | | |
| Applications | Configuration List | | | | | | |
| Recording | | | | | | | |
| Local storage | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Version: 0100a | - Firmware Version | | | | | | |

Each function on the configuration list will be explained in the following sections.

The Navigation Area provides access to all different views from the **Home** page (for live viewing), **Configuration** page, and multi-language selection.

System > General settings

This section explains how to configure the basic settings for the Network Camera, such as the host name and system time. It is composed of the following two columns: System, and System Time. When finished with the settings on this page, click **Save** at the bottom of the page to enable the settings.

System

| System | | |
|--------------|---------------|---------------------------|
| Host name: | | Mega-Pixel Network Camera |
| Turn off the | LED indicator | |

<u>Host name</u>: Enter a desired name for the Network Camera. The text will be displayed at the top of the main page, and also on the view cells of the ST7501 and VAST management software.

<u>Turn off the LED indicators</u>: If you do not want others to notice the network camera is in operation, you can select this option to turn off the LED indicators.

System time

| System time |
|--|
| Time zone: GMT+08:00 Beijing, Chongging, Hong Kong, Kuala Lumpur, Singapore, Taipei 💌 |
| Note: You can upload your daylight saving time rules on <u>Maintenance</u> page or use the camera default value. |
| Keep current date and time |
| Synchronize with computer time |
| lo Manual |
| Automatic |
| Save |

<u>Keep current date and time</u>: Select this option to preserve the current date and time of the Network Camera. The Network Camera's internal real-time clock maintains the date and time even when the power of the system is turned off.

<u>Synchronize with computer time</u>: Select this option to synchronize the date and time of the Network Camera with the local computer. The read-only date and time of the PC is displayed as updated.

<u>Manual</u>: The administrator can enter the date and time manually. Note that the date and time format are [yyyy/mm/dd] and [hh:mm:ss].

<u>Automatic</u>: The Network Time Protocol is a protocol which synchronizes computer clocks by periodically querying an NTP Server.

<u>NTP server</u>: Assign the IP address or domain name of the time-server. Leaving the text box blank connects the Network Camera to the default time servers. The precondition is that the camera must have the access to the Internet.

<u>Update interval</u>: Select to update the time using the NTP server on an hourly, daily, weekly, or monthly basis.

<u>Time zone</u> : Select the appropriate time zone from the list. If you want to upload Daylight Savings Time rules, please refer to **System > Maintenance > Import/ Export files** on page 45 for details.

System > Homepage layout

This section explains how to set up your own customized homepage layout.

General settings

This column shows the settings of your hompage layout. You can manually select the background and font colors in Theme Options (the second tab on this page). The settings will be displayed automatically in this Preview field. The following shows the homepage using the default settings:



Hide Powered by VIVOTEK

■ Hide Powered by VIVOTEK: If you check this item, it will be removed from the homepage.

Logo graph

Here you can change the logo that is placed at the top of your homepage.

| — Logo graph ——— | | |
|---|----------|---|
| A customized logo (Git 160x50 pixels to replac | | ed for main page. It will be resized to |
| | © Custom | Browse Upload |
| Logo link: http://www.viv | otek.com | |

Follow the steps below to upload a new logo:

- 1. Click **Custom** and the Browse field will appear.
- 2. Select a logo from your files.
- 3. Click **Upload** to replace the existing logo with a new one.
- 4. Enter a website link if necessary.
- 5. Click Save to enable the settings.

Customized button

If you want to hide manual trigger buttons on the homepage, please uncheck this item. This item is checked by default.


Show manual trigger button

Theme Options

Here you can change the color of your homepage layout. There are three types of preset patterns for you to choose from. The new layout will simultaneously appear in the **Preview** filed. Click **Save** to enable the settings.



- Follow the steps below to set up the customed homepage:
- 1. Click **Custom** on the left column.
- 2. Click the field where you want to change the color on the right column.



3. The palette window will pop up as shown below.

| Hex: | #000000 | | o 2 | | Hex: | #23538A |
|------------|---------|--|------------|---|-------------|---------|
| Red: | 0 | | | 1 | Red: | 35 |
| Green: | 0 | | | Ÿ | Green: | 83 |
| Blue: | 0 | | | | Blue: | 138 |
| Hue: | 0 | | | | Hue: | 212 |
| Saturation | : 0 | | | | Saturation: | 74.6 |
| Value: | 0 | | | | Value: | 54.1 |
| S | elect | | | | 4 Se | lect |

- 4. Drag the slider bar and click on the left square to select a desired color.
- 5. The selected color will be displayed in the corresponding fields and in the **Preview** column.
- 6. Click Save to enable the settings.

System > Logs

This section explains how to configure the Network Camera to send the system log to a remote server as backup.

| Log server settings | | |
|---------------------|-----|--|
| Enable remote log | | |
| IP address: | | |
| port: | 514 | |

Follow the steps below to set up the remote log:

- 1. Select Enable remote log.
- 2. In the IP address text box, enter the IP address of the remote server.
- 2. In the port text box, enter the port number of the remote server.
- 3. When completed, click **Save** to enable the setting.

You can configure the Network Camera to send the system log file to a remote server as a log backup. Before utilizing this feature, it is suggested that the user install a log-recording tool to receive system log messages from the Network Camera. An example is Kiwi Syslog Daemon. Visit http://www.kiwisyslog. com/kiwi-syslog-daemon-overview/.


| 2/85.57 | Spring Indu Uses Into | 110710-0-01 | contract 2.5.8 vertical |
|-------------|---|--|---|
| | Cominte . | many dama & town | |
| 100.00 | | 282,168.4.193 | \$115P SERVERS Show and services, IP-802,158-A.100 |
| 1.000 (61) | Unstitute | 1521064.103 | Appl sectory approximated 2 (proce |
| 7.66.13 | Lion July | 192,168.4,101 | PUTCP SERVICING Total and annuals, IP-132, 2014, 4101 |
| 2.66.12 | Georgiant. | 192108-4.103 | BTUP SERVICE: and another services, and the state of the SNLSP area. Received file (newhork/second stated "M |
| 7.68.12 | Kire-John | 152,165.4.103 | (H11P 32/R/R) 306.5Percer and after decount planet at low C'M |
| 7.06.12 | Unativity | 112168-41101 | (FTEP \$109478) Stop and increase, #1-052,108.4.107 |
| 7.08.12 | Con Jide | 102108-4-108 | DUDP REPORT from more account, IP-552, 100-4, 101 |
| 248.18 | Los Aylan | 192,168 4,103 | EXPERIENCE Pression and |
| 7.05 188 | Date Makes | 1921984100 | (Other Survival) Studieg Other survival |
| 7.65.87 | Double | 1521684.105 | [contributes] Reads to work hered |
| 200.00 | Common Period | 102108-4100 | ufferget des 192 102 8 85 193 108 8 20 |
| 7.01.06 | Carpon Ballet | 182168.4.182 | allingst mater 182 838 8 1 |
| 7.00.05 | Come Select | 1021084-101 | adhape # \$12,166.4.181 mitmak.255.256.258.8 |
| 200.00 | How Maning | 1121084-102 | (VCAT MUR) the process of room 21 is object because of law princip 8 |
| 10.01 | Darmon Maters | 1021084-003 | where were 10, 10, 41 |
| 746.08 | Corner Maleri | 1121108 4 101 | adhrige: 17 510 145 4 151 antennik 155 156 15 8 |
| 7.00.00 | Darmon Ballin | 112168-6-107 | sdage decody |
| 22222222222 | 株17 株17 株17 株18 株17 株18 株17 株18 株18 株13 株18 株17 株17 株17 株17 株17 株17 株17 株17 株17 株17 | 2012 Unit Jam 2012 Unit Jale 2012 Unit Jale 2012 Unit Jale 2012 Unit Jale 2018 Unit Jale 2018 Unit Jale 2018 Unit Jale 2018 Unit Jale 2018 Unit Jale 2018 Committee 2019 Committee 2019 Unit Jale 2019 Committee 2019 Unit Jale 2019 Committee 2019 Co | 201.7 Long Jung 512, 104, 102 201.7 Long Jung 102, 104, 102 201.8 Long Jung 102, 104, 102 |

System log

| System log Access log |
|--|
| Jan 5 11:36:07 syslogd 1.5.0: restart. |
| Jan 5 11:36:08 [swatchdog]: Ready to watch httpd. |
| Jan 5 11:36:09 [EVENT MGR]: Starting eventmgr with support for EcTun |
| Jan 5 11:36:11 [DRM Service]: Starting DRM service. |
| Jan 5 11:36:20 [UPnPIGDCP]: Search IGD failed |
| Jan 5 11:36:23 automount[718]: >> mount: mounting /dev/mmcblk0p1 on /mnt/auto/CF failed: No such |
| device or address |
| Jan 5 11:36:23 automount[718]: mount(generic): failed to mount /dev/mmcblk0p1 (type vfat) |
| on /mnt/auto/CF |
| Jan 5 11:36:23 [IR Cut Control]: Day mode |
| Jan 5 11:36:23 automount[728]: >> mount: mounting /dev/mmcblk0p1 on /mnt/auto/CF failed: No such |
| device or address |
| Jan 5 11:36:23 automount[728]: mount/generic): failed to mount /dev/mmcblk0p1 (type vfat) |
| on /mnt/auto/CF |
| Jan 5 11:36:23 [IR Cut Control]: Day mode |
| Jan 5 11:36:23 [SYS]: Serial number = 0002D10ED4C9 |
| Jan 5 11:36:23 [SYS]: System starts at Wed Jan 5 11:36:23 UTC 2011 |

This column displays the system log in a chronological order. The system log is stored in the Network Camera's buffer area and will be overwritten when reaching a certain limit.

You can install the included ST7501 recording software, which provides an Event Management function group for delivering event messages via emails, GSM short messages, onscreen event panel, or to trigger an alarm, etc. For more information, refer to the ST7501 User Manual.



Access log

 System log
 Access log

 Jan 5 11:36:28 [RTSP SERVER]: Start one session, IP=172.16.2.52

 Jan 5 11:49:15 [RTSP SERVER]: Start one session, IP=192.168.4.105

 Jan 5 13:11:20 [RTSP SERVER]: Start one session, IP=192.168.4.105

Access log displays the access time and IP address of all viewers (including operators and administrators) in a chronological order. The access log is stored in the Network Camera's buffer area and will be overwritten when reaching a certain limit.

System > Parameters

The View Parameters page lists the entire system's parameters. If you need technical assistance, please provide the information listed on this page.

```
Parameters
system hostname='CC8370-HV'
system ledoff='0'
system lowlight='1'
 system date='2015/06/03'
system time='10:24:11'
system datetime=''
system ntp="'
system timezoneindex='320'
system_daylight_enable='0'
 system daylight dstactualmode='1'
system daylight auto begintime='NONE'
system_daylight_auto_endtime='NONE'
system_daylight_timezones=',-360,-320,-280,-240,-241,-200,-201,-1
system updateinterval='0'
 system info modelname='CC8370-HV'
 system info extendedmodelname='CC8370-HV'
system info serialnumber='0002D1368C16'
system info firmwareversion='CC8370-VVTK-0100i'
system info language count='9'
system info language i0='English'
 system info language i1='Deutsch'
 system info language i2='Español'
 system_info_language_i3='Français'
 system info language i4='Italiano'
system info language i5='日本語'
 system info language i6='Português'
system info language i7='简体中文'
 system info language i8='繁體中文'
```

System > Maintenance

This chapter explains how to restore the Network Camera to factory default, upgrade firmware version, etc.

General settings > Upgrade firmware

| Upgrade firmware | ÷ | | |
|-----------------------|---|--------|---------|
| Select firmware file: | | Browse | Upgrade |

This feature allows you to upgrade the firmware of your Network Camera. It takes a few minutes to complete the process.


Note: Do not power off the Network Camera during the upgrade!

Follow the steps below to upgrade the firmware:

- 1. Download the latest firmware file from the VIVOTEK website. The file is in .pkg file format.
- 2. Click **Browse...** and locate the firmware file.
- 3. Click **Upgrade**. The Network Camera starts to upgrade and will reboot automatically when the upgrade completes.

If the upgrade is successful, you will see "Reboot system now!! This connection will close". After that, reaccess the Network Camera.

The following message is displayed when the upgrade has succeeded.



The following message is displayed when you have selected an incorrect firmware file.

| Starting firmware upgrade Do not power down the server during the upgrade. The server will restart automatically after the upgrade is completed. This will take about 1 - 5 minutes. Wrong PKG file format Unpack fail |
|--|
|--|

General settings > Reboot

| Reboot | | | |
|--------|--|--|--------|
| | | | Reboot |
| | | | |

This feature allows you to reboot the Network Camera, which takes about one minute to complete. When completed, the live video page will be displayed in your browser. The following message will be displayed during the reboot process.

The device is rebooting now. Your browser will reconnect to http://192.168.5.151:80/ If the connection fails, please manually enter the above IP address in your browser.

If the connection fails after rebooting, manually enter the IP address of the Network Camera in the address field to resume the connection.

General settings > Restore

| – Restore – | | |
|---|----------------------------|---------|
| Restore all settings to factory default e | except settings in | |
| 🗌 Network 🔲 Daylight saving tim | e 🗌 Custom language 🗌 VADP | |
| | | Restore |

This feature allows you to restore the Network Camera to factory default settings.

<u>Network</u>: Select this option to retain the Network Type settings (please refer to Network Type on page 70).

<u>Daylight Saving Time</u>: Select this option to retain the Daylight Saving Time settings (please refer to Import/Export files below on this page).

<u>Custom Language</u>: Select this option to retain the Custom Language settings.

VADP: Retain the VADP modules (3rd-party software stored on the SD card) and related settings.

If none of the options is selected, all settings will be restored to factory default. The following message is displayed during the restoring process.

| The device is rebooting now. Your browser will reconnect to http://192.168.5.151:80/ |
|--|
| If the connection fails, please manually enter the above IP address in your browser. |
| |
| |

Import/Export files


This feature allows you to Export / Update daylight saving time rules, custom language file, configuration file, and server status report.

| eneral settings Import/Export files | |
|--|---------------|
| Export files | |
| Export daylight saving time configuration file | Export |
| Export language file | Export |
| Export configuration file | Export |
| Export server status report | Export |
| Upload files | |
| Update daylight saving time rules: | Browse Upload |
| Update custom language file: | Browse Upload |
| Upload configuration file: | Browse Upload |

Export daylight saving time configuration file: Click to set the start and end time of DST (Daylight Saving).

Follow the steps below to export:

- 1. In the Export files column, click **Export** to export the daylight saving time configuration file from the Network Camera.
- 2. A file download dialog will pop up as shown below. Click **Open** to review the XML file or click **Save** to store the file for editing.



3. Open the file with Microsoft[®] Notepad and locate your time zone; set the start and end time of DST. When completed, save the file.

In the example below, DST begins each year at 2:00 a.m. on the second Sunday in March and ends at 2:00 a.m. on the first Sunday in November.

| D e | onfig_dst - Notepad | |
|------|---|------|
| File | Edit Format View Help | |
| | <pre><day></day> <weekinmonth>First</weekinmonth> <dayofweek>Sunday</dayofweek> <hour>2</hour> <finezone 10="-240" name="(GMT-06:00) Central Time (US and Canada)"> </finezone></pre> | |
| | <pre><shift>60</shift></pre> | |
| | <endrime> <shift>=60</shift> <month>11</month> <day></day> <weekinmonth>First</weekinmonth> <dayofweek> sunday <hour></hour></dayofweek></endrime> | |
| < | <rimezone id="-241" name="(GMT-06:00) Mexico City"></rimezone> | |

Update daylight saving time rules: Click Browse... and specify the XML file to update.

If the incorrect date and time are assigned, you will see the following warning message when uploading the file to the Network Camera.

| | 🔲 🛛 🗿 http://197.168.5.121/cgi-bin/admin/upload.cgi - Microsoft Int 🌉 🗆 🔀 |
|--------------------------------------|---|
| <pre>File Edit Format Wew Held</pre> | Invalid «Month» value in TimeZone id: -240 |

The following message is displayed when attempting to upload an incorrect file format.



<u>Export language file</u>: Click to export language strings. VIVOTEK provides nine languages: English, Deutsch, Español, Français, Italiano, 日本語, Português, 簡体中文, and 繁體中文.

Update custom language file: Click Browse... and specify your own custom language file to upload.

Export configuration file: Click to export all parameters for the device and user-defined scripts.

<u>Update configuration file</u>: Click **Browse...** to update a configuration file. Please note that the model and firmware version of the device should be the same as the configuration file. If you have set up a fixed IP or other special settings for your device, it is not suggested to update a configuration file.

<u>Export server staus report</u>: Click to export the current server status report, such as time, logs, parameters, process status, memory status, file system status, network status, kernel message ... and so on.



 If a firmware upgrade is accidentally disrupted, say, by a power outage, you still have a last resort method to restore normal operation. See the following for how to bring the camera back to work:

Applicable scenario:

- (a) Power disconnected during firmware upgrade.
- (b) Unknown reason causing abnormal LED status, and a Restore cannot recover normal working condition.

You can use the following methods to activate the camera with its backup firmware:

- (a) Press and hold down the reset button for at least one minute.
- (b) Power on the camera until the Red LED blinks rapidly.
- (c) After boot up, the firmware should return to the previous version before the camera hanged. (The procedure should take 5 to 10 minutes, longer than the normal boot-up process). When tthis process is completed, the LED status should return to normal.


Media > Image

This section explains how to configure the image settings of the Network Camera. It is composed of the following four columns: General settings, Picture settings, Exposure, and Privacy mask. The Focus window is available only for models that come with motorized lens.

| General settings | General settings | Image settings | Exposure | Privacy mask | |
|------------------|--------------------|------------------------|-----------------|--------------|------------------|
| j- | — Video settir | ngs — | | | |
| | Video title | | | | |
| | Show time | stamp and video ti | tle in video ar | nd snapshots | |
| | Position of time | estamp and video t | itle on image | : | Top 🔽 |
| | Timestamp an | d video title font-siz | e: | ĺ | 30 🗸 |
| | Video font (.ttf): | | | | Default 🗸 Upload |
| | Color: | | | | ⊖ B/W |
| | Power line freq | uency: | | | ○ 50 Hz |
| | Video orientatio | on: | | | 🗌 Flip 🗌 Mirror |
| | | | | | Rotate |

Video title

<u>Show_timestamp_and video_title_in_video_and_snapshots</u>: Enter a name that will be displayed on the title bar of the live video as the picture shown below. A zoom indicator will be displayed on the Home page when you zoom in/out on the live viewing window as shown below. You may zoom in/ out on the image by scrolling the mouse wheel inside the live viewing window, and the maximum zoom in will be up to 4 times.



<u>Position of timestamp and video title on image</u>: Select to display time stamp and video title on the top or at the bottom of the video stream.

<u>Timestamp and video title font size</u>: Select the font size for the time stamp and title.

<u>Video font (.ttf)</u>: You can select a True Type font file for the display of textual messages on video.

Color: Select to display color or black/white video streams.

<u>Power line frequency</u>: Set the power line frequency consistent with local utility settings to eliminate image flickering associated with fluorescent lights. Note that after the power line frequency is changed, you must disconnect and reconnect the power cord of the Network Camera in order for the new setting to take effect.

<u>Video orientation</u>: Flip - vertically reflect the display of the live video; Mirror - horizontally reflect the display of the live video. Select both options if the Network Camera is installed upside-down (e.g., on the ceiling) to correct the image orientation. Please note that if you have preset locations, those locations will be cleared after flip/mirror setting.

Rotate -

90 🖵 Degrees Rotate

The rotation here indicates clockwise rotation. Rotation can be applied with flip, mirror, and physical lens rotation (see below) settings to adapt to different mounting locations.

The figures in the illustration are shown in a consecutive order.

| Normal | Flip | Mirror | Rotate 90° Clockwise |
|--------|------|--------|-------------------------|
| | | | |
| | | | |
| | | | |
| | | | |

The camera may be installed on a vertical, side-facing, or tilted surface in order to accommodate the interior or exterior design of a building. The interior of a building can be shaped as a narrow rectangular space, such as corridor. The conventional HD image, such as that of a 16:9 aspect ratio, will be incongruous with its wide horizontal view. With video rotation, the camera can more readily cover the field of view on a tall and narrow scene.

| Day/Night Settings | — Day/Night settings — | |
|--------------------|-----------------------------|------------|
| | Switch to B/W in night mode | |
| | Day/Night filter: | Day mode 🔽 |

Switch to B/W in night mode

Select this to enable the Network Camera to automatically switch to Black/White during night mode.

Day/Night filter

Auto mode

The Network Camera automatically judges the current operation mode by the level of ambient light detected.

Day mode

In day mode, the camera streams color video.

■ Night mode

In night mode, the camera streams black and white video in low light environments.

Schedule mode

You can manually assign a period of time as the day time, during which the camera streams color video regardless of the light level the camera detects at the moment.

Note that selecting the Auto mode will disable the Profile setting in the Exposure configuration.

Image settings

On this page, you can tune the White balance and Image adjustment.

| | Conversionation in the second |
|------------------------|--|
| Sensor Setting 2: | |
| For special situations | Normal References Profile mode |
| | |
| | Ado V Prometuaue On Off |
| Sensor Setting 1: | image adjustment |
| For normal situations | argitess NS |
| | Contract 10% |
| | Batuzion: 10% |
| | Stappart 575 |
| | Damma sunw: Cestercis 🗹 |
| | (denote the second seco |
| | Netra |
| | Reston Sam |
| | |
| | |

<u>White balance</u>: Adjust the value for the best color temperature.

- You may follow the steps below to adjust the white balance to the best color temperature.
- 1. Place a sheet of paper of white or cooler-color temperature color, such as blue, in front of the lens, then allow the Network Camera to automatically adjust the color temperature.
- 2. Click the **On** button to **Fix current value** and confirm the setting while the white balance is being measured.
- You may also manually tune the color temperature by pulling the RGain and BGain slide bars.

Image Adjustment

- Brightness: Adjust the image brightness level, which ranges from 0% to 100%.
- Contrast: Adjust the image contrast level, which ranges from 0% to 100%.
- Saturation: Adjust the image saturation level, which ranges from 0% to 100%.
- Sharpness: Adjust the image sharpness level, which ranges from 0% to 100%.
- Gamma curve: Adjust the image sharpness level, which ranges from 0 to 0.45. You may let firmware Optimize your display or select a value to change the preferred level of Gamma correction towards higher contrast or towards the higher luminance for detailed expression for both dark and lighted areas of an image.

<u>Defog</u>: Defog helps improve the visibility quality of captured image in poor weather conditions such as smog, fog, or smoke.

Noise reduction

Enable noise reduction: Check to enable noise reduction in order to reduce noises and flickers in image. This applies to the onboard 3D Noise Reduction feature. Use the pull-down menu to adjust the reduction strength. Note that applying this function to the video channel will consume system computing power.

3D Noise Reduction is mostly applied in low-light conditions. When enabled in a low-light condition with fast moving objects, trails of after-images may occur. You may then select a lower strength level or disable the function.

Note that the **Preview** button has been cancelled, all changes made to image settings is directly shown on screen. You can click **Restore** to recall the original settings without incorporating the changes. When completed with the settings on this page, click **Save** to enable the setting. You can also click on **Profile mode** to adjust all settings above in a tabbed window for special lighting conditions during a specific period of time.

| Normal light mode | Profile mode | |
|-------------------|-------------------|--------|
| Enable to apply | these settings at | |
| | uicae aetuinga at | \sim |
| Night mode | ○ Schedule mode | |
| | | |

<u>Enable to apply these settings at</u>: Select the mode this profile to apply to: Day mode, Night mode, or Schedule mode. Please manually enter a range of time if you choose Schedule mode. Then check **Save** to take effect.

Exposure

On this page, you can set the Exposure measurement window, Exposure level, Exposure mode, Exposure time, Gain control, and Day/Night mode settings. You can configure two sets of Exposure settings: one for normal situations, the other for special situations, such as the day/night/schedule mode.

| | General settings Image settings Exposure Privacy mask | |
|------------------------|---|--|
| | EI Auto EI 100% | |
| | | |
| Sensor Setting 2: | Normal light mode Profile mode | |
| For special situations | Measurement window | |
| | Full view Custom BLC | |
| | — Exposure control — | |
| Sensor Setting 1: | Exposure level: +0.7 🔽 | |
| For normal situations | Exposure time: 1/32000 - 1/30 | |
| | Gain control: 0 - 100 % | |
| | — WDR — | |
| | | |
| | Restore Save | |
| | | |


<u>Measurement Window</u>: This function allows users to set measurement window(s) for low light compensation. For example, where low-light objects are posed against an extremely bright background. You may want to exclude the bright sunlight shining through a building's corridor.

- Full view: Calculate the full range of view and offer appropriate light compensation.
- Custom: This option allows you to manually add customized windows as inclusive or exclusive regions. A total of 10 windows can be configured. Please refer to the next page for detailed illustration.

NOTE:

When WDR Pro is enabled, the Measurement window and Exposure control settings will be disabled.

The inclusive window refers to the "weighed window"; the exclusive window refers to "ignored window". It adopts the weighed averages method to calculate the value. The inclusive windows have a higher priority. You can overlap these windows, and, if you place an exclusive window within a larger inclusive window, the exclusive part of the overlapped windows will be deducted from the inclusive window. An exposure value will then be calculated out of the remaining of the inclusive window.



- BLC (Back Light Compensation): This option will automatically add a "weighted region" in the middle of the window and give the necessary light compensation.
- Flickerless: This function helps avoid the flickering on images because of the fast shutter movement and the inconsistency between power line frequency (50 or 60Hz) and exposure time. When selected, the exposure time will be forced to stay longer than 1/120 second. For cameras that come with fixed iris lens, setting the exposure time to longer than 1/120 second may introduce too much lights to the lens. Users can use this option to observe whether the result of long exposure time is satisfactory.

Exposure control:

■ Exposure level: You can manually set the Exposure level, which ranges from -2.0 to +2.0 (dark to bright). You can click and drag the semi-circular pointers on the Exposure time and Gain control slide bars to specify a range of shutter time and Gain control values within which the camera can automatically tune to an optimal imaging result. You may prefer a shorter shutter time to better capture moving objects, while a faster shutter reduces light and needs to be compensated by electrical brightness gains.

WDR Pro:

This refers to the Wide Dynamic Range function that enables the camera to capture details in a high contrast environment. Use the checkbox to enable the function, and use the slide bar to select the strength of the WDR Pro functionality, depending on the lighting condition at the installation site. You can select a higher effect when the contrast is high (between the shaded area and the light behind the objects).

<u>Enable WDR enhanced</u>: This function allows users to identify more image details with an extreme contrast from an object of interest with one shadowed side against a bright background, e.g., an entrance. You may select the **Enable WDR enhanced** checkbox, and then adjust the strength (low, medium, high) to reach the best image quality.

You can click **Restore** to recall the original settings without incorporating the changes. When completed with the settings on this page, click **Save** to enable the settings.

If you want to configure another sensor setting for day/night/schedule mode, please click the **Profile mode** to open the Profile tabbed window of exposure settings as shown below.

<u>Activated period</u>: Select the mode this profile to apply to: Day mode, Night mode, or Schedule mode. Please manually enter a range of time if you choose Schedule mode. Then check **Save** for the configuration to take effect.

Please follow the steps below to set up a profile:

- 1. Select the **Profile mode** tab.
- 2. Select the applicable mode: Night mode or Schedule mode. Please manually enter a range of time if you choose Schedule mode.
- 3. Configure Exposure control settings in the following columns. Please refer to previous dicussions for detailed information.
- 4. Click **Save** to enable the setting and click **Close** to exit the page.



Privacy mask

Click **Privacy Mask** to open the settings page. On this page, you can block out sensitive zones to address privacy concerns.

Enable privacy mask



- To set the privacy mask windows, follow the steps below:
- 1. Click **New** to add a new window.
- 2. You can use 4 mouse clicks to create a new masking window, which is recommended to be at least twice the size of the object (height and width) you want to cover.
- 3. Enter a Window Name and click **Save** to enable the setting.
- 4. Click on the Enable privacy mask checkbox to enable this function.



- ▶ Up to 5 privacy mask windows can be set up on the same screen.
- If you want to delete the privacy mask window, please click the 'x' mark on the side of window name.

Media > Video

Stream settings

| Mode | Stream | | |
|------|--------------------------|----------------|------|
| Vid | eo settings for stream 1 | Viewing Window | |
| Vid | eo settings for stream 2 | Viewing Window | |
| Vid | eo settings for stream 3 | | |
| | | | |
| | | | Save |

This Network Camera supports multiple streams with frame sizes ranging from 176 x 144 to 2048 x 1536 pixels.

The definition of multiple streams:

- Stream 1: Users can define the "Region of Interest" (viewing region) and the "Output Frame Size" (size of the live view window).
- Stream 2: The default frame size for Stream 2 is set to the 640 x 480.
- Stream 3: The default frame size for Stream 3 is set to the 1280 x 960, and the Viewing Window function is not available for stream 3.

Click **Viewing Window** to open the viewing region settings page. On this page, you can configure the **Region of Interest** and the **Output Frame Size** for a video stream. For example, you can crop only a portion of the image that is of your interest, and thus save the bandwidth needed to transmit the video stream. As the picture shown below, the area of your interest in a parking lot should be the vehicles. The blue sky is of little value for the surveillance purpose.





Please follow the steps below to set up those settings for a stream:

- 1. Select a stream for which you want to set up the viewing region.
- 2. Select a Region of Interest from the drop-down list. The floating frame, the same as the one in the Gloabl View window on the home page, will resize accordingly. If you want to set up a customized viewing region, you can also resize and drag the floating frame to a desired position with your mouse.
- 3. Choose a proper Output Frame Size from the drop-down list according to the size of your monitoring device.




All the items in the "Region of Interest" should not be larger than the "Output Frame Size" (current maximum resolution).

The parameters of the multiple streams:

| | Region of Interest | Output frame size | |
|----------|--------------------------------------|--------------------------------------|--|
| Stream 1 | 2560 X 1920 ~ 176 x 144 (Selectable) | 2560 X 1920 ~ 176 x 144 (Selectable) | |
| Stream 2 | 2560 X 1920 ~ 176 x 144 (Selectable) | 2560 X 1920 ~ 176 x 144 (Selectable) | |
| Stream 3 | Fixed | Fixed | |

When completed with the settings in the Viewing Window, click Save to enable the settings and click Close to exit the window. The selected Output Frame Size will immediately be applied to the Frame size of each video stream. Then you can go back to the home page to test the e-PTZ function. For more information about the e-PTZ function, please refer to page 100.



(Size of the Live View Window)

Click the stream item to display the detailed information. The maximum frame size will follow your settings in the above Viewing Window sections.

| Irean | |
|---|--------------------------|
| Video settings for stream 1 Viewing Windo | m. |
| € H 264 | |
| Frame size: | 2048x1536 🗸 |
| Naximum frame rate | 20 tps 💙 |
| inita frame period | 18 🗸 |
| Video quality | |
| O Constant bit rate | |
| · Fixed quality: | |
| Quality | Excellent Y |
| Maximum bit rate | 40 Mbps 💙 |
| O Smart stream | |
| O JPEG | |
| Video settings for steam 2 Viewing Windo | w |
| € H264 | |
| Frame size: | 640x480 💙 |
| Normum trame rate | 15 tos 🗸 |
| intra trame period | 15 ¥ |
| Mdeo quality | |
| Constant bit rale | |
| Target bil rafe | 512 Kbps 💙 |
| Policy: | Image quality priority 👻 |
| Pixed quality: | |
| O Smart stream | |
| CuPEG. | |

This Network Camera offers real-time H.264 and MJPEG compression standards (Dual Codec) for real-time viewing. If the H.264 mode is selected, the video is streamed via RTSP protocol. There are several parameters through which you can adjust the video performance:

| | H.264 | | | | |
|--|---------------------|--------------------|--------|-----------|--------------|
| Frame size: | | ze: | | 2048x1536 | \checkmark |
| Maximum frame rate: | | | 30 fps | \sim | |
| | Intra frame period: | | | 1S 🗸 | |
| | Video quality | | | | |
| Constant bit rate: | | | | | |
| | () Fi | xed quality: | | | |
| | (| Quality: | | Excellent | \sim |
| | 1 | vlaximum bit rate: | | 40 Mbps | \sim |
| | ⊖ Sr | nart stream: | | | |

■ Frame size

You can set up different video resolutions for different viewing devices. For example, set a smaller frame size and lower bit rate for remote viewing on mobile phones and a larger video size and a higher bit rate for live viewing on web browsers, or recording the stream to an NVR. Note that a larger frame size takes up more bandwidth.

Maximum frame rate

This limits the maximum refresh frame rate per second. Set the frame rate higher for smoother video quality and for recognizing moving objects in the field of view.

If the power line frequency is set to 50Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 12fps, 15fps, and up to 25fps. If the power line frequency is set to 60Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 12fps, 15fps, and up to 30fps. You can also select **Customize** and manually enter a value.

The frame rate will decrease if you select a higher resolution.

Intra frame period

Determine how often for firmware to plant an I frame. The shorter the duration, the more likely you will get better video quality, but at the cost of higher network bandwidth consumption. Select the intra frame period from the following durations: 1/4 second, 1/2 second, 1 second, 2 seconds, 3 seconds, and 4 seconds.

Video quality

Constant bit rate:

 <u>Constant bit rate</u>: A complex scene generally produces a larger file size, meaning that higher bandwidth will be needed for data transmission. The bandwidth utilization is configurable to match a selected level, resulting in mutable video quality performance. The bit rates are selectable at the following rates: 20Kbps, 30Kbps, 40Kbps, 50Kbps, 64Kbps, 128Kbps, 256Kbps, 512Kbps, 768Kbps, 1Mbps, 2Mbps, 3Mbps, 4Mbps, 6Mbps, 8Mbps, 10Mbps, 12Mbps, 14Mbps, ~ to 32Mbps. You can also select **Customize** and manually enter a value up to 40Mbps.

- Target bit rate: select a bit rate from the pull-down menu. The bit rate ranges from 20kbps to a maximum of 32Mbps. The bit rate then becomes the Average or Upper bound bit rate number. The Network Camera will strive to deliver video streams around or within the bit rate limitation you impose.

- Policy: If Frame Rate Priority is selected, the Network Camera will try to maintain the frame rate per second performance, while the image quality will be compromised. If Image quality priority is selected, the Network Camera may drop some video frames in order to maintain image quality.

• <u>Fixed quality</u>: On the other hand, if **Fixed quality** is selected, all frames are transmitted with the same quality; bandwidth utilization is therefore unpredictable. The video quality can be adjusted to the following settings: Medium, Standard, Good, Detailed, and Excellent. You can also select **Customize** and manually enter a value.

Maximum bit rate: With the guaranteed image quality, you might still want to place a bit rate limitation to control the size of video streams for bandwidth and storage concerns. The configurable bit rate starts from 1Mbps to 40Mbps.

You may also manually enter a bit rate number by selecting the **Customized** option.

 <u>Smart stream</u>: Smart stream effectively reduces the quality of the whole or the non-interested areas on a screen and therefore reduces the bandwidth consumed.

You can manually specify the video quality for the foreground and the background areas.


| Smart stream: | |
|---------------------|-------------|
| Foreground quality: | Good 🗸 |
| Background quality: | Medium 🗸 |
| Maximum bit rate: | 40 Mbps 🗸 🗸 |
| Mode: | Hybrid 🗸 |
| | |

Manual window setting

Select an operation mode if Smart stream is preferred.

- Auto: The Auto mode configures the whole screen into the background area. The video quality of part of the screen returns to normal when one or more objects move in that area. The remainder of the screen where there are no moving objects (no pixel changes) will still be transmitted in low-quality format.
- Manual: The Manual mode allows you to configure 3 ROI windows (the Foreground areas) on the screen. Areas not included in any ROI windows will be considered as the Background areas. The details in the ROI areas will always be transmitted in a higher-quality video format.

As illustrated below, the upper screen may contain little details of your interest, while the sidewalk on the lower screen is included in an ROI window.



As the result, the lower screen is constantly displayed in high details, while the upper half is transmitted using a lower-quality format. Although the upper half is transmitted using a lower quality format, you still have an awareness of what is happening on the whole screen.



- **Hybrid**: The major difference between the "Manual" mode and the "Hybrid" mode is that:

In the "**Hybrid**" mode, any objects entering the background area will restore the video quality of the moving objects and the area around them. The video quality of the associated background area is immediately restored to normal to cover the moving objects.

In the "**Manual**" mode, the background area is always transmitted using a low-quality format regardless of the activities inside.

You should also select the Maximum bit rate from the pull-down menu as the threshold to contain the bandwidth consumption for both the high- and low-quality video sections in a smart stream.

If **JPEG** mode is selected, the Network Camera sends consecutive JPEG images to the client, producing a moving effect similar to a filmstrip. Every single JPEG image transmitted guarantees the same image quality, which in turn comes at the expense of variable bandwidth usage. Because the media contents are a combination of JPEG images, no audio data is transmitted to the client. There are three parameters provided in MJPEG mode to control the video performance:

| JPEG | | | |
|-------|----------------------|-----------|--------------|
| Frame | e size: | 2048x1536 | \sim |
| Maxim | um frame rate: | 30 fps | \checkmark |
| Video | quality | | |
| C |) Constant bit rate: | | |
| ۲ |) Fixed quality: | | |
| | Quality: | Good | \sim |
| | Maximum bit rate: | 40 Mbps | \sim |

Frame size

You can set up different video resolution for different viewing devices. For example, set a smaller frame size and lower bit rate for remote viewing on mobile phones and a larger video size and a higher bit rate for live viewing on web browsers. Note that a larger frame size takes up more bandwidth.

Maximum frame rate

This limits the maximum refresh frame rate per second. Set the frame rate higher for smoother video quality.

If the power line frequency is set to 50Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and up to 30fps. If the power line frequency is set to 60Hz, the frame rates are selectable at 1fps, 2fps, 3fps, 5fps, 8fps, 10fps, 15fps, and up to 30fps. You can also select **Customize** and manually enter a value. The frame rate will decrease if you select a higher resolution.

Video quality

Refer to the previous page setting an average or upper bound threshold for controlling the bandwidth consumed for transmitting motion jpegs. The configuration method is identical to that for H.264.

For Constant Bit Rate and other settings, refer to the previous page for details.

NOTE:

- Video quality and fixed quality refers to the compression rate, so a lower value will produce higher quality.
- Converting high-quality video may significantly increase the CPU loading, and you may encounter streaming disconnection or video loss while capturing a complicated scene. In the event of occurance, we suggest you customize a lower video resolution or reduce the frame rate to obtain smooth video.

Media > Audio

Audio Settings

| Audio settings | | |
|--------------------------------|-----------|---------|
| ✓ Mute | | |
| External microphone input gain | | 65% |
| Audio type | 0 | 100% |
| @ G.711: | pe mu 💌 | |
| © G.726: | 32 Kbps 💌 | |
| | | |
| | | Save |

<u>Mute</u>: Select this option to disable audio transmission from the Network Camera to all clients. Note that if muted, no audio data will be transmitted even if audio transmission is enabled on the Client Settings page. In that case, the following message is displayed:

| Narning 🛛 🗙 |
|---|
| The media type has been changed to video only because the media from server contains no audio |
| OK |

Internal microphone input gain: Select the gain of the internal audio input according to ambient conditions. Adjust the gain from 0% (no electrical gain) to 100% (highest electrical gain).

Audio type: Select audio codec and the sampling bit rate .

- G.711 also provides good sound quality and requires about 64Kbps. Select pcmu (µ-Law) or pcma (A-Law) mode.
- G.726 is a speech codec standard covering voice transmission at rates of 16, 24, 32, and 40kbit/ s.

When completed with the settings on this page, click **Save** to enable the settings.

Network > General settings

This section explains how to configure a wired network connection for the Network Camera.

| Notwork Type | | |
|--------------|--|------|
| Network Type | Network type Port | |
| | | |
| | e LAN | |
| | Get IP address automatically | |
| | Use fixed IP address | |
| | Enable UPnP presentation | |
| | Enable UPnP port forwarding | |
| | O PPPoE | |
| | Enable IPv6 | |
| | | Save |

LAN

Select this option when the Network Camera is deployed on a local area network (LAN) and is intended to be accessed by local computers. The default setting for the Network Type is LAN. Please rememer to click on the **Save** button when you complete the Network setting.

<u>Get IP address automatically</u>: Select this option to obtain an available dynamic IP address assigned by the DHCP server each time the camera is connected to the LAN.

<u>Use fixed IP address</u>: Select this option to manually assign a static IP address to the Network Camera.

| Network type Port | | |
|------------------------------|---------------|------|
| e LAN | | |
| Get IP address automatically | | |
| Use fixed IP address | | |
| IP address: | 172.16.168.10 | |
| Subnet mask: | 255.255.0.0 | |
| Default router: | 172.16.0.1 | |
| Primary DNS: | 192.168.0.21 | |
| Secondary DNS: | 192.168.0.22 | |
| Primary WINS server: | 192.168.0.21 | |
| Secondary WINS server: | 192.168.0.22 | |
| Enable UPnP presentation | | |
| Enable UPnP port forwarding | | |
| PPPoE | | |
| Enable IPv6 | | |
| | | Save |

- 1. You can make use of VIVOTEK Installation Wizard 2 on the software CD to easily set up the Network Camera on LAN. Please refer to Software Installation on page 16 for details.
- 2. Enter the Static IP, Subnet mask, Default router, and Primary DNS provided by your ISP or network administrator.

<u>Subnet mask</u>: This is used to determine if the destination is in the same subnet. The default value is "255.255.255.0".


<u>Default router</u>: This is the gateway used to forward frames to destinations in a different subnet. Invalid router setting will disable the transmission to destinations across different subnets. Primary DNS: The primary domain name server that translates hostnames into IP addresses.

Secondary DNS: Secondary domain name server that backups the Primary DNS.

<u>Primary WINS server</u>: The primary WINS server that maintains the database of computer names and IP addresses.

<u>Secondary WINS server</u>: The secondary WINS server that maintains the database of computer names and IP addresses.

<u>Enable UPnP presentation</u>: Select this option to enable UPnPTM presentation for your Network Camera so that whenever a Network Camera is presented to the LAN, the shortcuts to connected Network Cameras will be listed in My Network Places. You can click the shortcut to link to the web browser. Currently, UPnPTM is supported by Windows XP or later. Note that to utilize this feature, please make sure the UPnPTM component is installed on your computer.



<u>Enable UPnP port forwarding</u>: To access the Network Camera from the Internet, select this option to allow the Network Camera to open ports automatically on the router so that video streams can be sent out from a LAN. To utilize of this feature, make sure that your router supports UPnPTM and it is activated.

PPPoE (Point-to-point over Ethernet)

Select this option to configure your Network Camera to make it accessible from anywhere as long as there is an Internet connection. Note that to utilize this feature, it requires an account provided by your ISP.

Follow the steps below to acquire your Network Camera's public IP address.

- 1. Set up the Network Camera on the LAN.
- 2. Go to Configuration > Event > Event settings > Add server (please refer to Add server on page 108) to add a new email or FTP server.
- 3. Go to Configuration > Event > Event settings > Add media (please refer to Add media on page 113).

Select System log so that you will receive the system log in TXT file format which contains the Network Camera's public IP address in your email or on the FTP server.

4. Go to Configuration > Network > General settings > Network type. Select PPPoE and enter the user name and password provided by your ISP. Click **Save** to enable the setting.

| Network type | |
|-------------------|------|
| C LAN | |
| PPPoE | |
| User name: | |
| Password: | |
| Confirm password: | |
| Enable IPv6 | |
| | |
| | Save |


- 5. The Network Camera will reboot.
- 6. Disconnect the power to the Network Camera; remove it from the LAN environment.

DOTE:


- ► If the default ports are already used by other devices connected to the same router, the Network Camera will select other ports for the Network Camera.
- If UPnP[™] is not supported by your router, you will see the following message: Error: Router does not support UPnP port forwarding.
- Steps to enable the UPnP[™] user interface on your computer: Note that you must log on to the computer as a system administrator to install the UPnP[™] components.
 - 1. Go to Start, click Control Panel, then click Add or Remove Programs.

| ti Diramettaa Haanstaan A | Pick a category | |
|------------------------------|--|------------------------------|
| a data in the | Approximation (Income) | 💒 formation the first sector |
| a respectively | and the state of t | See Service |
| (| and the second second | |
| | | 6 |
| | | |


2. In the Add or Remove Programs dialog box, click Add/Remove Windows Components.



3. In the Windows Components Wizard dialog box, select **Networking Services** and click **Details**.



4. In the Networking Services dialog box, select Universal Plug and Play and click OK.



5. Click Next in the following window.

| To add or remove a component, click the checkbox. A shaded box means that part of the component will be installed. To see what's included in a component. | |
|--|-------|
| Details | click |
| Components: | |
| ₹ v MSN Explorer 135M | |
| P An Networking Services 0.3 M | _ |
| Other Network File and Print Services 0.0 M | 8 |
| Fall Indate Boot Certificates 0.0 M | n N |

6. Click **Finish**. UPnP[™] is enabled.

► How does UPnP[™] work?

UPnP[™] networking technology provides automatic IP configuration and dynamic discovery of devices added to a network. Services and capabilities offered by networked devices, such as printing and file sharing, are available among each other without the need for cumbersome network configuration. In the case of Network Cameras, you will see Network Camera shortcuts under My Network Places.

Enabling UPnP port forwarding allows the Network Camera to open a secondary HTTP port on the router-not HTTP port-meaning that you have to add the secondary HTTP port number to the Network Camera's public address in order to access the Network Camera from the Internet. For example, when the HTTP port is set to 80 and the secondary HTTP port is set to 8080, refer to the list below for the Network Camera's IP address.

| From the Internet | In LAN |
|----------------------------|--|
| http://203.67.124.123:8080 | http://192.168.4.160 or http://192.168.4.160:8080 |

If the PPPoE settings are incorrectly configured or the Internet access is not working, restore the Network Camera to factory default; please refer to Restore on page 45 for details. After the Network Camera is reset to factory default, it will be accessible on the LAN.

Enable IPv6

Select this option and click **Save** to enable IPv6 settings.

Please note that this only works if your network environment and hardware equipment support IPv6. The browser should be Microsoft[®] Internet Explorer 6.5, Mozilla Firefox 3.0 or above.

| Network type | |
|-------------------------------|------|
| C LAN | |
| PPPoE | |
| User name: | |
| Password: | |
| Confirm password: | |
| Enable IPv6 | |
| IPv6 information | |
| Manually setup the IP address | |
| | |
| | Save |

When IPv6 is enabled, by default, the network camera will listen to router advertisements and be assigned with a link-local IPv6 address accordingly.

IPv6 Information: Click this button to obtain the IPv6 information as shown below.

| | close |
|---|-------|
| [eth0 address] | |
| fe80 0000 0000 0000 0202 d1ff fe0e d4c8/64@Link | |
| [Gateway] | |
| IPv6 address list of gateway | |
| [DNS] | |
| IPv6 address list of DNS | |
| IPv6 address list of DNS | |
| | |
| | |
| | |

If your IPv6 settings are successful, the IPv6 address list will be listed in the pop-up window. The IPv6 address will be displayed as follows:

Refers to Ethernet

| [eth0 address] | |
|---|---------------------------------------|
| 2001:0c08:2500:0002:0202:d1ff:fe04:65f4/64@Global | Link-global IPv6 address/network mask |
| fe80:0000.0000:0000:0202:d1ff:fe04:65f4/64@Link | Link-local IPv6 address/network mask |
| [Gateway] | |
| fe80::211:d8ff:fea2:1a2b | |
| [DNS] | |
| 2010:05c0:978d:: | |

Please follow the steps below to link to an IPv6 address:

- 1. Open your web browser.
- 2. Enter the link-global or link-local IPv6 address in the address bar of your web browser.
- 3. The format should be:



4. Press **Enter** on the keyboard or click **Refresh** button to refresh the webpage. For example:

| Network Camera - Microsoft Internet Explorer File Edit View Favorites Tools Help | |
|---|---------|
| Back Image: Search Image: Search <th>🖉 - 😓 🖓</th> | 🖉 - 😓 🖓 |
| VIVOTEK | |

🖉 NOTE:

If you have a Secondary HTTP port (the default value is 8080), you can also link to the webpage using the following address format: (Please refer to HTTP streaming on page 77 for detailed information.)



► If you choose PPPoE as the Network Type, the [PPP0 address] will be displayed in the IPv6 information column as shown below.

| [eth0 address] fe80:0000:0000:0000:0202:d1ff:fe11:2299/64@Link |
|---|
| [ppp0 address] |
| fe80:0000:0000:0000:0202:d1ff:fe11:2299/10@Link |
| 2001:b100:01c0:0002:0202:d1ff:fe11:2299/64@Global |
| [Gateway] |
| fe80::90:1a00:4142:8ced |
| [DNS] |
| 2001:b000::1 |

<u>Manually setup the IP address</u>: Select this option to manually set up IPv6 settings if your network environment does not have DHCPv6 server and router advertisements-enabled routers. If you check this item, the following blanks will be displayed for you to enter the corresponding information:

🔽 Enable IPv6

Port

| IPv6 information | |
|------------------------------|---------------|
| 📝 Manually setup the IP a | address |
| Optional IP address / Prefix | x length / 64 |
| Optional default router | |
| Optional primary DNS | |
| Network type Port | |
| HTTPS port: | 443 |
| FTP port: | 21 |
| | Save |

<u>HTTPS port</u>: By default, the HTTPS port is set to 443. It can also be assigned to another port number between 1025 and 65535.

<u>FTP port</u>: The FTP server allows the user to save recorded video clips. You can utilize VIVOTEK's Installation Wizard 2 to upgrade the firmware via FTP server. By default, the FTP port is set to 21. It also can be assigned to another port number between 1025 and 65535.

Network > Streaming protocols

HTTP streaming

To utilize HTTP authentication, make sure that your have set a password for the Network Camera first; please refer to Security > User account on page 87 for details.

| HTTP streaming | RTSP streaming | |
|-----------------|----------------|-------------|
| Authentication: | | basic 🗸 |
| HTTP port: | | 80 |
| Secondary HTTP | port: | 8080 |
| Access name for | stream 1: | video.mjpg |
| Access name for | stream 2: | video2.mjpg |
| Access name for | stream 3: | video3.mjpg |
| | | |
| | | |
| | | Save |

<u>Authentication</u>: Depending on your network security requirements, the Network Camera provides two types of security settings for an HTTP transaction: basic and digest.

If **basic** authentication is selected, the password is sent in plain text format and there can be potential risks of being intercepted. If **digest** authentication is selected, user credentials are encrypted using MD5 algorithm and thus provide better protection against unauthorized accesses.

<u>HTTP port / Secondary HTTP port</u>: By default, the HTTP port is set to 80 and the secondary HTTP port is set to 8080. They can also be assigned to another port number between 1025 and 65535. If the ports are incorrectly assigned, the following warning messages will be displayed:

| Microsoft Internet Explorer | Microsoft Internet Explorer |
|--|--|
| HTTP port must be 80 or from 1025 to 65535 | Secondary HTTP port must be from 1025 to 65535 |
| ОК | ОК |

To access the Network Camera on the LAN, both the HTTP port and secondary HTTP port can be used to access the Network Camera. For example, when the HTTP port is set to 80 and the secondary HTTP port is set to 8080, refer to the list below for the Network Camera's IP address.

| On the LAN |
|---------------------------|
| http://192.168.4.160 or |
| http://192.168.4.160:8080 |

<u>Access name for stream 1 ~ 3</u>: This Network camera supports multiple streams simultaneously. The access name is used to identify different video streams. Users can click **Media > Video > Stream settings** to set up the video quality of linked streams. For more information about how to set up the video quality, please refer to Stream settings on page 61.

When using **Mozilla Firefox** to access the Network Camera and the video mode is set to JPEG, users will receive video comprised of continuous JPEG images. This technology, known as "server push", allows the Network Camera to feed live pictures to Mozilla Firefox.

URL command -- http://<ip address>:<http port>/<access name for stream 1, 2, 3> For example, when the Access name for stream 2 is set to video2.mjpg:

- 1. Launch Mozilla Firefox or Netscape.
- 2. Type the above URL command in the address bar. Press Enter.
- 3. The JPEG images will be displayed in your web browser.



NOTE:

Microsoft[®] Internet Explorer does not support server push technology; therefore, you will not be able to access a video stream using http://<ip address>:<http port>/<access name for stream 1, 2, 3>.

RTSP Streaming

To utilize RTSP streaming authentication, make sure that you have set a password for controlling the access to video stream first. Please refer to Security > User account on page 87 for details.

| Access name for stream 3: IIIve3.sdp RTSP port RTSP port for video: 5554 RTCP port for video: 5556 RTCP port for metadata 6556 RTCP port for metadata 0557 RTP port for metadata 0557 RTCP port for audio 5558 RTCP port for audio 5558 RTCP port for audio 5558 RTCP port for stream 1 Multicast settings for stream 2 | Authentication: | basic 🗸 | |
|---|---------------------------------|-----------|------|
| Access name for stream 3: IIVe3.sdp RTSP port RTSP port RTSP port for video: 5556 RTCP port for video: 5556 RTCP port for metadata 5556 RTCP port for metadata 0557 RTP port for audio 5558 RTCP port for audio 5558 RTCP port for audio 5558 RTCP port for stream 1 Multicast settings for stream 2 | Access name for stream 1: | live.sdp | |
| RTSP port 554 RTP port for wdeo: 6656 RTCP port for metadata 6556 RTCP port for metadata 6556 RTCP port for metadata 0657 RTCP port for audio. 5558 RTCP port for audio. 6550 ♦ Multicast settings for stream 1 ♦ Multicast settings for stream 2 | Access name for stream 2: | live2.sdp | |
| RTP port for video: 5556 RTP port for video: 5557 RTP port for metadata 6556 RTCP port for metadata 0557 RTP port for metadata 0557 RTP port for audio 5558 RTCP port for audio 5558 RTCP port for audio 5558 Multicast settings for stream 1 4000000000000000000000000000000000000 | Access name for stream 3: | live3.sdp | |
| RTP port for video: 5556 RTP port for video: 5556 RTP port for metadata 6556 RTCP port for metadata 0557 RTP port for metadata 0557 RTP port for audio 5558 RTCP port for audio 5558 RTCP port for audio 5558 Multicast settings for stream 1 Visitional settings for stream 2 | | 554 | |
| RTP port for metadata 6556 RTCP port for metadata 0557 RTP port for audio 5558 RTCP port for audio 5550 Multicast settings for stream 1 5558 | | | |
| RTCP port for metadata 00557 RTP port for audio 5558 RTCP port for audio 5558 Multicast settings for stream 1 Multicast settings for stream 2 | RTCP part for video: | 5557 | |
| RTP port for audio 5558 RTCP port for audio 5550 Multicast settings for stream 1 5550 | RTP port for metadata | 6556 | |
| RTCP port for audio 5550 Multicast settings for stream 1 Multicast settings for stream 2 | RTCP port for metadata | 0557 | |
| Multicast settings for stream 1 Multicast settings for stream 2 | RTP port for audio | 5558 | |
| Multicast settings for stream 2 | RTCP port for audio | 6560 | |
| Multicast settings for stream 2 Multicast settings for stream 3 | Multicast settings for stream 1 | | |
| Multicast settings for stream 3 | Multicast settings for stream 2 | | |
| - · · · · · · · · · · · · · · · · · · · | Multicast settings for stream 3 | | |
| | | | Save |

<u>Authentication</u>: Depending on your network security requirements, the Network Camera provides three types of security settings for streaming via RTSP protocol: disable, basic, and digest. If **basic** authentication is selected, the password is sent in plain text format, but there can be potential risks of it being intercepted. If **digest** authentication is selected, user credentials are encrypted using MD5 algorithm, thus providing better protection against unauthorized access. The availability of the RTSP streaming for the three authentication modes is listed below:

| | Quick Time player | VLC |
|---------|-------------------|-----|
| Disable | 0 | 0 |
| Basic | 0 | 0 |
| Digest | 0 | Х |

<u>Access name for stream 1 ~ 3</u>: This Network camera supports multiple streams simultaneously. The access name is used to differentiate the streaming source.

If you want to use an RTSP player to access the Network Camera, you have to set the video mode to H.264 and use the following RTSP URL command to request transmission of the streaming data. rtsp://<ip address>:<rtsp port>/<access name for stream 1 to 3>

For example, when the access name for stream 1 is set to live.sdp:

- 1. Launch an RTSP player.
- 2. Choose File > Open URL. A URL dialog box will pop up.
- 3. Type the above URL command in the text box.
- 4. The live video will be displayed in your player as shown below.



| Open URL | |
|-----------------------------------|---|
| Enter an Internet URL to open | |
| rtsp://192.168.5.151 554/live.sdp | ~ |

RTSP port /RTP port for video, audio/ RTCP port for video, audio

- RTSP (Real-Time Streaming Protocol) controls the delivery of streaming media. By default, the port number is set to 554.
- The RTP (Real-time Transport Protocol) is used to deliver video and audio data to the clients. By default, the RTP port for video is set to 5556.
- The RTCP (Real-time Transport Control Protocol) allows the Network Camera to transmit the data by monitoring the Internet traffic volume. By default, the RTCP port for video is set to 5557.

The ports can be changed to values between 1025 and 65535. The RTP port must be an even number and the RTCP port is the RTP port number plus one, and thus is always an odd number. When the RTP port changes, the RTCP port will change accordingly.

If the RTP ports are incorrectly assigned, the following warning message will be displayed:



<u>Multicast settings for streams</u>: Click the items to display the detailed configuration information. Select the Always multicast option to enable multicast for video streams.



Unicast video transmission delivers a stream through point-to-point transmission; multicast, on the other hand, sends a stream to the multicast group address and allows multiple clients to acquire the stream at the same time by requesting a copy from the multicast group address. Therefore, enabling multicast can effectively save Internet bandwith.

The ports can be changed to values between 1025 and 65535. The multicast RTP port must be an even number and the multicast RTCP port number is the multicast RTP port number plus one, and thus is always odd. When the multicast RTP port changes, the multicast RTCP port will change accordingly.

If the multicast RTP video ports are incorrectly assigned, the following warning message will be displayed:



<u>Multicast TTL [1~255]</u>: The multicast TTL (Time To Live) is the value that tells the router the range a packet can be forwarded.

| Initial TTL | Scope |
|-------------|-----------------------------------|
| 0 | Restricted to the same host |
| 1 | Restricted to the same subnetwork |
| 32 | Restricted to the same site |
| 64 | Restricted to the same region |
| 128 | Restricted to the same continent |
| 255 | Unrestricted in scope |

MPORTANT:

The Multicast metadata port is utilized by VIVOTEK VADP modules to transfer video analytics results, PTZ stream, textual data, and event messages between the camera and the client side running and observing the video analysis. If your client side computer is located outside the local network, you may need to open the associated TCP port on routers and firewall.

Network > DDNS

This section explains how to configure the dynamic domain name service for the Network Camera. DDNS is a service that allows your Network Camera, especially when assigned with a dynamic IP address, to have a fixed host and domain name.

Express link

Express Link is a free service provided by VIVOTEK server, which allows users to register a domain name for a network device. One URL can only be mapped to one MAC address. This service will examine if the host name is valid and automatically open a port on your router. If using DDNS, the user has to manually configure UPnP port forwarding. Express Link is more convenient and easier to set up.

| Express link | Manual setup | | | |
|------------------------|---|---------------------------|------------------------------------|--|
| ☑ Enable ex http:// | xpress link | .2bthere.net | Help Save | |
| | link, all users need to do is cr camera from internet. | eate host name for the ca | mera. It will generate the link to | |

Please follow the steps below to enable Express Link:

- 1. Make sure that your router supports UPnP port forwarding and it is activated.
- 2. Check Enable express link.
- 3. Enter a host name for the network device and click **Save**. If the host name has been used by another device, a warning message will show up. If the host name is valid, it will display a message as shown below.

| _ | Expre | ess link | Manual setup | | | | |
|----------|----------|--|-----------------------|---------------------------------------|----------------------|---------------|----------|
| | 🔽 E | Enable ex | press link | | | | |
| | http:// | 0002D | 1123456 | | .2bthere.net | <u>Help</u> S | ave |
| | The (| camera c | an now be acces | ssed at <u>http://0002</u> | D1123456.2bthere.net |] | |
| | | | | | | • | |
| 🗿 Netwo | ork Cam | era - Micro | soft Internet Explo | rer | | | |
| File Edi | t View | Favorites | Tools Help | | | | |
| G Back | • 6 | - 🗙 | 👔 🏠 🔎 Sear | rch 🤺 Favorites 🥝 | 🔗 - 邊 🖂 🦓 | | |
| | 🞒 https: | //0002D112 | 3456.2bthere.net | | · | | |
| | ſ | Y | VOTEK | | Mega-Pi | xel Netw | ork Came |
| | | Video Strea Manual T Digital Outp Focus Assis | rigger: out On Off | El Auto El 100% El 30% El (TCP-AV) | 25% | | |
| | | | | | | | |

Manual setup

DDNS: Dynamic domain name service

| Enable DDNS: | |
|--------------|-----------------------|
| Provider: | Dyndns.org(Dynamic) 🗸 |
| Host name: | |
| User name: | |
| Password: | |

Enable DDNS: Select this option to enable the DDNS setting.

<u>Provider</u>: Select a DDNS provider from the provider drop-down list.

VIVOTEK offers **Safe100.net**, a free dynamic domain name service, to VIVOTEK customers. It is recommended that you register **Safe100.net** to access VIVOTEK's Network Cameras from the Internet. Additionally, we offer other DDNS providers, such as Dyndns.org(Dynamic), and CustomSafe100.

Note that before utilizing this function, please apply for a dynamic domain account first.

■ Safe100.net

- 1. In the DDNS column, select **Safe100.net** from the drop-down list. Click **I accept** after reviewing the terms of the Service Agreement.
- 2. In the Register column, fill in the Host name (xxxx.safe100.net), Email, Key, and Confirm Key, and click **Register**. After a host name has been successfully created, a success message will be displayed in the DDNS Registration Result column.

| Register | | | | |
|---|---|--|--|--|
| Register | | | | |
| Host name: | VVTK.safe100.net | | | |
| Email: | wtk@vivotek.com | | | |
| Key: | •••• Forget key | | | |
| Confirm key: | •••• | | | |
| To apply for a domain name for the camera, or to modify the previously registered information, fill in | | | | |
| the following fields and then click "Registe | er". | | | |
| Register | | | | |
| DDNS Registration Result: | | | | |
| [Register] Successfully Your account been mailed to registered e-mail address | (=9) | | | |
| Upon successful registration, you can click copy to automatically upload relevant information to the | | | | |
| DDNS form or you can manually fill it in. T | hen, click "Save" to save new settings. | | | |
| | | | | |

3. Click **Copy** and all the registered information will automatically be uploaded to the corresponding fields in the DDNS column at the top of the page as seen in the picture.

| Host name: VVTK.safe100.net [".safe100.net] Email: wtk@vivotek.com | Provider: | Safe100.net | * | | |
|--|---|-------------------------------------|-----------------------------------|--|--|
| Key: ••••• Save Register VTK.safe100.net Email: Host name: VVTK.safe100.net VVTK.safe100.net Email: wtk@vivotek.com Forget key Confirm key: •••• Forget key Confirm key: •••• To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has Mathematical Super Su | Host name: VVTK.safe100.net [*.safe100.net] | | | | |
| Register Host name: VVTK.safe100.net Email: wtk@vivotek.com Key: •••• Confirm key: •••• To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Email: wtk@vivotek.com | | | | |
| Register Host name: VVTK.safe100.net Email: wtk@vivotek.com Key: •••• Confirm key: •••• To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Key: | •••• | | | |
| Email: wtk@vivotek.com Key: •••• Forget key Confirm key: •••• To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Register | | Save | | |
| Key: Forget key Confirm key: To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Host name: VVTK.safe100.net | | | | |
| Confirm key: To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Email: wtk@vivotek.com | | | | |
| To apply for a domain name for the camera, or to modify the previously registered information, fill in the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Key: •••• Forget key | | | | |
| the following fields and then click "Register". Register DDNS Registration Result: [Register] Successfully Your account information has | Confirm key: | •••• | | | |
| Register DDNS Registration Result: [Register] Successfully Your account information has | To apply for a domain name for the | camera, or to modify the previously | y registered information, fill in | | |
| DDNS Registration Result: [Register] Successfully Your account information has | the following fields and then click "F | Register". | | | |
| [Register] Successfully Your account information has | Register | | | | |
| [Register] Successfully Your account information has | DDNS Registration Result: | | | | |
| been mailed to registered e-mail address | | ccount information has | <u>^</u> | | |

4. Select Enable DDNS and click **Save** to enable the setting.

CustomSafe100

VIVOTEK offers documents to establish a CustomSafe100 DDNS server for distributors and system integrators. You can use CustomSafe100 to register a dynamic domain name if your distributor or system integrators offer such services.

- 1. In the DDNS column, select CustomSafe100 from the drop-down list.
- 2. In the Register column, fill in the Host name, Email, Key, and Confirm Key; then click **Register**. After a host name has been successfully created, you will see a success message in the DDNS Registration Result column.
- Click Copy and all for the registered information will be uploaded to the corresponding fields in the DDNS column.
- 4. Select Enable DDNS and click **Save** to enable the setting.

<u>Forget key</u>: Click this button if you have forgotten the key to Safe100.net or CustomSafe100. Your account information will be sent to your email address.

Refer to the following links to apply for a dynamic domain account when selecting other DDNS providers:

Dyndns.org(Dynamic) / Dyndns.org(Custom): visit http://www.dyndns.com/

Network > QoS (Quality of Service)

Quality of Service refers to a resource reservation control mechanism, which guarantees a certain quality to different services on the network. Quality of service guarantees are important if the network capacity is insufficient, especially for real-time streaming multimedia applications. Quality can be defined as, for instance, a maintained level of bit rate, low latency, no packet dropping, etc.

The following are the main benefits of a QoS-aware network:

- The ability to prioritize traffic and guarantee a certain level of performance to the data flow.
- The ability to control the amount of bandwidth each application may use, and thus provide higher reliability and stability on the network.

Requirements for QoS

To utilize QoS in a network environment, the following requirements must be met:

- All network switches and routers in the network must include support for QoS.
- The network video devices used in the network must be QoS-enabled.

QoS models

CoS (the VLAN 802.1p model)

IEEE802.1p defines a QoS model at OSI Layer 2 (Data Link Layer), which is called CoS, Class of Service. It adds a 3-bit value to the VLAN MAC header, which indicates the frame priority level from 0 (lowest) to 7 (highest). The priority is set up on the network switches, which then use different queuing disciplines to forward the packets.

Below is the setting column for CoS. Enter the **VLAN ID** of your switch ($0\sim4095$) and choose the priority for each application ($0\sim7$).

| CoS | |
|--------------|-----|
| Enable CoS | |
| VLAN ID: | 1 |
| Live video: | 0 💌 |
| Live sudio: | 0 💌 |
| Event/Alarm: | 0 💌 |
| Management: | 0 💌 |
| | |

If you assign Video the highest level, the switch will handle video packets first.

🖉 NOTE:

► A VLAN Switch (802.1p) is required. Web browsing may fail if the CoS setting is incorrect.

- The Class of Service technologies do not guarantee a level of service in terms of bandwidth and delivery time; they offer a "best-effort." Users can think of CoS as "coarsely-grained" traffic control and QoS as "finely-grained" traffic control.
- Although CoS is simple to manage, it lacks scalability and does not offer end-to-end guarantees since it is based on L2 protocol.

QoS/DSCP (the DiffServ model)

DSCP-ECN defines QoS at Layer 3 (Network Layer). The Differentiated Services (DiffServ) model is based on packet marking and router queuing disciplines. The marking is done by adding a field to the IP header, called the DSCP (Differentiated Services Codepoint). This is a 6-bit field that provides 64 different class IDs. It gives an indication of how a given packet is to be forwarded, known as the Per Hop Behavior (PHB). The PHB describes a particular service level in terms of bandwidth, queueing theory, and dropping (discarding the packet) decisions. Routers at each network node classify packets according to their DSCP value and give them a particular forwarding treatment; for example, how much bandwidth to reserve for it.

Below are the setting options of DSCP (DiffServ Codepoint). Specify the DSCP value for each application (0~63).

| Qo S/DSCP | | |
|-----------------|---|------|
| Enable QoS/DSCP | | |
| Live video: | 0 | |
| Live audio: | 0 | |
| Event/Alarm: | 0 | |
| Management: | 0 | |
| | | Save |
| | | Save |

Network > SNMP (Simple Network Management Protocol)

This section explains how to use the SNMP on the network camera. The Simple Network Management Protocol is an application layer protocol that facilitates the exchange of management information between network devices. It helps network administrators to remotely manage network devices and find, solve network problems with ease.

- The SNMP consists of the following three key components:
- 1. Manager: Network-management station (NMS), a server which executes applications that monitor and control managed devices.
- 2. Agent: A network-management software module on a managed device which transfers the status of managed devices to the NMS.
- 3. Managed device: A network node on a managed network. For example: routers, switches, bridges, hubs, computer hosts, printers, IP telephones, network cameras, web server, and database.

Before configuring SNMP settings on the this page, please enable your NMS first.

SNMP Configuration

Enable SNMPv1, SNMPv2c

~

Select this option and enter the names of Read/Write community and Read Only community according to your NMS settings.

| Ena | nable SNMPv1, SNMPv2c | | | | | |
|-----|------------------------|---------|--|--|--|--|
| | SNMPv1, SNMPv2c Settin | gs | | | | |
| | Read/Write community: | Private | | | | |
| | Read only community: | Public | | | | |

Enable SNMPv3

This option contains cryptographic security, a higher security level, which allows you to set the Authentication password and the Encryption password.

- Security name: According to your NMS settings, choose Read/Write or Read Only and enter the community name.
- Authentication type: Select MD5 or SHA as the authentication method.
- Authentication password: Enter the password for authentication (at least 8 characters).
- Encryption password: Enter a password for encryption (at least 8 characters).

| 🗹 Ena | ble SNMPv3 | | |
|-------|---------------------------|---------|--|
| | SNMPv3 Settings | | |
| | Read/Write Security name: | Private | |
| | Authentication Type: | MD5 🗸 | |
| | Authentication Password: | | |
| | Encryption Password: | | |
| | Read only Security name: | Public | |
| | Authentication Type: | MD5 🗸 | |
| | Authentication Password: | | |
| | Encryption Password: | | |

Security > User accounts

This section explains how to enable password protection and create multiple accounts.

| Root Password | | |
|----------------------|------------------------|------|
| Γ | Root password | |
| | Root password: | |
| | Confirm root password: | Save |
| | | |

The administrator account name is "root", which is permanent and can not be deleted. If you want to add more accounts in the Manage User column, please apply the password for the "root" account first.

- 1. Type the password identically in both text boxes, then click **Save** to enable password protection.
- A window will be prompted for authentication; type the correct user's name and password in their respective fields to access the Network Camera.

Privilege Management

| Root passwor | Privilege managemen | Account management | |
|--------------|---------------------|--------------------|------|
| Allow anor | nymous viewing | | |
| Operator: | PTZ control | | |
| View er: | PTZ control | | Save |
| | | | |

<u>PTZ control</u>: You can modify the management privilege for operators or viewers. Select or deselect the checkboxes, then click **Save** to enable the settings. If you give Viewers the privilege, Operators will also have the ability to control the Network Camera through the main page. (Please refer to Configuration on page 35).

<u>Allow anonymous viewing</u>: If you check this item, any client can access the live stream without entering a User ID and Password.

Account Management

| Manage user | |
|------------------------|----------------------|
| Existing user name: | Add new user |
| User name: | |
| User password: | Delete |
| Confirm user password: | Add |
| Privilege: | Administrator Update |
| | Operator Viewer |

Administrators can create up to 20 user accounts.

- 1. Input the new user's name and password.
- 2. Select the privilege level for the new user account. Click **Add** to enable the setting.

Access rights are sorted by user privilege (Administrator, Operator, and Viewer). Only administrators can access the Configuration page. Although operators cannot access the Configuration page, they can use the URL Commands to get and set the value of parameters. For more information, please refer to URL Commands of the Network Camera on page 136. Viewers can only access the main page for live viewing.

Here you also can change a user's access rights or delete user accounts.

- 1. Select an existing account to modify.
- 2. Make necessary changes and click **Update** or **Delete** to enable the setting.

Security > HTTPS (Hypertext Transfer Protocol over SSL)

This section explains how to enable authentication and encrypted communication over SSL (Secure Socket Layer). It helps protect streaming data transmission over the Internet on higher security level.

Create and Install Certificate Method

Before using HTTPS for communication with the Network Camera, a **Certificate** must be created first. There are three ways to create and install a certificate:

Create self-signed certificate


- 1. Select this option from a pull-down menu.
- 2. In the first column, select **Enable HTTPS secure connection**, then select a connection option: "HTTP & HTTPS" or "HTTPS only".
- 3. Click **Create certificate** to generate a certificate.

| - HTTPS | S | |
|---------|------------------------------|--|
| 🔽 Ena | able HTTPS secure connection | |
| 🐭 Mo | | |
| | HTTP & HTTPS O HTTPS only | Please wait while the certificate is being |
| 👻 Cer | rtificate: | generated |
| | Certificate information | |
| | Status: | Not installed |
| | method: | Create self-signed certificate |
| | Country: | TW |
| | State or province: | Asia |
| | Locality: | Asia |
| | Organization: | VIVOTEK.Inc |
| | Organization unit: | VIVOTEK.Inc |
| | Common name: | www.vivotek.com |
| | Validity: | 3650 days |
| | | Create certificate |
| | | |

4. The Certificate Information will automatically be displayed as shown below. You can click **Certificate properties** to view detailed information about the certificate.

| Certificate information | |
|-------------------------|---|
| Status: | Active |
| method: | Create self-signed certificate |
| Country: | TW |
| State or province: | Asia |
| Locality: | Asia |
| Organization: | VIVOTEK.Inc |
| Organization unit: | VIVOTEK.Inc |
| Common name: | www.vivotek.com |
| | Certificate properties Remove certificate |

- 5. Click **Save** to preserve your configuration, and your current session with the camera will change to the encrypted connection.
- 6. If your web session does not automatically change to an encrypted HTTPS session, click Home to return to the main page. Change the URL address from "<u>http://</u>" to "<u>https://</u>" in the address bar and press Enter on your keyboard. Some Security Alert dialogs will pop up. Click OK or Yes to enable HTTPS.



https://

Create certificate request and install

- 1. Select the option from the **Method** pull-down menu.
- 2. Click Create certificate to proceed.
- 3. The following information will show up in a pop-up window after clicking **Create**. Then click **Save** to generate the certificate request.

| 🌱 Ce | rtificate: | |
|------|---|--|
| | Certificate information | |
| | Status: | Not installed |
| | Method: | Create certificate request and install |
| | Country: | TW |
| | State or province: | Asia |
| | Locality: | Asia |
| | Organization: | VIVOTEK Inc. |
| | Organization unit: | VIVOTEK Inc. |
| | Common name: | www.vivotek.com |
| | Please wait while the certific generated | Create certificate |

4. The Certificate request window will prompt.

| Create | erblicate request completed | |
|----------------|--|---------|
| Copy the | EM formal request below and send it to a CA for identify validation. After that, you have to | install |
| by clickin | the "Upbad" button on HTTPS page. | |
| Certific | te request (PEM format) | |
| | SIN CERTIFICATE REQUEST | 1 |
| | CARWCAQIWCXELMARGA1UEB5MCVTcxDTALBgHVHAgTBEFzzWExDTALBgHV | |
| | ##NEwFTATRgNURAmTDFZJV#9030#gRN5jLjEVHRMCAlUEC#9607%1MT13F | |
| | uMRgvFgYDVQQDEv93d3cudml2b3R1ay6jb23vg28vDQYJKoIIhvcMAQEB | I . |
| | AMIGJAGGBALEFSjkjhiCeurOHp43rOWUngGEPtQ8si84HCTbravhpun/W | |
| | HEhLQwGpepsNy9erSYcu0JuS7bkbLAuHn/T97RdvI4UC0xGvenSAg1SI6 Y9L144VnhuaircwywR1VHOmXixflodD1UEKeC3UHpNL8x5J3r7vA5AgNB | I . |
| Soft Landson | Nigkghk199w08AQ0FAA08gQ8dQgpKd01cbwf61RPnE05HEMBnBr108gY | |
| Contraction of | IIXwPWE8Kalgi8I4XpFNjXVBUs0LvUOOh/nyHDSe2a2xIIZWiSJhD1A1Fm | |
| 10.000 | AvC46saCh3bgT3e3ILK6V11vC1pRXMmoEuUgHs4XYVysRgd3soeQuISVs | |
| ablaur f | An and the second s | |
| | D CERTIFICATE RECUEST | I . |

If you see the following Information bar, click **OK** and click on the Information bar at the top of the page to allow pop-ups.



5. Look for a trusted certificate authority, such as Symantec's VeriSign Authentication Services, that issues digital certificates. Sign in and purchase the SSL certification service. Copy the certificate request from your request prompt and paste it in the CA's signing request window. Proceed with the rest of the process as CA's instructions on their webpage.

| ee Trial > Occurs > # 255c | leten Certari 🕒 3 CSR. (H-1) Summer | | Chat With Us | 1 |
|---|---|----------------------------|--|---|
| Enter Certificate Signing Request | CSR) | | | |
| Server platform: 💿 Selectione 📃 | Sample CSI - Book percent Analysis - Provide a provide the second second - Provide a provide the second second second - Provide a provide the second second second second - Provide the second second second second second - Provide the second second second second second second - Provide the second | | Order details Symmetric ** SSL Text Certil • Validly period 30 aleys | k.ate |
| | Berndellander, der verschlichte Leisenbergerten, der Stehn Berndellander, St | And a Collection of States | Total: (Free Bilat: | 175 34 |
| BACTOPISHEATTA TSAMBACT SyBambaffowl Gritovidou Av406Awg (ndg) TA3gtTown Showg and galant the table Shouge and Banghootthe Automotistic States and the Automotistic States | 1 | 쾨 | What is a CSR? A CSR is generaled then you your senerit undue "Topen motake your server public motakes your server public motakes your server public motakes your server public motakes annumber a CSR? == | rinf. The CSR key, which is and sectore |
| | | | Geer | |

6. Once completed, your SSL certificate should be delivered to you via an email or other means. Copy the contents of the certificate in the email and paste it in a text/HTML/hex editor/converter, such as IDM Computer Solutions' UltraEdit.

| immediately, please dial 066.093.6565 or 650.476.5113 option 3 or send an email to internet-sales@verisign.com |
|--|
| Thank you for your interest in Symantee! |
| BEGIH CERTIFICATE BEGIH CERTIFICATE NITFROCAL YQAYIMA QUYACTANU YESBI SONQOONI LANEYAN KONAQUYADCE YYELMAKGALUENAKUVAK FAVNANYA YESBI SONQOONI LANEYAN KONAQUYADCE EYHESIGYVYACBQKXAN SIIL-QYERMAXSLAQTING YYNANYA YWYQO BATOWI HENI COMMUNYA SONCOM KANONYA YWYQO BATOWI HENI COMMUNYA SONCOM KANONYA YWYQO CARAFYYANI SONCOM KANONYA YWYQO CARAFYYANI SONCOM KANONYA YWYQO QUYAANISYU YYYYACBONG SONCOM KANONYA YWYQO QUYAANISYU YYYYACBONG SONCOM KANONYA YWYQO QUYAANISYU YYYYYYI LIWYYY TATBONYSA SOTCOM YWYGU YYYAL SILIYAT YYYAHTIXMUU YUYYYYYAL HIWYY XTATBONYSA SOTCOM YWYGU YYYAL SILIYACH YYYAHTIXMUU YUYYAL HIWYY XTATBONYSA SOTCOM YWYGU YYYAL SILIYACH YYYAHTIXMUU YUYYAL HIWYY XTATBONYSA SOTCOM YWYGU YYYAL SILIYACH YYYAHTIXMUU YUYYAL HIWYYA YTATBONYSA SOTCOM YWYGU YYYAL SILIYACH YYYAHTIXMUU YUYYAL HIWYYA YTATBONYSA SOTCOM YYYAL SILIYACH YYYAHTIXMUU YUXYAL HIWYYA YYYYYYYYYYYA YYYAHTIXMUU YUXYAL HIWYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYY |
| |

7. Open a new edit, paste the certificate contents, and press ENTER at the end of the contents to add an empty line.

| | | 60 |
|---|---|----------------------------------|
| | X Centre · | a x i |
| At: At: At: Ct: Ct: Ct: Ct: Ct: Ct: Ct: Ct: Ct: C | Conception Concepting Concepting Concepting Concepting Concepting C | ant Holby Macro Lut. Scritt Litt |
| | | 2041, Manager |

8. Convert file format from DOS to UNIX. Open File menu > Conversions > DOS to Unix.

| | tide Search Insert Prop jew gen Jack Open Jace Jace Al Piles Except This TP/Toilwit come to Second jew are Al | ct Veew Form Chi+N Chi+O Chi+Q Chi+Shift+P4 Chi+S F12 | CI X CSAGG+EUEEX L1XVCy90230 dIwQYNBoAFCo | 20. 20. 20. DuHTAVRggt BgR NOY2 EwBoyDVRd | арана И И И И И И И И И И И И И И И И И И | Contractory 93 state united | Nya3Np224u | | • • x) |
|------------------|--|---|--|---|---|--|-------------------|---------------------|--------|
| | Jack Open Jose Jose Al Biles Jose Al Piles Except Tijs Tip/Teiluet Tip/Teiluet Tip/Teiluet Seven Jove Ave Bd | Corl+Q Corl+Shift+F4 Corl+S | ti x DSAGG+EUBEX tL2Necy90230 dIwQYMBaAPC | 20 Dumtavnggr bgr NOV2 Ewiloyddyrad | 30. УВQоСАРТЈАНЗ | Contractory 93 state united | Ja NywXDp 224u | | _ |
| | Jose Jose Al Eles Jose Al Files Except Tijs "IP/Teluet control Except Jore Are Bd | Corl+Shift+F4 | ti x DSAGG+EUBEX tL2Necy90230 dIwQYMBaAPC | 20 Dumtavnggr bgr NOV2 Ewiloyddyrad | 30. УВQоСАРТЈАНЗ | toeHR6Ly93d3cudm | Nya3Np224u | and a second second | * a x |
| | Jose Al Elles Jose Al Files Except This "IP/Tobiet control Except Jore Are Bd | , Col+S | 10 OSAGG+EUREx tL2Nwcy90230 dIwQYMBaAFC | Uwntavbggrbgb NOV2EwnQYDVR0 | FBQeCARTjaH | toeHR6Ly93d3cudm | Nya3Np224u | and a second second | |
| F S S S | Rose All Files Except Tigs (P/Toket (cont to Sover) and As | , Col+S | 10 OSAGG+EUREx tL2Nwcy90230 dIwQYMBaAFC | Uwntavbggrbgb NOV2EwnQYDVR0 | FBQeCARTjaH | toeHR6Ly93d3cudm | Nya3Np224u | and a second second | |
| F | (IP/Tohiet revent to Sover) lave As | Corl+S | GSAGG+EUREx tl2Nwcy90233 dIwQYMBaAFC | Uwntavbggrbgb NOV2EwnQYDVR0 | FBQeCARTjaH | toeHR6Ly93d3cudm | Nya3Np224u | and a second second | |
| | event to Soverf . lave lave As | Corl+S | GSAGG+EUREx tl2Nwcy90233 dIwQYMBaAFC | Uwntavbggrbgb NOV2EwnQYDVR0 | FBQeCARTjaH | toeHR6Ly93d3cudm | Nya3Np224u | | |
| | ave ave <u>8</u> 5 | 01005-0 | tl2Nwcy90233 dIwQYMBaAFC | NOY2 EwHQYDVRO | | | | | |
| | ave ave <u>8</u> 5 | 01005-0 | | 1000 C 1000 C 1000 C 1000 | A ADA A WE ALL ARMS | BBQUEAvEGCCsGAQ | UFBWMCMB8G | | |
| 5 | ave As | 01005-0 | the Date of Distance & State | | | 1MHQGCCaGAQUFBw | | | |
| 111 | 20220 | | | | | p234u729tMD4GCC | | | |
| | arc re | AR+F12 | | | | .zaWduLmNvbS9TV1 iIae/X7T6z/zzr9z | | | |
| -11- | ere Sendon Ak | PRITIA | | | | LFXAEUITr3W19Co | | | |
| -103 | take Copy/Backup | | | | | Tu3pWeAKbAH/U+x | | | |
| - 19 | and the second | | | | | Presv7oErbnLhup InhCHUwwgOxNBuce | | | |
| | noryption | | | | | iZARPH/gi//XeGg | | | |
| R R | tename File | | END CERTIN | ICATE | | | | | |
| 2 0 | logpare | Alt+F11 | | | | | | _ | |
| - 5 | iet - | • | 1 | | | | | | |
| - 0 | ionversions. | | TINED WAS TO | DOS | | | | | |
| 3 | ipecial Functions | , | DOS to MAC | | | | | | |
| H B | 999 | Other | DOS to UNIX | | | - | | . A | |
| (P | rist All Files | | EBCDOC to AS | ctt | | and a second sec | | | |
| P | mnt Preview | | ASCEL to good | DDC | | mplate List | | | |
| P | vint Setup/Configuration | • | CEM to ANST | | | Gobal | | | _ |
| 0 F | agorte Piles | Ctrl+Shift+F | ANSI IN CEM | | | Power User | | | |
| R | lecent Files | | ASCIL to Unio | xde - | | | | | |
| R | ecent Projects/WorkSpace | | LITT-E La Litta | | | | | | |
| | st. | | La tawarde to A3 | | | | | | |

| | ave As | | | | | <u>?</u> × | |
|---|---|--|---|---|-----------|-----------------|---|
| + 8 x lect Open Explorer Lists | Save in | Desktop | | 203 | | | |
| A: C: D: F: F: Network FTP Accounts | My Placeret Documentol Desit trap Desit trap My Documentol My Computer | My Documents My Computer My Ketwork Pl Adobe Reader Frézilis Clerk Gougle Chrom Distalation W UrveClerk Mozéla Frefox Misstone XPro Mozéla Frefox Playback QuiciTime Ra QuiciTime Ra ReaPlayer | aces 9 e and 2 ty Scan Has tect Smart Client ver | LitraCompare UtraEdt WVV0TDK EliacitholePM 44 45 46 802.1x | 2.用資料文 ((| (15° Blackhole) | |
| | - | Team//lewer 6 | | activeX_plugi | ni | 2 | |
| | My Natural Places | File name: | CAceit.cit | | • | Save | |
| | NICE AL | Save at type: | All Files. (".") | | - | Cancel | |
| 1 21 | | Line Terminator: | Default | | - | | 1 |
| المرودة لا | | Format: | Defailt | | * | | |
| | | | Leave as "Dela /" h | e norma une se charge auterel | r. | | |
| | | ADS Stream: | - | defor Beschilltäden | - | | |

9. Save the edit using the ".crt" extension, using a file name like "CAcert.crt."

10. Return to the original firmware session, use the **Browse** button to locate the crt certificate file, and click **Upload** to enable the certification.

| SUPREME | | Home Client settings Contiguration Langu | | |
|---------------|-----------------------------|--|--|--|
| | Security > HTTPS | | | |
| System | P HTTPS | | | |
| Madia | Enable HTTPS secure connect | bon | | |
| Network | - Mode | | | |
| Security | F HITP & HTTPS C HTTPS only | | | |
| User accounts | 🛩 Certificate: | | | |
| HTTPS | Certificate information | | | |
| Access list | Status: | Waiting for contificated | | |
| BEE 802.1x | Select certificate file: | CiDocuments and Se Drowse. Upload | | |
| PTZ | Method: | Create certificate request and install | | |
| Event | Country. | TW | | |
| Applications | State or province: | Asia | | |
| | Locality | Asia | | |
| Recording | Organization: | VIVOTEK Inc. | | |
| local storage | Organization unit | VIVOTEK Inc. | | |
| | Common name: | www.vivalek.com | | |
| (Basic mode) | | Remove certificate | | |

11. When the certifice file is successfully loaded, its status will be stated as **Active**. Note that a certificate must have been created and installed before you can click on the "**Save**" button for the configuration to take effect.

| Mode: | |
|-------------------------|---|
| I HTTP&HTTPS C HT | TPS only |
| Certificate: | |
| Certificate information | |
| Status: | Active |
| Method | Create certificate request and install |
| Country: | TW |
| State or province: | Asia |
| Locality: | Asia |
| Organization. | VIVOTEK Inc. |
| Organization unit | VIVOTEK Inc. |
| Common name: | www.vivotek.com |
| | Certificate properties Remove certificate |

12.To begin an encrypted HTTPS session, click **Home** to return to the main page. Change the URL address from "<u>http://</u>" to "<u>https://</u>" in the address bar and press **Enter** on your keyboard. Some Security Alert dialogs will pop up. Click **OK** or **Yes** to enable HTTPS.

| Security Alert | | | Security | Information | |
|-----------------------|---|--|--|---|---|
| Any infor viewed b | about to view pages over a secur nation you exchange with this site y anyone else on the Web. future, do not show this warning OK | | £ | This page contains bot items. Do you want to display Yes | th secure and nonsecure the nonsecure items? No More Info |
| | Securi | changed by others. How security certificate. The security certifinot chosen to trust you want to trust the security certifies The security certifies | security certificate is invalid or d the site | e site's you have ne whether loes not | |

Security > Access List

This section explains how to control access permission by verifying the client PC's IP address.

General Settings

| Γ | General settings | | | |
|---|---------------------------------------|---------|-----------------------|--|
| | Maximum number of concurrent streamin | g: 10 💌 | Connection management | |

<u>Maximum number of concurrent streaming connection(s) limited to</u>: Simultaneous live viewing for 1~10 clients (including stream 1 to stream 3). The default value is 10. If you modify the value and click **Save**, all current connections will be disconnected and automatically attempt to re-link (IE Explorer or Quick Time Player).

<u>View Information</u>: Click this button to display the connection status window showing a list of the current connections. For example:

| | IP address | | | |
|---|------------|------------------|------------|-------|
| | 172.1 | 6.2.53 | 00:00:05 | |
| | 192.16 | 8.4.104 | 01:49:35 | |
| F | Refresh | Add to deny list | Disconnect | Close |

Note that only consoles that are currently displaying live streaming will be listed in the View Information list.

- IP address: Current connections to the Network Camera.
- Elapsed time: How much time the client has been at the webpage.
- User ID: If the administrator has set a password for the webpage, the clients have to enter a user name and password to access the live video. The user name will be displayed in the User ID column. If the administrator allows clients to link to the webpage without a user name and password, the User ID column will be empty.

There are some situations that allow clients access to the live video without a user name and password:

- 1. The administrator does not set up a root password. For more information about how to set up a root password and manage user accounts, please refer to Security > User account on page 87.
- 2. The administrator has set up a root password, but set **RTSP Authentication** to "disable". For more information about **RTSP Authentication**, please refer to RTSP Streaming on page 78.
- 3. The administrator has set up a root password, but allows anonymous viewing. For more information about **Allow Anonymous Viewing**, please refer to page 87.

- Refresh: Click this button to refresh all current connections.
- Add to deny list: You can select entries from the Connection Status list and add them to the Deny List to deny access. Please note that those checked connections will only be disconnected temporarily and will automatically try to re-link again (IE Explore or Quick Time Player). If you want to enable the denied list, please check Enable access list filtering and click Save in the first column.
- Disconnect: If you want to break off the current connections, please select them and click this button. Please note that those checked connections will only be disconnected temporarily and will automatically try to re-link again (IE Explore or Quick Time Player).

Filter

<u>Enable access list filtering</u>: Check this item and click **Save** if you want to enable the access list filtering function.

<u>Filter type</u>: Select **Allow** or **Deny** as the filter type. If you choose **Allow Type**, only those clients whose IP addresses are on the Access List below can access the Network Camera, and the others cannot. On the contrary, if you choose **Deny Type**, those clients whose IP addresses are on the Access List below will not be allowed to access the Network Camera, and the others can.

| Filter | |
|--|--|
| Enable access list filtering | |
| Filter type: C Allow @ Deny | |
| IPv4 access list | |
| | |
| | |
| | |
| Add Delete | |
| IPvő access list | |
| | |
| | |
| La contra de la co | |
| Add Delete | |

Then you can **Add** a rule to the following Access List. Please note that the IPv6 access list column will not be displayed unless you enable IPv6 on the Network page. For more information about **IPv6 Settings**, please refer to Network > General settings on page 69 for detailed information.

There are three types of rules:

<u>Single</u>: This rule allows the user to add an IP address to the Allowed/Denied list. For example:

| Filter address | |
|-------------------------|--|
| Rule: Single | |
| IP address: 192.168.2.1 | |
| OK Cancel | |

<u>Network</u>: This rule allows the user to assign a network address and corresponding subnet mask to the Allow/Deny List. The address and network mask are written in CIDR format. For example:

| Filter address | |
|------------------------------------|-----------------|
| Rule: Network | |
| Network address / Network mask: 19 | 02.168.2.0 / 24 |
| OK Cancel | |
| | |

IP address range 192.168.2.x will be bolcked.

If IPv6 filter is preferred, you will be prompted by the following window. Enter the IPv6 address and the two-digit prefix length to specify the range of IP addresses in your configuration.

| 'liter address | |
|---------------------------------|---|
| Rule: Network | |
| Network address / Network mask: | 1 |

<u>Range</u>: This rule allows the user to assign a range of IP addresses to the Allow/Deny List. Note: This rule only applies to IPv4 addresses. For example:

| Filter address | | | |
|--------------------------|-------------|-----------------|--|
| Rule: Range 💌 | | | |
| IP address - IP address: | 192.168.2.0 | - 192.168.2.255 | |

Administrator IP address

<u>Always allow the IP address to access this device</u>: You can check this item and add the Administrator's IP address in this field to make sure the Administrator can always connect to the device.

| Administrator IP address | |
|---|------|
| Always allow the IP address to access this device | |
| | Save |

Security > IEEE 802.1X

Enable this function if your network environment uses IEEE 802.1x, which is a port-based network access control. The network devices, intermediary switch/access point/hub, and RADIUS server must support and enable 802.1x settings.

The 802.1x standard is designed to enhance the security of local area networks, which provides authentication to network devices (clients) attached to a network port (wired or wireless). If all certificates between client and server are verified, a point-to-point connection will be enabled; if authentication fails, access on that port will be prohibited. 802.1x utilizes an existing protocol, the Extensible Authentication Protocol (EAP), to facilitate communication.

■ The components of a protected network with 802.1x authentication:



- 1. Supplicant: A client end user (camera), which requests authentication.
- 2. Authenticator (an access point or a switch): A "go between" which restricts unauthorized end users from communicating with the authentication server.
- 3. Authentication server (usually a RADIUS server): Checks the client certificate and decides whether to accept the end user's access request.
- VIVOTEK Network Cameras support two types of EAP methods to perform authentication: EAP-PEAP and EAP-TLS.

Please follow the steps below to enable 802.1x settings:

- 1. Before connecting the Network Camera to the protected network with 802.1x, please apply a digital certificate from a Certificate Authority (i.e., your network administrator) which can be validated by a RADIUS server.
- Connect the Network Camera to a PC or notebook outside of the protected LAN. Open the configuration page of the Network Camera as shown below. Select EAP-PEAP or EAP-TLS as the EAP method. In the following blanks, enter your ID and password issued by the CA, then upload related certificate(s).


| IEEE 802.1x | |
|--------------------|---------------|
| Enable IEEE 802.1x | |
| EAP method: | EAP-PEAP 💌 |
| Identity: | |
| Password: | |
| CA certificate: | Browse Upload |
| Status: no file | Remove |
| | |

| IEEE 802.1x | |
|----------------------|---------------|
| Enable 802.1x | |
| EAP method: | EAP-TLS 💌 |
| Identity: | |
| Private key passord: | |
| CA certificate: | Browse Upload |
| Status: no file | Remove |
| client certificate: | Browse Upload |
| Status: no file | Remove |
| Client private key: | Browse Upload |
| Status: no file | Remove |
| | |

3. When all settings are complete, move the Network Camera to the protected LAN by connecting it to an 802.1x enabled switch. The devices will then start the authentication automatically.



- ► The authentication process for 802.1x:
- 1. The Certificate Authority (CA) provides the required signed certificates to the Network Camera (the supplicant) and the RADIUS Server (the authentication server).
- 2. A Network Camera requests access to the protected LAN using 802.1X via a switch (the authenticator). The client offers its identity and client certificate, which is then forwarded by the switch to the RADIUS Server, which uses an algorithm to authenticate the Network Camera and returns an acceptance or rejection back to the switch.
- 3. The switch also forwards the RADIUS Server's certificate to the Network Camera.
- 4. Assuming all certificates are validated, the switch then changes the Network Camera's state to authorized and is allowed access to the protected network via a pre-configured port.



PTZ > PTZ settings

This section explains how to control the Network Camera's Pan/Tilt/Zoom operation.

Digital: Control the e-PTZ operation. Within a field of view, it allows users to quickly move the focus to a target area for close-up viewing without physically moving the camera.

Digital PTZ Operation (E-PTZ Operation)

The e-PTZ control settings section will be displayed as shown below:

| OP-V) | 2015/ | 05/2 | 0 09:57:30 | | | | |
|---|-------|------|--|---------------|------------------------|---------|-----|
| < 1.8 | - | | | • | Home | | ۲ |
| | - | | - | | | | |
| | | p. | | * | Zoom | | • |
| | - | | and a state | Pan spe | 251 | 0 | 1 |
| 59 Jan | | | | Tilt spee | | 0 | _ |
| | - | - | | Zoom sp | | 0 | _ |
| | - | 00 | | Go to: | /patrol speed. | 1 | - |
| Pal | | | - | - Selec | t one | | |
| Preset and patrol settings | | | Select Preset I | Locations for | Patrol | | |
| ame: Add preset location | | | Select Preset | | | vell ti | |
| ame: Add preset location | | | Patrol lor | | Dv | | |
| ame: Add preset location | | | Patrol los | | | | |
| ame: Add preset location Image: Vser preset locations Image: lower left | | > | Patrol los | | D v 5 | | |
| ame: Add preset locations Image: Add preset locations Image: I | | | Patrol los | | D* 5 | | ec) |
| ame: Add preset locations Image: Add preset locations Image: User preset locations Image: lower left Image: center Image: right | | | Patrol loo upper left left lower left | | D* 5 5 | | ec) |
| ame: Add preset locations Invertent Invertight | | | Patrol los upper left left lower left center right | | D* 5 5 5 5 | | ec) |
| ame: Add preset locations Invertent Invertight | | | Patrol los upper left left lower left center right | calions | D* 5 5 5 5 | (s | ec) |

For e-PTZ related details, please refer to page 102.

Auto pan/patrol speed: Select the speed from 1~5 (slow/fast) to set up the Auto pan/patrol speed control.

Zoom factor display

If you check this item, the zoom indicator will be displayed on the home page when you zoom in/out the live viewing window as the picture shown on the next page.

When completed with the e-PTZ settings, click **Save** to enable the settings on this page.

Home page in the E-PTZ Mode



- The e-Preset Positions will also be displayed on the home page. Select one from the drop-down list, and the Network Camera will move to the selected position.
- If you have set up different preset positions for different streams, you can select one of the video streams to display its separate preset positions.

Global View

In addition to using the e-PTZ control panel, you can also use the mouse to drag or resize the floating frame to pan/tilt/zoom the viewing region. The live view window will also move to the viewing region accordingly.

Moving Instantly

If you check this item, the live view window will switch to the new viewing region instantly after you move the floating frame. If not selected, the process of moving from one position to another will be shown.

Click on Image

The e-PTZ function also supports "Click on Image". When you click on any point of the Global View Window or Live View Window, the viewing region will also move to that point.


Note that the "Click on Image" function only applies when you have configured a smaller "Region of Interest" out of the maximum output frame! e.g., an 800 x 600 region from out of the camera's maximum frame size.

<u>Patrol button</u>: Click this button, then the Network Camera will patrol among the selected preset positions continuously.

Patrol settings

You can select some preset positions for the Network Camera to patrol.

- Please follow the steps below to set up a patrol schedule:
- 1. Select the preset locations on the list, and click \ge .
- 2. The selected preset locations will be displayed on the Patrol locations list.
- 3. Set the **Dwelling time** for the preset location during an auto patrol.
- 4. If you want to delete a preset location from the Patrol locations list, select it and click **Remove**.
- 5. Select a location and click 🚺 🔽 to rearrange the patrol order.
- 6. Select patrol locations you want to save in the list and click **Save** to enable the patrol settings.
- 7. To implement the patrol schedule, please go to homepage and click on the **Patrol** button. Please refer to the next page.





► The Preset Positions will also be displayed on the Home page. Select one from the **Go to** menu, and the Network Camera will move to the selected preset position.

► Click Patrol: The Network Camera will patrol along the selected positions repeatedly.

Event > Event settings

This section explains how to configure the Network Camera to respond to particular situations (event). A typical application is that when a motion is detected, the Network Camera sends buffered images to an FTP server or e-mail address as notifications. Click on **Help**, there is an illustration shown in the pop-up window explaining that an event can be triggered by many sources, such as motion detection or external digital input devices. When an event is triggered, you can specify what type of action that will be performed. You can configure the Network Camera to send snapshots or videos to your email address or FTP site.

| Event | | | | | | | |
|-------|------------|-----|---|------------------|-------------|-----------------|------------------|
| Name | Status Sun | Mon | Tue Wed | Thu F | ri Sat | Time | Trigger |
| Add | Help | | Event Trigg Ex. Motion detection Digital input, Sy | n, Periodically, | Actio | on (What to do) | close or Esc Key |
| | | | | Media (Wha | et to send) | Ex. | |

Event

To configure an event with reactive measures such as recording video or snapshots, it is necessary to configure the server and media settings so that the Network Camera will know what action to take (such as which server to send the media files to) when a trigger is activated. An event is an action initiated by a user-defined trigger source. In the **Event** column, click **Add** to open the event settings window. Here you can arrange three elements -- Schedule, Trigger, and Action to set an event. A total of 3 event settings can be configured.

| Event — | |
|------------------------------|---|
| Name S | status Sun Mon Tue Wed Thu Fri Sat Time Trigger |
| Add | Help |
| - | |
| Event name: | |
| Enable this event | |
| Priority: Normal 💌 | |
| Detect next motion detection | on or digital input after 10 second(s). |
| | Event Schedule |
| 1. Schedule | Sun V Mon V Tue V Wed V Thu V Fr V Sat |
| | Time |
| | 👻 Aways |
| Company of the Party of the | From 00.00 to 24.00 [bh.mm] |
| 2. Trigger | |
| | |
| - | |
| 3. Action | |
| | |
| | |
| | |
| | Save event Olizee |

- Event name: Enter a name for the event setting.
- Enable this event: Select this option to enable the event setting.
- Priority: Select the relative importance of this event (High, Normal, or Low). Events with a higher priority setting will be executed first.
- Detect next event after seconds: Enter the duration in seconds to pause motion detection after a motion is detected. This can prevent event-related actions to take place too frequently.

1. Schedule

Specify the period of them during which the event trigger will take effect. Please select the days of the week and the time in a day (in 24-hr time format) for the event triggering schedule. For example, you may prefer an event to be triggered only during the off-office hours.

2. Trigger

This is the cause or stimulus which defines when to trigger the Network Camera. The trigger source can be configured to use the Network Camera's built-in motion detection mechanism or external digital input devices.

There are several choices of trigger sources as shown on the next page. Select the item to display the detailed configuration options.

Video motion detection

This option makes use of the built-in motion detection mechanism as a trigger source. To enable this function, you need to configure a Motion Detection Window first. For more information, please refer to Motion Detection on page 118 for details.

| Video motion detection | |
|------------------------|-------------------------------|
| Normal: 📄 door | |
| Profile: 📄 hallway | |
| Note: Please configure | <u>Motion detection</u> first |

Periodically

This option allows the Network Camera to trigger periodically for every other defined minute. Up to 999 minutes are allowed.



Trigger every other 1 minutes

System boot

This option triggers the Network Camera when the power to the Network Camera is disconnected and re-connected.

Recording notify

This option allows the Network Camera to trigger when the recording disk is full or when recording starts to overwrite older data.

Audio detection

A preset threshold can be configured with an external microphone as the trigger to system event. The triggering condition can be an input exceeding or falling below a threshold. Audio detection can take place as a complement to motion detection or as a method to detect activities not covered by the camera's view.

Camera tampering detection

This option allows the Network Camera to trigger when the camera detects that is is being tampered with. To enable this function, you need to configure the Tampering Detection option first. Please refer to page 122 for detailed information.

|] Tampering detection | | | |
|-----------------------|----|------------------|--|
| Trigger duration 1 | 0 | seconds [10-600] | |
| Trigger threshold | 12 | [0~100] | |

Manual Triggers

This option allows users to enable event triggers manually by clicking the on/off button on the homepage. Please configure 1 to 3 associated events before using this function.

Manual Trigger

1 2 3



VADP

It is presumed that you already uploaded and enabled the VADP modules before you can associatee VADP triggers with an Event setting.

Click on the Set VADP Trigger button to open the VADP setup menu. The triggering conditions available with 3rd-party software modules known as VADP will be listed. Use the arrow buttons to select these triggers. Users may implant these modules for different purposes such as triggering motion detection, or applications related to video analysis, etc. Please refer to page 125 for the configuration options with VADP modules.

| t VADP Trigger | |
|---|-----------------------------|
| ADP Triggers | Triggers for Event Settings |
| ManualTrigger TriggerA TriggerB TriggerC TriggerD | >> |
| | Close Save |
| | |
| | |

Once the triggers are configured, they will be listed under the VADP option.

| VADP | | |
|------------------|--|------|
| TriggerD | | |
| TriggerA. | | |
| V TriggerB | | |
| TriggerC | | |
| Set VADP Trigger | | |
| ManualTrigger | >> << TriggerD TriggerA TriggerB TriggerC | |
| | Close | Save |

3. Action

Define the actions to be performed by the Network Camera when a trigger is activated.

| Action — | | |
|----------|---------------------|---|
| 🔲 Backup | media if the networ | k is disconnected |
| Server | Media | Extra parameter |
| SD | None 💌 | SD test View |
| HTTP | None 💌 | |
| 🔲 nas | None 💌 | Create folders by date time and hour automatically <u>View</u> |
| Add serv | er 💟 Add med | <u>tia</u> 💟 |
| | | |

Backup media if the network is disconnected

Select this option to backup media file on SD card if the network is disconnected. This function will only be displayed after you set up a network storage (NAS). The media to back up can include snapshot images, video, or system logs depending on your event settings.

Add server

It is necessary to configure the server and media settings so that the Network Camera will know what action to take (such as which server to send the media files to) when a trigger is activated. Click **Add server** to open the server setting window. You can specify where the notification messages are sent to when a trigger is activated. A total of 5 server settings can be configured.

There are four choices of server types available: Email, FTP, HTTP, and Network storage. Select the item to display the detailed configuration options. You can configure either one or all of them.

| Add server | Add media 💟 | | |
|--------------|----------------------|-----------------------|-------|
| Server name: | Email | | |
| Server type | | | |
| Email | | | |
| Sender e | email address: | Camera@vivotek.com | |
| Recipien | t email address: | recipient@vivotek.com | |
| Server a | ddress: | Ms.vivotek.tw | |
| User nar | me: | user | |
| Passwor | rd: | ••••• | |
| Server po | ort | 25 | |
| This | server requires a se | cure connection (SSL) | |
| ◎ FTP | | | |
| HTTP | | | |
| Network sto | rage | | |
| | Test | Save server | Close |

Server type - Email

Select to send the media files via email when a trigger is activated.

- Server name: Enter a name for the server setting.
- Sender email address: Enter the email address of the sender.
- Recipient email address: Enter the email address of the recipient.
- Server address: Enter the domain name or IP address of the email server.
- User name: Enter the user name of the email account if necessary.
- Password: Enter the password of the email account if necessary.
- Server port: The default mail server port is set to 25. You can also manually set another port.

If your SMTP server requires a secure connection (SSL), select **This server requires a secure connection (SSL)**.

To verify if the email settings are correctly configured, click **Test**. The result will be shown in a pop-up window. If successful, you will also receive an email indicating the result.

| 🗈 kily (1922 Mill 5, 1916 gelandelmarkistarier og 👘 📰 🐻 | 🗿 bilg #192.168.5.131A.g-Siebelandbelarren ogi - 👘 💽 🔯 |
|---|--|
| The email has been sent successfully. | Error in sending email. |
| | |

Click **Save server** to enable the settings.

Note that after you configure the first event server, the new event server will automatically display on the Server list. If you wish to add other server options, click **Add server**.

| Se | rver | Media | | | Extra parameter | |
|-------|-------|-------------|----------------|------|-----------------|--|
| SD |) | None 💌 | <u>SD test</u> | View | | |
| En En | nail | None 💌 | | | | |
| Add s | serve | r 💟 Add med | lia 🔽 | | | |

Server type - FTP

Select to send the media files to an FTP server when a trigger is activated.

| ftp.vivotek.com |
|------------------------|
| 21 |
| vivotek |
| ••••• |
| |
| |
| |
| |
| Test Save server Close |
| |

- Server name: Enter a name for the server setting.
- Server address: Enter the domain name or IP address of the FTP server.
- Server port: By default, the FTP server port is set to 21. It can also be assigned to another port number between 1025 and 65535.
- User name: Enter the login name of the FTP account.
- Password: Enter the password of the FTP account.
- FTP folder name

Enter the folder where the media files will be placed. If the folder name does not exist, the Network Camera will automatically create one on the FTP server.

Passive mode

Most firewalls do not accept new connections initiated from external requests. If the FTP server supports passive mode, select this option to enable passive mode FTP and allow data transmission to pass through the firewall. The firmware default has the Passive mode checkbox selected.

To verify if the FTP settings are correctly configured, click **Test**. The result will be shown in a pop-up window as shown below. If successful, you will also receive a test.txt file on the FTP server.



Click Save server to enable the settings.

Server type - HTTP

Select to send the media files to an HTTP server when a trigger is activated.

| Server name: HTTP | | | |
|-------------------|----------------|-----------------------|-------|
| Server Type | | | |
| 🔘 Email | | | |
| ◎ FTP | | | |
| HTTP | | | |
| URL: | http://192.168 | .5.10/cgi-bin/upload. | cgi |
| User name: | | | |
| Password: | | | |
| Network storage | | | |
| | Test | Save server | Close |

- Server name: Enter a name for the server setting.
- URL: Enter the URL of the HTTP server.
- User name: Enter the user name if necessary.
- Password: Enter the password if necessary.

To verify if the HTTP settings are correctly configured, click **Test**. The result will be shown in a pop-up window as shown below. If successful, you will receive a test.txt file on the HTTP server.

| ttp://192.168.5.121/cgi-bin/admin/testserver.cgi 🔳 🗖 🗙 | http://192.168.5.121/cgi-bin/admin/testserver.cgi |
|--|---|
| TTP Transmission successfully. Thanks | HTTP Transmission failed. |
| | |
| | |

Click Save server to enable the settings.

Network storage:


Select to send the media files to a networked storage when a trigger is activated. Please refer to **NAS** server on page 130 for details. Note that only one NAS server can be configured.

| Click Save | e server to | enable | the settings. |
|------------|-------------|--------|---------------|
|------------|-------------|--------|---------------|

| Action — | | | | | | |
|-----------|---------------------|---------------------|-------------|---------------|----------|-------------------|
| | | | | | | |
| Backup I | media if the networ | k is disco | onnecte | t | | |
| Server | Media | | | Extra pa | arameter | |
| SD | None 💌 | <u>SD test</u> | <u>View</u> | | | |
| Email | None 💌 | | | | | |
| FTP | None 💌 | | | | | |
| HTTP | None 💌 | | | | | |
| NAS | None 💌 | Crea <u>View</u> | ate folde | rs by date ti | me and h | our automatically |
| Add serve | er 💟 Add med | lia 🔽 | | | | |
| | | | | Clo | se | Save event |

- SD Test: Click to test your SD card. The system will display a message indicating the result as a success or a failure. If you want to use your SD card for local storage, please format it before use. Please refer to page 113 for detailed information.
- View: Click this button to open a file list window. This function is only for SD card and Network Storage. If you click the View button for an SD card, a Local storage page will prompt so that you can manage the recorded files on SD card. For more information about Local storage, please refer to page 132. If you click the View button for a Network storage, a file directory window will prompt for you to view recorded data on Network storage. For detailed illustration, please refer to the next page.
- Create folders by date, time, and hour automatically: If you select this item, the system will automatically create folders by the date when video footages are stored onto the networked storage.

The following is an example of a file destination with video clips:



Click to delete selected items

Click 20150120 to open the directory:

The format is: HH (24r)

Click to open the file list for that hour

| < 07 <u>08 09 10 11</u> | <u>12 13 14 1</u> | . <u>5 16 17 ≥</u> | | | |
|--|-------------------|--------------------|----------|--|--|
| file name | size | date | time | | |
| Recording1 58.mp4 | 2526004 | 2015/01/20 | 07 58 28 | | |
| Recording1 59.mp4 | 2563536 | 2015/01/20 | 07 59 28 | | |
| Delete all Back | | | | | |
| Click to delete Click to go back to the previous selected items level of the directory | | | | | |

Click to delete all recorded data

| | < 07 <u>08 09 10 11</u> | <u>12 13 14 1</u> | <u>5 16 17 ></u> | | |
|-----------------|-------------------------|-------------------|---------------------|----------|--|
| | file name | size | date | time | |
| | Recording1 58.mp4 | 2526004 | 2015/01/20 | 07:58:28 | |
| | Recording1 59.mp4 | 2563536 | 2015/01/20 | 07:59:28 | |
| Delete all Back | | | | | |

The format is: File name prefix + Minute (mm)

You can set up the file name prefix on Add media page. Please refer to next page for detailed information.

Add media

Click **Add media** to open the media setting window. You can specify the type of media that will be sent when a trigger is activated. A total of 5 media settings can be configured. There are three choices of media types available: Snapshot, Video Clip, and System log. Select the item to display the detailed configuration options. You can configure either one or all of them.

| Add server 💟 Add media |
|---------------------------------------|
| Media name: |
| Media type |
| Attached media: |
| Snapshot |
| Source: Stream 1 💌 |
| Send 1 pre-event image(s) [0~7] |
| Send 1 post-event image(s) [0~7] |
| File name prefix: Snapshot_ |
| Add date and time suffix to file name |
| Video clip |
| System log |
| Save media Close |

<u>Media type - Snapshot</u>

Select to send snapshots when a trigger is activated.

- Media name: Enter a name for the media setting.
- Source: Select to take snapshots from any of the video streams.
- Send □ pre-event images

The Network Camera has a buffer to temporarily hold data up to a certain limit. Enter a number to decide how many images to capture before a trigger is activated. Up to 7 images can be generated.

■ Send
post-event images

Enter a number to decide how many images to capture after a trigger is activated. Up to 7 images can be generated.

For example, if both the Send pre-event images and Send post-event images are set to 7, a total of 15 images can be generated after a trigger is activated.



■ File name prefix

Enter the text that will be appended to the front of the file name.

Add date and time suffix to the file name Select this option to add a date/time suffix to the file name. For example:

| Snapshot_2 | 0150513_100341 |
|------------------|--|
| 1 | ↑ |
| File name prefix | Date and time suffix The format is: YYYYMMDD_HHMMSS |

Click Save media to enable the settings.

Note that after you set up the first media server, a new column for media server will automatically display on the Media list. If you wish to add more media options, click **Add media**.

Media type - Video clip

Select to send video clips when a trigger is activated.


| Media name: | Video Clip |
|-------------|---|
| Media Ty | гре |
| Attached m | nedia: |
| 🔘 Sn | apshot |
| Vid | leo Clip |
| | Source: Stream 1 |
| | Pre-event recording: 0 seconds [0~9] |
| | Maximum duration: 5 seconds [1~20] |
| | Maximum file size: 500 Kbytes [50~4096] |
| | File name prefix: Video Clip_ |
| System | stem log |
| | Save media Close |

- Media name: Enter a name for the media setting.
- Source: Select a video stream as the source of video clip.
- Pre-event recording

The Network Camera has a buffer to temporarily hold data up to a certain limit. Enter a number to decide the duration of recording before a trigger is activated. Up to 9 seconds can be set.

Maximum duration

Specify the maximum recording duration in seconds. The duration can be up to 10 seconds. For example, if pre-event recording is set to five seconds and the maximum duration is set to ten seconds, the Network Camera continues to record for another 4 seconds after a trigger is activated.



Maximum file size

Specify the maximum file size allowed. Some users may need to stitch the video clips together when searching and packing up forensic evidence.

■ File name prefix

Enter the text that will be appended to the front of the file name.

For example:



Click Save media to enable the settings.

Media type - System log

Select to send a system log when a trigger is activated.

| Media name: System log | |
|------------------------|------------------|
| Media Type | |
| Attached media: | |
| Snapshot | |
| Video Clip | |
| System log | |
| | Save media Close |

Click **Save media** to enable the settings, then click **Close** to exit the page.

| Action — | | | | | |
|----------|--|----------------|-------------|-----------------|-------|
| Backup | media if the networ | k is disco | nnected | | |
| Server | Media | | | Extra parameter | |
| SD | None 💌 | <u>SD test</u> | <u>View</u> | | |
| mail | None None a email log snapshot | <u>lia</u> 💟 | | | |
| | | | | Save event | Close |

In the Event settings column, the Servers and Medias you configured will be listed; please make sure the Event -> Status is indicated as **ON**, in order to enable the event triggering action.

When completed, click the **Save event** button to enable the settings and click **Close** to exit Event Settings page. The new Event / Server settings / Media will appear in the event drop-down list on the Event setting page.

| Event | | | | | | | | | | | |
|-------------------------|-----------|---------------|-----|-----|-----|------|--------|-------|-------------|---------|--------|
| Name | Status | Sun | Mon | Tue | Wed | Thu | Fri | Sat | Time | Trigger | |
| event1 | <u>ON</u> | ۷ | ۷ | ۷ | ۷ | ۷ | V | ۷ | 00:00~24:00 | seq | Delete |
| Add | He | <u>lp</u> | | | | | | | | | |
| Server setting | gs — | | | | | | | | | | |
| Name | Туре | е | | | | Ado | Iress | /Loca | ation | | |
| HTTP | http |) | | | | http | ://192 | .168. | 5.10 | | Delete |
| Add | | | | | | | | | | | |
| Name <u>Snapshot</u> | s | Type napsi | | | | | | | | | Delete |
| Video clip | | ideoc | | | | | | | | | Delete |
| System log | Sy | /stem | log | | | | | | | | Delete |
| Add | | | | | | | | | | | |
| Customized | d script | | | | | | | | | | |
| Name | | Dat | е | | Ti | me | | | | | |
| Add | | | | | | | | | | | |
| | | | | | | | | | | | |

Please see the example of the Event setting page below:

When the Event Status is <u>ON</u>, the event configuration above is triggered by motion detection, the Network Camera will automatically send snapshots via e-mail.

If you want to stop the event trigger, you can click on the <u>ON</u> button to turn it to <u>OFF</u> status or click the **Delete** button to remove the event setting.

To remove a server setting from the list, select a server name from the drop-down list and click **Delete**. Note that you can only delete a server setting when it is not applied in an existing event setting.

To remove a media setting from the list, select a media name from the drop-down list and click **Delete**. Note that you can only delete a media setting when it is not applied in an existing event setting.


Customized Script

This function allows you to upload a sample script (.xml file) to the webpage, which will save your time on configuring the settings. Please note that there is a limited number of customized scripts you can upload; if the current amount of customized scripts has reached the limit, an alert message will prompt. If you need more information, please contact VIVOTEK technical support.



Applications > Motion detection

This section explains how to configure the Network Camera to enable motion detection. A total of 5 motion detection windows can be configured.



Follow the steps below to enable motion detection:

- 1. Click **New** to add a new motion detection window.
- 2. In the Window Name text box, enter a name for the motion detection window.
 - Use 4 mouse clicks to designate a detection window. You can change the window shape by dragging the corner marks to a preferred location.
 - Drag the item size tab to change the minimum size of item to trigger an alarm. An iten size box will appear in the center of screen for your reference. An intruding object must be larger than the Item size to trigger an alarm. Change the item size according to the live view.
 - To delete a window, click the X mark on the right of the window name.
- 3. Define the sensitivity to moving objects and the space ratio of all alerted pixels by moving the Sensitivity and Percentage slider bar.
- 4. Click **Save** to enable the settings.
- 5. Select Enable motion detection to enable this function.

2 Enable motion detection


For example:

| 068 06 | Modow name Motion 1 | 1 |
|--------|------------------------|---|
| | | |
| | | |

The Percentage Indicator will rise or fall depending on the variation between sequential images. When motions are detected by the Network Camera and are considered to exceed the preset threshold, the red bar rises. Meanwhile, the motion detection window will be outlined in red.

Photos or videos can be captured instantly and configured to be sent to a remote server (via an Email or FTP server). For more information on how to configure an event setting, please refer to Event settings on page 104.

A green bar indicates that even though motions have been detected, the event has not been triggered because the image variations still fall under the preset threshold.



If you want to configure other motion detection settings for day/night/schedule mode (e.g., for a different lighting condition or for the off-office hours), please click **Profile** to open the Motion Detection Profile Settings page as shown below. Another three motion detection windows can be configured on this page.


| | 068 | Window Motion | 11 | 38 |
|------------------|-----|------------------|---|----|
| Sensitivity: 80% | | • N | able to apply these s ight mode chedule mode [hh: | |

Please follow the steps beolw to set up a profile:

- 1. Create a new motion detection window.
- 2. Click the **Profile mode** tab.
- 3. Select the applicable mode: Night mode or Schedule mode. Please manually enter a time range if you choose Schedule mode.
- 4. Click **Save** to enable the settings and click **Close** to exit the page.

This motion detection window will also be displayed on the Event Settings page. You can go to **Event** > **Event settings** > **Trigger** to select it as a trigger source. Please refer to page 128 for detailed information.

NOTE:



How does motion detection work?

There are two motion detection parameters: Sensitivity and Percentage. In the illustration above, frame A and frame B are two sequential images. Pixel differences between the two frames are detected and highlighted in gray (frame C) and will be compared with the sensitivity setting. Sensitivity is a value that expresses the sensitivity to moving objects. Higher sensitivity settings are expected to detect slight movements while smaller sensitivity settings will neglect them. When the sensitivity is set to 70%, the Network Camera defines the pixels in the purple areas as "alerted pixels" (frame D).

Percentage is a value that expresses the proportion of "alerted pixels" to all pixels in the motion detection window. In this case, 50% of pixels are identified as "alerted pixels". When the percentage is set to 30%, the motions are judged to exceed the defined threshold; therefore, the motion window will be outlined in red.

For applications that require a high level of security management, it is suggested to use higher sensitivity settings and smaller percentage values.

Applications > Tampering detection

This section explains how to set up camera tamper detection. With tamper detection, the camera is capable of detecting incidents such as **redirection**, **blocking or defocusing**, or even **spray paint**.

| Camera tampering detection | |
|--------------------------------------|------|
| Tampering detection | |
| Trigger duration 10 seconds [10~600] | |
| Trigger threshold 12 [0~100] | |
| Image too dark detection | |
| Trigger duration 2 seconds [1~10] | |
| Trigger threshold 15 [0~100] | |
| Image too bright detection | |
| Trigger duration 2 seconds [1~10] | |
| Trigger threshold 15 [0~100] | |
| Image too blurry detection | |
| Trigger duration 7 seconds [1~10] | |
| Trigger threshold 12 [0~100] | |
| | Save |
| | Jave |

Please follow the steps below to set up the camera tamper detection function:

- 1. Check Enable camera tampering detection.
- 2. Enter the tamper trigger duration. (10 sec. ~ 10 min.) The tamper alarm will be triggered only when the tampering factor (the difference between current frame and pre-saved background) exceeds the trigger threshold. Conditions such as image too dark, too bright, or too blurry (defocused) can also be configured as tampering conditions.
- 3. You can configure Tampering Detection as a trigger element to the proactive event configurations in Event -> Event settings -> Trigger. For example, when the camera is tampered with, camera can be configured to send pre- and post-event video clips to a networked storage device. Please refer to page 106 for detailed information.

Applications > Audio detection

Audio detection, along with video motion detection, is applicable in the following scenarios:

- 1. Detection of activities not covered by camera view, e.g., a loud input by gun shots or breaking a door/window.
- A usually noisy environment, such as a factory, suddenly becomes quiet due to a breakdown of machines.
- 3. A PTZ camera can be directed to turn to a preset point by the occurrence of audio events.
- 4. Dark environments where video motion detection may not function well.

| 90 | | | ٨ | Alarm Level |
|----------|-----|----|------------|-------------|
| 80 70 | | - | ~ | |
| 60 | 0.0 | ~- | \bigcirc | |
| 50 | V | | L | |
| 40 30 | | | | |
| 20 | | | | |
| 10 | | | | |
| 0 | | | | |

The red circles indicate where the audio alarms can be triggered when breaching or falling below the preset threshold.

How to configure Audio detection:

- 1. Once the Audio detection window is opened, the current sound input will be interactively indicated by a fluctuating yellow wave diagram.
- 2. Use a mouse click to drag the Alarm level tab to a preferred location on the slide bar.
- 3. Select the "Enable audio detection" checkbox and click Save to enable the feature.



- 1. Note that the volume numbers (0~100) on the side of wave diagram does not represent decibel (dB). Sound intensity level has already been mapped to preset values. You can, however, use the real-world inputs at your installation site that are shown on the wave diagram to configure an alarm level.
- 2. To configure this feature, you must not mute the audio in **Configuration > Media > Audio**. The default of the camera can be muted due to the lack of an internal microphone. An external microphone is provided by users.

You can use the **Profile** window to configure a different Audio detection setting. For example, a place can be noisy in the day time and become very quiet in the night.

- 1. Click on the **Enable this profile** checkbox. Once the Audio detection window is opened, the current sound input will be interactively indicated by a fluctuating yellow wave diagram.
- 2. Use a mouse click to drag the **Alarm level** tab to a preferred location on the slide bar.
- 3. Select the **Day**, **Night**, or **Schedule** mode check circles. You may also manually configure a period of time during which this profile will take effect.
- 4. Click Save and then click Close to complete your configuration.

| 90 | Alarm Li |
|--------------------------------|-------------------------------------|
| 80 | Volume |
| 70 | |
| 60 | |
| 50 | |
| 40 | |
| 30 | |
| 20 | |
| 10 | |
| 0 | |
|] Enab iis profi) Day r | ode |
| | |
| Sche | le mode n 18:00 to 06:00 [hh:mm] |



- If the Alarm level and the received volume are set within a range of 20% on the wave diagram, frequent alarms will be triggered. It is recommended to set the Alarm level farther apart from the detected sound level.
- To configure and enable this feature, you must not configure video stream #1 into Motion JPEG. If an external microphone input is connected and recording of audio stream is preferred, audio stream is transmitted between camera and viewer/recording station along with stream #1.
- Refer to page 68 for Audio settings, and page 63 for video streaming settings.


Applications > Package management - a.k.a., VADP (VIVOTEK Application Development Platform)

| Upload package — | | | |
|----------------------|----------------|------------|---------------------|
| Save to SD card | | | |
| Select file | | | Browse Upload |
| Resource status | | | |
| 🐭 Storage status: | | | |
| storage_size: | 10240 KBytes | Free size: | 10240 KBytes |
| SD card status: Deta | iched | | |
| Total size: | 0 KBytes | Free size: | 0 KBytes |
| Used size: | 0 KBytes | Use (%): | 0 % |
| Memory status: | | | |
| Total size: | 24576 KBytes • | Free size: | 24576 KBytes |
| — Package list — | | | |
| Module nam | e Ver | ndor Ver | sion Status License |
| Backup | Reload Rest | ore Star | rt Stop |
| Баскир | Rest | Star | Stop |

Users can store and execute VIVOTEK's or 3rd-party software modules onto the camera's flash memory or SD card. These software modules can apply in video analysis for intelligent video applications such as license plate recognition, object counting, or as an agent for edge recording, etc.

- Once the software package is successfully uploaded, the module configuration (vadp. xml) information is displayed. When uploading a module, the camera will examine whether the module fits the predefined VADP requirements. Please contact our technical support or the vendor of your 3rd-party module for the parameters contained within.
- Users can also run VIVOTEK's VADP packages as a means to access updated functionality instead of replacing the entire firmware.
- Note that for some cameras the flash is too small to hold VADP packages. These cameras will have its "Save to SD card" checkbox selected and grayed-out for all time.
- The file system of SD card (FAT32) does not support soft (symbolic) link. It will return failure if your module tries to create soft links on SD card.

To utilize a software module, acquire the software package and click **Browse** and **Upload** buttons. The screen message for a successful upload is shown below:




To start a module, select the checkcircle in front, and click the Start button.

| | Package list | | | | | | |
|---|---------------|---------|---------|--------|---------|---|----|
| | Module name | Vendor | Version | Status | License | Ŧ | |
| 0 | Hello World | ABC | 1.0.0 | ON | yes | | 88 |
| | Backup Reload | Restore | Sta | art | Stop | | |

If you should need to remove a module, select the checkcircle in front and then click the **Stop** button. By then the module status will become **OFF**, and the **X** button will appear at the end of the row. Click on the **X** button to remove an existing module.

| Packa | ge list — | | | | | | |
|-------|-----------|--------|---------|---------|--------|---------|-----|
| | Module n | ame | Vendor | Version | Status | License | ± |
| ۲ | Hello Wo | orld | ABC | 1.0.0 | ON | no | • 8 |
| Bac | :kup | Reload | Restore | Sta | art | Stop | |

When prompted by a confirm message, Click **Yes** to proceed.



Note that the actual memory consumed while operating the module will be indicated on the **Memory status** field. This helps determine whether a running module has consumed too much of system resources.

Recording > Recording settings

This section explains how to configure the recording settings for the Network Camera.

Recording Settings

| Status Sun Mon Tue Wed Thu Fri Sat Time Source Destination Delete Add SD test Iote: Before setup recording, you may setup network storage via NAS server page | | | In | sert yo | ur SD c | ard and c | lick h |
|--|--------------------|----------------|---------|---------|---------|-------------|--------|
| Add <u>SD test</u> | Recording settings | | | | | | |
| | lame Status Sun M | on Tue Wed Thu | Fri Sat | Time | Source | Destination | Delete |
| inte: Refore setup recording, you may setup petwork storage via NAS server page | Add SD te | <u>est</u> | | | | | |
| te. Beible b | | | | | | | |



Please remember to format your SD card via the camera's web console (in the Local storage . SD card management page) when using it for the first time. Please refer to page 132 for detailed information.


Recording Settings

Click **Add** to open the recording setting window. On this page, you can define the adaptive recording, recording source, recording schedule, and recording capacity. A total of 2 recording settings can be configured.

| Recording name: video | |
|---------------------------|---|
| Enable this recording | |
| | |
| With adaptive recording | 9 |
| Pre-event recording | : 5 seconds [0~9] |
| Post-event recordin | g: 5 seconds [0~10] |
| Priority: Normal 💌 | |
| Source: Stream 1 💌 | |
| | Trigger |
| 1. Trigger | Schedule |
| i. mggei | 🗸 Sun 🗸 Mon 🖉 Tue 🖉 Wed 🖉 Thu 🖉 Fri 🖉 Sat |
| | Time |
| + | Always |
| 2. Destination | From 00:00 to 24:00 [hh:mm] |
| | Network fail |
| | |
| Note: To onable recording | notification please configure Event first |
| Note. To enable recording | Close Save |
| | |

- Recording name: Enter a name for the recording setting.
- Enable this recording: Select this option to enable video recording.
- With adaptive recording:

Select this option will activate the frame rate control according to alarm trigger. The frame control means that when there is a triggered alarm, the frame rate will raise up to the value you've configured on the Video quality page. Please refer to page 64 for more information. If you enable adaptive recording on a camera, only when an event is triggered on Camera A will the server record the full frame rate streaming data; otherwise, it will only request the I frame data during normal monitoring, thus effectively saves bandwidths and storage space.



The alarm trigger includes: motion detection and DI detection. Please refer to Event Settings on page 104.

Pre-event recording and post-event recording

The Network Camera has a buffer that temporarily holds data for a period of time. Therefore, when an event occurs, the camera can restrieve image frames taken several seconds ago. Enter a number to define the duration of recording before and after a trigger is activated.

- Priority: Select the relative importance of this recording (High, Normal, or Low). Recording with a higher priority setting will be executed first.
- Source: Select a video stream as the recording source.



► To enable recording notification please configure *Event settings* first . Please refer to page 104.

Please follow the steps below to set up the recording.

<u>1. Trigger</u>

Select a trigger source.

| Trigg | er | | | |
|-------|---------------|------------|-------------------|--|
| Sc | hedule | | | |
| | Sun 🔽 Mon 🔽 T | ue 🔽 Wed 🔽 |] Thu 👿 Fri 👿 Sat | |
| Ti | me | | | |
| | Always | | | |
| | From 00:00 | to 24:00 | [hh:mm] | |
| D Ne | twork fail | | | |

- Schedule: The server will start to record files on the local storage or network storage (NAS).
- Network fail: Since network fail, the server will start to record files on the local storage (SD card).

<u>2. Destination</u> You can select the SD card or network storage (NAS) for the recorded video files. If you have not configured a NAS server, see details in the following.

| | Destination |
|----------------|--------------------------------------|
| 1. Trigger | Destination: NAS |
| • | Capacity: |
| Ļ | Intire free space |
| | Reserved space: 100 Mbytes |
| 2. Destination | Enable cyclic recording |
| | Recording file management |
| | Maximum duration: 1 minutes [1~30] |
| | Maximum file size: 100 MB [100~2000] |
| | File name prefix: |

NAS server

Click Add NAS server to open the server setting window and follow the steps below to set up: 1. Fill in the information for your server.

For example:

| 1. Trigger | Destination: SD Add NAS server |
|----------------|---|
| 2. Destination | Server name: NAS Network_storage path (\\server name or IP address\folder name) |
| El Dodilidion | Server type ((Server hane of in address tolder hane) |
| | Network storage location: \\192.168.5.12\NAS |
| | (For example: \\my_nas\disk\folder) |
| | Workgroup: vivotek |
| | User name: |
| | Password: |
| | Test Close Save server |
| | 2 4 |

User name and password for your server

2. Click Test to check the setting. The result will be shown in the pop-up window.

| 🗿 http://192.168.5.151/cgi-bin/admin/testserver 🔲 🗖 🔀 | 🗿 http://192.168.5.151/cgi-bin/admin/testserver 🔲 🗖 🔀 |
|---|---|
| Mount successfully. Thanks | Mount failed. |
| | |
| 🗑 Done 👘 👘 Internet 🥠 | 🖉 Done 🔹 Internet |

| 30 - 🖓 ((10.22.22.22) | | <u>.</u> |
|------------------------------|---|----------|
| Organize · Search active de | ectory Retwork and Sharing Center. View resolute printers | |
| * Favorites | devel devel | |
| Downloads | Shore Shore | |
| Libraries | L KE | |
| Music See Pictures | | |
| Hdeos | 🛱 lest - Notopad | |
| Contraction (Contraction) | File Edit Format Vew Help | |
| | [NOTIFICATION]The Result of Server Test of Your IP Came | rab |
| Computer | | |

If successful, you will receive a test.txt file on the network storage server.

- 3. Enter a server name.
- 4. Click **Save** to complete the settings and click **Close** to exit the page.

| 7 Enable this recording | | | | | | |
|-------------------------|----------|--------------------|----------|----------------|----------------------|--|
| With adaptive records | o illein | 2 | | | | |
| Pre-event records | 1.00 | seconds (D~9) | | | | |
| | | | | | | |
| Post-event record | ng: s | seconds [0+10] | | | | |
| iorty Normal 💌 | | | | | | |
| ource: Stream 1 💌 | | | | | | |
| | T | estination | | | | |
| 1. Trigger | | estination: NAS | • | | | |
| 1. 11(2901 | | Capacity: | | | | |
| | | | free spa | C.F. | | |
| + | | O Reser | | | Moytes | |
| 2. Destination - | | | | | action of the second | |
| | | Enable cyclic | recordin | 1. | | |
| | | Recording file m | anagen | sent | | |
| | | Maximum duration | 1 | minutes [1-30] | | |
| | | Maximum file size: | 100 | MB [100-900] | | |
| | | File name prefix: | | | | |
| | | | | | | |

- Capacity: You can choose either the entire free space available or limit the reserved space. The recording size limit must be larger than the reserved amount for cyclic recording.
- Enable cyclic recording: If you check this item, when the maximum capacity is reached, the oldest file will be overwritten by the latest one. The reserved amount is reserved for the transaction stage when the storage space is about to be full and new data arrives. The minimum for the Reserved space must be larger than 15 MegaBytes.
- Recording file management: You can manually assign the Maximum duration and the Maximum file size for each recording footage. You may need to stitch individual files together under some circumstances. You may also designate a file name prefix by filling in the responsive text field.
- File name prefix: Enter the text that will be appended to the front of the file name.

f you want to enable recording notification, please click *Event* to configure event triggering settings. Please refer to **Event > Event settings** on page 104 for more details.

When completed, select **Enable this recording**. Click **Save** to enable the setting and click **Close** to exit this page. When the system begins recording, it will send the recorded files to the network storage. The new recording name will appear in the drop-down list on the recording page as shown below.

To remove a recording setting from the list, select a recording name from the drop-down list and click **Delete**.

| Record | ing set | tings | | | | | | | | | | |
|------------------|-----------|----------|--------|-----|-----|-----|-----|-----|-------------|---------|-------------|--------|
| Name | Status | Sun | Mon | Tue | Wed | Thu | Fri | Sat | Time | Source | Destination | Delete |
| <u>recording</u> | <u>ON</u> | V | ۷ | ۷ | V | V | V | V | 00:00~24:00 | stream1 | NAS | Delete |
| Ado | d | <u>s</u> |) test | | | | | | | | | |

- Click recording (Name): Opens the Recording Settings page to modify.
- Click <u>ON</u> (Status): The Status will become <u>OFF</u> and stop recording.
- Click <u>NAS</u> (Destination): Opens the file list of recordings as shown below. For more information about folder naming rules, please refer to page 111 for details.

| <u>20150210</u> |
|-----------------------|
| ☐ <u>20150211</u> |
| <u> 20150212 </u> |
| Delete Delete all |

Local storage > SD card management

This section explains how to manage the local storage on the Network Camera. Here you can view SD card status, and implement SD card control.

SD card staus

This column shows the status and reserved space of your SD card. Please remember to format the SD card when using for the first time.

| SD card status | | | |
|--------------------------|-----------------|------------|-----------------|
| SD card status: Detach | ed | no SD card | |
| Total size: 0 KBytesFree | size:0 KBytes | | |
| Used size:0 KBytesUse | (%): 0 % | | |
| | | | Format |
| - SD card status | | | |
| SD card status: Ready | | | |
| File system: FAT32 | | | |
| Total size: | 15323496 KBytes | Free size: | 15087976 KBytes |
| Used size: | 235520 KBytes | Use (%): | 1.537 % |

SD card format

The Linux kernel EXT4 file system format applies to SD card larger than 32GB. However, if EXT4 is applied, the computers running **Windows** will not be able to access the contents on the SD card.

| SD card format | | |
|-----------------------|--------|--|
| Ext4 Ext4 FAT32 | Format | |

SD card control

| Γ | SD card control | | | | |
|---|-------------------------------------|---|------|----|-----|
| | Enable cyclic storage | | | | |
| | Enable automatic disk cleanup | | | | |
| | Maximum duration for keeping files: | 7 | days | | |
| | | | | Sa | ave |

- Enable cyclic storage: Check this item if you want to enable cyclic recording. When the maximum capacity is reached, the oldest file will be overwritten by the latest one.
- Enable automatic disk cleanup: Check this item and enter the number of days you wish to retain a file. For example, if you enter "7 days", the recorded files will be stored on the SD card for 7 days.

Click **Save** to enable your settings.

Local storage > Content management

This section explains how to manage the content of recorded videos on the Network Camera. Here you can search and view the records and view the searched results.

Searching and Viewing the Records

This column allows the user to set up search criteria for recorded data. If you do not select any criteria and click **Search** button, all recorded data will be listed in the **Search Results** column.

| Search — | | | | | | | |
|--------------------------------|-----------|-----------|--------------|-------|---------|------------|----------|
| Trigger type | | | | | | | |
| Backup | | Syste | m boot | | Motion | | |
| Network fail | | Reco | rding notify | | Periodi | cally | |
| Tampering de | etection | VADF | , , | | Manua | l triggers | |
| Audio detection | n | | | | | | |
| Media type | | | | | | | |
| Video clip | | 🔿 Sna | apshot | | ⊖ Tex | đ | |
| Time | | | | | | | |
| Search for last | 1 min | ute(s) ho | ours days | weeks | | | |
| From: | 2015/05/1 | 8 | i | 02 | 36 | PM | |
| to: | 2015/05/2 | 5 | i | 02 | 36 | PM | |
| | | | | | | | Q Search |

- File attributes: Select one or more items as your search criteria.
- Trigger time: Manually enter the time range you want to search for contents created at a specific point in time.

Click **Search** and the recorded data corresponding to the search criteria will be listed in **Search Results** window.

Search Results

The following is an example of search results. There are four columns: Trigger time, Media type, Trigger type, and Locked. Click 🖕 to sort the search results in either direction.

| - | Name | Trigger type | Starting time | Ending time | |
|---|-------|--------------|------------------|------------------|---------------------------|
| | to SD | Periodically | Today at 3:45 PM | Today at 3:58 PM | Click to open a live view |
| | to SD | Periodically | Today at 3:58 PM | - | |
| | test | Motion | Today at 3:45 PM | Today at 3:45 PM | |
| | test | Motion | Today at 3:49 PM | Today at 3:49 PM | |
| | test | Motion | Today at 3:49 PM | Today at 3:49 PM | |
| | test | Motion | Today at 3:50 PM | Today at 3:50 PM | |
| | test | Motion | Today at 3:50 PM | Today at 3:50 PM | |

Play: Click on a search result which will highlight the selected item. A Play window will appear on top for immediate review of the selected file. For example:



- Download: Click on a search result to highlight the selected item in purple as shown above. Then click the **Download** button and a file download window will pop up for you to save the file.
- JPEGs to AVI: This functions only applies to "JPEG" format files such as snapshots. You can select several snapshots from the list, then click this button. Those snapshots will be converted into an AVI file.

Lock/Unlock: Select the checkbox in front of a desired search result, then click this button. The selected items will become Locked, which will not be deleted during cyclic recording. You can click again to unlock the selections. For example:

| Periodically Periodically Motion | Today at 3:45 PM Today at 3:58 PM | Today at 3:58 PM | ^ | |
|--|--------------------------------------|---|---|---|
| , | Today at 3:58 PM | | | |
| Motion | | | | |
| motion | Today at 3:45 PM | Today at 3:45 PM | | |
| Motion | Today at 3:49 PM | Today at 3:49 PM | | |
| Motion | Today at 3:49 PM | Today at 3:49 PM | | |
| Motion | Today at 3:50 PM | Today at 3:50 PM | | |
| Motion | Today at 3:50 PM | Today at 3:50 PM | \sim | |
| | Motion Motion | Motion Today at 3:49 PM Motion Today at 3:50 PM | Motion Today at 3:49 PM Today at 3:49 PM Motion Today at 3:50 PM Today at 3:50 PM Motion Today at 3:50 PM Today at 3:50 PM Motion Today at 3:50 PM Today at 3:50 PM | Motion Today at 3:49 PM Today at 3:49 PM Motion Today at 3:50 PM Today at 3:50 PM Motion Today at 3:50 PM Today at 3:50 PM Motion Today at 3:50 PM Today at 3:50 PM |

■ Remove: Select the desired search results, then click this button to delete the files.

Appendix URL Commands for the Network Camera

1. Overview

For some customers who already have their own web site or web control application, the Network Camera/Video Server can be easily integrated through URL syntax. This section specifies the external HTTP-based application programming interface. The HTTP-based camera interface provides the functionality to request a single image, control camera functions (PTZ, output relay etc.), and get and set internal parameter values. The image and CGI-requests are handled by the built-in Web server.

2. Style Convention

In URL syntax and in descriptions of CGI parameters, text within angle brackets denotes content that is to be replaced with either a value or a string. When replacing the text string, the angle brackets should also be replaced. An example of this is the description of the name for the server, denoted with <servername> in the URL syntax description below, that is replaced with the string myserver in the URL syntax example further down in the page.

URL syntax is denoted with the word "Syntax:" written in bold face followed by a box with the referenced syntax as shown below. For example, name of the server is written as <servername> and is intended to be replaced with the name of the actual server. This can either be a name, e.g., "mywebcam" or "thecam. adomain.net" or the associated IP number for the server, e.g., 192.168.0.220.

Syntax:

http://<servername>/cgi-bin/viewer/video.jpg

Description of returned data is written with "**Return:**" in bold face followed by the returned data in a box. All data is returned in HTTP format, i.e., each line is separated with a Carriage Return and Line Feed (CRLF) printed as \r\n.

Return:

HTTP/1.0 <HTTP code> <HTTP text>\r\n

URL syntax examples are written with "**Example:**" in bold face followed by a short description and a light grey box with the example.

Example: request a single snapshot image

http://mywebserver/cgi-bin/viewer/video.jpg

3. General CGI URL Syntax and Parameters

CGI parameters are written in lower-case and as one word without any underscores or other separators. When the CGI request includes internal camera parameters, these parameters must be written exactly as they are named in the camera or video server. The CGIs are organized in functionally-related directories under the cgi-bin directory. The file extension .cgi is required.

Syntax:

```
http://<servername>/cgi-bin/<subdir>[/<subdir>...]/<cgi>.<ext>
[?<parameter>=<value>[&<parameter>=<value>...]]
```

Example: Set digital output #1 to active

http://mywebserver/cgi-bin/dido/setdo.cgi?do1=1

4. Security Level

| SECURITY LEVEL | SUB-DIRECTORY | DESCRIPTION |
|-----------------------------|--------------------------|--|
| 0 | anonymous | Unprotected. |
| 1 [view] anonymous, viewer, | | 1. Can view, listen, talk to camera. |
| | dido, camctrl | 2. Can control DI/DO, PTZ of the camera. |
| 4 [operator] | anonymous, viewer, | Operator access rights can modify most of the camera's |
| | dido, camctrl, operator | parameters except some privileges and network options. |
| 6 [admin] | anonymous, viewer, | Administrator access rights can fully control the camera's |
| | dido, camctrl, operator, | operations. |
| | admin | |
| 7 | N/A | Internal parameters. Unable to be changed by any external |
| | | interfaces. |

5. Get Server Parameter Values

Note: The access right depends on the URL directory. **Method:** GET/POST

| Syntax: |
|---|
| http://< <i>servername</i> >/cgi-bin/anonymous/getparam.cgi?[< <i>parameter</i> >] |
| [& <parameter>]</parameter> |
| |
| http://< <i>servername</i> >/cgi-bin/viewer/getparam.cgi?[< <i>parameter</i> >] |
| [& <parameter>]</parameter> |
| |
| http:// <servername>/cgi-bin/operator/getparam.cgi?[<parameter>]</parameter></servername> |
| [& <parameter>]</parameter> |
| |
| http://< <i>servername</i> >/cgi-bin/admin/getparam.cgi?[< <i>parameter</i> >] |
| [& <parameter>]</parameter> |

Where the *<parameter>* should be *<group>*[_*<name>*] or *<group>*[.*<name>*]. If you do not specify any parameters, all the parameters on the server will be returned. If you specify only *<group>*, the parameters oftherelated group will be returned.

When querying parameter values, the current parameter values are returned.

A successful control request returns parameter pairs as follows:

| Return: | | | |
|---|--|--|--|
| HTTP/1.0 200 OK\r\n | | | |
| Content-Type: text/html\r\n | | | |
| Context-Length: <length>\r\n</length> | | | |
| \r\n | | | |
| <parameter pair=""></parameter> | | | |
| where <parameter pair=""> is</parameter> | | | |
| <parameter>=<value>\r\n</value></parameter> | | | |
| [<parameter pair="">]</parameter> | | | |

<length> is the actual length of content.

Example: Request IP address and its response

Request: http://192.168.0.123/cgi-bin/admin/getparam.cgi?network_ipaddress

Response: HTTP/1.0 200 OK\r\n Content-Type: text/html\r\n Context-Length: 33\r\n \r\n network.ipaddress=192.168.0.123\r\n

6. Set Server Parameter Values

Note: The access right depends on the URL directory. **Method:** GET/POST

Syntax:

```
http://<servername>/cgi-bin/anonymous/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>][&return=<return page>]
http://<servername>/cgi-bin/viewer/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>] [&return=<return page>]
http://<servername>/cgi-bin/operator/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>] [&return=<return page>]
http://<servername>/cgi-bin/operator/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>] [&return=<return page>]
http://<servername>/cgi-bin/admin/setparam.cgi? <parameter>=<value>
[&<parameter>=<value>...][&update=<value>] [&return=<return page>]
```

| PARAMETER | VALUE | DESCRIPTION |
|-------------------------------|---------------------------|--|
| <group>_<name></name></group> | value to assigned | Assign <value> to the parameter <group>_<name>.</name></group></value> |
| update | <boolean></boolean> | Set to 1 to update all fields (no need to update parameter in each |
| | | group). |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The <i><return i="" page<="">>can be a full URL path or relative path according to</return></i> |
| | | the current path. If you omit this parameter, it will redirect to an |
| | | empty page. |
| | | |

| (Note: The return page can be a general HTML file(.htm, .html) or a |
|---|
| VIVOTEK server script executable (.vspx) file. It cannot be a CGI |
| commandor have any extra parameters. This parameter must be |
| placed at the end of the parameter list |

| Return: | | | |
|---|--|--|--|
| HTTP/1.0 200 OK\r\n | | | |
| Content-Type: text/html\r\n | | | |
| Context-Length: <length>\r\n</length> | | | |
| \r\n | | | |
| <parameter pair=""></parameter> | | | |
| where <parameter pair=""> is</parameter> | | | |
| <parameter>=<value>\r\n</value></parameter> | | | |
| [<parameter pair="">]</parameter> | | | |

Only the parameters that you set and are readable will be returned.

Example: Set the IP address of server to 192.168.0.123:

Request:

http://myserver/cgi-bin/admin/setparam.cgi?network_ipaddress=192.168.0.123

Response: HTTP/1.0 200 OK\r\n Content-Type: text/html\r\n Context-Length: 33\r\n \r\n network.ipaddress=192.168.0.123\r\n

7. Available parameters on the server

Valid values:

| VALID VALUES | DESCRIPTION |
|----------------------------------|--|
| string[<n>]</n> | Text strings shorter than 'n' characters. The characters ",',<,>,& are invalid. |
| string[n~m] | Text strings longer than `n' characters and shorter than `m' characters. The |
| | characters ",',<,>,& are invalid. |
| password[<n>]</n> | The same as string but displays'*' instead. |
| <integer></integer> | Any single integer number in 32-bits. |
| | The range is -2147483648~2147483647. |
| <positive integer=""></positive> | Any single positive integer number in 32-bits. |
| | The range is 1~ 4294967295. |
| <m> ~ <n></n></m> | Any number between 'm' and 'n'. |
| domain name[<n>]</n> | A string limited to a domain name shorter than 'n' characters (eg. www.ibm.com). |
| email address [<n>]</n> | A string limited to an email address shorter than `n' characters (eg. |
| | joe@www.ibm.com). |
| <ip address=""></ip> | A string limited to an IP address (eg. 192.168.1.1). |
| <mac address=""></mac> | A string limited to contain a MAC address without hyphens or colons. |
| <boolean></boolean> | A boolean value of 1 or 0 represents [Yes or No], [True or False], [Enable or |
| | Disable]. |
| <value1>,</value1> | Enumeration. Only given values are valid. |
| <value2>,</value2> | |
| <value3>,</value3> | |
| | |
| blank | A blank string. |
| everything inside <> | A description |
| integer primary key | SQLite data type. A 32-bit signed integer. The value is assigned a unique integer by |
| | the server. |
| <text></text> | SQLite data type. The value is a text string, stored using the |
| | database encoding (UTF-8, UTF-16BE or UTF-16-LE). |
| <coordinate></coordinate> | x, y coordinate (eg. 0,0) |
| <window size=""></window> | window width and height (eg. 800x600) |
| <w,h></w,h> | The format for coordinate in 2D. |
| | W is the pixel number of width. |
| | H is the pixel number of height. |
| | EX: (176,144) |
| <wxh></wxh> | The format for resolution. |

| | W is the pixel number of width. | |
|--|----------------------------------|--|
| | H is the pixel number of height. | |
| | Ex: 1920x1080, 2048x1536 | |

NOTE: The camera should not be restarted when parameters are changed.

7.1 system

Group: system

| NAME | VALUE | SECURITY (get/set) | DESCRIPTION |
|---------------|--|-----------------------|---|
| hostname | string[64] | 1/6 | Host name of server |
| | | | (Network Camera, |
| | | | Wireless Network Camera, |
| | | | Video Server, |
| | | | Wireless Video Server). |
| ledoff | <boolean></boolean> | 6/6 | Turn on (0) or turn off (1) all led indicators. |
| date | <yyyy dd="" mm="">,</yyyy> | 6/6 | Current date of system. Set to 'keep' to keep |
| | keep, | | date unchanged. Set to 'auto' to use NTP to |
| | auto | | synchronize date. |
| time | <hh:mm:ss>,</hh:mm:ss> | 6/6 | Current time of the system. Set to 'keep' to |
| | keep, | | keep time unchanged. Set to 'auto' to use NTP |
| | auto | | to synchronize time. |
| datetime | <mmddhhmmyyyy< td=""><td>6/6</td><td>Another current time format of the system.</td></mmddhhmmyyyy<> | 6/6 | Another current time format of the system. |
| | .ss> | | |
| | | | |
| ntp | <domain name="">,</domain> | 6/6 | NTP server. |
| | <ip address="">,</ip> | | *Do not use "skip to invoke default server" for |
| | <blank></blank> | | default value. |
| timezoneindex | -489 ~ 529 | 6/6 | Indicate timezone and area. |
| | | | -480: GMT-12:00 Eniwetok, Kwajalein |
| | | | -440: GMT-11:00 Midway Island, Samoa |
| | | | -400: GMT-10:00 Hawaii |
| | | | -360: GMT-09:00 Alaska |
| | | | -320: GMT-08:00 Las Vegas, San_Francisco, |
| | | | Vancouver |
| | | | -280: GMT-07:00 Mountain Time, Denver |
| | | | -281: GMT-07:00 Arizona |
| | | | -240: GMT-06:00 Central America, Central |
| | | | Time, Mexico City, Saskatchewan |
| | | | -200: GMT-05:00 Eastern Time, New York, |
| | | | Toronto |
| | | | -201: GMT-05:00 Bogota, Lima, Quito, Indiana |
| | | | -180: GMT-04:30 Caracas |
| | | | -160: GMT-04:00 Atlantic Time, Canada, La |
| | | | Paz, Santiago |

| | -140: GMT-03:30 Newfoundland |
|--|--|
| | -120: GMT-03:00 Brasilia, Buenos Aires, |
| | Georgetown, Greenland |
| | -80: GMT-02:00 Mid-Atlantic |
| | -40: GMT-01:00 Azores, Cape_Verde_IS. |
| | 0: GMT Casablanca, Greenwich Mean Time: |
| | Dublin, |
| | Edinburgh, Lisbon, London |
| | 40: GMT 01:00 Amsterdam, Berlin, Rome, |
| | Stockholm, Vienna, Madrid, Paris |
| | 41: GMT 01:00 Warsaw, Budapest, Bern |
| | 80: GMT 02:00 Athens, Helsinki, Istanbul, Riga |
| | 81: GMT 02:00 Cairo |
| | 82: GMT 02:00 Lebanon, Minsk |
| | 83: GMT 02:00 Israel |
| | 120: GMT 03:00 Baghdad, Kuwait, Riyadh, |
| | Moscow, St. Petersburg, Nairobi |
| | 121: GMT 03:00 Iraq |
| | 140: GMT 03:30 Tehran |
| | 160: GMT 04:00 Abu Dhabi, Muscat, Baku, |
| | Tbilisi, Yerevan |
| | 180: GMT 04:30 Kabul |
| | 200: GMT 05:00 Ekaterinburg, Islamabad, |
| | Karachi, Tashkent |
| | 220: GMT 05:30 Calcutta, Chennai, Mumbai, |
| | New Delhi |
| | 230: GMT 05:45 Kathmandu |
| | 240: GMT 06:00 Almaty, Novosibirsk, Astana, |
| | Dhaka, Sri Jayawardenepura |
| | 260: GMT 06:30 Rangoon |
| | 280: GMT 07:00 Bangkok, Hanoi, Jakarta, |
| | Krasnoyarsk |
| | 320: GMT 08:00 Beijing, Chongging, Hong |
| | Kong, Kuala Lumpur, Singapore, Taipei |
| | 360: GMT 09:00 Osaka, Sapporo, Tokyo, |
| | Seoul, Yakutsk |
| | 380: GMT 09:30 Adelaide, Darwin |
| | 400: GMT 10:00 Brisbane, Canberra, |
| | Melbourne, Sydney, Guam, Vladivostok |
| | 440: GMT 11:00 Magadan, Solomon Is., New |
| | |

| | | | Caledonia |
|-----------------------------|----------------------------------|---------------------|--|
| | | | 480: GMT 12:00 Aucklan, Wellington, Fiji, |
| | | | Kamchatka, Marshall Is. |
| | | | 520: GMT 13:00 Nuku'Alofa |
| daylight_enable | <boolean></boolean> | 6/6 | Enable automaticdaylight saving time in time |
| daylight_enable | | 0/0 | |
| davlight data stualmada | (nocitivo integan) | 6/7 | zone. |
| daylight_dstactualmode | <positive integer=""></positive> | 6/7 | Check if current time is under daylight saving time. |
| | | | (Used internally) |
| daylight_auto_begintime | string[19] | 6/7 | Display the current daylight saving start time. |
| daylight_auto_endtime | string[19] | 6/7 | Display the current daylight saving start time. |
| | | 6/6 | |
| daylight_timezones | string | 0/0 | List time zone index which support daylight |
| | | <i>C</i> 1 <i>C</i> | saving time. |
| updateinterval | 0, | 6/6 | 0 to Disable automatic time adjustment, |
| | 3600, | | otherwise, it indicates the seconds between |
| | 86400, | | NTP automatic update intervals. |
| | 604800, | | |
| | 2592000 | | |
| restore | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | | values after <value> seconds.</value> |
| reset | 0, | 7/6 | Restart the server after <value> seconds if</value> |
| | <positive integer=""></positive> | | <value> is non-negative.</value> |
| restoreexceptnet | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | | values except (ipaddress, subnet, router, |
| | | | dns1, dns2, pppoe). |
| | | | This command can cooperate with other |
| | | | "restoreexceptXYZ" commands. When |
| | | | cooperating with others, the system |
| | | | parameters will be restored to the default |
| | | | value except for a union of the combined |
| | | | results. |
| restoreexceptdst | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | | values except all daylight saving time settings. |
| | | | This command can cooperate with other |
| | | | "restoreexceptXYZ" commands. When |
| | | | cooperating with others, the system |
| | | | parameters will be restored to default values |
| | | | except for a union of combined results. |
| restoreexceptlang | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | ., | values except the custom language file the |
| | | I | |

| | | | user has uploaded. |
|-------------------------|----------------------------------|-----|---|
| | | | This command can cooperate with other |
| | | | "restoreexceptXYZ" commands. When |
| | | | cooperating with others, the system |
| | | | parameters will be restored to the default |
| | | | value except for a union of the combined |
| | | | results. |
| restoreexceptvadp | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | | values except the vadp parameters and VADP |
| | | | modules that stored in the system. |
| | | | This command can cooperate with other |
| | | | "restoreexceptXYZ" commands. When |
| | | | cooperating with others, the system |
| | | | parameters will be restored to the default |
| | | | value except for a union of the combined |
| | | | results. |
| restoreexceptfocusvalue | 0, | 7/6 | Restore the system parameters to default |
| | <positive integer=""></positive> | | values except zoom and focus value. |
| | | | This command can cooperate with other |
| | | | "restoreexceptXYZ" commands. When |
| | | | cooperating with others, the system |
| | | | parameters will be restored to the default |
| | | | value except for a union of the combined |
| | | | results. |
| | | | * Only available when |
| | | | "capability_image_c <n>_ remotefocus" is 1 or</n> |
| | | | "capability_image_c <n>_ backfocus" is 1.</n> |

7.1.1 system.info

Subgroup of **system**: **info** (The fields in this group are unchangeable.)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------------|------------------------|-----------|--|
| | | (get/set) | |
| modelname | string[40] | 0/7 | Internal model name of the server |
| extendedmodelname | string[40] | 0/7 | ODM specific model name of server (eg. |
| | | | DCS-5610). If it is not an ODM model, this field |
| | | | will be equal to "modelname" |
| serialnumber | <mac address=""></mac> | 0/7 | 12 characters MAC address (without hyphens). |
| firmwareversion | string[40] | 0/7 | Firmware version, including model, company, |
| | | | and version number in the |

| | | | format: < MODEL-BRAND-VERSION> |
|-------------------------|---|-----|--|
| language_count | <positive integer=""></positive> | 0/7 | Number of webpage languages available on |
| | | | the server. |
| language_i<0~(count-1)> | string[16] | 0/7 | Available language lists. |
| | language_i0 : | | |
| | English | | |
| | language_i1 : | | |
| | Deutsch | | |
| | language_i2 : | | |
| | Español | | |
| | language_i3 : | | |
| | Français | | |
| | language_i4 : | | |
| | Italiano | | |
| | language_i5:日本 | | |
| | 語 | | |
| | language_i6 : | | |
| | Português | | |
| | language_i7: 简体 | | |
| | 中文 | | |
| | language_i8: 繁體 | | |
| | 中文 | | |
| customlanguage_maxcoun | 0, <positive< td=""><td>0/6</td><td>Maximum number of custom languages</td></positive<> | 0/6 | Maximum number of custom languages |
| t | integer> | | supported on the server. |
| customlanguage_count | 0, <positive< td=""><td>0/6</td><td>Number of custom languages which have been</td></positive<> | 0/6 | Number of custom languages which have been |
| | integer> | | uploaded to the server. |
| customlanguage_i<0~(ma | string | 0/6 | Custom language name. |
| xcount-1)> | | | |

7.2 status

Group: status

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|--|-----------|--|
| | | (get/set) | |
| di_i<0~(capability_ndi-1)> | <boolean></boolean> | 1/7 | 0 => Inactive, normal |
| <product dependent=""></product> | | | 1 => Active, triggered |
| | | | (capability.ndi > 0) |
| do_i<0~(capability_ndo-1)> | <boolean></boolean> | 1/7 | 0 => Inactive, normal |
| <product dependent=""></product> | | | 1 => Active, triggered |
| | | | (capability.ndo > 0) |
| onlinenum_rtsp | 0, <positive< td=""><td>6/7</td><td>Current number of RTSP connections.</td></positive<> | 6/7 | Current number of RTSP connections. |
| | integer> | | |
| onlinenum_httppush | 0, <positive< td=""><td>6/7</td><td>Current number of HTTP push server</td></positive<> | 6/7 | Current number of HTTP push server |
| | integer> | | connections. |
| onlinenum_sip | 0, <positive< td=""><td>6/7</td><td>Current number of SIP connections.</td></positive<> | 6/7 | Current number of SIP connections. |
| | integer> | | |
| eth_i0 | <string></string> | 1/7 | Get network information from mii-tool. |
| vi_i<0~(capability_nvi-1)> | <boolean></boolean> | 1/7 | Virtual input |
| <product dependent=""></product> | | | 0 => Inactive |
| | | | 1 => Active |
| | | | (capability.nvi > 0) |

7.3 digital input behavior define

Group: **di_i<0~(n-1)>** for n is the value of "capability_ndi" (capability.ndi > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------|-------|-----------|--|
| | | (get/set) | |
| normalstate | high, | 1/1 | Indicates open circuit or closed circuit |
| | low | | (inactive status) |

7.4 digital output behavior define

Group: **do_i<0~(n-1)>** for n is the value of "capability_ndo" (capability.ndo > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------|----------|-----------|---|
| | | (get/set) | |
| normalstate | open, | 1/1 | Indicate open circuit or closed circuit (inactive |
| | grounded | | status) |

7.5 security

Group: security

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------------------|-----------------|-----------|---|
| | | (get/set) | |
| privilege_do | view, operator, | 1/6 | Indicate which privileges and above can |
| | admin | | control digital output |
| | | | (capability.ndo > 0) |
| privilege_camctrl | view, operator, | 1/6 | Indicate which privileges and above can |
| | admin | | control PTZ |
| | | | (capability.ptzenabled > 0 or capability.eptz > |
| | | | 0) |
| user_i0_name | string[64] | 6/7 | User name of root |
| user_i<1~20>_name | string[64] | 6/7 | User name |
| user_i0_pass | password[64] | 6/6 | Root password |
| user_i<1~20>_pass | password[64] | 7/6 | User password |
| user_i0_privilege | view, | 6/7 | Root privilege |
| | operator, | | |
| | admin | | |
| user_i<1~20>_ privilege | view, | 6/6 | User privilege |
| | operator, | | |
| | admin | | |

7.6 network

Group: network

| NAME | VALUE | SECURITY | DESCRIPTION |
|------------|----------------------------------|-----------|---|
| | | (get/set) | |
| preprocess | <positive integer=""></positive> | 6/6 | An 32-bit integer, each bit can be set |
| | | | separately as follows: |
| | | | Bit 0 => HTTP service; |
| | | | Bit 1=> HTTPS service; |
| | | | Bit 2=> FTP service; |
| | | | Bit 3 => Two way audio and RTSP Streaming |
| | | | service; |
| | | | |
| | | | To stop service before changing its port |
| | | | settings. It's recommended to set this |
| | | | parameter when change a service port to the |
| | | | port occupied by another service currently. |

| | | | Otherwise, the service may fail. |
|-----------|----------------------|-----|--|
| | | | Stopped service will auto-start after changing |
| | | | port settings. |
| | | | Ex: |
| | | | Change HTTP port from 80 to 5556, and |
| | | | change RTP port for video from 5556 to 20480. |
| | | | Then, set preprocess=9 to stop both service |
| | | | first. |
| | | | "/cgi-bin/admin/setparam.cgi? |
| | | | network_preprocess=9&network_http_port= |
| | | | 5556& network_rtp_videoport=20480" |
| type | lan, | 6/6 | Network connection type. |
| | рррое | | |
| | | | |
| resetip | <boolean></boolean> | 6/6 | 1 => Get ipaddress, subnet, router, dns1, |
| | | | dns2 from DHCP server at next reboot. |
| | | | 0 => Use preset ipaddress, subnet, rounter, |
| | | | dns1, and dns2. |
| ipaddress | <ip address=""></ip> | 6/6 | IP address of server. |
| subnet | <ip address=""></ip> | 6/6 | Subnet mask. |
| router | <ip address=""></ip> | 6/6 | Default gateway. |
| dns1 | <ip address=""></ip> | 6/6 | Primary DNS server. |
| dns2 | <ip address=""></ip> | 6/6 | Secondary DNS server. |
| wins1 | <ip address=""></ip> | 6/6 | Primary WINS server. |
| wins2 | <ip address=""></ip> | 6/6 | Secondary WINS server. |
| L | | | |

7.6.1 802.1x

Subgroup of **network: ieee8021x (**capability.protocol.ieee8021x > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------------------|--|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable/disable IEEE 802.1x |
| eapmethod | eap-peap, eap-tls | 6/6 | Selected EAP method |
| identity_peap | string[64] | 6/6 | PEAP identity |
| identity_tls | string[64] | 6/6 | TLS identity |
| password | string[200] | 6/6 | Password for TLS |
| privatekeypassword | string[200] | 6/6 | Password for PEAP |
| ca_exist | <boolean></boolean> | 6/6 | CA installed flag |
| ca_time | 0, <positive< td=""><td>6/7</td><td>CA installed time. Represented in EPOCH</td></positive<> | 6/7 | CA installed time. Represented in EPOCH |

| | integer> | | |
|-------------------|---|-----|--|
| ca_size | 0, <positive< td=""><td>6/7</td><td>CA file size (in bytes)</td></positive<> | 6/7 | CA file size (in bytes) |
| | integer> | | |
| certificate_exist | <boolean></boolean> | 6/6 | Certificate installed flag (for TLS) |
| certificate_time | 0, <positive< td=""><td>6/7</td><td>Certificate installed time. Represented in</td></positive<> | 6/7 | Certificate installed time. Represented in |
| | integer> | | EPOCH |
| certificate_size | 0, <positive< td=""><td>6/7</td><td>Certificate file size (in bytes)</td></positive<> | 6/7 | Certificate file size (in bytes) |
| | integer> | | |
| privatekey_exist | <boolean></boolean> | 6/6 | Private key installed flag (for TLS) |
| privatekey_time | 0, <positive< td=""><td>6/7</td><td>Private key installed time. Represented in</td></positive<> | 6/7 | Private key installed time. Represented in |
| | integer> | | EPOCH |
| privatekey_size | 0, <positive< td=""><td>6/7</td><td>Private key file size (in bytes)</td></positive<> | 6/7 | Private key file size (in bytes) |
| | integer> | | |

7.6.2 QOS

Subgroup of **network: qos_cos (**capability.protocol.qos.cos > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|---------------------|-----------|----------------------------------|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable/disable CoS (IEEE 802.1p) |
| vlanid | 1~4095 | 6/6 | VLAN ID |
| video | 0~7 | 6/6 | Video channel for CoS |
| audio | 0~7 | 6/6 | Audio channel for CoS |
| <product dependent=""></product> | | | (capability.naudioin > 0) |
| eventalarm | 0~7 | 6/6 | Event/alarm channel for CoS |
| management | 0~7 | 6/6 | Management channel for CoS |
| eventtunnel | 0~7 | 6/6 | Event/Control channel for CoS |

Subgroup of **network: qos_dscp** (capability.protocol.qos.dscp > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------|---------------------|-----------|--------------------------------|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable/disable DSCP |
| video | 0~63 | 6/6 | Video channel for DSCP |
| audio | 0~63 | 6/6 | Audio channel for DSCP |
| | | | (capability.naudioin > 0) |
| eventalarm | 0~63 | 6/6 | Event/alarm channel for DSCP |
| management | 0~63 | 6/6 | Management channel for DSCP |
| eventtunnel | 0~63 | 6/6 | Event/Control channel for DSCP |

7.6.3 IPV6

Subgroup of **network**: **ipv6** (capability.protocol.ipv6 > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------|----------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable IPv6. |
| addonipaddress | <ip address=""></ip> | 6/6 | IPv6 IP address. |
| addonprefixlen | 0~128 | 6/6 | IPv6 prefix length. |
| addonrouter | <ip address=""></ip> | 6/6 | IPv6 router address. |
| addondns | <ip address=""></ip> | 6/6 | IPv6 DNS address. |
| allowoptional | <boolean></boolean> | 6/6 | Allow manually setup of IP address setting. |

7.6.4 FTP

Subgroup of **network**: **ftp**

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|----------------|-----------|------------------------|
| | | (get/set) | |
| port | 21, 1025~65535 | 6/6 | Local ftp server port. |

7.6.5 HTTP

Subgroup of **network**: http

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|---------------------|-----------|--|
| | | (get/set) | |
| port | 80, 1025 ~ 65535 | 1/6 | HTTP port. |
| alternateport | 1025~65535 | 6/6 | Alternate HTTP port. |
| authmode | basic, | 1/6 | HTTP authentication mode. |
| | digest | | |
| s<0~(nmediastream-1)> | string[32] | 1/6 | Http server push access name for stream N, |
| _accessname | | | N= 1~ capability.nmediastream. |
| <product dependent=""></product> | | | (capability.protocol.spush_mjpeg =1 and |
| | | | capability.nmediastream > 0) |
| | | | The value are shown as |
| | | | video.mjpg = s0_accessname, (stream1) |
| | | | video2.mjpg = s1_accessname, (stream2) |
| | | | video3.mjpg = s2_accessname, (stream3) |
| | | | video4.mjpg = s3_accessname, (stream4) |
| | | | etc. |
| anonymousviewing | <boolean></boolean> | 1/6 | Enable anonymous streaming viewing. |

7.6.6 HTTPS port

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|-------------------|-----------|-------------|
| | | (get/set) | |
| port | 443, 1025 ~ 65535 | 1/6 | HTTPS port. |

Subgroup of **network**: **https** (capability.protocol.https > 0)

7.6.7 RTSP

Subgroup of **network**: **rtsp** (capability.protocol.rtsp > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|---------------------|-----------|---|
| | | (get/set) | |
| port | 554, 1025 ~ 65535 | 1/6 | RTSP port. |
| | | | (capability.protocol.rtsp=1) |
| anonymousviewing | <boolean></boolean> | 1/6 | Enable anoymous streaming viewing. |
| authmode | disable, | 1/6 | RTSP authentication mode. |
| | basic, | | (capability.protocol.rtsp=1) |
| | digest | | |
| s<0~(nmediastream-1)> | string[32] | 1/6 | RTSP access name for stream N, N= $1\sim$ |
| _accessname | | | capability.nmediastream. |
| <product dependent=""></product> | | | (capability.protocol.spush_mjpeg =1 and |
| | | | capability.nmediastream > 0) |
| | | | The value are shown as |
| | | | live.sdp = s0_accessname, (stream1) |
| | | | live2.sdp = s1_accessname, (stream2) |
| | | | live3.sdp = s2_accessname, (stream3) |
| | | | live4.sdp = s3_accessname, (stream4) |
| | | | etc. |

7.6.7.1 RTSP multicast

Subgroup of **network_rtsp_s<0~(n-1)>_multicast** n is stream count (capability.protocol.rtp.multicast > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|----------------------|-----------|---------------------------|
| | | (get/set) | |
| alwaysmulticast | <boolean></boolean> | 4/4 | Enable always multicast. |
| ipaddress | <ip address=""></ip> | 4/4 | Multicast IP address. |
| videoport | 1025 ~ 65535 | 4/4 | Multicast video port. |
| audioport | 1025 ~ 65535 | 4/4 | Multicast audio port. |
| <product dependent=""></product> | | | (capability.naudioin > 0) |

| metadataport | 1026~65534 | 4/4 | Multicast metadata port. |
|--------------|------------|-----|------------------------------|
| ttl | 1 ~ 255 | 4/4 | Multicasttime to live value. |

7.6.8 SIP port

Subgroup of **network**: **sip** (capability.protocol.sip> 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|--------------|-----------|-------------|
| | | (get/set) | |
| port | 1025 ~ 65535 | 1/6 | SIP port. |

7.6.9 RTP port

Subgroup of **network**: **rtp**

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------------|--------------|-----------|-------------------------------------|
| | | (get/set) | |
| videoport | 1025 ~ 65535 | 6/6 | Video channel port for RTP. |
| | | | (capability.protocol.rtp_unicast=1) |
| audioport | 1025 ~ 65535 | 6/6 | Audio channel port for RTP. |
| | | | (capability.protocol.rtp_unicast=1) |
| metadataport | 1025 ~ 65535 | 6/6 | Metadata channel port for RTP. |

7.6.10 PPPoE

Subgroup of **network**: **pppoe** (capability.protocol.pppoe > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|--------------|-----------|--------------------------|
| | | (get/set) | |
| user | string[128] | 6/6 | PPPoE account user name. |
| pass | password[64] | 6/6 | PPPoE account password. |

7.7 IP Filter

Group: ipfilter

| NAME | VALUE | SECURITY (get/set) | DESCRIPTION |
|-----------------|--|-----------------------|---|
| enable | <boolean></boolean> | 6/6 | Enable access list filtering. |
| admin_enable | <boolean></boolean> | 6/6 | Enable administrator IP address. |
| admin_ip | string[43] | 6/6 | Administrator IP address. |
| maxconnection | 1~10 | 6/6 | Maximum number of concurrent streaming connection(s). |
| type | 0, 1 | 6/6 | Ipfilter policy : |
| | | | $0 \Rightarrow allow$ |
| | | | 1 => deny |
| ipv4list_i<0~9> | Single address: <ip< td=""><td>6/6</td><td>IPv4 address list.</td></ip<> | 6/6 | IPv4 address list. |
| | address> | | |
| | Network address: | | |
| | <ip <="" address="" td=""><td></td><td></td></ip> | | |
| | network mask> | | |
| | Range | | |
| | address: <start ip<="" td=""><td></td><td></td></start> | | |
| | address - end ip | | |
| | address> | | |
| ipv6list_i<0~9> | string[43] | 6/6 | IPv6 address list. |

7.8 Video input

Group: videoin

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------------------------|--|-----------|---|
| | | (get/set) | |
| cmosfreq | 50, 60 | 4/4 | CMOS frequency. |
| | | | (capability.videoin.type=2) |
| whitebalance | auto, | 4/4 | "auto" indicates auto white balance. |
| | manual, | | "manual" indicates keep current value. |
| | rbgain | | "rbgain" indicates using rgain and gbain. |
| exposurelevel | 0~12 | 4/4 | Exposure level |
| | | | "0,12": This range takes the concept from DC's |
| | | | exposure tuning options. The definition is: |
| | | | 0: EV -2.0 |
| | | | 1: EV -1.7 |
| | | | 2: EV -1.3 |
| | | | 3: EV -1.0 |
| | | | 4: EV -0.7 |
| | | | 5: EV -0.3 |
| | | | 6: EV 0 |
| | | | 7: EV +0.3 |
| | | | 8: EV +0.7 |
| | | | 9: EV +1.0 |
| | | | 10: EV +1.3 |
| | | | 11: EV +1.7 |
| | | | 12: EV +2.0 |
| irismode | fixed, indoor, | 4/4 | Control DC-Iris mode. |
| | outdoor | | "outdoor": Auto-setting DC-Iris to get best |
| | <product< td=""><td></td><td>quality, but easy to meet rolling or flicker effect</td></product<> | | quality, but easy to meet rolling or flicker effect |
| | independent> | | in indoor environment. |
| | | | "indoor": Avoid rolling and flicker effect first. |
| | | | "fixed": Open the iris to maximum. |
| | | | * Only available when |
| | | | "capability_image_c <n>_iristype"=dciris</n> |
| enableblc | <boolean></boolean> | 4/4 | Enable backlight compensation. |
| <not anymore="" support=""></not> | | | * Not support this parameter anymore when |
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| | | | * It's recommanded to use |

| | | | "exposurewin_c <n>_mode" to switch on/off</n> |
|------------------|---|-----|---|
| | | | BLC. |
| color | 0, 1 | 4/4 | 0 =>monochrome |
| | | | 1 => color |
| flip | <boolean></boolean> | 4/4 | Flip the image. |
| mirror | <boolean></boolean> | 4/4 | Mirror the image. |
| rotate | 0,90,180,270 | 1/4 | The rotation angle of image. |
| | | | Support only in Rotation mode |
| | | | (capability.videoin.c <n>.rotation=1)</n> |
| ptzstatus | 0, <positive< td=""><td>1/7</td><td>A 32-bit integer, each bit can be set separately</td></positive<> | 1/7 | A 32-bit integer, each bit can be set separately |
| | integer> | | as follows: |
| | | | Bit 0 => Support camera control function; |
| | | | 0(not support), 1(support) |
| | | | Bit 1 => Built-in or external camera; 0 |
| | | | (external), 1(built-in) |
| | | | Bit 2 => Support pan operation; 0(not |
| | | | support), 1(support) |
| | | | Bit 3 => Support tilt operation; 0(not |
| | | | support), 1(support) |
| | | | Bit 4 => Support zoom operation; 0(not |
| | | | support), 1(support) |
| | | | Bit 5 => Support focus operation; 0(not |
| | | | support), 1(support)(SD/PZ/IZ series only) |
| text | string[64] | 1/4 | Enclose caption. |
| imprinttimestamp | <boolean></boolean> | 4/4 | Overlay time stamp on video. |
| maxexposure | <1~32000>, | 4/4 | Maximum exposure time |
| | <5~32000>, | | 1~32000 => 1s ~ 1/32000s |
| | <1~8000>, | | 5~32000 => 1/5s ~ 1/32000s |
| | <5~8000>, | | 1~8000 => 1s ~ 1/8000s |
| | etc. | | 5~8000 => 1/5s ~ 1/8000s |
| | | | etc. |
| | * Available value is | | |
| | listed in | | * This parameter may also restrict image |
| | "capability_image_c | | frame rate from sensor due to sensor |
| | <n>_exposure_ma</n> | | generates a frame per exposure time. Ex: If |
| | xrange" | | this is set to 1/5s ~ 1/8000s and camera takes |
| | | | 1/5s on the night, then sensor only outputs 5 |
| | | | frame/s. |

| | | | <pre>* Only available when "capability_image_c<n>_exposure_maxrang e" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed</n></pre> |
|---------------|---------------------|-----|--|
| enablepreview | <boolean></boolean> | 1/4 | Usage for UI of exposure settings. Preview settings of video profile. |

7.8.1 Video input setting per channel

Group: **videoin_c<0~(n-1)>** for n channel products, and m is stream number

n denotes the value of "capability_nvideoin", m denotes the value of "capability_nmediastream"

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------------|--|-----------|--|
| | | (get/set) | |
| cmosfreq | 50, 60 | 4/4 | CMOS frequency. |
| | | | (capability.videoin.type=2) |
| mode | 0 ~ | 4/4 | Indicate the video mode on use. |
| | "capability_videoin_c <n>_nmode"-1</n> | | |
| whitebalance | auto, manual, rbgain | 4/4 | Modes of white balance. |
| | | | "auto": Auto white balance |
| | (Available values are listed in | | "rbgain": Use rgain and bgain to set |
| | "capability_image_c <n>_wbmode")</n> | | white balance manually. |
| | | | "manual": 2 cases: |
| | | | a. if "rbgain" is not supported, this |
| | | | means keep current white balance |
| | | | status. |
| | | | b. if "rbgain" is supported, "rgain" |
| | | | and "bgain" are updated to the current |
| | | | values which is got from white balance |
| | | | module. Then, act as rbgain mode |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_wbmode" !=</n> |
| | | | "_" |
| rgain | 0~100 | 4/4 | Manual set rgain value of gain control |
| | | | setting. |
| | | | 0: Weak <-> 100: Strong |
| | | | |
| | | | * Only available when "rbgain" is listed |

| | | | T |
|---------------|----------------------------------|-----|---|
| | | | in "capability_image_c <n>_wbmode".</n> |
| | | | * Only valid when |
| | | | "videoin_c <n>_whitebalance" != auto</n> |
| | | | * Normalized range. |
| bgain | 0~100 | 4/4 | Manual set bgain value of gain control |
| | | | setting. |
| | | | 0: Weak <-> 100: Strong |
| | | | * Only available when "rbgain" is listed |
| | | | in "capability_image_c <n>_wbmode".</n> |
| | | | * Only valid when |
| | | | "videoin_c <n>_whitebalance" != auto</n> |
| | | | * Normalized range. |
| exposurelevel | 0~12 | 4/4 | Exposure level |
| | | | "0,12": This range takes the concept |
| | | | from DC's exposure tuning options. |
| | | | The definition is: |
| | | | 0: EV -2.0 |
| | | | 1: EV -1.7 |
| | | | 2: EV -1.3 |
| | | | 3: EV -1.0 |
| | | | 4: EV -0.7 |
| | | | 5: EV -0.3 |
| | | | 6: EV 0 |
| | | | 7: EV +0.3 |
| | | | 8: EV +0.7 |
| | | | 9: EV +1.0 |
| | | | 10: EV +1.3 |
| | | | 11: EV +1.7 |
| | | | 12: EV +2.0 |
| irismode | fixed, indoor, outdoor | 4/4 | Control DC-Iris mode. |
| | <product dependent=""></product> | | "outdoor": Auto-setting DC-Iris to get |
| | | | best quality, but easy to meet rolling or |
| | | | flicker effect in indoor environment. |
| | | | "indoor": Avoid rolling and flicker |
| | | | effect first. |
| | | | "fixed": Open the iris to maximum. |
| | | | * Only available when |
| | | | "capability_image_c <n>_iristype"=dc</n> |
| | | | |

| piris_mode manual, indoor, outdoor 1/4 | Control P-Iris mode. |
|--|---|
| <pre>>product</pre> | "outdoor": Auto-setting P-Iris to get |
| dependent> | best quality, but easy to meet rolling or |
| | flicker effect in indoor environment. |
| | "indoor": Avoid rolling and flicker |
| | effect first. |
| | "manual": Manual set P-Iris by |
| | "piris_position". |
| | * Only available when |
| | "capability_image_c <n>_iristype"=pi</n> |
| | ris |
| piris_position 1~100 1/4 | Manual set P-Iris. |
| <pre>>printposition: 1 100</pre> | 1: Open <-> 100: Close |
| dependent> | |
| | * Only vaild when |
| | "piris_mode"=manual |
| enableblc <boolean> 4/4</boolean> | Enable backlight compensation |
| <not support<="" td=""><td>* Not support this parameter anymore</td></not> | * Not support this parameter anymore |
| anymore> | when the version number |
| | (httpversion) is equal or greater than |
| | 0301a. |
| | * It's recommanded to use |
| | "exposurewin_c <n>_mode" to switch</n> |
| | on/off BLC. |
| maxgain 0~100 4/4 | Maximum gain value. |
| | 0: Low <-> 100: High |
| | |
| | * Only available when |
| | "capability_image_c <n>_agc_maxgai</n> |
| | n" != "-" |
| | * Only valid when |
| | "piris_mode"=manual or |
| | "irismode"=fixed |
| | * Normalized range. |
| mingain 0~100 4/4 | Minimum gain value. |
| | 0: Low <-> 100: High |
| | |
| | * Only available when |
| | |
| | "capability_image_c <n>_agc_mingai</n> |

| | | | * Only valid when |
|-----------------|-------------------------------------|-------|---|
| | | | "piris_mode"=manual or |
| | | | "irismode"=fixed |
| | | | |
| | | | * Normalized range. |
| color | 0, 1 | 4/4 | 0 =>monochrome |
| | | | 1 => color |
| flip | <boolean></boolean> | 4/4 | Flip the image. |
| mirror | <boolean></boolean> | 4/4 | Mirror the image. |
| rotate | 0,90,180,270 | 1/4 | The rotation angle of image. |
| | | | Support only in Rotation mode |
| | | | (capability.videoin.c <n>.rotation=1)</n> |
| ptzstatus | 0, <positive integer=""></positive> | 1/7 | A 32-bit integer, each bit can be set |
| | | | separately as follows: |
| | | | Bit 0 => Support camera control |
| | | | function; 0(not support), 1(support) |
| | | | Bit 1 => Built-in or external camera; |
| | | | 0 (external), 1(built-in) |
| | | | Bit 2 => Support pan operation; |
| | | | 0(not support), 1(support) |
| | | | Bit 3 => Support tilt operation; 0(not |
| | | | support), 1(support) |
| | | | Bit 4 => Support zoom operation; |
| | | | 0(not support), 1(support) |
| | | | Bit 5 => Support focus operation; |
| | | | 0(not support), 1(support)(SD/PZ/IZ |
| | | | series only) |
| text | string[64] | 1/4 | Enclose caption. |
| imprinttimesta | <boolean></boolean> | 4/4 | Overlay time stamp on video. |
| mp | | | |
| textonvideo_po | top, bottom | 4/4 | Text on video string position |
| sition | | ., . | · · · · · · · · · · · · · · · · · · · |
| textonvideo_siz | 20~40 | 4/4 | Text on video font size |
| e | | | |
| textonvideo_fon | /usr/share/font/Default.ttf, | 4/4 | Choose camera default font file |
| tpath | /mnt/flash2/upload.ttf | -7/-7 | (/usr/share/font/Default.ttf) or user |
| | | | uploaded font |
| | | | |
| handar da i | | 1/7 | file(/mnt/flash2/upload.ttf). |
| textonvideo_upl | Depends on the font file name | 1/7 | Show the uploaded font file name. |
| oadfilename | uploaded by user | | |
| minexposure | <1~32000>, | 4/4 | Minimum exposure time |

| | | | 1 |
|---------------|--|-----|---|
| | <5~32000>, | | 1~32000 => 1s ~ 1/32000s |
| | <1~8000>, | | 5~32000 => 1/5s ~ 1/32000s |
| | <5~8000>, | | 1~8000 => 1s ~ 1/8000s |
| | etc. | | 5~8000 => 1/5s ~ 1/8000s |
| | | | etc. |
| | * Available value is listed in | | |
| | "capability_image_c <n>_exposure_m</n> | | * Only available when |
| | inrange" | | "capability_image_c <n>_exposure_m</n> |
| | | | inrange" != "-" |
| | | | * Only valid when |
| | | | "piris_mode"=manual or |
| | | | "irismode"=fixed |
| maxexposure | <1~32000>, | 4/4 | Maximum exposure time |
| | <5~32000>, | | 1~32000 => 1s ~ 1/32000s |
| | <1~8000>, | | 5~32000 => 1/5s ~ 1/32000s |
| | <5~8000>, | | 1~8000 => 1s ~ 1/8000s |
| | etc. | | 5~8000 => 1/5s ~ 1/8000s |
| | | | etc. |
| | * Available value is listed in | | |
| | "capability_image_c <n>_exposure_m</n> | | * This parameter may also restrict |
| | axrange" | | image frame rate from sensor due to |
| | | | sensor generates a frame per |
| | | | exposure time. Ex: If this is set to 1/5s |
| | | | $\sim1/8000s$ and camera takes 1/5s on |
| | | | the night, then sensor only outputs 5 |
| | | | frame/s. |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_exposure_m</n> |
| | | | axrange" != "-" |
| | | | * Only valid when |
| | | | "piris_mode"=manual or |
| | | | "irismode"=fixed |
| enablepreview | <boolean></boolean> | 1/4 | Usage for UI of exposure settings. |
| | | | Preview settings of video profile. |
| crop_position | <coordinate></coordinate> | 1/7 | Crop left-top corner coordinate. |
| | (x,y) | | |
| crop_size | <window size=""></window> | 1/7 | Crop width and height. |
| | (WxH) | | (width must be 16x or 32x and height |
| | | | must be 8x) |

| s<0~(m-1)>_e | <boolean></boolean> | 4/4 | Indicate whether stream supprts eptz |
|-----------------|---------------------------------------|-----|---|
| nableeptz | | | or not |
| s<0~(m-1)>_c | Listed at "capability_videoin_codec" | 1/4 | Codec type for this stream |
| odectype | Possible values are: mjpeg, h264,h265 | | |
| | <product dependent=""></product> | | |
| s<0~(m-1)>_re | Available options are list in | 1/4 | Video resolution in pixels. |
| solution | "capability_videoin_c0_resolution". | | |
| s<0~(m-1)>_h | 250, 500, 1000, 2000, 3000, 4000 | 4/4 | Intra frame period in milliseconds. |
| 264_intraperiod | | | |
| s<0~(m-1)>_h | cbr, vbr, smart | 4/4 | cbr: Constant bit rate mode. |
| 264_ratecontrol | | | vbr: Fixed quality mode, all frames are |
| mode | | | encoded in the same quality. |
| | | | smart: Smart stream mode. Only valid |
| | | | when |
| | | | capability_smartstream_support=1 |
| s<0~(m-1)>_h | 1~5, | 4/4 | Set the pre-defined quality level: |
| 264_quant | 99, 100 | | 1: Medium |
| | | | 2: Standard |
| | | | 3: Good |
| | | | 4: Detailed |
| | | | 5: Excellent |
| | | | 100: Use the quality level in |
| | | | "qpercent" |
| | | | 99: Use the quality level in "qvalue" |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr. |
| s<0~(m-1)>_h | 0~51 | 4/4 | Manual video quality level input. |
| 264_qvalue | | | The Q value which is used by encoded |
| | | | library directly. |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr and s<0~(m-1)>_h264_quant = |
| | | | 99. |
| s<0~(m-1)>_h | 1~100 | 4/4 | Select customized quality in a |
| 264_qpercent | | | normalized full range. |
| | | | 1: Worst quality |
| | | | 100: Best quality |

| | | | * Only valid when "ratecontrolmode"= |
|------------------|--|-----|--|
| | | | vbr and "quant"= 100. |
| s<0~(m-1)>_h | 20000~"capability_videoin_c <n>_h2</n> | 4/4 | The target bit rate in constant bit rate |
| 264_bitrate | 64_maxbitrate" | , | mode. |
| _ | | | |
| | | | * Only valid when "ratecontrolmode"= |
| | | | cbr |
| s<0~(m-1)>_h | 20000~"capability_videoin_c <n>_mj</n> | 4/4 | The maximum allowed bit rate in fixed |
| 264_maxvbrbitr | peg_maxbitrate" | | quality mode. |
| ate | | | When the bit rate exceeds this value, |
| | | | frames will be dropped to restrict the |
| | | | bit rate. |
| | | | |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr |
| s<0~(m-1)>_h | 1~"capability_videoin_c <n>_h264_m</n> | 1/4 | The maximum frame rates of a H264 |
| 264_maxframe | axframerate" | | stream at different |
| | | | resolutions("capability_videoin_c0_re |
| | | | solution ") are recorded in |
| | | | "capability_videoin_c <n>_h264_maxf</n> |
| | | | ramerate" |
| s<0~(m-1)>_h | 0~2 | 1/4 | Indicate H264 profiles |
| 264_profile | | | 0: baseline |
| | | | 1: main profile |
| | | | 2: high profile |
| s<0~(m-1)>_h | framerate, imagequality | 4/4 | Set prioritypolicy |
| 264_prioritypoli | | | |
| су | | | |
| s<0~(m-1)>_h | 250, 500, 1000, 2000, 3000, 4000 | 4/4 | Intra frame period in milliseconds. |
| 265_intraperiod | | | |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| s<0~(m-1)>_h | cbr, vbr, smart | 4/4 | cbr: Constant bit rate mode. |
| 265_ratecontrol | | | vbr: Fixed quality mode, all frames are |
| mode | | | encoded in the same quality. |
| | | | smart: Smart stream mode. Only valid |
| | | | when |
| | | | capability_smartstream_support=1 |
| | | | |

| | | | * Only available when h265 is listed in |
|--------------|--|------|--|
| | | | "capability_videoin_codec". |
| s<0~(m-1)>_h | 1~5, | 4/4 | Set the pre-defined quality level: |
| 265_quant | 99, 100 | ., . | 1: Medium |
| quane | 55, 200 | | 2: Standard |
| | | | 3: Good |
| | | | 4: Detailed |
| | | | 5: Excellent |
| | | | 100: Use the quality level in |
| | | | "qpercent" |
| | | | 99: Use the quality level in "qvalue" |
| | | | |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec" and |
| | | | "ratecontrolmode"= vbr. |
| s<0~(m-1)>_h | 0~51 | 4/4 | Manual video quality level input. |
| 265_qvalue | | | The Q value which is used by encoded |
| | | | library directly. |
| | | | * Only available when b205 is listed in |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr and s<0~(m-1)>_h265_quant = 99. |
| s<0~(m-1)>_h | 1~100 | 4/4 | Select customized quality in a |
| 265_qpercent | | | normalized full range. |
| | | | 1: Worst quality |
| | | | 100: Best quality |
| | | | |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr and "quant"= 100. |
| s<0~(m-1)>_h | 20000~"capability_videoin_c <n>_h2</n> | 4/4 | The target bit rate in constant bit rate |
| 265_bitrate | 65_maxbitrate" | | mode. |
| | | | |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| | | | * Only valid when "ratecontrolmode"= |
| | | | cbr |

| s<0~(m-1)>_h | 20000~"capability_videoin_c <n>_mj</n> | 4/4 | The maximum allowed bit rate in fixed |
|-----------------------------|--|-----|---|
| 265_maxvbrbitr | peg_maxbitrate" | | quality mode. |
| ate | | | When the bit rate exceeds this value, |
| | | | frames will be dropped to restrict the |
| | | | bit rate. |
| | | | |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr |
| s<0~(m-1)>_h | 1~"capability_videoin_c <n>_h265_m</n> | 1/4 | The maximum frame rates of a H265 |
| 265_maxframe | axframerate" | | stream at different |
| | | | resolutions("capability_videoin_c0_re |
| | | | solution ") are recorded in |
| | | | "capability_videoin_c <n>_h265_maxf</n> |
| | | | ramerate" |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| $a < 0 \cdot (m, 1) > b$ | 0~2 | 1/4 | |
| s<0~(m-1)>_h 265_profile | 0~2 | 1/4 | Indicate H265 profiles 0: baseline |
| 205_prome | | | |
| | | | 1: main profile |
| | | | 2: high profile |
| | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| s<0~(m-1)>_h | framerate, imagequality | 4/4 | Set prioritypolicy |
| 265_prioritypoli | | | |
| су | | | * Only available when h265 is listed in |
| | | | "capability_videoin_codec". |
| s<0~(m-1)>_m | cbr, vbr | 4/4 | cbr: Constant bit rate mode. |
| jpeg_ratecontro | | | vbr: Fixed quality mode, all frames are |
| Imode | | | encoded in the same quality. |
| | | | |
| s<0~(m-1)>_m | | 4/4 | * Only valid when "ratecontrolmode"= |
| jpeg_quant | 99, 100 | | vbr. |
| | | | Set the pre-defined quality level: |
| | | | 1: Medium |
| | | | 2: Standard |
| | | | 3: Good |

| | | 1 | |
|----------------|---|-----|--|
| | | | 4: Detailed |
| | | | 5: Excellent |
| | | | 100: Use the quality level in |
| | | | "qpercent" |
| | | | 99: Use the quality level in "qvalue" |
| s<0~(m-1)>_m | 10~200 | 4/4 | Manual video quality level input. The Q |
| jpeg_qvalue | (Only valid when | | value which is used by encoded library |
| | "capability_api_httpversion" format is | | directly. |
| | XXXXX_1, | | |
| | ex: 0301a_1) | | * Only valid when "ratecontrolmode"= |
| | or 1~99 | | vbr and s<0~(m-1)>_mjpeg_quant = |
| | (Only valid when | | 99 |
| | "capability_api_httpversion" format is | | |
| | XXXXX_2, | | |
| | ex: 0301a_2) | | |
| | | | |
| | <pre><product dependent=""></product></pre> | | |
| s<0~(m-1)>_m | 1~100 | 4/4 | Select customized quality in a |
| jpeg_qpercent | | | normalized full range. |
| | | | 1: Worst quality |
| | | | 100: Best quality |
| | | | |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr and s<0~(m-1)>_mjpeg_quant = |
| | | | 100. |
| s<0~(m-1)>_m | 20000~"capability_videoin_c <n>_mj</n> | 4/4 | The target bit rate in constant bit rate |
| jpeg_bitrate | peg_maxbitrate" | | mode. |
| | | | |
| | | | * Only valid when "ratecontrolmode"= |
| | | | cbr |
| s<0~(m-1)>_m | 20000~"capability_videoin_c <n>_mj</n> | 4/4 | The maximum allowed bit rate in fixed |
| jpeg_maxvbrbit | peg_maxbitrate" | | quality mode. |
| rate | | | When the bit rate exceeds this value, |
| | | | frames will be dropped to restrict the |
| | | | bit rate. |
| | | | |
| | | | * Only valid when "ratecontrolmode"= |
| | | | vbr |
| | | 1/4 | |
| s<0~(m-1)>_m | 1~"capability_videoin_c <n>_mjpeg_</n> | 1/4 | The maximum frame rates of a mjpeg |
| jpeg_maxframe | maxframerate" | | stream at different |
| | | | resolutions("capability_videoin_c0_re |

| | | | solution ") are recorded in |
|--|-----------------------|-----|--|
| | | | "capability_videoin_c <n>_mjpeg_ma</n> |
| | | | xframerate" |
| s<0~(m-1)>_m fra | amerate, imagequality | 4/4 | Set prioritypolicy |
| jpeg_prioritypoli | | , | |
| cy | | | |
| | boolean> | 4/4 | Enable WDR pro |
| <product< td=""><td></td><td></td><td></td></product<> | | | |
| dependent> | | | * Only available when |
| | | | "capability_image_c <n>_wdrpro_mo</n> |
| | | | de" > 0 |
| wdrpro_strengt 1 | ~100 | 4/4 | The strength of WDR Pro. |
| h | | | The bigger value means the stronger |
| <product< td=""><td></td><td></td><td>strength of WDR Pro.</td></product<> | | | strength of WDR Pro. |
| dependent> | | | * Only available when |
| | | | ' "capability_image_c <n>_wdrpro_stre</n> |
| | | | ngth" is 1 |
| wdrc_mode < | boolean> | 4/4 | Enable WDR enhanced. |
| <product< td=""><td></td><td></td><td>* Only available when</td></product<> | | | * Only available when |
| dependent> | | | "capability_image_c <n>_wdrc_mode</n> |
| | | | " is 1 |
| wdrc_strength 1 | ~100 | 4/4 | The strength of WDR enhanced. |
| <product< td=""><td></td><td>,</td><td>The bigger value means the stronger</td></product<> | | , | The bigger value means the stronger |
| dependent> | | | strength of WDR enhanced. |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_wdrc_mode</n> |
| | | | " is 1 |
| aespeed_mode < | boolean> | 4/4 | Turning AE converge speed on or off. |
| <product< td=""><td></td><td></td><td>0: off</td></product<> | | | 0: off |
| dependent> | | | 1: on |
| | | | * Only available when |
| | | | ' "capability_image_c <n>_aespeed" is</n> |
| | | | 1 |
| aespeed_speedl 1 | ~100 | 4/4 | The speed level of AE converge speed. |
| evel | | | 1~20: level 1 |
| <product< td=""><td></td><td></td><td>21~40: level 2</td></product<> | | | 21~40: level 2 |
| dependent> | | | 41~60: level 3 |
| | | | |
| | | | 61~80: level 4 |

| | 1 | | |
|---|--|-----|---|
| | | | Level 1~4(low ~ high) |
| | | | The higher speed level meas shorter |
| | | | AE converged time during AE |
| | | | executing. |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is</n> |
| | | | 1 |
| aespeed_sensiti | 1~100 | 4/4 | The sensitivity of AE converge speed. |
| vity | | | 1~20: level 1 |
| <product< td=""><td></td><td></td><td>21~40: level 2</td></product<> | | | 21~40: level 2 |
| dependent> | | | 41~60: level 3 |
| | | | 61~80: level 4 |
| | | | 81~100: level 5 |
| | | | Level 1~4(low ~ high) |
| | | | The higher sensitivity level meas that |
| | | | it is easy to be trigger while scene |
| | | | changed. |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is</n> |
| | | | 1 |
| flickerless | <boolean></boolean> | 4/4 | Turn on(1) or turn off(0) the flickerless |
| <product< td=""><td></td><td></td><td>mode</td></product<> | | | mode |
| dependent> | | | * Only available when |
| | | | "capability_image_c <n>_flickerless"</n> |
| | | | is 1 |
| mounttype | ceiling, wall, floor | 1/6 | wall mount: 180° panoramic view |
| <product< td=""><td></td><td></td><td>ceiling mount: 360° surround view</td></product<> | | | ceiling mount: 360° surround view |
| dependent> | | | without blind spots |
| | | | floor mount: 360° surround view |
| | | | without blind spots |
| | | | |
| | | | * Only available when |
| | | | "capability_fisheye" > 0 |
| enablewatermar | 0, 1 | 1/6 | 0: Not to add watermarks on images |
| k | | 1,0 | 1: Add watermarks on images |
| <product< td=""><td></td><td></td><td></td></product<> | | | |
| dependent> | | | * Only available when |
| | | | "capability_fisheye" > 0 |
| c < 0 < (m - 2) > f | | 1/4 | |
| s<0~(m-2)>_fi | '10, 1P, 2P, 1R, 4R' for ceiling/floor | 1/4 | Local dewarp mode. |
| sheyedewarpmo | mount | | "10" is original mode (disable). |

| de | '10, 1P, 1R, 4R' for wall mount | Supported dewarp mode is different by |
|--|----------------------------------|--|
| <product< td=""><td><product dependent=""></product></td><td>mount type.</td></product<> | <product dependent=""></product> | mount type. |
| dependent> | | (videoin_c <n>_mounttype)</n> |
| | | Supported mode list could be |
| | | extracted from |
| | | (capability_videoin_c <n>_localdewar</n> |
| | | p_typeceilingmount) and |
| | | (capability_videoin_c <n>_localdewar</n> |
| | | p_typewallmount) |
| | | |
| | | * Only available when |
| | | "capability_fisheyelocaldewarp_c<0~(|
| | | capability_nvideoin)-1>" > 0 |

Group: videoin_c<0~(n-1)>_s<0~(m-1)>_h264_smartstream (capability_smartstream_support=1) Group: videoin_c<0~(n-1)>_s<0~(m-1)>_h265_smartstream (capability_smartstream_support=1 and h265 is listed in "capability_videoin_codec")

| n denotes the value of | "canability | nvidooin" n | a donatos th | o valuo of " | canability | nmodiactroam" |
|-------------------------|-------------|--------------|--------------|--------------|-------------|---------------|
| IT denotes the value of | capability | _nviueoni ,n | i denotes th | e value ol | capability_ | _mmeulastream |

| NAME | VALUE | SECURITY | DESCRIPTION |
|------------------|----------------------------|-----------|---|
| | | (get/set) | |
| mode | autotracking,manual,hybrid | 4/4 | Set Smart stream mode |
| foreground_quant | 0~5 | 4/4 | Quality of foreground quality 0 = worst |
| | | | quality, 5 = best quality. |
| background_quant | 0~5 | 4/4 | Quality of background quality $0 =$ |
| | | | worst quality, 5 = best quality. |
| maxbitrate | 20000~40000000 | 4/4 | Maximum bitrate |

Group: videoin_c<0~(n-1)>_s<0~(m-1)>_h264_smartstream_win_i<0~(k-1)>

(capability_smartstream_support=1 and capability_smartstream_mode_manual = 1)
Group: videoin_c<0~(n-1)>_s<0~(m-1)>_h265_smartstream_win_i<0~(k-1)>
(capability_smartstream_support=1 and h265 is listed in "capability_videoin_codec" and
capability_smartstream_mode_manual = 1)

n denotes the value of "capability_nvideoin",m denotes the value of " capability_nmediastream",k denotes the value of "capability_smartstream_nwindow_manual".

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------|---------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable or disable the window. |
| home | 0~320,0~240 | 4/4 | Left-top corner coordinate of the window. |
| size | 0~320x0~240 | 4/4 | Width and height of the window |

7.8.1.1 Alternative video input profiles per channel

In addition to the primary setting of video input, there can be alternative profile video input setting for each channel which might be for different scene of light (daytime or nighttime).

Group: videoin_c0_profile_i<0~(m-1)> for n channel profucts and m profile

m denotes the value of "capability_nvideoinprofile" (capability.nvideoinprofile> 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------|----------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable/disable this profile setting |
| policy | night, | 4/4 | The mode which the profile is applied to. |
| | schedule | | |
| | | | * Not support "policy=day" anymore when the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0301a. |
| begintime | hh:mm | 4/4 | Begin time of schedule mode. |
| endtime | hh:mm | 4/4 | End time of schedule mode. |
| minexposure | <1~32000>, | 4/4 | Minimum exposure time |
| | <5~32000>, | | 1~32000 => 1s ~ 1/32000s |
| | <1~8000>, | | 5~32000 => 1/5s ~ 1/32000s |
| | <5~8000>, | | 1~8000 => 1s ~ 1/8000s |
| | etc. | | 5~8000 => 1/5s ~ 1/8000s |
| | | | etc. |
| | * Available value is | | |
| | listed in | | * Only available when |
| | "capability_image_c | | "capability_image_c <n>_exposure_minrange</n> |
| | <n>_exposure_min</n> | | "!= "-" |
| | range" | | * Only valid when "piris_mode"=manual or |
| | | | "irismode"=fixed |
| maxexposure | <1~32000>, | 4/4 | Maximum exposure time |
| | <5~32000>, | | 1~32000 => 1s ~ 1/32000s |
| | <1~8000>, | | 5~32000 => 1/5s ~ 1/32000s |
| | <5~8000>, | | 1~8000 => 1s ~ 1/8000s |
| | etc. | | 5~8000 => 1/5s ~ 1/8000s |
| | | | etc. |
| | * Available value is | | |
| | listed in | | * This parameter may also restrict image |
| | "capability_image_c | | frame rate from sensor due to sensor |

| | | 1 | |
|-----------------------------------|-----------------------|-----|---|
| | <n>_exposure_ma</n> | | generates a frame per exposure time. Ex: If |
| | xrange" | | this is set to 1/5s \sim 1/8000s and camera takes |
| | | | 1/5s on the night, then sensor only outputs 5 |
| | | | frame/s. |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_exposure_maxrang</n> |
| | | | e" != "-" |
| | | | * Only valid when "piris_mode"=manual or |
| | | | "irismode"=fixed |
| enableblc | <boolean></boolean> | 4/4 | Enable backlight compensation. |
| <not anymore="" support=""></not> | | | * Not support this parameter anymore when |
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| | | | * It's recommanded to use |
| | | | "exposurewin_c <n>_mode" to switch on/off</n> |
| | | | BLC. |
| exposurelevel | 0~12 | 4/4 | Exposure level |
| | | | "0,12": This range takes the concept from DC's |
| | | | exposure tuning options. The definition is: |
| | | | 0: EV -2.0 |
| | | | 1: EV -1.7 |
| | | | 2: EV -1.3 |
| | | | 3: EV -1.0 |
| | | | 4: EV -0.7 |
| | | | 5: EV -0.3 |
| | | | 6: EV 0 |
| | | | 7: EV +0.3 |
| | | | 8: EV +0.7 |
| | | | 9: EV +1.0 |
| | | | 10: EV +1.3 |
| | | | 11: EV +1.7 |
| | | | 12: EV +2.0 |
| whitebalance | auto, manual, | 4/4 | Modes of white balance. |
| | rbgain | | "auto": Auto white balance |
| | | | "rbgain": Use rgain and bgain to set white |
| | (Available values are | | balance manually. |
| | listed in | | "manual": 2 cases: |
| | "capability_image_c | | a. if "rbgain" is not supported, this means |
| | <n>_wbmode")</n> | | keep current white balance status. |
| L | 1 | 1 | 1 |

| margain 0~100 4/4 Manual set or supported, "rgain" and "bgain" are updated to the current values which is got from white balance module. Then, act as rbgain mode rgain 0~100 4/4 Manual set ragin value of gain control setting. 0: Weak <-> 100: Strong rgain 0~100 4/4 Manual set ragin value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set ragin value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set dgain value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set dgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Manual set dgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Manual set dgain value of gain control setting. 0: Low <-> 100: High maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "risimode" = manual or "Irismode" = fixed ** Normalized range. * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "pirs_mode" = manual or "Irismode" = fixed ** Normalized range. * Only available when ** Only available when ** Only available when ** On | | 1 | | |
|--|------------|-----------------|-----|---|
| which is got from white balance module. Then, act as rbgain modergain0~1004/4Manual set rgain value of gain control setting. 0: Weak <>> 100: Strongrgain0~1004/4Manual set rgain value of gain control setting. 0: Weak <>> 100: Strongbgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <>> 100: Strongbgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <>> 100: Strongbgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <>> 100: Strongmaxgain0~1004/4Marian set bgain value of gain control setting. 0: Weak <>> 100: Strongmaxgain0~1004/4Maximum gain value. 0: Low <>> 100: Highmingain0~1004/4Maximum gain value. 0: Low <>> 100: High* Only valiable when "capability_image_cons_age_maxgain"!="-" * Only valiable when "capability_image_cons_age_maxgain"!="-" * Only valiable when "capability_image_cons_age_maxgain"!="-" * Only valiable when "capability_image_cons_age_maxgain"!="-" * Only valiable when "capability_image_cons_age_mingain"!= "-" * Only valiable w | | | | |
| Image | | | | - |
| Image: | | | | which is got from white balance module. Then, |
| Image: constraint of the second sec | | | | act as rbgain mode |
| rgain 0~100 4/4 Manual set raja value of gain control setting. 0: Weak <-> 100: Strong * Only available when "rbgain" is listed in "capability_image_c <n>_wbmode". * Only valid when "videoin_c<n>_whitebalance" != auto bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "rismode"=fixed * Normalized range. mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n> | | | | * Only available when |
| mingain 0~100 4/4 Normalized range. mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "rbgain" is listed in "capability_image_c <n>_whitebalance" != auto * Normalized range. bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong * Only available when "rbgain" is listed in "capability_image_c<n>_whitebalance" != auto * Normalized range. maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "rbgain" != "-" * Only valiable when "capability_image_c<n>_agc_maxgain" != "-" * Normalized range. mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "rbgain" != "-" * * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * * Only availab</n></n></n></n></n></n></n></n></n></n></n> | | | | "capability_image_c <n>_wbmode" !="-"</n> |
| bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "-" * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only vailable when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only vailable when</n></n></n></n></n></n></n></n></n></n></n> | rgain | 0~100 | 4/4 | Manual set rgain value of gain control setting. |
| minipain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong * Only available when "rbgain" is listed in "capability_image_c <n>_wbmode". * Only available when "rbgain" is listed in "capability_image_c<n>_wbmode". * Only valid when "videoin_c<n>_wbmode". * Only valid when "inismode"=fixed * Only valid when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "inismode"=fixed * Only valid when "capability_image_c<n>_agc_mingain" != "." * Only valid when "p</n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n> | | | | 0: Weak <-> 100: Strong |
| minipain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong * Only available when "rbgain" is listed in "capability_image_c <n>_wbmode". * Only available when "rbgain" is listed in "capability_image_c<n>_wbmode". * Only valid when "videoin_c<n>_wbmode". * Only valid when "inismode"=fixed * Only valid when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "inismode"=fixed * Only valid when "capability_image_c<n>_agc_mingain" != "." * Only valid when "p</n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n> | | | | |
| Part and the second s | | | | * Only available when "rbgain" is listed in |
| Image:Image:Image:bgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <-> 100: Strongbgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <-> 100: Strongmaxgain0~1004/4Maximum gain value. 0: Low <-> 100: Highmaxgain0~1004/4Maximum gain value. 0: Low <-> 100: Highmingain0~1004/4Maximum gain value. 0: Low <-> 100: Highiningain0~1004/4Minimum gain value. 0: Low <-> 100: Highiningaininingaininingain* Only valiable when "capability_image_c <n>_age_mingain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | "capability_image_c <n>_wbmode".</n> |
| Image:Image:bgain0~1004/4Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong* Only available when "rbgain" is listed in "capability_image_c <n>_wbmode". * Only valid when "videoin_c<n>_whitebalance" != auto * Normalized range.maxgain0~1004/4Maximum gain value. 0: Low <-> 100: High * Only valid when "irismode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only valiable when "capability_image_<n>_ac_maxgain" != "." * Only valiable when "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_<n>_ac_mingain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n> | | | | * Only valid when |
| bgain 0~100 4/4 Manual set bgain value of gain control setting. 0: Weak <-> 100: Strong * Only available when "rbgain" is listed in "capability_image_c <n>_wbmode". * Only valid when "videoin_c<n>_wbmode". * Only valid when "videoin_c<n>_whitebalance" != auto * Normalized range. maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only available when "capability_image_c<n>_agc_mingain" != "." * Normalized range.</n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n> | | | | "videoin_c <n>_whitebalance" != auto</n> |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "." * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "." * Only available when "capability_image_c<n>_agc_mingain" != "." * Only available when "capability_image_c<n>_agc_mingain" != "." * Norny available when "capability_image_c<n>_agc_mingain" != "." * Normalized range.</n></n></n></n></n></n></n></n></n></n></n></n> | | | | * Normalized range. |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High mingain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "." * Only available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High iningain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High iningain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "." * Norny ava</n></n></n></n></n></n></n></n></n></n></n></n></n></n> | bgain | 0~100 | 4/4 | Manual set bgain value of gain control setting. |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only valiable when * Conly available when * capability_image_c <n>_agc_maxgain" != "." mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when * Conly available when * Conly available when "capability_image_c<n>_agc_maxgain" != "." * Only valid when "piris_mode"=manual or "irismode"=fixed mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when * Conly available when * Conly available when "capability_image_c<n>_agc_mingain" != "." * Only available when "mingain Volume * Normalized range.</n></n></n></n></n></n></n></n></n></n> | | | | 0: Weak <-> 100: Strong |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only valid when * Only available when * Conly available when "capability_image_c <n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only valid when "piris_m</n></n></n></n></n></n></n></n></n></n></n></n> | | | | |
| * Only valid when "videoin_c <n>_whitebalance" != auto * Normalized range.maxgain0~1004/4Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n> | | | | * Only available when "rbgain" is listed in |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n> | | | | "capability_image_c <n>_wbmode".</n> |
| maxgain0~1004/4Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain"!="-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain"!= "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n></n></n> | | | | * Only valid when |
| maxgain 0~100 4/4 Maximum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n> | | | | "videoin_c <n>_whitebalance" != auto</n> |
| mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n></n></n></n> | | | | * Normalized range. |
| mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_maxgain" != "-" * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Only available when "capability_image_c<n>_agc_mingain" != "-" * Normalized range.</n></n></n></n> | maxgain | 0~100 | 4/4 | Maximum gain value. |
| mingain0~1004/4Minimum gain value. 0: Low <-> 100: High* Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | 0: Low <-> 100: High |
| mingain0~1004/4Minimum gain value. 0: Low <-> 100: High* Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.mingain0~1004/4Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | * Only available when |
| * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | |
| mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High 0: Low <-> 100: High * Only available when * capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or * irismode"=fixed * Normalized range. * Normalized range.</n> | | | | |
| mingain0~1004/4Minimum gain value. 0: Low <-> 100: High* Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | |
| mingain 0~100 4/4 Minimum gain value. 0: Low <-> 100: High 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. * Normalized range.</n> | | | | |
| 0: Low <-> 100: High * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | mingain | 0~100 | 4/4 | |
| * Only available when "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | iningani | 0.0100 | | _ |
| "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | 0. Low (/ 100. High |
| "capability_image_c <n>_agc_mingain" != "-" * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range.</n> | | | | * Only available when |
| * Only valid when "piris_mode"=manual or "irismode"=fixed * Normalized range. | | | | |
| "irismode"=fixed * Normalized range. | | | | |
| * Normalized range. | | | | |
| | | | | |
| piris_mode manual, indoor, 1/4 Control P-Iris mode. | piris_mode | manual, indoor, | 1/4 | Control P-Iris mode. |

| and the second second | aut da arr | | Housedoord, Auto active D Tricks and hash |
|----------------------------------|--|------|---|
| <product dependent=""></product> | outdoor | | "outdoor": Auto-setting P-Iris to get best |
| | | | quality, but easy to meet rolling or flicker effect |
| | | | in indoor environment. |
| | | | "indoor": Avoid rolling and flicker effect first. |
| | | | "manual": Manual set P-Iris by |
| | | | "piris_position". |
| | | | * Only available when |
| | | | "capability_image_c <n>_iristype"=piris</n> |
| piris_position | 1~100 | 1/4 | Manual set P-Iris. |
| <product dependent=""></product> | | | 1: Open <-> 100: Close |
| | | | |
| | | | * Only vaild when "piris_mode"=manual |
| irismode | fixed, indoor, | 4/4 | Control DC-Iris mode. |
| | outdoor | | "outdoor": Auto-setting DC-Iris to get best |
| | <product< td=""><td></td><td>quality, but easy to meet rolling or flicker effect</td></product<> | | quality, but easy to meet rolling or flicker effect |
| | dependent> | | in indoor environment. |
| | | | "indoor": Avoid rolling and flicker effect first. |
| | | | "fixed": Open the iris to maximum. |
| | | | * Only available when |
| | | | "capability_image_c <n>_iristype"=dciris</n> |
| wdrpro_mode | <boolean></boolean> | 4/4 | Enable WDR pro |
| <product dependent=""></product> | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_wdrpro_mode" > 0</n> |
| wdrpro_strength | 1~100 | 4/4 | The strength of WDR Pro. |
| <product dependent=""></product> | | ., . | The bigger value means the stronger strength |
| | | | of WDR Pro. |
| | | | * Only available when |
| | | | "capability_image_c <n>_wdrpro_strength" is</n> |
| | | | 1 |
| wdrc_mode | <boolean></boolean> | 4/4 | Enable WDR enhanced. |
| _ | | 4/4 | * Only available when |
| <product dependent=""></product> | | | |
| | 1 100 | 4/4 | "capability_image_c <n>_wdrc_mode" is 1</n> |
| wdrc_strength | 1~100 | 4/4 | The strength of WDR enhanced. |
| <product dependent=""></product> | | | The bigger value means the stronger strength |
| | | | of WDR enhanced. |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_wdrc_mode" is 1</n> |
| aespeed_mode | <boolean></boolean> | 4/4 | Turning AE converge speed on or off. |

| <product dependent=""></product> | | | 0: off |
|---|---------------------|------|---|
| <pre><pre>product dependent></pre></pre> | | | 1: on |
| | | | |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is 1</n> |
| aespeed_speedlevel | 1~100 | 4/4 | The speed level of AE converge speed. |
| <product dependent=""></product> | | | 1~20: level 1 |
| | | | 21~40: level 2 |
| | | | 41~60: level 3 |
| | | | 61~80: level 4 |
| | | | 81~100: level 5 |
| | | | Level $1 \sim 4$ (low \sim high) |
| | | | The higher speed level meas shorter AE |
| | | | converged time during AE executing. |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is 1</n> |
| aespeed_sensitivity | 1~100 | 4/4 | The sensitivity of AE converge speed. |
| <product dependent=""></product> | | | 1~20: level 1 |
| | | | 21~40: level 2 |
| | | | 41~60: level 3 |
| | | | 61~80: level 4 |
| | | | 81~100: level 5 |
| | | | Level 1~4(low ~ high) |
| | | | The higher sensitivity level meas that it is easy |
| | | | to be trigger while scene changed. |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is 1</n> |
| flickerless | <boolean></boolean> | 4/4 | Turn on(1) or turn off(0) the flickerless mode |
| <pre><pre>conduct dependent></pre></pre> | | ., . | * Only available when |
| | | | "capability_image_c <n>_flickerless" is 1</n> |
| | | | |

7.9 Time Shift settings

Group: timeshift for n channel profucts and m stream

n denotes the value of "capability_nvideoin", m denotes the value of "capability_nmediastream"

(capability.timeshift > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable time shift streaming. |
| c<0~(n-1)>_s<0~(m-1) | <boolean></boolean> | 4/4 | Enable time shift streaming for specific |
| >_allow | | | stream. |

7.10 IR cut control

Group: **ircutcontrol** (capability.nvideoinprofile> 0 and capability_daynight_c<0~(n-1)>_ircutfilter=1, n denotes the value of "capability_nvideoin")

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------------------|---|-----------|--|
| | | (get/set) | |
| mode | auto, | 6/6 | Set IR cut control mode |
| | day, | | |
| | night, | | |
| | di, | | |
| | schedule | | |
| | <product< td=""><td></td><td></td></product<> | | |
| | dependent> | | |
| sir | <boolean></boolean> | 6/6 | Enable/disable Smart IR |
| <product dependent=""></product> | | | * Only available when |
| | | | "capability_daynight_c<0~"capability_nvideoi |
| | | | n"-1>_smartir" is 1 |
| daymodebegintime | 00:00~23:59 | 6/6 | Day mode begin time |
| daymodeendtime | 00:00~23:59 | 6/6 | Day mod end time |
| disableirled | <boolean></boolean> | 6/6 | Enable/disable built-in IR led |
| | | | (capability_daynight_c<0~"capability_nvideoi |
| | | | n"-1>_buildinir > 0) |
| enableextled | <boolean></boolean> | 1/6 | Enable/disable external IR led |
| | | | (capability_daynight_c<0~"capability_nvideoi |
| | | | n"-1>externalir > 0) |
| bwmode | <boolean></boolean> | 6/6 | Switch to B/W in night mode if enabled |
| sensitivity | low, | 6/6 | Sensitivity of light sensor |

170 - User's Manual

| normal, | |
|---------|--|
| high | |

7.11 Image setting per channel

Group: image_c<0~(n-1)> for n channel profucts

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|---|----------|-----------|---|
| | | (get/set) | |
| brightness | -5~5,100 | 4/4 | -5: Darker <-> 5: Bright |
| <not recommended="" this="" to="" use=""></not> | | | 100: Use " image_c <n>_brightnesspercent"</n> |
| | | | |
| | | | * Only available when bit 0 of |
| | | | "capability_image_c <n>_basicsetting" is 1</n> |
| | | | |
| | | | * We replace "brightness" with |
| | | | "brightnesspercent". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| contrast | -5~5,100 | 4/4 | -5: Less contrast <-> 5: More contrast |
| <not recommended="" this="" to="" use=""></not> | | | 100: Use " image_c <n>_contrastpercent"</n> |
| | | | * Only available when bit 1 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| | | | |
| | | | * We replace "contrast" with "contrastpercent |
| | | | и. |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| saturation | -5~5,100 | 4/4 | -5: Less saturation <-> 5: More saturation |
| <not recommended="" this="" to="" use=""></not> | | | 100: Use " image_c <n>_saturationpercent"</n> |
| | | | |
| | | | * Only available when bit 2 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| | | | |
| | | | * We replace "saturation" with |
| | | | "saturationpercent". |
| | | | * This parameter will not be used after the |

| | | | version number (httpversion) is equal or |
|---|----------|------|--|
| | | | greater than 0400a. |
| sharpness | -3~3,100 | 4/4 | -3: Softer <-> 3: Sharper |
| <not recommended="" this="" to="" use=""></not> | 5 5,100 | ., . | 100: Use " image_c <n>_sharpnesspercent"</n> |
| | | | |
| | | | * Only available when bit 3 of |
| | | | ' "capability_image_c <n>_basicsetting" is 1.</n> |
| | | | |
| | | | * We replace "sharpness" with |
| | | | "sharpnesspercent". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| brightnesspercent | 0~100 | 4/4 | Set brightness in the normalized range. |
| | | | 0: Darker <-> 100: Bright |
| | | | |
| | | | * Only available when bit 0 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| contrastpercent | 0~100 | 4/4 | Set contrast in the normalized range. |
| | | | 0: Less contrast <-> 100: More contrast |
| | | | |
| | | | * Only available when bit 1 of |
| | | | "capability_image_c <n>_basicsetting" is 1</n> |
| saturationpercent | 0~100 | 4/4 | Set saturation in the normalized range. |
| | | | 0: Less saturation <-> 100: More saturation |
| | | | |
| | | | * Only available when bit 2 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| sharpnesspercent | 0~100 | 4/4 | Set sharpness in the normalized range. |
| | | | 0: Softer <-> 100: Sharper |
| | | | |
| | | | * Only available when bit 3 of |
| | | | "capability_image_c <n>_basicsetting" is 1</n> |
| gammacurve | 0~100 | 4/4 | 0: Fine-turned gamma curve by Vivotek. |
| | | | 1: Gamma value = 0.01 |
| | | | 2: Gamma value = 0.02 |
| | | | 3: Gamma value = 0.03 |
| | | | |
| | | | 100: Gamma value = 1 |
| | | | |
| | | 1 | |

| | | | * Note: Although we set gamma value to 100 |
|----------------------------------|------------------------|-----|--|
| | | | level, but not all gamma values are valid. |
| | | | |
| | | | Internal module will take the closest valid |
| | | | one. For example, 1~45 may all be mapped |
| | | | to gamma value = 0.45, etc. |
| lowlightmode | <boolean></boolean> | 4/4 | Enable/disable low light mode. |
| <product dependent=""></product> | | | * Only available when |
| | | | "capability_image_c <n>_lowlightmode" is 1</n> |
| dnr_mode | <boolean></boolean> | 4/4 | 3D noise reduction. |
| <product dependent=""></product> | | | 0:disable |
| | | | 1:enable |
| | | | * Only available when |
| | | | "capability_image_c <n>_dnr" is 1</n> |
| dnr_strength | 1~100 | 4/4 | Strength of 3DNR |
| <product dependent=""></product> | | | * Only available when |
| | | | "capability_image_c <n>_dnr" is 1</n> |
| defog_mode | <boolean></boolean> | 4/4 | Enable/disable defog mode. |
| <product dependent=""></product> | | | 0:disable |
| | | | 1:enable |
| | | | * Only available when |
| | | | "capability_image_c <n>_defog_mode" is 1</n> |
| defog_strength | 1~100 | 4/4 | Strength of defog |
| <product dependent=""></product> | | | * Only available when |
| | | | "capability_image_c <n>_defog_mode" is 1</n> |
| eis | <boolean></boolean> | 4/4 | Electronic image stabilizer |
| <product dependent=""></product> | | | 0:disable |
| | | | 1:enable |
| | | | * Only available when |
| | | | "capability_image_c <n>_eis" is 1</n> |
| scene_enable | <boolean></boolean> | 4/4 | Enable/disable scene mode |
| <product dependent=""></product> | | | 0: disable |
| | | | 1: enable |
| | | | * Only available when |
| | | | "capability_image_c <n>_scenemode_support</n> |
| | | | " is 1 |
| scene_mode | visibility, | 4/4 | Value of scene mode |
| <product dependent=""></product> | noiseless, | | * Only available when |
| | lpcparkinglot, | | "capability_image_c <n>_scenemode_support</n> |
| | lpcstreet | | " is 1 |
| | <pre>product</pre> | | * Available value is listed in |
| L | <pre>>product</pre> | | |

| | dependent> | | "capability_image_c <n>_scenemode_support</n> |
|---|---------------------|------|---|
| | | | type" |
| restoreatwb | 1~ | 4/4 | Restore of adjusting white balance of image |
| | | | according to mode settings |
| profile_i0_enable | <boolean></boolean> | 4/4 | Enable/disable this profile setting |
| profile_i0_policy | night, | 4/4 | The mode which the profile is applied to. |
| | schedule | | |
| | | | * Not support "policy=day" anymore when the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0301a. |
| profile_i0_begintime | hh:mm | 4/4 | Begin time of schedule mode. |
| profile_i0_endtime | hh:mm | 4/4 | End time of schedule mode. |
| profile_i0_brightness | -5~5,100 | 4/4 | -5: Darker <-> 5: Bright |
| <not recommended="" this="" to="" use=""></not> | | | 100: Use " image_c <n>_brightnesspercent"</n> |
| | | | * Only available when bit 0 of |
| | | | |
| | | | "capability_image_c <n>_basicsetting" is 1</n> |
| | | | * We replace "profile_i0_brightness" with |
| | | | "profile_i0_brightnesspercent". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| profile_i0_contrast | -5~5,100 | 4/4 | -5: Less contrast <-> 5: More contrast |
| <not recommended="" this="" to="" use=""></not> | | | 100: Use " image_c <n>_contrastpercent"</n> |
| | | | * Only available when hit 1 of |
| | | | * Only available when bit 1 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| | | | * We replace "profile_i0_contrast" with |
| | | | "profile_i0_contrastpercent ". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| profile_i0_saturation | -5~5,100 | 4/4 | -5: Less saturation <-> 5: More saturation |
| <not recommended="" this="" to="" use=""></not> | 0 0,100 | ., ' | 100: Use " image_c <n>_saturationpercent"</n> |
| | | | |
| | | | * Only available when bit 2 of |
| | | | "capability_image_c <n>_basicsetting" is 1.</n> |
| | | | |

| image: standard dependent> image: standard dependent> image: standard dependent> image: standard | | | | |
|--|---|---------------------|-----|--|
| Note: Although we set gamma value to 100 level, but not all gamma values are valid. Internal module will take the closest valid one. For example, 1-45 may all be mapped to gamma value = 0.45, etc.profile_i0_lowlightmode <pre>cyroduct dependent><boolean>4/4Enable/disable low light mode. * Only available when "capability_image_c<n>_lowlightmode" is 1profile_i0_dnr_mode <pre>cyroduct dependent><boolean>4/4Enable/disable low light mode. * Only available when "capability_image_c<n>_lowlightmode" is 1profile_i0_dnr_mode <pre>cyroduct dependent><boolean>4/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_i0_dnr_strength <pre>cyroduct dependent>1~1004/4Enable/disable defog mode. 0.disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_i0_defog_mode <pre>cyroduct dependent><boolean>4/4Enable/disable defog mode. 0.disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_i0_defog_strength <pre>cyroduct dependent>1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_defog_strength <pre>cyroduct dependent>1~1004/4Electronic image stabilizer 0.disable 1:enable * Only available when "capability_image_c<n>_cn>_edfog_mode" is 1profile_i0_defog_strength <pre>cyroduct dependent><boolean>4/4Electronic image stabilizer 0.disable 1:enable * Only available when "capability_image_c<n>_cn>_edfog_mode" is 1profile_i0_defog_strength <pre>cyroduct dependent><boolean>4/4<!--</td--><td></td><td></td><td></td><td></td></boolean></pre></n></boolean></pre></n></pre></n></pre></n></boolean></pre></n></pre></n></boolean></pre></n></boolean></pre></n></boolean></pre> | | | | |
| Internal module will take the closest valid one. For example, 1.~45 may all be mapped to gamma value = 0.45, etc.profile_10_lowlightmode <product dependent=""><boolean>4/4Enable/disable low light mode. * Only available when "capability_image_<n>_ens_lowingprofile_10_dnr_mode <product dependent=""><boolean>4/43D noise reduction. 0:disable 1:enable * Only available when "capability_image_<n>_ens_dnr" is 1profile_10_dnr_mode <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_<n>_ens_dnr" is 1profile_10_dnr_strength <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_<n>_dnr" is 1profile_0_defog_mode <product dependent=""><boolean>4/4Strength of 3DNR * Only available when "capability_image_<n>_dnr" is 1profile_10_defog_mode <product dependent=""><boolean>4/4Strength of defog * Only available when "capability_image_<n>_defog_mode" is 1profile_10_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_<n>_defog_mode" is 1profile_10_defog_strength <product dependent=""><boolean>4/4Electronic image stabilizer * Only available when "capability_image_<n>_elefog_mode" is 1profile_10_defog_tot <pre><boolean>4/4Electronic image stabilizer * Only available when * capability_image_<n>_elefog_mode" is 1profile_10_defog_nodent><boolean>4/4Electronic image stabilizer * Only available when * capability_image_<n>_elefog_mode" is 1prof</n></boolean></n></boolean></pre></n></boolean></product></n></product></n></boolean></product></n></boolean></product></n></product></n></product></n></boolean></product></n></boolean></product> | | | | |
| Internal module will take the closest valid one. For example, 1.~45 may all be mapped to gamma value = 0.45, etc.profile_10_lowlightmode <product dependent=""><boolean>4/4Enable/disable low light mode. * Only available when "capability_image_<n>_ens_lowingprofile_10_dnr_mode <product dependent=""><boolean>4/43D noise reduction. 0:disable 1:enable * Only available when "capability_image_<n>_ens_dnr" is 1profile_10_dnr_mode <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_<n>_ens_dnr" is 1profile_10_dnr_strength <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_<n>_dnr" is 1profile_0_defog_mode <product dependent=""><boolean>4/4Strength of 3DNR * Only available when "capability_image_<n>_dnr" is 1profile_10_defog_mode <product dependent=""><boolean>4/4Strength of defog * Only available when "capability_image_<n>_defog_mode" is 1profile_10_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_<n>_defog_mode" is 1profile_10_defog_strength <product dependent=""><boolean>4/4Electronic image stabilizer * Only available when "capability_image_<n>_elefog_mode" is 1profile_10_defog_tot <pre><boolean>4/4Electronic image stabilizer * Only available when * capability_image_<n>_elefog_mode" is 1profile_10_defog_nodent><boolean>4/4Electronic image stabilizer * Only available when * capability_image_<n>_elefog_mode" is 1prof</n></boolean></n></boolean></pre></n></boolean></product></n></product></n></boolean></product></n></boolean></product></n></product></n></product></n></boolean></product></n></boolean></product> | | | | * Note: Although we set gamma value to 100 |
| Internal module will take the closest valid one. For example, 1~45 may all be mapped to gamma value = 0.45, etc.profile_10_lowlightmode <boolean>4/4Enable/disable low light mode. * Only available when "capability_image_c<n>_owlightmode" is 1profile_10_dnr_mode<boolean>4/43D noise reduction. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_dnr_strength <pre>cyroduct dependent>1~1004/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode<boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode<boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_strength <pre>cyroduct dependent>1~1004/4Strength of dfog * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_eis<boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_eis<boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_scene_enable <pre>cyroduct dependent><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_0_scene_enable <pre>cyroduct dependent><boolean>4/4Enable/disable scene mode 0: disable 1:enable<b< td=""><td></td><td></td><td></td><td></td></b<></boolean></pre></n></boolean></pre></n></boolean></n></boolean></n></pre></n></boolean></n></boolean></n></pre></n></boolean></n></boolean> | | | | |
| profile_i0_lowlightmode <boolean> 4/4 Enable/disable low light mode. <product dependent=""> <boolean> 4/4 Enable/disable low light mode. <product dependent=""> <boolean> 4/4 Enable/disable low light mode. <product dependent=""> <boolean> 4/4 3D noise reduction. <product dependent=""> <boolean> 4/4 3D noise reduction. <product dependent=""> <boolean> 4/4 Strength of 3DNR <product dependent=""> 1~100 4/4 Strength of 3DNR <product dependent=""> <boolean> 4/4 Strength of defog mode. <product dependent=""> <boolean> 4/4 Strength of defog <product dependent=""> 1~100 4/4 Strength of defog <product dependent=""> 1~100 4/4 Strength of defog <product depend<="" td=""><td></td><td></td><td></td><td></td></product></product></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean> | | | | |
| profile_10_lowlightmode <pre>cproduct dependent><boolean>4/4Enable/disable low light mode. * Only available when "capability_image_c<n>_lowlightmode" is 1profile_10_dnr_mode <pre>cproduct dependent><boolean>4/43D noise reduction. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_dnr_strength <pre>cproduct dependent>1~1004/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode <pre>cproduct dependent><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode <pre>cproduct dependent><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_defog_strength <pre>croduct dependent>1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_eis <pre>cproduct dependent><boolean>4/4Electronic image stabilizer (cisable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_scene_enable <pre>cproduct dependent><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_scenemode_support " is 1profile_10_scene_modevisibility,4/4Value of scene mode</n></boolean></pre></n></boolean></pre></n></pre></n></boolean></pre></n></boolean></pre></n></pre></n></boolean></pre></n></boolean></pre> | | | | |
| profile_i0_lowlightmode <boolean> 4/4 Enable/disable low light mode. <product dependent=""> * Only available when * Capability_image_c<n>_lowlightmode" is 1 profile_i0_dnr_mode <boolean> 4/4 3D noise reduction. <product dependent=""> 0:disable 1:enable <product dependent=""> * Only available when * Capability_image_c<n>_dnr" is 1 profile_i0_dnr_strength 1~100 4/4 Strength of 3DNR <product dependent=""> * Only available when * Capability_image_c<n>_dnr" is 1 profile_0_defog_mode <boolean> 4/4 Enable/disable defog mode. <product dependent=""> <boolean> 4/4 Enable/disable when profile_0_defog_mode <boolean> 4/4 Enable/disable when <product dependent=""> 1~100 4/4 Strength of defog profile_10_defog_strength 1~100 4/4 Electronic image stabilitzer <product dependent=""> 1~100 4/4 Electronic image stabilizer profile_10_scene_enable <boolean> 4/4 Electronic image stabilizer <product dependent=""> <boolean> 4/4 Electronic image stabilizer</boolean></product></boolean></product></product></boolean></boolean></product></boolean></n></product></n></product></product></boolean></n></product></boolean> | | | | |
| <product dependent="">* Only available when "capability_image_c<n>_lowlightmode" is 1profile_10_dnr_mode <product dependent=""><boolean>4/43D noise reduction. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_dnr_strength <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode <product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_10_defog_mode <product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_10_scene_enable <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_10_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_scenemode_support " is 1profile_10_scene_modevisibility,4/4Value of scene mode</n></boolean></product></n></boolean></product></n></boolean></product></n></product></n></boolean></product></n></boolean></product></n></product></n></boolean></product></n></product> | profile i0 lewlightmode | chooloon> | 1/1 | |
| Image: constraint of the sector of the sec | | | 4/4 | |
| profile_i0_dnr_mode <boolean> 4/4 3D noise reduction. ordide_ion_endent> </boolean> | | | | , |
| <product dependent="">0:disableprofile_i0_dnr_strength1~1004/4Strength of 3DNR<product dependent="">1~1004/4Strength of 3DNR<product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable<product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable<product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable<product dependent="">1~1004/4Strength of defog<product dependent="">1~1004/4Electronic image stabilizer 0:disable when "capability_image_c<n>_defog_mode" is 1profile_i0_eis<boolean>4/4Electronic image stabilizer 0:disable<product dependent=""><boolean>4/4Enable/disable scene mode 0: disable<product dependent=""><boolean>4/4Enable/disable scene mode<product dependent=""><boolean>4/4Enable/disable scene mode<produ< td=""><td>profile i0 dar mede</td><td>chooloop</td><td>4/4</td><td></td></produ<></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></n></product></product></product></product></product></product></boolean></product></boolean></product></boolean></product></product></product> | profile i0 dar mede | chooloop | 4/4 | |
| Image: series of the series | | <doolean></doolean> | 4/4 | |
| * Only available when "capability_image_c <n>_dnr" is 1profile_i0_dnr_strength <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_i0_defog_mode <product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_dnr" is 1profile_i0_defog_strength <product dependent="">1~1004/4Enable/disable defog 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_disable 1:enable * Only available when "capability_image_c<n>_disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></product></n></n></n></boolean></product></n></product></n></product></n></boolean></product></n></product></n> | <product dependent=""></product> | | | |
| Image: constant of the term of the term of the term of | | | | |
| profile_i0_dnr_strength <product dependent="">1~1004/4Strength of 3DNR * Only available when "capability_image_c<n>_dnr" is 1profile_i0_defog_mode <product dependent=""><boolean>4/4Enable/disable defog mode. 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></product></n></boolean></product></n></boolean></product></n></product></n></product></n></boolean></product></n></product> | | | | |
| <product dependent=""> <product dependent=""> </product> <product dependent=""> <product dependent=""> <product dependent=""> <product dependent=""> </product> <product dependent=""> <product dependent=""> <product dependent=""> <product dependent=""> <product dependent=""> </product> <product dependent=""> <product dependent=""> </product> <product dependent=""> </product> <product dependent=""> <product dependent=""> </product> </product> <product dependent=""> </product> </product> <product dependent=""> </product> </product> </product> <product dependent=""> </product> </product> </product> </product> <product dependent=""> </product> </product> </product> </product> <product dependent=""> </product> <product dependent=""> <product dependent=""> </product></product> | | | | |
| Image: Instant and the sector of the secto | | 1~100 | 4/4 | |
| profile_i0_defog_mode <boolean>4/4Enable/disable defog mode.<product dependent="">.0:disable1:enableprofile_i0_defog_strength1~1004/4Strength of defog<product dependent="">1~1004/4Strength of defog<product dependent="">Strength of defog<product dependent="">optile_i0_eis<boolean>4/4Electronic image stabilizer<product dependent="">optile_i0_scene_enable<product dependent=""><product dependent=""><product dependent="">.4/4Electronic image stabilizer<product dependent=""><product dependent=""><td><product dependent=""></product></td><td></td><td></td><td>,</td></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></boolean></product></product></product></product></boolean> | <product dependent=""></product> | | | , |
| <pre><pre><pre>cyroduct dependent></pre> <pre>0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1 profile_i0_defog_strength <pre>cyroduct dependent></pre> <pre>1~100</pre> 4/4</n></pre> Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1 profile_i0_eis <pre>cyroduct dependent></pre> 4/4 Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_defog_mode" is 1 Drofile_i0_eis <pre>cyroduct dependent></pre> 4/4 Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1 profile_i0_scene_enable <pre>cyroduct dependent></pre> 4/4 Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1 profile_i0_scene_mode</n></n></n></n></pre> Visibility, 4/4 Value of scene mode</pre> | | | | "capability_image_c <n>_dnr" is 1</n> |
| I makeI makeI makeI makeprofile_i0_defog_strength1~1004/4Strength of defog <product dependent="">1~1004/4Strength of defog<product dependent="">1~1004/4Strength of defogprofile_i0_eis<boolean>4/4Electronic image stabilizer<product dependent=""><boolean>4/4Electronic image stabilizer<product dependent=""><boolean>4/4Electronic image stabilizer<product dependent=""><boolean>4/4Enable<product dependent=""><boolean>4/4Enable/<product dependent=""><boolean>4/4Enable/<product dependent=""><boolean>4/4Enable/disable scene mode<product dependent=""><boolean>4/4Strength dependent<product dependent=""><boolean>4/4Strength dependent<product dependent=""><boolean>4/4Strength dependent<product dependent=""><boolean>4/4Strength dependent<product dependent=""><boolean><boolea< td=""><td>profile_i0_defog_mode</td><td><boolean></boolean></td><td>4/4</td><td>Enable/disable defog mode.</td></boolea<></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></product> | profile_i0_defog_mode | <boolean></boolean> | 4/4 | Enable/disable defog mode. |
| * Only available when "capability_image_c <n>_defog_mode" is 1profile_i0_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></product></n></boolean></product></n></product></n> | <product dependent=""></product> | | | 0:disable |
| Image: constraint of the sector of the sec | | | | 1:enable |
| profile_i0_defog_strength <product dependent="">1~1004/4Strength of defog * Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis <product dependent=""><boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></product></n></boolean></product></n></boolean></product></n></product> | | | | * Only available when |
| <product dependent="">* Only available when "capability_image_c<n>_defog_mode" is 1profile_i0_eis<boolean>4/4Electronic image stabilizer 0:disable 1:enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable<boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_enable<boolean>4/4Enable/disable scene mode 0: disable 1: enable * Only available when "capability_image_c<n>_eis" is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></n></boolean></n></boolean></n></product> | | | | "capability_image_c <n>_defog_mode" is 1</n> |
| Image: constraint of the sector of the sec | profile_i0_defog_strength | 1~100 | 4/4 | Strength of defog |
| profile_i0_eis <boolean>4/4Electronic image stabilizer<product dependent=""><boolean>4/4Electronic image stabilizer<product dependent=""><boolean>1:enableprofile_i0_scene_enable<boolean>4/4Enable/disable scene mode<product dependent=""><boolean>4/4Enable/disable scene mode<pre>* Only available when</pre>* Only available when* capability_image_c<n>_scenemode_support* is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></boolean></product></boolean></product></boolean> | <product dependent=""></product> | | | * Only available when |
| <pre><product dependent=""> </product></pre> <pre></pre> | | | | "capability_image_c <n>_defog_mode" is 1</n> |
| iii | profile_i0_eis | <boolean></boolean> | 4/4 | Electronic image stabilizer |
| * Only available when "capability_image_c <n>_eis" is 1profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode<product dependent=""><boolean>4/4Enable/disable scene mode<product dependent=""><boolean>1: enable<product dependent=""><boolean>* Only available when<product dependent=""><boolean>: enable<product dependent="">: enable: enable<product dependent="">: enable: enable<product dependent="">: enable: enable<product dependent=""><product dependent="">: enable<product dependent="">: enable<product dependent="">: enable<product dependent<="" pre="">: enable<product dependent<="" pre=""><product dependent<="" pre="">: enable<product dependent<="" pre=""><</product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></boolean></product></n> | <product dependent=""></product> | | | 0:disable |
| profile_i0_scene_enable <product dependent=""><boolean>4/4Enable/disable scene mode<product dependent=""><boolean>4/4Enable/disable scene mode<product dependent="">1: enable * Only available when "capability_image_c<n>_scenemode_support " is 1profile_i0_scene_modevisibility,4/4Value of scene mode</n></product></boolean></product></boolean></product> | | | | 1:enable |
| profile_i0_scene_enable <boolean> 4/4 Enable/disable scene mode <product dependent=""> 0: disable 1: enable * Only available when "capability_image_c<n>_scenemode_support "is 1 profile_i0_scene_mode visibility, 4/4</n></product></boolean> | | | | * Only available when |
| <pre><product dependent=""> </product></pre> <pre></pre> | | | | "capability_image_c <n>_eis" is 1</n> |
| profile_i0_scene_mode visibility, 4/4 1: enable 1: enable * Only available when "capability_image_c <n>_scenemode_support " is 1</n> | profile_i0_scene_enable | <boolean></boolean> | 4/4 | Enable/disable scene mode |
| profile_i0_scene_mode visibility, 4/4 1: enable 1: enable * Only available when "capability_image_c <n>_scenemode_support " is 1</n> | <product dependent=""></product> | | | 0: disable |
| profile_i0_scene_mode visibility, 4/4 Value of scene mode | | | | 1: enable |
| profile_i0_scene_mode visibility, 4/4 Value of scene mode | | | | * Only available when |
| profile_i0_scene_mode visibility, 4/4 Value of scene mode | | | | |
| profile_i0_scene_mode visibility, 4/4 Value of scene mode | | | | |
| | profile_i0_scene_mode | visibility, | 4/4 | |
| | <pre><pre>conduct dependent></pre></pre> | noiseless, | | * Only available when |

| lpc | cparkinglot, | "capability_image_c <n>_scenemode_support</n> | |
|---|--------------|---|--|
| Ipc | cstreet | " is 1 | |
| <p< td=""><td>product</td><td>* Available value is listed in</td><td></td></p<> | product | * Available value is listed in | |
| de | ependent> | "capability_image_c <n>_scenemode_support</n> | |
| | | type" | |

7.12 Exposure window setting per channel

Group: exposurewin_c<0~(n-1)> for n channel profucts

n denotes the value of "capability_nvideoin"

* Only available when "capability_image_c<n>_exposure_mode"=1

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|------------------------------------|-----------|--|
| | | (get/set) | |
| mode | auto, custom,blc | 4/4 | auto: Use full image view as the only exposure |
| | | | window. |
| | * Available values are listed in | | custom: Use custom windows. |
| | "capability_image_c <n>_exposu</n> | | blc: Use BLC, and the only exposure window is |
| | re_winmode" | | located at the center of view. |

Group: exposurewin_c<0~(n-1)>_win_i<0~(k-1)>

n denotes the value of "capability_nvideoin", k denotes the value of "capability_image_c<n>_exposure_winnum".

* Only available when custom is listed in "capability_image_c<n>_exposure_winmode".

* Only valid when exposurewin_c<n>_mode=custom.

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable or disable the window. |
| policy | 0~1 | 4/4 | 0: Indicate exclusive. |
| | | | 1: Indicate inclusive. |
| | | | * Only available when exclusive is listed in |
| | | | "capability_image_c <n>_exposure_wintype".</n> |
| home | <0~320,0~240> | 4/4 | Left-top corner coordinate of the window. |
| | | | |
| | | | * Only available when qvga is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| size | <0~320x0~240> | 4/4 | Width and height of the window. |
| | | | |
| | | | * Only available when qvga is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |

| homepx | <0~W,0~H> | 4/4 | Left-top corner coordinate of the window. |
|---------|---|-----|---|
| | W: 0~ The current image width -1 H: 0~ The current image height -1 | | * Only available when px is listed in "capability_image_c <n>_exposure_windomai n".</n> |
| sizepx | <0~Wx0~ H> | 4/4 | Width and height of the window. |
| | W: 0~ The current image width -1 H: 0~ The current image height -1 | | * Only available when px is listed in "capability_image_c <n>_exposure_windomai n".</n> |
| homestd | <0~9999,0~9999> | 4/4 | Left-top corner coordinate of the window. |
| | | | * Only available when std is listed in "capability_image_c <n>_exposure_windomai n".</n> |
| sizestd | <0~9999x0~9999> | 4/4 | Width and height of the window. |
| | | | * Only available when std is listed in "capability_image_c <n>_exposure_windomai n".</n> |

Group: exposurewin_c<0~(n-1)>_profile_i<0~m-1> for n channel profuct and m profile,

n denotes the value of "capability_nvideoin", m denotes the value of "capability_nvideoinprofile",

* Only valid when capability_image_c<n>_exposure_mode =1.

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|------------------------------------|-----------|--|
| | | | |
| | | (get/set) | |
| mode | auto, custom,blc | 4/4 | The mode indicates how to decide the |
| | | | exposure. |
| | * Available values are listed in | | auto: Use full view as the only one exposure |
| | "capability_image_c <n>_exposu</n> | | window. |
| | re_winmode" | | custom: Use inclusive and exclusive window. |
| | | | blc: Use BLC. |

Group: exposurewin_c<0~(n-1)>_profile_i<0~m-1>_win_i<0~k> for m profile and n channel product,

n denotes the value of "capability_nvideoin", m denotes the value of "capability_nvideoinprofile",

k denotes the value of "capability_image_c<n>_exposure_winnum".

* Only valid when exposurewin_c<n>_mode=custom.

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------|---------------------|-----------|-------------------------------|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable or disable the window. |

| policy | 0~1 | 4/4 | 0: Indicate exclusive. |
|---------|-----------------------------------|------|--|
| | | | 1: Indicate inclusive. |
| | | | * Only available when exclusive is listed in |
| | | | "capability_image_c <n>_exposure_wintype".</n> |
| home | <0~320,0~240> | 4/4 | Left-top corner coordinate of the window. |
| | | | * Only available when qvga is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| size | <0~320x0~240> | 4/4 | Width and height of the window. |
| 5120 | | ., . | What and height of the Whatwi |
| | | | * Only available when qvga is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| homepx | <0~W,0~H> | 4/4 | Left-top corner coordinate of the window. |
| | W. O. The summer increase width 1 | | * Only systems when my is listed in |
| | W: 0~ The current image width -1 | | * Only available when px is listed in |
| | H: 0~ The current image height -1 | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| sizepx | <0~Wx0~ H> | 4/4 | Width and height of the window. |
| | W: 0~ The current image width -1 | | * Only available when px is listed in |
| | H: 0~ The current image height -1 | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| homestd | <0~9999,0~9999> | 4/4 | Left-top corner coordinate of the window. |
| | | | * Only available when std is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |
| sizestd | <0~9999x0~9999> | 4/4 | Width and height of the window. |
| | | | * Only available when and is listed in |
| | | | * Only available when std is listed in |
| | | | "capability_image_c <n>_exposure_windomai</n> |
| | | | n". |

7.13 Audio input per channel

Group: **audioin_c<0~(n-1)>** for n channel products (capability.audioin>0)

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|---|---|-----------|---|
| | | (get/set) | |
| source | micin, linein | 4/4 | micin => use built-in microphone input. |
| <not recommended="" td="" to="" use<=""><td><product< td=""><td></td><td>linein => use external microphone input.</td></product<></td></not> | <product< td=""><td></td><td>linein => use external microphone input.</td></product<> | | linein => use external microphone input. |
| this> | dependent> | | |
| | | | * Reserved for compatibility, and suggest don't |
| | | | use this since the version number |
| | | | (httpversion) is equal or greater than 0301a. |
| | | | * We replace "source" with "input". More |
| | | | details, please refer the parameter description |
| | | | of "input". |
| input | intmic, extmic | 4/4 | intmic: Internal (built-in) microphone. |
| | <product< td=""><td></td><td>(Only available when capability_audio_intmic</td></product<> | | (Only available when capability_audio_intmic |
| | dependent> | | = 1) |
| | | | extmic: External microphone input. |
| | | | (Only available when capability_audio_extmic |
| | | | =1) |
| | | | * Note: If physical microphone switch is |
| | | | showed on product, this value is updated |
| | | | during booting to fit switch status. |
| volume_internal | 0~100 | 4/4 | Volume when take internal microphone as |
| | | | input source. |
| | | | 0: Minimum |
| | | | 100: Maximum |
| | | | * Only available when the channel supports |
| | | | internal microphone (The related bit of |
| | | | "capability_audio_intmic" is equal to 1). |
| volume_external | 0~100 | 4/4 | Volume when take external microphone as |
| | | | input source. |
| | | | 0: Minimum |
| | | | 100: Maximum |
| | | | * Only available when the channel supports |

| [| | | |
|--|----------------------|-----|---|
| | | | external microphone (The related bit of |
| | | | "capability_audio_extmic" is equal to 1). |
| mute | 0, 1 | 1/4 | 0: Mute off |
| | | | 1: Mute on |
| gain | 0~100 | 4/4 | Gain of input. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>$(audioin_c<0~(n-1)>_source = linein)$</td></not> | | | $(audioin_c<0~(n-1)>_source = linein)$ |
| this> | | | |
| | | | * Reserved for compatibility, and suggest don't |
| | | | use this since the version number |
| | | | (httpversion) is equal or greater than 0301a. |
| | | | * We replace "gain" with "volume_internal" |
| | | | and "volume_external". More details, please |
| | | | refer the parameter description of |
| | | | "volume_internal" and "volume_external". |
| boostmic | 0~100 | 4/4 | Enable microphone boost. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>Gain of input.</td></not> | | | Gain of input. |
| this> | | | (audioin_c<0~(n-1)>_source = micin) |
| | | | |
| | | | * Reserved for compatibility, and suggest don't |
| | | | use this since the version number |
| | | | (httpversion) is equal or greater than 0301a. |
| | | | * We replace "boostmic" with |
| | | | "volume_internal" and "volume_external". |
| | | | More details, please refer the parameter |
| | | | description of "volume_internal" and |
| | | | "volume_external". |
| s0_codectype | aac4, gamr, g711, | 4/4 | Set audio codec type for input. |
| so_couectype | g726 | -/- | aac4: Advanced Audio Coding (AAC) |
| | (Available codec are | | gamr: Adaptive Multi-Rate (AMR) |
| | listed in | | |
| | | | g711: G.711 |
| | "capability_audioin_ | | g726: G.726 |
| | codec") | | |
| | 1,000 | | |
| s0_aac4_bitrate | 16000, | 4/4 | Set AAC4 bitrate in bps. |
| | 32000, | | |
| | 48000, | | * Only available if AAC is supported. |
| | 64000, | | |
| | 96000, | | |
| | 128000 | | |
| s0_gamr_bitrate | 4750, | 4/4 | AMR encoded bitrate in bps. |

| | 1 | r | |
|--------------------------|---------------------|------|---|
| | 5150, | | |
| | 5900, | | * Only available if AMR is supported. |
| | 6700, | | |
| | 7400, | | |
| | 7950, | | |
| | 10200, | | |
| | 12200 | | |
| s0_g711_mode | pcmu, | 4/4 | Set G.711 companding algorithm. |
| | рста | | pcmu: µ-law algorithm |
| | | | pcma: A-law algorithm |
| | | | |
| | | | * Only available if G.711 is supported. |
| | | | |
| s0_g726_bitrate | 16000, | 4/4 | Set G.726 encoded bitrate in bps. |
| | 24000, | | |
| | 32000, | | * Only available if G.726 is supported. |
| | 40000 | | |
| s0_g726_bitstreampackin | little, big | 4/4 | Set G.726 bit streaming packing mode. |
| gmode | | , | little: Little-endian bitstream format. |
| 5 | | | big: Big-endian bitstream format. |
| | | | |
| | | | * Only available if G.726 is supported. |
| | | | |
| s0_g726_vlcmode | 0, 1 | 4/4 | Enable vlcmode for G.726. |
| 50_g/20_viemoue | 0,1 | ', ' | 0: Standard mode. |
| | | | 1: Solve compatibility problem with VLC |
| | | | |
| | | | player. |
| | | | * Only available if C 726 is supported |
| | | | * Only available if G.726 is supported. |
| alarm_enable | <boolean></boolean> | 4/4 | Enable audio detection |
| alarm_level | 1~100 | 4/4 | Audio detection alarm level |
| profile_i0_enable | <boolean></boolean> | 4/4 | Enable/disable this profile setting |
| profile_i0_policy | night, | 4/4 | The mode which the profile is applied to. |
| F | schedule | ., ' | |
| | | | * Not support "policy=day" anymore when the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0301a. |
| profile_i0_begintime | hh:mm | 4/4 | Begin time of schedule mode. |
| | | | |
| profile_i0_endtime | hh:mm | 4/4 | End time of schedule mode. |

| profile_i0_alarm_level | 1~100 | 4/4 | Audio detection alarm level | |
|------------------------|-------|-----|-----------------------------|--|
|------------------------|-------|-----|-----------------------------|--|

7.14 Motion detection settings

Group: motion_c<0~(n-1)> for n channel products

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable motion detection. |
| win_sensitivity | 1 ~ 100 | 4/4 | Sensitivity of all motion detection windows. |

Group: motion_c<0~(n-1)>_win_i<0~(k-1)>

n denotes the value of "capability_nvideoin", k denotes the value of "capability_nmotion".

| NAME | VALUE | SECURITY | DESCRIPTION |
|---|-----------------------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable motion detection window. |
| name | string[14] | 4/4 | Name of motion window. |
| polygonstd | 0 ~ 9999,0 ~ 9999, | 4/4 | Coordinate of polygon window position. |
| | 0 ~ 9999,0 ~ 9999, | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| | 0 ~ 9999,0 ~ 9999, | | * Only available when |
| | 0 ~ 9999,0 ~ 9999 | | "capability_motion_wintype" = polygon. |
| | | | * Only available when std is listed in |
| | | | "capability_motion_windomain" |
| objsize | 1 ~ 100 | 4/4 | Percent of motion detection window. |
| sensitivity | 1 ~ 100 | 4/4 | Sensitivity of motion detection window. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td></td></not> | | | |
| this> | | | * We replace "sensitivity" with |
| | | | "win_sensitivity". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| polygonpx | 0 ~ W,0 ~ H, 0 ~ | 4/4 | Coordinate of polygon window position. |
| <not recommended="" td="" to="" use<=""><td>W,0 \sim H, 0 \sim W,0 \sim</td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not> | W,0 \sim H, 0 \sim W,0 \sim | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| this> | H, 0 ~ W,0 ~ H | | * Only available when |
| | W: 0~ The current | | "capability_motion_wintype" = polygon. |
| | image width -1 | | |
| | H: 0~ The current | | * Only available when px is listed in |
| | image height -1 | | "capability_motion_windomain |

| polygon <not recommended="" to="" use<br="">this></not> | 0 ~ 320,0 ~ 240, 0 ~ 320,0 ~ 240, 0 ~ 320,0 ~ 240, 0 ~ | 4/4 | * It's recommended to use polygonsd * This parameter will not be used after the version number (httpversion) is equal or greater than 0400a. Coordinate of polygon window position. (4 points: x0,y0,x1,y1,x2,y2,x3,y3) * Only available when |
|--|--|------|---|
| | 320,0 ~ 240, 0 ~ 320,0 ~ 240 | | "capability_motion_wintype" = polygon. |
| | | | * Only available when qvga is listed in "capability_motion_windomain |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the version number (httpversion) is equal or |
| | | | greater than 0400a. |
| left | 0 ~ 320 | 4/4 | Left coordinate of window position. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain". |
| | | | * It's recommended to use polygonsd * This parameter will not be used after the version number (httpversion) is equal or greater than 0400a. |
| top | 0 ~ 240 | 4/4 | Top coordinate of window position. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | * Only available when qvga is listed in "capability_motion_windomain". |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| width | 0 ~ 320 | 4/4 | greater than 0400a. Width of motion detection window. |
| | 0 520 | ד (ד | width of motion detection window. |

| <not recommended="" th="" to="" use<=""><th></th><th></th><th>* Only available when</th></not> | | | * Only available when |
|--|---------|-----|---|
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | cupublicy_inclosi_wittype rectanglei |
| | | | * Only available when qvga is listed in |
| | | | |
| | | | "capability_motion_windomain". |
| | | | |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| height | 0 ~ 240 | 4/4 | Height of motion detection window. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain". |
| | | | |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |

Group: motion_c<0~(n-1)>_profile_i<0~(m-1)> for m profile and n channel product,

n denotes the value of "capability_nvideoin", m denotes the vaule of " capability_nmotionprofile ",

(capability_nmotionprofile > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable profile 1 ~ (m-1). |
| policy | night, | 4/4 | The mode which the profile is applied to. |
| | schedule | | |
| | | | * Not support "policy=day" anymore when the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0301a. |
| begintime | hh:mm | 4/4 | Begin time of schedule mode. |
| endtime | hh:mm | 4/4 | End time of schedule mode. |
| win_sensitivity | 1 ~ 100 | 4/4 | Sensitivity of all motion detection windows. |

Group: motion_c<0~(n-1)>_profile_i<0~(m-1)>_win_i<0~(k-1)> for m profile and n channel product, n denotes the value of "capability_nvideoin", m denotes the value of "capability_nmotionprofile",

k denotes the value of "capability_nmotion".

| NAME | VALUE | SECURITY | DESCRIPTION |
|---|-------------------------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable motion detection window. |
| name | string[14] | 4/4 | Name of motion window. |
| polygonstd | 0 ~ 9999,0 ~ 9999, | 4/4 | Coordinate of polygon window position. |
| | 0 ~ 9999,0 ~ 9999, | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| | 0 ~ 9999,0 ~ 9999, | | * Only available when |
| | 0 ~ 9999,0 ~ 9999 | | "capability_motion_wintype" = polygon. |
| | | | * Only available when std is listed in |
| | | | "capability_motion_windomain |
| objsize | 1 ~ 100 | 4/4 | Percent of motion detection window. |
| sensitivity | 1 ~ 100 | 4/4 | Sensitivity of motion detection window. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td></td></not> | | | |
| this> | | | * We replace "sensitivity" with |
| | | | "win_sensitivity". |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| polygonpx | 0 ~ W,0 ~ H, 0 ~ | 4/4 | Coordinate of polygon window position. |
| <not recommended="" td="" to="" use<=""><td>W,0 \sim H, 0 \sim W,0 \sim</td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not> | W,0 \sim H, 0 \sim W,0 \sim | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| this> | H, 0 ~ W,0 ~ H | | * Only available when |
| | W: 0~ The current image width -1 | | "capability_motion_wintype" = polygon. |
| | H: 0~ The current | | * Only available when px is listed in |
| | image height -1 | | "capability_motion_windomain |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| polygon | 0 ~ 320,0 ~ 240, 0 | 4/4 | Coordinate of polygon window position. |
| <not recommended="" td="" to="" use<=""><td>~ 320,0 ~ 240, 0 ~</td><td></td><td>(4 points: x0,y0,x1,y1,x2,y2,x3,y3)</td></not> | ~ 320,0 ~ 240, 0 ~ | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| this> | 320,0 ~ 240, 0 ~ | | * Only available when |
| | 320,0 ~ 240 | | "capability_motion_wintype" = polygon. |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain |

| | | | * It's recommended to use polygonsd |
|--|---------|-----|---|
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| left | 0 ~ 320 | 4/4 | Left coordinate of window position. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain". |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| top | 0 ~ 240 | 4/4 | Top coordinate of window position. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain". |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| width | 0 ~ 320 | 4/4 | Width of motion detection window. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |
| this> | | | "capability_motion_wintype" = rectangle. |
| | | | * Only available when qvga is listed in |
| | | | "capability_motion_windomain". |
| | | | * It's recommended to use polygonsd |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or |
| | | | greater than 0400a. |
| height | 0 ~ 240 | 4/4 | Height of motion detection window. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* Only available when</td></not> | | | * Only available when |

| this> | "capability_motion_wintype" = rectangle. |
|-------|---|
| | * Only available when qvga is listed in "capability_motion_windomain". |
| | * It's recommended to use polygonsd* This parameter will not be used after the |
| | version number (httpversion) is equal or greater than 0400a. |

7.15 Tampering detection settings

Group: **tampering_c<0~(n-1)>** for n channel products (capability.tampering > 0)

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|------------------|-------------------------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable or disable tamper detection. |
| threshold | 0~100 | 4/4 | Threshold of tamper detection. |
| duration | 10~600 | 4/4 | If tampering value exceeds the "threshold" for |
| | | | more than "duration" second(s), then tamper |
| | | | detection is triggered. |
| ignorewidth | 0, <positive integer=""></positive> | 1/7 | Indicate the width to offset to start to analysis |
| | | | the image. |
| dark_enable | <boolean></boolean> | 4/4 | Enable or disable image too dark detection |
| dark_threshold | 0~100 | 4/4 | Threshold of image too dark detection |
| dark_duration | 1~10 | 4/4 | If image too dark value exceeds the |
| | | | "threshold" for more than "duration" |
| | | | second(s), then image too dark detection is |
| | | | triggered. |
| bright_enable | <boolean></boolean> | 4/4 | Enable or disable image too bright detection |
| bright_threshold | 0~100 | 4/4 | Threshold of image too bright detection |
| bright_duration | 1~10 | 4/4 | If image too bright value exceeds the |
| | | | "threshold" for more than "duration" |
| | | | second(s), then image too bright detection is |
| | | | triggered. |
| blurry_enable | <boolean></boolean> | 4/4 | Enable or disable image too blurry detection |
| blurry_threshold | 0~100 | 4/4 | Threshold of image too blurry detection |
| blurry_duration | 1~10 | 4/4 | If image too blurry value exceeds the |
| | | | "threshold" for more than "duration" |

| | | second(s), then image too blurry detection is |
|--|--|---|
| | | triggered. |

7.16 **DDNS**

Group: **ddns** (capability.ddns > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------------------------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable or disable the dynamic DNS. |
| provider | CustomSafe100, | 6/6 | Safe100 => safe100.net |
| | DyndnsDynamic, | | DyndnsDynamic => dyndns.org (dynamic) |
| | DyndnsCustom, | | DyndnsCustom => dyndns.org |
| | Safe100 | | CustomSafe100 => |
| | | | Custom server using safe100 method |
| <provider>_hostname</provider> | string[128] | 6/6 | Your DDNS hostname. |
| <provider>_usernameem</provider> | string[64] | 6/6 | Your user name or email to login to the DDNS |
| ail | | | service provider |
| <provider>_passwordkey</provider> | string[64] | 6/6 | Your password or key to login to the DDNS |
| | | | service provider. |
| <provider>_servername</provider> | string[128] | 6/6 | The server name for safe100. |
| | | | (This field only exists if the provider is |
| | | | customsafe100) |

7.17 Express link

Group: expresslink

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-----------|---------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable or disable express link. |
| state | onlycheck, | 6/6 | Camera will check the status of network |
| | onlyoffline, | | environment and express link URL |
| | checkonline, | | |
| | badnetwork | | |
| url | string[64] | 6/6 | The url user define to link to camera |

7.18 UPnP presentation

Group: upnppresentation

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------|---------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable or disable the UPnP presentation |
| | | | service. |

7.19 UPnP port forwarding

Group: upnpportforwarding

| NAME | VALUE | SECURITY | DESCRIPTION |
|---------------|---------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Enable or disable the UPnP port forwarding |
| | | | service. |
| upnpnatstatus | 0~3 | 6/7 | The status of UPnP port forwarding, used |
| | | | internally. |
| | | | 0 = OK, 1 = FAIL, 2 = no IGD router, 3 = no |
| | | | need for port forwarding |

7.20 System log

Group: **syslog**

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------|----------------------|-----------|--|
| | | (get/set) | |
| enableremotelog | <boolean></boolean> | 6/6 | Enable remote log. |
| serverip | <ip address=""></ip> | 6/6 | Log server IP address. |
| serverport | 514, 1025~65535 | 6/6 | Server port used for log. |
| level | 0~7 | 6/6 | Levels used to distinguish the importance of |
| | | | the information: |
| | | | 0: LOG_EMERG |
| | | | 1: LOG_ALERT |
| | | | 2: LOG_CRIT |
| | | | 3: LOG_ERR |
| | | | 4: LOG_WARNING |
| | | | 5: LOG_NOTICE |
| | | | 6: LOG_INFO |
| | | | 7: LOG_DEBUG |
| setparamlevel | 0~2 | 6/6 | Show log of parameter setting. |

| 0: disable |
|---|
| 1: Show log of parameter setting set from |
| external. |
| 2. Show log of parameter setting set from |
| external and internal. |

7.21 SNMP

Group: **snmp** (capability.snmp > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|---------------|---------------------|-----------|--|
| | | (get/set) | |
| v2 | <boolean></boolean> | 6/6 | SNMP v2 enabled. 0 for disable, 1 for enable |
| v3 | <boolean></boolean> | 6/6 | SNMP v3 enabled. 0 for disable, 1 for enable |
| secnamerw | string[31] | 6/6 | Read/write security name |
| secnamero | string[31] | 6/6 | Read only security name |
| authpwrw | string[8~128] | 6/6 | Read/write authentication password |
| authpwro | string[8~128] | 6/6 | Read only authentication password |
| authtyperw | MD5,SHA | 6/6 | Read/write authentication type |
| authtypero | MD5,SHA | 6/6 | Read only authentication type |
| encryptpwrw | string[8~128] | 6/6 | Read/write passwrd |
| encryptpwro | string[8~128] | 6/6 | Read only password |
| encrypttyperw | DES | 6/6 | Read/write encryption type |
| encrypttypero | DES | 6/6 | Read only encryption type |
| rwcommunity | string[31] | 6/6 | Read/write community |
| rocommunity | string[31] | 6/6 | Read only community |
| syslocation | string[128] | 6/6 | System location |
| syscontact | string[128] | 6/6 | System contact |

7.22 Layout configuration

Group: layout

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------------------|---------------------|-----------|--|
| | | (get/set) | |
| logo_default | <boolean></boolean> | 1/6 | 0 => Custom logo |
| | | | 1 => Default logo |
| logo_link | string[128] | 1/6 | Hyperlink of the logo |
| | http://www.vivotek. | | |
| | <u>com</u> | | |
| logo_powerbyvvtk_hidden | <boolean></boolean> | 1/6 | 0 => display the power by vivotek logo |
| | | | 1 => hide the power by vivotek logo |
| custombutton_manualtrig | <boolean></boolean> | 1/6 | Show or hide manual trigger (VI) button in |
| ger_show | | | homepage |
| | | | 0 -> Hidden |
| | | | 1 -> Visible |
| theme_option | 1~4 | 1/6 | 1~3: One of the default themes. |
| | | | 4: Custom definition. |
| theme_color_font | string[7] | 1/6 | Font color |
| theme_color_configfont | string[7] | 1/6 | Font color of configuration area. |
| theme_color_titlefont | string[7] | 1/6 | Font color of video title. |
| theme_color_controlback | string[7] | 1/6 | Background color of control area. |
| ground | | | |
| theme_color_configbackg | string[7] | 1/6 | Background color of configuration area. |
| round | | | |
| theme_color_videobackgr | string[7] | 1/6 | Background color of video area. |
| ound | | | |
| theme_color_case | string[7] | 1/6 | Frame color |

7.23 Privacy mask

Group: privacymask_c<0~(n-1)> for n channel products

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------------------|---------------------|-----------|--|
| | | (get/set) | |
| enable | <boolean></boolean> | 4/4 | Enable privacy mask. |
| win_i<0~4>_enable | <boolean></boolean> | 4/4 | Enable privacy mask window. |
| win_i<0~4>_name | string[14] | 4/4 | Name of the privacy mask window. |
| win_i<0~4>_left | 0 ~ 320 | 4/4 | Left coordinate of window position. |
| | | | * Only available when |
| | | | "capability_image_c <n>_privacymask_wintype"</n> |
| | | | = rectangle. |
| win_i<0~4>_top | 0 ~ 240 | 4/4 | Top coordinate of window position. |
| | | | * Only available when |
| | | | "capability_image_c <n>_privacymask_wintype"</n> |
| | | | = rectangle. |
| win_i<0~4>_width | 0 ~ 320 | 4/4 | Width of privacy mask window. |
| | | | * Only available when |
| | | | "capability_image_c <n>_privacymask_wintype"</n> |
| | | | = rectangle. |
| win_i<0~4>_height | 0 ~ 240 | 4/4 | Height of privacy mask window. |
| | | | * Only available when |
| | | | "capability_image_c <n>_privacymask_wintype"</n> |
| | | | = rectangle. |
| win_i<0~4>_polygon | 0 ~ 320,0 ~ 240, | 4/4 | Coordinate of polygon window position. |
| | 0 ~ 320,0 ~ 240, | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| | 0 ~ 320,0 ~ 240, | | * Only available when |
| | 0 ~ 320,0 ~ 240 | | "capability_image_c <n>_privacymask_wintype"</n> |
| | | | = polygon. |
| | | | * Only available when qvga is listed in |
| | | | |
| | | | "capability_image_c <n>_privacymask_windomai n</n> |
| win_i<0~4>_polygonpx | 0 ~ W,0 ~ H, 0 ~ | 4/4 | Coordinate of polygon window position. |
| | W,0 ~ H, 0 ~ W,0 | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| | ~ H, 0 ~ W,0 ~ H | | * Only available when |
| | W: 0~ The | | "capability_image_c <n>_privacymask_wintype"</n> |

| | current image | | = polygon. |
|-----------------------|-------------------|-----|--|
| | width -1 | | |
| | H: 0~ The current | | * Only available when px is listed in |
| | image height -1 | | "capability_image_c <n>_privacymask_windomai</n> |
| | | | n |
| win_i<0~4>_polygonstd | 0 ~ 9999,0 ~ | 4/4 | Coordinate of polygon window position. |
| | 9999, 0 ~ 9999,0 | | (4 points: x0,y0,x1,y1,x2,y2,x3,y3) |
| | ~ 9999, 0 ~ | | * Only available when |
| | 9999,0 ~ 9999, 0 | | "capability_image_c <n>_privacymask_wintype"</n> |
| | ~ 9999,0 ~ 9999 | | = polygon. |
| | | | |
| | | | * Only available when std is listed in |
| | | | "capability_image_c <n>_privacymask_windomai</n> |
| | | | n |

7.24 Capability

Group: capability

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------|-------------------|-----------|--|
| | | (get/set) | |
| api_httpversion | <string></string> | 0/7 | The version of VIVOTEK WebAPI with 4 |
| | This number start | | integers plus 1 alphabet, There are composed |
| | with 0301a. | | by "major version", "minor version", |
| | | | "revision","_platform". ex: 0301a_1 |
| | | | <u>Major version</u> |
| | | | Increase the major version when change, |
| | | | remove the old features/interfaces or the |
| | | | firmware has substantially change in |
| | | | architecture and not able to roll back to |
| | | | previous version. This may cause |
| | | | incompatibility with supporting software. |
| | | | Minor version |
| | | | Increase the minor version when add new |
| | | | features/interfaces without change the old |
| | | | features and interfaces. |
| | | | <u>Revision</u> |
| | | | Increase the revision when fix bugs without |
| | | | change any features of the output. |
| | | | |
| | | | _platform |

| | | | This is a constant, it is used to distinguish between different platforms |
|-----------------------------------|--|-----|---|
| | | | between different platforms |
| | | | API version format: |
| | | | MMmmr_k |
| | | | Where "MM" is the major version, "mm" is the |
| | | | minor version and "r" is the revision. |
| | | | 'M' and 'm' and 'k' are decimal digit from 0 to 9, |
| | | | while 'r' is an alphabetic. |
| | | | EX: 0302b_1 => Major version = 03, minor |
| | | | version = 02, revision = b, platform = 1 |
| | | | The 4 integer numbers are WebAPI version, we |
| | | | use short name: [httpversion] for it in this document. |
| | | | The 5th character is model-based version for |
| | | | API bug-fix and it's default to "a". |
| | | | Ex: If some APIs in a model does not follow the |
| | | | API definition of 0301a_1, we will fix them and |
| | | | change this API value to 0301b_1. |
| bootuptime | <positive integer=""></positive> | 0/7 | Server bootup time. |
| nir | 0, | 0/7 | Number of IR interfaces. |
| <not anymore="" support=""></not> | <positive integer=""></positive> | | (Recommand to use |
| | | | capability_daynight_c<0~"capability_nvideoi |
| | | | n"-1>_builtinir for built-in IR and |
| | | | capability_daynight_c<0~"capability_nvideoi |
| | | | n"-1>_externalir for external IR) |
| | | | * Not support this parameter anymore when |
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| npir | 0, <positive integer=""></positive> | 0/7 | Number of PIRs. |
| ndi | 0, | 0/7 | Number of digital inputs. |
| | <positive integer=""></positive> | | |
| nvi | 0, | 0/7 | Number of virtual inputs (manual trigger) |
| | <positive integer=""></positive> | 0/7 | |
| ndo | 0, | 0/7 | Number of digital outputs. |
| | <positive integer=""></positive> | | |
| naudioin | 0, | 0/7 | The number of audio input channel. 0 means |

| | <positive integer=""></positive> | | no audio input support. |
|--|---|-----|--|
| naudioout | 0, <positive integer=""></positive> | 0/7 | The number of audio output channel |
| nvideoin | <positive integer=""></positive> | 0/7 | Number of video inputs. |
| nvideoout | 0, <positive Integer></positive | 0/7 | Number of video out interface. |
| nvideoinprofile | <positive integer=""></positive> | 0/7 | Number of video input profiles. |
| nmediastream | <positive integer=""></positive> | 0/7 | Number of media stream per channels. |
| naudiosetting <not anymore="" support=""></not> | <positive integer=""></positive> | 0/7 | Number of audio settings per channel. * Not support this parameter anymore when the version number (httpversion) is equal or greater than 0301a. * We replace "naudiosetting" with "naudioin". More details, please refer the parameter description of "volume_internal" and "volume_external". |
| nuart | 0, <positive integer=""></positive> | 0/7 | Number of UART interfaces. |
| nmotion | <positive integer=""></positive> | 0/7 | The number of motion window. |
| nmotionprofile | 0, <positive integer></positive | 0/7 | Number of motion profiles. |
| ptzenabled | 0, <positive integer></positive | 0/7 | An 32-bit integer, each bit can be set separately as follows: Bit 0 => Support camera control function; O(not support), 1(support) Bit 1 => Built-in or external video source; O(external), 1(built-in) Bit 2 => Support pan operation; O(not support), 1(support) Bit 3 => Support tilt operation; O(not support), 1(support) Bit 4 => Support zoom operation; O(not support), 1(support) (only available when RS-485 interface is supported or SD/PZ/PT/PD/video server series) Bit 5 => Support focus operation; O(not support), 1(support) |

| | | | (only available when RS-485 interface is |
|--|---------------------|----------|--|
| | | | supported or SD/PZ/PT/PD/video server |
| | | | series) |
| | | | Bit 6 => Support iris operation; |
| | | | 0(not support), 1(support) |
| | | | Bit 7 => External or built-in PT; |
| | | | 0(built-in), 1(external) |
| | | | Bit 8 => Invalidate bit 1 \sim 7; |
| | | | 0(bit 1 \sim 7 are valid), |
| | | | 1(bit 1 \sim 7 are invalid) |
| | | | Bit 9 => Reserved bit; Invalidate lens_pan, |
| | | | lens_tilt, lens_zoon, lens_focus, len_iris. |
| | | | 0(fields are valid), |
| | | | 1(fields are invalid) |
| windowless | <boolean></boolean> | 0/7 | Indicate whether to support windowless |
| | | | plug-in. |
| evctrlchannel | <boolean></boolean> | 0/7 | Indicate whether to support HTTP tunnel for |
| | | , | event/control transfer. |
| joystick | <boolean></boolean> | 0/7 | Indicate whether to support joystick control. |
| | | | |
| remotefocus | <boolean></boolean> | 0/7 | An 4-bit integer, which indicates the supportive |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>application of remotefocus.</td></not> | | | application of remotefocus. |
| this> | | | If the value of this parameter is larger than 0, |
| | | | it means that the camera supports |
| | | | remotefocus function. |
| | | | bit 0 => Indicate whether to support both |
| | | | zoom and focus function. |
| | | | bit 1 => Only support zoom function. |
| | | | bit 2 => Only support focus function. |
| | | | bit 3 => Currently, this is a reserved bit, and |
| | | | the default value is 0. |
| | | | |
| | | | * It's strongly non-recommended to use this. |
| | | | * This is kept for compatibility. |
| | | | * You can check " |
| | | | capability_image_c<0~nvideoin-1>_remotef |
| | | | ocus" for support remotefocus function; |
| | | | capability_image_c<0~nvideoin-1>_backfocu |
| | | | s" for support backfocus function. |
| | | <u> </u> | |

| npreset | 0, <positive< th=""><th>0/7</th><th>Number of preset locations</th></positive<> | 0/7 | Number of preset locations |
|------------|---|-----|---|
| | integer> | | |
| eptz | 0, <positive< td=""><td>0/7</td><td>For "nvideoin" = 1, the definition is as</td></positive<> | 0/7 | For "nvideoin" = 1, the definition is as |
| | integer> | | following: |
| | | | A 32-bits integer, each bit can be set |
| | | | separately as follows: |
| | | | Bit 0 => 1st stream supports ePTZ or not. |
| | | | Bit 1 => 2nd stream supports ePTZ or not, and |
| | | | so on. |
| | | | For nvideoin >= 2, the definition is different: |
| | | | First all 32 bits are divided into groups for |
| | | | channel. |
| | | | Ex: |
| | | | nvideoin = 2, bit $0 \sim 15$ are the 1st group for 1st |
| | | | channel, bit 16~31 are the 2nd group for 2nd |
| | | | channel. |
| | | | nvideoin = 3, bit $0 \sim 9$ are the 1st group for 1st |
| | | | channel, bit 10~19 are the 2nd group for 2nd |
| | | | channel, bit 20~31 are the 3rd group for 3rd |
| | | | channel. |
| | | | Then, the 1st bit of the group indicates 1st |
| | | | stream of a channel support ePTZ or not. The |
| | | | 2nd bit of the group indicates 2nd stream of a |
| | | | channel support ePTZ or not, and so on. |
| | | | * For most products, the last stream of a |
| | | | channel will not support ePTZ. It is reserved |
| | | | for full view of the channel. For some |
| | | | dual-stream products, both streams support |
| | | | ePTZ. |
| nanystream | 0, <positive< td=""><td>0/7</td><td>number of any media stream per channel</td></positive<> | 0/7 | number of any media stream per channel |
| | integer> | | |
| iva | <boolean></boolean> | 0/7 | Indicate whether to support Intelligent Video |
| | | | analysis |
| whitelight | <boolean></boolean> | 0/7 | Indicate whether to support white light led. |
| iris | <boolean></boolean> | 0/7 | Indicate whether to support iris control. |
| supportsd | <boolean></boolean> | 0/7 | Indicate whether to support local storage. |
| fisheye | <boolean></boolean> | 0/7 | Indicate where fisheye camera |

| tampering | <boolean></boolean> | 0/7 | Indicate whether to support tampering |
|--|--|-------------------|--|
| | | | detection. |
| tamperingmode | tamper,toodark,toob | 0/7 | Available tampering mode list |
| | right,tooblurry | | |
| adaptiverecording | <boolean></boolean> | 0/7 | Indicate whether to support adaptive |
| | | | recording. |
| adaptivestreaming | <boolean></boolean> | 0/7 | Indicate whether to support adaptive |
| | | | streaming. |
| supporttriggertypes | seq,boot,motion,net | 0/7 | list all the trigger types which are supported in |
| | workfail,recnotify,ta | | the camera: |
| | mpering,vi,vadp,di, | | "seq" = Periodic condition |
| | volalarm,temperatu | | "boot" = System boot |
| | re,pir, visignal, | | "motion" = Video motion detection |
| | backup | | "networkfail" = network connection failure |
| | <product< td=""><td></td><td>"recnotify" = Recording notification.</td></product<> | | "recnotify" = Recording notification. |
| | dependent> | | "tampering" = Tamper detection. |
| | | | "vi" = Virtual input (Manual trigger) |
| | | | "vadp" = VADP trigger |
| | | | "di"= Digital input |
| | | | "volalarm" = Audio detection |
| | | | "temperature" = Temperature detection |
| | | | "pir" = PIR detection |
| | | | "visignal" = Video input signal loss. |
| | | | "backup" = Backing up recorded files |
| | | | * Only available when [httpversion] >= 0301a |
| storage_dbenabled | <boolean></boolean> | 0/7 | Media files are indexed in database. |
| protocol_https | < boolean > | 0/7 | Indicate whether to support HTTP over SSL. |
| protocol_rtsp | < boolean > | 0/7 | Indicate whether to support RTSP. |
| | | | |
| protocol_sip | <boolean></boolean> | 0/7 | Indicate whether to support SIP. |
| protocol_sip protocol_maxconnection | <boolean><boolean></boolean></boolean> | 0/7 | Indicate whether to support SIP. The maximum number of allowed |
| | | | |
| | | | The maximum number of allowed |
| protocol_maxconnection | <positive integer=""></positive> | 0/7 | The maximum number of allowed simultaneous connections. |
| protocol_maxconnection protocol_maxgenconnecti | <positive integer=""></positive> | 0/7 | The maximum number of allowed simultaneous connections. The maximum general streaming connections . |
| protocol_maxconnection protocol_maxgenconnecti on | <positive integer=""> <positive integer=""></positive></positive> | 0/7 | The maximum number of allowed simultaneous connections. |
| protocol_maxconnection protocol_maxgenconnecti on protocol_rtp_multicast_sc alable | <positive integer=""> <positive integer=""></positive></positive> | 0/7 | The maximum number of allowed simultaneous connections. The maximum general streaming connections . Indicate whether to support scalable multicast. |
| protocol_maxconnection protocol_maxgenconnecti on protocol_rtp_multicast_sc | <positive integer=""> <positive integer=""> <boolean> </boolean></positive></positive> | 0/7 0/7 0/7 | The maximum number of allowed simultaneous connections. The maximum general streaming connections . |

| protocol_rtp_http | <boolean></boolean> | 0/7 | Indicate whether to support RTP over HTTP. |
|----------------------------|---|------|--|
| protocol_spush_mjpeg | <boolean></boolean> | 0/7 | Indicate whether to support server push |
| | | | MJPEG. |
| protocol_snmp | <boolean></boolean> | 0/7 | Indicate whether to support SNMP. |
| protocol_ipv6 | <boolean></boolean> | 0/7 | Indicate whether to support IPv6. |
| protocol_pppoe | <boolean></boolean> | 0/7 | Indicate whether to support PPPoE. |
| protocol_ieee8021x | <boolean></boolean> | 0/7 | Indicate whether to support IEEE802.1x. |
| protocol_qos_cos | <boolean></boolean> | 0/7 | Indicate whether to support CoS. |
| protocol_qos_dscp | <boolean></boolean> | 0/7 | Indicate whether to support QoS/DSCP. |
| protocol_ddns | <boolean></boolean> | 0/7 | Indicate whether to support DDNS. |
| videoin_type | 0, 1, 2 | 0/7 | 0 => Interlaced CCD |
| | | | 1 => Progressive CCD |
| | | | 2 => CMOS |
| videoin_nresolution | <positive integer=""></positive> | 0/7 | This equals |
| | | | "capability_videoin_c0_nresolution". |
| | | | * This is kept for compatibility. |
| videoin_resolution | A list of <wxh></wxh> | 0/7 | This equals |
| | <pre><pre>product</pre></pre> | 0, 1 | "capability_videoin_c0_resolution". |
| | | | |
| | dependent> | | * This is kept for compatibility. |
| videoin_maxframerate | A list of <integer></integer> | 0/7 | This equals |
| | | | "capability_videoin_c0_maxframerate". |
| | | | * This is kept for compatibility. |
| uideein minee meufreme | A list of stategers | 0/7 | |
| videoin_mjpeg_maxframe | A list of <integer></integer> | 0/7 | This equals |
| rate | and "-" | | "capability_videoin_c0_mjpeg_maxframerate |
| | | | ". |
| | | | * This is kept for compatibility. |
| videoin_h264_maxframer | A list of <integer></integer> | 0/7 | This equals |
| ate | and "-" | 0, , | "capability_videoin_c0_h264_maxframerate". |
| | | | |
| | | | * This is kept for compatibility. |
| videoin_codec | mjpeg, h264, h265 | 0/7 | Available codec of a device, split by comma. |
| | <product< td=""><td></td><td>The sequence is not limited.</td></product<> | | The sequence is not limited. |
| | <pre>>product</pre> | | The sequence is not innited. |

| | | | EX: |
|-----------------------------------|---|-----|--|
| | | | FD8183 supports H.264 and MJPEG, then this |
| | | | is "mjpeg,h264". |
| | | | IP9171 supports H.264, MJPEG and H.265, |
| | | | then this is "mjpeg,h264,h265" |
| videoin_streamcodec | A list of <positive< td=""><td>0/7</td><td>This equals</td></positive<> | 0/7 | This equals |
| videom_streamcodee | Integer> | 0,7 | "capability_videoin_c0_streamcodec". |
| | Integers | | |
| | | | * This is kept for compatibility. |
| videoin_flexiblebitrate | <boolean></boolean> | 0/7 | Indicate whether to support |
| | | | flexible bit rate control. |
| videoout_codec | -, ntsc, pal | 0/7 | Current output information about video out. |
| | | | 1st element for 1st video-out, 2nd element for |
| | | | 2nd video-out, and so on. The number of |
| | | | element depends on "capability_nvideooout". |
| | | | "-": Video-out is not available |
| | | | ntsc: NTSC analog output |
| | | | pal: PAL analog output |
| | | | |
| | | | Ex: |
| | | | "nvideoout"=0, "videoout_codec"=- |
| | | | "nvideoout"=1 with NTSC, |
| | | | "videoout_codec"=ntsc |
| | | | "nvideoout"=1 with PAL, |
| | | | "videoout_codec"=pal |
| | | | "nvideoout"=2 with both NTSC, |
| | | | "videoout_codec"=ntsc,ntsc |
| | | | * For camera, this feature is controlled by |
| | | | physical jump on device. No WebAPI to control |
| | | | it. This value is set only on camera power-on |
| | | | and maintains the status. |
| | | | * Only available when [httpversion] >= 0301a |
| timeshift | <boolean></boolean> | 0/7 | Indicate whether to support time shift caching |
| | | | stream. |
| audio_aec | <boolean></boolean> | 0/7 | Indicate whether to support acoustic echo |
| _ | | | cancellation. |
| audio_mic | <boolean></boolean> | 0/7 | Indicate whether to support built-in |
| <not anymore="" support=""></not> | | | microphone input. |
| | | | |

| | | | * Not support this parameter anymore when |
|-----------------------------------|---|-----|---|
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| | | | * We replace "audio_mic" with "audio_intmic". |
| | | 0/7 | |
| audio_intmic | <0~Positive | 0/7 | Internal (Built-in) Microphone. |
| | Integer> | | 0: Not support |
| | | | 1: Support |
| | | | Bit 0 for CH0, bit 1 for CH1, and so on. |
| audio_extmic | <0~Positive | 0/7 | External Microphone. |
| | Integer> | | 0: Not support |
| | | | 1: Support |
| | | | Bit 0 for CH0, bit 1 for CH1, and so on. |
| audio_alarm | <0~Positive | 0/7 | 0: Not support audio alarm. |
| | Integer> | | 1: Support audio alarm. |
| | | | Bit 0 for CH0, bit 1 for CH1, and so on. |
| audio_linein | <boolean></boolean> | 0/7 | Indicate whether to support external line |
| <not anymore="" support=""></not> | | | input. |
| | | | * Not support this parameter anymore when |
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| | | | * It will be replaced by audio_intmic and |
| | | | audio_extmic. |
| audio_lineout | <boolean></boolean> | 0/7 | Indicate whether to support line output. |
| audio_michardwareswitch | <boolean></boolean> | 0/7 | Indicate whether the hardware supports |
| | | | built-in/external mic switch |
| audio_headphoneout | <boolean></boolean> | 0/7 | Indicate whether to support headphone |
| <not anymore="" support=""></not> | | | output. |
| | | | |
| | | | * Not support this parameter anymore when |
| | | | the version number (httpversion) is equal or |
| | | | greater than 0301a. |
| audioin_codec | aac4, gamr, g711, | 0/7 | Available audio codec. We take comma to split |
| | g726, - | | codec without any space. |
| | <product< td=""><td></td><td></td></product<> | | |
| | dependent> | | aac4: Advanced Audio Coding (AAC) |
| | | | gamr: Adaptive Multi-Rate (AMR) |
| | | | g711: G.711 |
| | | | g726: G.726 |
| | | | - |
| | | | -: Not supported. |

| Product dependent>-: Not supported.motion_wintyperectangle, polygon0/7The supported motion window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a polygon shape.motion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_windomainqvga, px, std, -0/7Number of stream that support smart streamsmartstream_mindomainqvga, px, std, -0/7Indicate whether smart stream is supported.smartstream_mindomainqvga, px, std, -0/7Indicate whether smart stream is supported.smartstream_mindomainqvga, px, std, -0/7Indicate whether smart stream is supported.smartstream_mode_mon<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mon<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mindow_mon<boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean></boolean> | audiaaut aadaa | ~711 | 0/7 | Available codec list for SIP. |
|--|-------------------------|----------------------------------|------|---|
| dependent>inclinclmotion_wintyperectangle, polygon0/7The supported motion window is a polygon shape. rectangle: The motion window is a rectangle shape.motion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. p: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_nstream voisitive integer>0/7Indicate whether smart stream is supported.smartstream_mindomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. -: Not supported.smartstream_nstream voisitive integer>0/7Indicate whether smart stream is supported.smartstream_mindomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_mati coolean>0/7Indicate whether antutracking smart stream is supported.smartstream_mode_mati smartstream_mode_mati <td>audioout_codec</td> <td>g711, -</td> <td>0/7</td> <td></td> | audioout_codec | g711, - | 0/7 | |
| motion_wintyperectangle, polygon0/7The supported motion window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a polygon | | | | -: Not supported. |
| motion_windomainqvga, px, std, -0/7The domain to set an motion window is a polygon shape. rectangle: The motion window is a rectangle shape.motion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_windomainqvga, px, std, -0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_man<boolean>0/7Indicate whether anual smart stream is supported.smartstream_mode_man<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_man<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_mode_man<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_a<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h<positive integer="">0/</positive></positive></positive></positive></boolean></boolean></boolean></boolean></boolean> | | - | | |
| shape. rectangle: The motion window is a rectangle shape.motion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_mindomainqvga, px, std, -0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot<boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_motion<boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_motion<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_motion<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supported.smartstream_mode_motion<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_mindow_m<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manual<td>motion_wintype</td><td>rectangle, polygon</td><td>0/7</td><td></td></positive></positive></positive></positive></boolean></boolean></boolean></boolean></boolean> | motion_wintype | rectangle, polygon | 0/7 | |
| notion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. - Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_windomainqvga, px, std, -0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. - Not supported.smartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. - Not supported.smartstream_mode_autt<boolean>0/7Indicate whether autoracking smart stream is supported.smartstream_mode_mot<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mot<boolean>0/7Indicate whether hybrid(autoracking+ manual) smart stream is supportedsmartstream_mode_mot<boolean>0/7Maximum number of tracking window of manualsmartstream_mindnow_m<positive integer="">0/7Maximum number of tracking window of manualsmartstream_mindnow_m<positive integer="">0/7Maximum number of tracking window of manualsmartstream_mindnow_m<positive integer="">0/7Maximum number of tracking window of manual<td></td><td></td><td></td><td></td></positive></positive></positive></boolean></boolean></boolean></boolean></boolean> | | | | |
| ImportationImportatio | | | | |
| motion_windomainqvga, px, std, -0/7The domain to set an motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_nstream<positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot<boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_nwindow_a uutoracking<positive integer="">0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a naual<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h vybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h vybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotrack</positive></positive></positive></positive></boolean></boolean></positive></boolean> | | | | rectangle: The motion window is a rectangle |
| And the second | | | | shape. |
| image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_nstream<positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot<boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_man ual<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_man ual<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_man ual<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_man smartstream_nwindow_man<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_man vprid_autotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_man vprid_manualspositive integer>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_man vprid_manualspositive integer>0/7Maximum number of tracking windo</positive></positive></positive></boolean></boolean></boolean></boolean></positive></boolean> | motion_windomain | qvga, px, std, - | 0/7 | The domain to set an motion window. |
| pr:Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_nstream<positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autt<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether hybrid(autoracking + manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autoracking + manual) smart stream is supportedsmartstream_nwindow_mant<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_mantspositive integer>0/7Maximum number of tracking window of manualsmartstream_nwindow_mantspositive integer>0/7Maximum number of tracking window of manualsmartstream_nwindow_mantspositive integer>0/7Maximum number of tracking window of manualsmartstream_nwindow_mant<positive integer="">0/7Maximum number of tracking window of</positive></positive></boolean></boolean></boolean></boolean></boolean></positive></boolean> | | | | qvga: a 320x240 range to represent the whole |
| shift a normalized 0~9999 range. -: Not supported.smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_nstream<positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autt<boolean>0/7Indicate whether anuotarsking smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether manual smart stream is supported.smartstream_mode_mant<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_mant<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_mant<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid mode</positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean></boolean></positive></boolean> | | | | image. |
| Image: set | | | | px: Locate a window in the image with pixels. |
| smartstream_support <boolean>0/7Indicate whether smart stream is supported.smartstream_nstream<positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot<boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_man<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_a<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive i<="" td=""><td></td><td></td><td></td><td>std: A normalized 0~9999 range.</td></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean></boolean></positive></boolean> | | | | std: A normalized 0~9999 range. |
| smartstream_nstream <positive integer="">0/7Number of stream that support smart streamsmartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot<boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwi</positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean></positive> | | | | -: Not supported. |
| smartstream_windomainqvga, px, std, -0/7The domain to set an focus window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot <boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_man<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid mode<td>smartstream_support</td><td><boolean></boolean></td><td>0/7</td><td>Indicate whether smart stream is supported.</td></positive></positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean> | smartstream_support | <boolean></boolean> | 0/7 | Indicate whether smart stream is supported. |
| And and a set of the set of | smartstream_nstream | <positive integer=""></positive> | 0/7 | Number of stream that support smart stream |
| image.smartstream_mode_autot <boolean>0/7Indicate whether autotracking smart stream is supported.smartstream_mode_man<boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_mode_hybri<boolean>0/7Indicate whether hybrid(autotracking + manual) smart stream is supportedsmartstream_nwindow_m<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manual in hyb</positive></positive></positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean></boolean> | smartstream_windomain | qvga, px, std, - | 0/7 | The domain to set an focus window. |
| px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot racking <boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean> | | | | qvga: a 320x240 range to represent the whole |
| std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot racking <boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of manual)smartstream_nwindow_m auual<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking</positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean> | | | | image. |
| std: A normalized 0~9999 range. -: Not supported.smartstream_mode_autot racking <boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of manual)smartstream_nwindow_m auual<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_autotracking</positive></positive></positive></positive></positive></boolean></boolean></boolean></boolean> | | | | px: Locate a window in the image with pixels. |
| Image: series of the series | | | | |
| smartstream_mode_autot racking <boolean>0/7Indicate whether autotracking smart stream is supportedsmartstream_mode_man ual<boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m anual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_m autotracking<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqual<positive integer="">0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean> | | | | _ |
| rackingImage: support of the support of t | smartstream mode autot | <boolean></boolean> | 0/7 | |
| smartstream_mode_man ual <boolean>0/7Indicate whether manual smart stream is supportedsmartstream_mode_hybri d<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedd<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m anual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_supportqual smartstream_supportqual<positive integer="">0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive></positive></positive></positive></boolean></boolean></boolean> | | | | _ |
| ualsupportedsmartstream_mode_hybri <boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedd<boolean>0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_a<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_m<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_nwindow_h<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqualexcellent,detailed,g0/7Available quality of smart stream</positive></positive></positive></positive></positive></positive></positive></positive></boolean></boolean> | | <boolean></boolean> | 0/7 | |
| smartstream_mode_hybri <boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedd<boolean>0/7Indicate whether hybrid(autotracking+ manual) smart stream is supportedsmartstream_nwindow_a utotracking<positive integer="">0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m anual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqual<positive integer="">0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive></positive></positive></boolean></boolean> | | | 0, , | |
| dimanualimanualimanualimanualimanualsmartstream_nwindow_a utotracking <positive integer=""> amartstream_nwindow_m anual<positive integer=""> o0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m ybrid_autotracking<positive integer=""> o0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer=""> o0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> o0/7Maximum number of tracking window of manual in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> o0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqualexcellent,detailed,g0/7Available quality of smart stream</positive></positive></positive></positive></positive></positive> | | <pre>choolean></pre> | 0/7 | |
| smartstream_nwindow_a utotracking <positive integer=""> o0/7Maximum number of tracking window of autotrackingsmartstream_nwindow_m anual<positive integer=""> o0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer=""> o0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer=""> o0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> o0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqual<positive integer=""> excellent,detailed,g0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive></positive></positive> | | | 0/ / | |
| utotrackingautotrackingsmartstream_nwindow_m anual <positive integer=""> anual0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer=""> amartstream_nwindow_h ybrid_manual0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> amartstream_nwindow_h ybrid_manual0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_supportqual<positive integer=""> excellent,detailed,g0/7Maximum number of tracking window of manual in hybrid mode</positive></positive></positive></positive> | | | 0/7 | |
| smartstream_nwindow_m anual <positive integer=""> anual0/7Maximum number of tracking window of manualsmartstream_nwindow_h ybrid_autotracking<positive integer=""> vbrid_autotracking0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> vbrid_manual0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> vbrid_manual0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqual excellent,detailed,g0/7Available quality of smart stream</positive></positive></positive></positive> | | <positive integer=""></positive> | 0/7 | - |
| anualmanualsmartstream_nwindow_h ybrid_autotracking <positive integer=""> u0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer=""> u0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqualexcellent,detailed,g0/7Available quality of smart stream</positive></positive> | | | | |
| smartstream_nwindow_h ybrid_autotracking <positive integer="">0/7Maximum number of tracking window of autotracking in hybrid modesmartstream_nwindow_h ybrid_manual<positive integer="">0/7Maximum number of tracking window of manual in hybrid modesmartstream_supportqualexcellent,detailed,g0/7Available quality of smart stream</positive></positive> | | <positive integer=""></positive> | 0/7 | |
| ybrid_autotrackingautotracking in hybrid modesmartstream_nwindow_h <positive integer="">0/7Maximum number of tracking window of manual in hybrid modeybrid_manualexcellent,detailed,g0/7Available quality of smart stream</positive> | | | | |
| smartstream_nwindow_h <positive integer=""> 0/7 Maximum number of tracking window of manual in hybrid mode smartstream_supportqual excellent,detailed,g 0/7 Available quality of smart stream</positive> | smartstream_nwindow_h | <positive integer=""></positive> | 0/7 | Maximum number of tracking window of |
| ybrid_manual manual in hybrid mode smartstream_supportqual excellent,detailed,g 0/7 Available quality of smart stream | ybrid_autotracking | | | autotracking in hybrid mode |
| smartstream_supportqual excellent,detailed,g 0/7 Available quality of smart stream | smartstream_nwindow_h | <positive integer=""></positive> | 0/7 | Maximum number of tracking window of |
| | ybrid_manual | | | manual in hybrid mode |
| ity ood standard mediu | smartstream_supportqual | excellent,detailed,g | 0/7 | Available quality of smart stream |
| oujstandu difficult | ity | ood,standard,mediu | | |
| m,low | | m,low | | |

| smartstream_supportmax | 1Mbps,2Mbps,4Mbp | 0/7 | Available maxbitrate of smart stream |
|------------------------|--|-----|---|
| bitrate | s,6Mbps,8Mbps,10M | 0,7 | |
| | bps,20Mbps,30Mbps | | |
| | ,40Mbps | | |
| vadp_supportfeature | <pre>> <pre>> <pre>> </pre></pre></pre> | 0/7 | An 32-bit integer, each bit can be set |
| | | | separately as follows: |
| | | | Bit 0 => VADP interface |
| | | | Bit 1 => Capture video raw data |
| | | | Bit 2 => Support encode jpeg |
| | | | Bit 3 => Capture audio raw data |
| | | | Bit 4 => Support event trigger |
| | | | Bit 5 => Support license registration |
| | | | Bit 6 => Support shared memory API |
| | | | Bit $7 = $ Support digital signature of package |
| | | | Bit 8 => Support snapshot |
| vadp_npackage | <positive integer=""></positive> | 0/7 | Indicate the maximum number of VADP |
| | | | package that can be uploaded to the device. |
| thermal_support | <boolean></boolean> | 0/7 | Indicate whether to support thermal IC. |
| | <boolean></boolean> | 0/7 | Indicate whether to support temperature |
| ction | | | detection. |
| camctrl_httptunnel | <boolean></boolean> | 0/7 | Indicate whether to support httptunnel. |
| camctrl_privilege | <boolean></boolean> | 0/7 | Indicate whether to support "Manage |
| | | | Privilege" of PTZ control in the Security page. |
| | | | 1: support both /cgi-bin/camctrl/camctrl.cgi |
| | | | and /cgi-bin/viewer/camctrl.cgi |
| | | | 0: support only /cgi-bin/viewer/camctrl.cgi |
| uart_httptunnel | <boolean></boolean> | 0/7 | Indicate whether to support HTTP tunnel for |
| | | | UART transfer. |
| transmission_mode | Tx, | 0/7 | Indicate transmission mode of the machine: |
| | Rx, | | TX = server, Rx = receiver box, Both = DVR. |
| | Both | | |
| network_wire | <boolean></boolean> | 0/7 | Indicate whether to support Ethernet. |
| network_wireless | <boolean></boolean> | 0/7 | Indicate whether to support wireless. |
| wireless_s802dot11b | <boolean></boolean> | 0/7 | Indicate whether to support wireless |
| | | | 802.11b+. |
| wireless_s802dot11g | <boolean></boolean> | 0/7 | Indicate whether to support wireless 802.11g. |
| wireless_s802dot11n | <boolean></boolean> | 0/7 | Indicate whether to support wireless 802.11n. |

| wireless_beginchannel | 1 ~ 14 | 0/7 | Indicate the begin channel of wireless network |
|---|----------------------------------|-----|---|
| wireless_endchannel | 1 ~ 14 | 0/7 | Indicate the end channel of wireless network |
| wireless_encrypt_wep | <boolean></boolean> | 0/7 | Indicate whether to support wireless WEP. |
| wireless_encrypt_wpa | <boolean></boolean> | 0/7 | Indicate whether to support wireless WPA. |
| wireless_encrypt_wpa2 | <boolean></boolean> | 0/7 | Indicate whether to support wireless WPA2. |
| derivative_brand | <boolean></boolean> | 0/7 | Indicate whether to support the upgrade function for the derivative brand. For example, if the value is true, the VVTK product can be upgraded to VVXX. (TCVV<->TCXX is excepted) |
| test_ac | <boolean></boolean> | 0/7 | Indicate whether to support test ac key. |
| version_onvifdaemon | <string></string> | 0/7 | Indicate ONVIF daemon version |
| version_onviftesttool | <string></string> | 0/7 | Indicate ONVIF test tool version |
| media_totalspace | <positive integer=""></positive> | 0/7 | Available memory space (KB) for media. |
| media_snapshot_maxpre event | <positive integer=""></positive> | 0/7 | Maximum snapshot number before event occurred. |
| media_snapshot_maxpost event | <positive integer=""></positive> | 0/7 | Maximum snapshot number after event occurred. |
| media_snapshot_maxsize | <positive integer=""></positive> | 0/7 | Maximum size (KB) of a snapshot. |
| media_videoclip_maxsize | <positive integer=""></positive> | 0/7 | Maximum size (KB) of a videoclip. |
| media_videoclip_maxleng th | <positive integer=""></positive> | 0/7 | Maximum length (second) of a videoclip. |
| media_videoclip_maxpree vent | <positive integer=""></positive> | 0/7 | Maximum duration (second) after event occurred in a videoclip. |
| <pre>image_iristype <not recommended="" this="" to="" use=""></not></pre> | <string></string> | 0/7 | <pre>Indicate iris type. "piris": P-Iris "dciris": DC-Iris "dciris": DC-Iris "-": No Iris control support When "capability_iris"=0, this value must be "-". Note: For some box-type cameras, this value may be varied depending on mounted lens. We replace "capability_image_iristype" with "capability_image_c0_iristype ". Reserved for compatibility, and suggest don't</pre> |

| | | | use this since [httpversion] > 0301a |
|--|---|-----|--|
| image_focusassist | <boolean></boolean> | 0/7 | Indicate whether to support focus assist. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>* We replace "capability_image_ focusassist "</td></not> | | | * We replace "capability_image_ focusassist " |
| this> | | | with " capability_image_c0_ focusassist ". |
| | | | * Reserved for compatibility, and suggest don't |
| | | | use this since [httpversion] > 0301a |
| localstorage_manageable | <boolean></boolean> | 0/7 | Indicate whether manageable local storage is |
| | | | supported. |
| localstorage_seamless | <boolean></boolean> | 0/7 | Indicate whether seamless recording is |
| | | | supported. |
| localstorage_modnum | 0, | 0/7 | The maximum MOD connection numbers. |
| | <positive integer=""></positive> | | |
| localstorage_modversion | <string></string> | 0/7 | Indicate MOD daemon version |
| localstorage_stormgrversi | <string></string> | 0/7 | Indicate storage manager daemon version |
| on | | | |
| localstorage_supportedge | 0, | 0/7 | An 32-bit integer, which indicates the |
| | <positive integer=""></positive> | | supportive application of edge storage. |
| | | | If the value of this parameter is larger than 0, |
| | | | it means that the camera supports edge |
| | | | recording function. |
| | | | bit 0 : It supports to record directly to an |
| | | | on-board SD-Card. |
| | | | bit 1~: Currently, they are reserved bit, and |
| | | | the default value is 0. |
| localstorage_slconnum | 0, <positive integer=""></positive> | 0/7 | The maximum seamless connection number. |
| remotecamctrl_master | 0, <positive< td=""><td>0/7</td><td>Indicate whether to support remote auxiliary</td></positive<> | 0/7 | Indicate whether to support remote auxiliary |
| | integer> | | camera (master side), this value means |
| | | | supporting max number of auxiliary camera. |
| remotecamctrl_slave | <boolean></boolean> | 0/7 | Indicate whether to support remote camera |
| | | | control (slave side). |
| fisheyelocaldewarp_c<0~ | 0, <positive< td=""><td>0/7</td><td>Indicate the supported streams of local</td></positive<> | 0/7 | Indicate the supported streams of local |
| (capability_nvideoin)-1> | integer> | | dewarp. One bit represents one supported |
| <product dependent=""></product> | | | stream. The LSB indicates stream 0. |
| | | | Ex: "3" means stream 0 and stream 1 support |
| | | | local dewarp. |
| | | | * Only available when "capability_fisheye" > 0 |

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-------------|---------------------|-----------|--|
| | | (get/set) | |
| support | <boolean></boolean> | 0/7 | Indicate whether the camera supports day/night |
| | | | mode switch |
| builtinir | <boolean></boolean> | 0/7 | Indicate whether to support built-in IR led. |
| externalir | <boolean></boolean> | 0/7 | Indicate whether to support external IR led. |
| smartir | <boolean></boolean> | 0/7 | Indicate whether to support smart IR. |
| ircutfilter | <boolean></boolean> | 0/7 | Indicate whether to support IR cut. |
| lightsensor | <boolean></boolean> | 0/7 | Indicate whether to support light sensor. |

Group: **capability_daynight_c<0~(n-1)>** n denotes the value of "capability_nvideoin"

Group: capability_videoin_c<0~(n-1)> n denotes the value of "capability_nvideoin"

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-------------|----------------------------------|-----------|---|
| | | (get/set) | |
| lens_type | fisheye, fixed, | 0/7 | The lens type of this channel. |
| | varifocal, changeable, | | fisheye: Fisheye lens |
| | motor, - | | fixed: Build-in fixed-focus lens. |
| | <product dependent=""></product> | | varifocal: Build-in varifocal lens. |
| | | | changeable: changeable lens. Like box-type |
| | | | camera, users can install any C-Mount or |
| | | | CS-Mount lens as they wish. |
| | | | motor: Lens with motor to support zoom, focus, |
| | | | etc. |
| | | | -: N/A |
| | | | |
| | | | * Only available when [httpversion] >= 0301a |
| rotation | <boolean></boolean> | 0/7 | Indicate current mode whether support video |
| | | | rotation |
| streamcodec | <positive integer=""></positive> | 0/7 | Represent supported codec types of each |
| | | | stream. |
| | | | This contains a list of positive integers, split by |
| | | | comma. Each one stands for a stream, and the |
| | | | definition is as following: |
| | | | Bit 0: Support MPEG4. |
| | | | Bit 1: Support MJPEG |
| | | | Bit 2: Support H.264 |
| | | | Bit 3: Support H.265 |

| mode | 0, <positive integer=""></positive> | 0/7 | Indicate current video mode. |
|---------------|-------------------------------------|-----|--|
| nmode | <positive integer=""></positive> | 0/7 | Indicate how many video modes supported by |
| | | | this channel. |
| maxsize | <wxh></wxh> | 0/7 | The maximum resolution of all modes in this |
| | | | channel, the unit is pixel. |
| nprivacymask | 0, <positive integer=""></positive> | 0/7 | Number of privacy mask per channel |
| nresolution | <positive integer=""></positive> | 0/7 | The maximum resolution options (listed in |
| | | | "resolution") in current video mode. |
| resolution | A list of <wxh></wxh> | 0/7 | Resolution options in current video mode. These |
| | <product dependent=""></product> | | options are the possible options for |
| | | | "videoin_c <n>_s<m>_resolution".</m></n> |
| | | | The last one is the maximum resolution in |
| | | | current mode. |
| maxresolution | A list of <integer></integer> | 0/7 | Represent supported maximum resolution of |
| | | | each stream in current video mode. |
| | | | * The element number is defined as |
| | | | "capability_nmediastream". |
| maxframerate | A list of <integer></integer> | 0/7 | Indicate frame rate that the video source |
| | | | outputs in current video mode. |
| | | | One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter may be changed when |
| | | | "videoin c <n> cmosfreq"=50 or</n> |
| | | | "videoin_c <n>_modulation"=pal.</n> |
| | | | Ex: 30 fps is changed to 25 fps, 60 fps is changed |
| | | | |
| | | | to 50 fps, and so on. |

| mjpeg_maxframerate | A list of <positive< th=""><th>0/7</th><th>Maximum fps that the device can encoded with</th></positive<> | 0/7 | Maximum fps that the device can encoded with |
|--------------------|--|-----|--|
| | Integer> and "-" | | MJPEG on resolutions in current video mode. |
| | | | "-" means not support. |
| | | | |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter may be changed when |
| | | | "videoin_c <n>_cmosfreq"=50 or</n> |
| | | | "videoin_c <n>_modulation"=pal.</n> |
| | | | Ex: 30 fps is changed to 25 fps, 60 fps is |
| | | | changed to 50 fps, and so on. |
| | | | * Only available when 'mjpeg' is listed in |
| | | | "capability_videoin_codec". |
| mjpeg_maxbitrate | <positive integer="">, -</positive> | 0/7 | Maximum bitrates of MJPEG. |
| | | | The unit is bps. |
| | | | "-" means MJPEG does not support bit rate |
| | | | control. |
| | | | |
| | | | * Only available when 'mjpeg' is listed in |
| | | | "capability_videoin_codec". |
| h264_maxframerate | A list of <positive< td=""><td>0/7</td><td>Maximum fps that the device can encoded with</td></positive<> | 0/7 | Maximum fps that the device can encoded with |
| | Integer> and "-" | | H.264 on resolutions in current video mode. |
| | | | "-" means not support. |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter may be changed when |
| | | | "videoin_c <n>_cmosfreq"=50 or</n> |
| | | | "videoin_c <n>_modulation"=pal.</n> |
| | | | Ex: 30 fps is changed to 25 fps, 60 fps is |
| | | | changed to 50 fps, and so on. |
| | | | * Only available when 'h264' is listed in |
| | | | "capability_videoin_codec". |
| | | | |

| h264_maxbitrate | <positive integer=""></positive> | 0/7 | Maximum bitrates of H.264. |
|----------------------------------|--|-----|---|
| | | | The unit is bps. |
| | | | * Only available when 'h264' is listed in |
| | | | "capability_videoin_codec". |
| h265_maxframerate | A list of <positive< td=""><td>0/7</td><td>Maximum fps that the device can encoded with</td></positive<> | 0/7 | Maximum fps that the device can encoded with |
| | Integer> and "-" | | H.265 on resolutions in current video mode. |
| | | | "-" means not support. |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter may be changed when |
| | | | "videoin_c <n>_cmosfreq"=50 or</n> |
| | | | "videoin_c <n>_modulation"=pal.</n> |
| | | | Ex: 30 fps is changed to 25 fps, 60 fps is |
| | | | changed to 50 fps, and so on. |
| | | | * Only available when 'h265' is listed in |
| | | | "capability_videoin_codec". |
| h265_maxbitrate | <positive integer=""></positive> | 0/7 | Maximum bitrates of H.265. |
| | | | The unit is bps. |
| | | | * Only available when 'h265' is listed in |
| | | | "capability_videoin_codec". |
| fisheye_mounttype | ceiling, wall, floor | 0/7 | Indicate the supported type. |
| <product dependent=""></product> | <product dependent=""></product> | | wall mount: 180° panoramic view |
| | | | ceiling mount: 360° surround view without blind |
| | | | spots |
| | | | floor mount: 360° surround view without blind |
| | | | spots |
| | | | * Only available when "capability_fisheye" > 0 |

Group: capability_videoin_c<0~(n-1)>_localdewarp

(capability_fisheyelocaldewarp_c<0~(capability_nvideoin)-1> > 0)

n denotes the value of "capability_nvideoin"

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|------------------|-----------------------|-----------|---|
| | | (get/set) | |
| typeceilingmount | 10, 1P, 2P, 1R, 4R | 0/7 | Available dewarp types of ceiling and floor |
| | | | mount. |
| typewallmount | 10, 1P, 1R, 4R | 0/7 | Available dewarp types of wall mount. |
| resolutionC1P | A list of <wxh></wxh> | 0/7 | Available resolutions of 1P mode of ceiling and |
| | | | floor mount. |
| resolutionC2P | A list of <wxh></wxh> | 0/7 | Available resolutions of 2P mode of ceiling and |
| | | | floor mount. |
| resolutionC1R | A list of <wxh></wxh> | 0/7 | Available resolutions of 1R mode of ceiling and |
| | | | floor mount. |
| resolutionC4R | A list of <wxh></wxh> | 0/7 | Available resolutions of 4R mode of ceiling and |
| | | | floor mount. |
| resolutionW1P | A list of <wxh></wxh> | 0/7 | Available resolutions of 1P mode of wall mount. |
| resolutionW1R | A list of <wxh></wxh> | 0/7 | Available resolutions of 1R mode of wall mount. |
| resolutionW4R | A list of <wxh></wxh> | 0/7 | Available resolutions of 4R mode of wall mount. |

Group: capability_videoin_c<0~(n-1)>_mode<0~(m-1)> n denotes the value of "capability_nvideoin", m

denotes the value of "capability_videoin_c<n>_nmode"

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|----------------|---------------------|-----------|--|
| | | (get/set) | |
| rotation | <boolean></boolean> | 0/7 | Indicate this mode whether support video |
| | | | rotation |
| effectivepixel | <wxh></wxh> | 0/7 | The visible area of full scene in this video mode. |
| | | | The unit is pixel in source. |
| | | | |
| | | | * This value must <= |
| | | | "capability_videoin_c <n>_maxsize"</n> |
| | | | * If |
| | | | "effectivepixel"<"capability_videoin_c <n>_max</n> |
| | | | size", then the visible area is located at the |
| | | | center of full scene. |

| outputsize | <wxh></wxh> | 0/7 | The output size of source, equal to the captured |
|---------------|----------------------------------|-----|--|
| | | -,- | size by device, in this video mode. The unit is |
| | | | pixel. |
| | | | This value is used as a basic coordinate system |
| | | | for many features, like ePTZ, privacy mask, |
| | | | motion, etc. |
| | | | , |
| | | | * Source (most for image sensor) may perform |
| | | | scale or binning, etc on image data, and output |
| | | | data with smaller size. This parameter is |
| | | | designed to represent this. |
| binning | 0, 1, 3 | 0/7 | Indicate binning is used or not in this video |
| | | | mode. |
| | | | 0: No binning |
| | | | 1: 2x2 binning |
| | | | 3: 3x3 binning |
| | | | |
| | | | * Binning is a technology to increase light |
| | | | sensitivity by combining multiple pixels to one. |
| | | | The drawback is reduced resolution. We design |
| | | | this parameter to disclose this information. |
| nresolution | <positive integer=""></positive> | 0/7 | How many resolution options in this video mode. |
| resolution | A list of <wxh></wxh> | 0/7 | Resolution options in this video mode. |
| | | | The last one is the maximum resolution in this |
| | | | video mode. |
| | | | |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| maxresolution | A list of <integer></integer> | 0/7 | Represent supported maximum resolution of |
| | | | each stream in current video mode. |
| | | | * The element number is defined as |
| | | | "capability_nmediastream". |

| maxframerate | A list of <positive< th=""><th>0/7</th><th>Indicates frame rate that the video source</th></positive<> | 0/7 | Indicates frame rate that the video source |
|--------------|---|-----|---|
| | Integer> | | outputs in this video mode. |
| | | | |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter records the frame rate when |
| | | | "videoin_c <n>_cmosfreq"=60 or</n> |
| | | | "videoin_c <n>_modulation"=ntsc</n> |
| maxfps_mjpeg | A list of <positive< td=""><td>0/7</td><td>Maximum fps which the device can encoded with</td></positive<> | 0/7 | Maximum fps which the device can encoded with |
| | Integer> and "-" | | MJPEG on resolutions in this video mode. |
| | | | "-" means not support. |
| | | | |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter records the frame rate when |
| | | | "videoin_c <n>_cmosfreq"=60 or</n> |
| | | | "videoin_c <n>_modulation"=ntsc</n> |
| | | | * Only available when 'mjpeg' is listed in |
| | | | "capability_videoin_codec". |
| maxfps_h264 | A list of <positive< td=""><td>0/7</td><td>Maximum fps which the device can encoded with</td></positive<> | 0/7 | Maximum fps which the device can encoded with |
| | Integer> and "-" | | H.264 on resolutions in this video mode. |
| | | | "-" means not support. |
| | | | |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter records the frame rate when |
| | | | "videoin_c <n>_cmosfreq"=60 or</n> |
| | | | "videoin_c <n>_modulation"=ntsc</n> |
| | | | * Only available when 'h264' is listed in |
| | | | "capability_videoin_codec". |

| maxfps_h265 | A list of <positive< th=""><th>0/7</th><th>Maximum fps which the device can encoded with</th></positive<> | 0/7 | Maximum fps which the device can encoded with |
|-------------|---|-----|---|
| | Integer> and "-" | | H.265 on resolutions in this video mode. |
| | | | "-" means not support. |
| | | | |
| | | | * One to one mapping to the resolution in |
| | | | "resolution". |
| | | | * The element number is defined as |
| | | | "nresolution" in this group. |
| | | | * This parameter records the frame rate when |
| | | | "videoin_c <n>_cmosfreq"=60 or</n> |
| | | | "videoin_c <n>_modulation"=ntsc</n> |
| | | | * Only available when 'h265' is listed in |
| | | | "capability_videoin_codec". |
| description | <string[128]></string[128]> | 0/7 | Description about this mode. |

Group: capability_videoin_c<0~(n-1)>_mode<0~(m-1)>_defaultsetting_s<0~(j-1)>

n denotes the value of "capability_nvideoin", m denotes the value of "capability_videoin_c<n>_nmode", j denotes the value of "capability_nmediastream"

| * Only available when "capability_videoin_c <n>_nmode" > 1</n> | * | Only available | when | "capability_ | videoin | _c <n>_</n> | _nmode" > | 1 |
|---|---|----------------|------|--------------|---------|-------------|-----------|---|
|---|---|----------------|------|--------------|---------|-------------|-----------|---|

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-----------------|--|-----------|--|
| | | (get/set) | |
| resolution | A list of <wxh></wxh> | 0/7 | Default setting of resolution options. |
| | | | "-" means not support. |
| | | | * The element number is defined as |
| | | | "capability_nresolution". |
| mjpeg_framerate | A list of <positive< td=""><td>0/7</td><td>Default setting of mjpeg framerate on</td></positive<> | 0/7 | Default setting of mjpeg framerate on |
| | Integer> and "-" | | resolutions in this video mode. |
| | | | "-" means not support. |
| | | | |
| | | | * The element number is defined as |
| | | | "capability_nresolution". |
| mjpeg_bitrate | A list of <positive< td=""><td>0/7</td><td>Default setting of mjpeg bitrate on resolutions in</td></positive<> | 0/7 | Default setting of mjpeg bitrate on resolutions in |
| | Integer> and "-" | | this video mode. |
| | | | "-" means not support. |
| | | | * The element number is defined as |
| | | | "capability_nresolution". |
| h264_framrate | A list of <positive< td=""><td>0/7</td><td>Default setting of h264 framerate on resolutions</td></positive<> | 0/7 | Default setting of h264 framerate on resolutions |
| | Integer> and "-" | | in this video mode. |

| | | | "-" means not support. |
|---------------|--|-----|---|
| | | | * The element number is defined as "capability_nresolution". |
| h264_bitrate | A list of <positive Integer> and "-"</positive | 0/7 | Default setting of h264 bitrate on resolutions in this video mode. "-" means not support. |
| | | | * The element number is defined as "capability_nresolution". |
| h265_framrate | A list of <positive Integer> and "-"</positive | 0/7 | Default setting of h265 framerate on resolutions in this video mode. "-" means not support. |
| | | | * The element number is defined as "capability_nresolution". |
| h265_bitrate | A list of <positive Integer> and "-"</positive | 0/7 | Default setting of h265 bitrate on resolutions in this video mode. "-" means not support. |
| | | | * The element number is defined as "capability_nresolution". |

Group: capability_image_c<0~(n-1)> n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------|-------------------------------------|-----------|--|
| | | (get/set) | |
| basicsetting | 0, <positive integer=""></positive> | 0/7 | A 32-bits integer, each bit can be set |
| | | | separately as follows: |
| | | | Bit 0 => Supports Brightness or not. |
| | | | Bit 1 => Supports Contrast or not. |
| | | | Bit 2 => Supports Saturation or not. |
| | | | Bit 3 => Supports Sharpness or not. |
| wdrpro_mode | 0, 1, 2 | 0/7 | 0: Non-support WDR Pro |
| | | | 1: Support WDR Pro |
| | | | 2: Support WDR Pro and WDR Pro II |
| wdrpro_strength | 0, 1 | 0/7 | 0: Non-support tuning strength of |
| | | | WDR Pro |
| | | | 1: Support tuning strength of WDR Pro |
| | | | |
| | | | * If |

| wdrpro_supportlevel <positive integer="">0/7This contains a list of positive integers, split by comma. If "wdrpro_mode" =1, then the value indicate the support strength level of WDR Pro. If "wdrpro_mode" =2, then the first number indicate the support strength level of WDR Pro. If "wdrpro_mode" =2, then the first number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro II.wdrpro_affect-,0/7When WDR Pro or WDR Enhanced is exposurewin.mode:fixed:au to, exposurelevel:fixed:0/7When WDR Pro or WDR Enhanced is enabled, some features may become walue. The affect ductions are list here. aespeci.disabled:, exposurelevel:fixed:1exposurelevel:fixed:-,0/7When WDR Pro or WDR Enhanced is enabled, some features may become walue. The affect ductions are list here. aespeci.disabled:, exposurelevel:fixed:The format is "Affect API name":"Policy": "Value" exposurelevel:fixed:<,-,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,-,<<,-,</positive> | | | | "conshility image can udmrs"-1 |
|---|---------------------|---|------|--|
| wdrpro_supportievel <positive integer=""> 0/7 This contains a list of positive integers, split by comma. If "wdrpro_mode" =1, then the value indicate the support strength level of WDR Pro. If "wdrpro_mode" =2, then the first number indicate the support strength level of WDR Pro. wdrpro_affect -, 0/7 When WDR Pro or WDR Enhanced is exposurewin.mode.flxed:aut to, exposurelevel:hidden:, etc. The format is "Affect API name": "Policy": "Value" <x>: nonnegative integer <pre> (disabled) : UI turns grey and users</pre> (disabled) : UI keeps the status as before and user can't change it. t <(hidden) : UI is hidden.</x></positive> | | | | <pre>"capability_image_c<n>_wdrpro"=1, this may be sitter 0 or 1</n></pre> |
| split by comma.If "wdrpro_mode" =1, then the valueindicate the support strengthivdrpro_mode" =2, then the firstnumber indicate the support strengthlevel of WDR Pro.If "wdrpro_mode" =2, then the firstnumber indicate the support strengthlevel of WDR Pro.If "wdrpro_mode" =2, then the firstnumber indicate the support strengthlevel of WDR Pro.If "wdrpro_mode" =2, then the firstnumber indicate the support strengthlevel of WDR Pro and the scecordnumber indicate the support strengthlevel of WDR Pro or WDR Enhanced isexposurewin.mode.fixed:auexposurelevel:fixed:x>,exposurelevel:fixed:x>,exposurelevel:fixed:x>,exposurelevel:fixed:x>,exposurelevel:fixed:x>,exposurelevel:fixed:autofollowing groups:exposurelevel:fixed:auto | | | 0.17 | |
| If "wdrpro_mode" = 1, then the value indicate the support strength level of WDR Pro. If "wdrpro_mode" = 2, then the first number indicate the support strength level of WDR Pro, and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second number indicate the support strength level of WDR Pro and the second maintuction are list here. aespeed:disabled:, exposurelevel:fixed:< | wdrpro_supportlevel | <positive integer=""></positive> | 0/7 | |
| indicate the support strength level of WDR Pro.if "wdrpro_mode" = 2, then the first number indicate the support strength level of WDR Pro, and the second number indicate the support strength level of WDR Pro II.wdrpro_affect-,o/7When WDR Pro or WDR Enhanced is exposurewin.mode:fixed:au to, exposurelevel:fixed:real; exposurelevel:fixed: <x>, exposurelevel:fixed:<x>, exposurelevel:fixed:auto r0/7wdrpro_affect-,o/7When WDR Pro or WDR Enhanced is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here.ied:, aespeed:disabled:, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:auto (disabled) : UI turns grey and users can't select it. - (disabled) : UI turns grey and users can't select it. - (inchanged) : UI turns grey and users can't select it. - (fixed) : UI is fixed to multiple selections or value.ent- (fixed) : UI is fixed to multiple selections or values.>>>***<td></td><td></td><td></td><td></td></x></x></x></x></x> | | | | |
| WDR Pro.WDR Pro.If "wdrpro_mode" =2, then the first number indicate the support strength level of WDR Pro, and the second number indicate the support strength level of WDR Pro II.wdrpro_affect-,0/7Wdrpro_affect-,0/7Wdrpro_affect-,0/7wdrpro_affect-,0/7wdrpro_affect-,0/7wdrpro_affect-,0/7wdrpro_affect-,0/7wdrpro_affect-,0/7wdrpro_affect-,exposurewin.mode.blc:disable led:, aesped:disabled:, exposurelevel:fixed:Nmen WDR Pro or WDR Enhanced is enabled, some features may become maffunction or be forced to a given value. The affected functions are list here.exposurelevel:fixed:-,The format is "Affect API name":"Policy": Value" exposurelevel:ranged: <x>, exposurelevel:ranged: <x>,-,"Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it,-,</x></x> | | | | |
| Image: series of the series | | | | indicate the support strength level of |
| number indicate the support strength level of WDR Pro, and the second number indicate the support strength level of WDR Pro II.wdrpro_affect-,0/7When WDR.Pro or WDR Enhanced is exposurewin.mode:fixed:au to, exposurewin.mode.blc:disab led:, aespeed:disabled;, exposurelevel:hidden:, exposurelevel:hidden:, exposurelevel:hidden:, exposurelevel:hidden:, exposurelevel:fixed: <x>, exposurelevel:hidden:, exposurelevel:fixed:<x>, exposurelevel:hidden:, exposurelevel:hidden:, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed:<x>, exposurelevel:fixed: exposurelevel:fixed: exposurelevel:fixed: exposurelevel:fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelevel: fixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposurelixed: exposur</x></x></x></x></x></x></x></x></x></x></x></x></x></x></x></x></x> | | | | WDR Pro. |
| wdrpro_affect-,0/7When WDR Pro, and the scecond number indicate the support strength level of WDR Pro II.wdrpro_affect-,0/7When WDR Pro or WDR Enhanced is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. aespeed:disabled:, exposurelevel:fixed: <x>,Note affected functions are list here.exposurelevel:fixed:<x>,name":"Policy":"Value"exposurelevel:fixed:<x>,reposurelevel:ranged:<x>-<x>,"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as oduc t-,<td></td><td></td><td></td><td>If "wdrpro_mode" =2, then the first</td></x></x></x></x></x> | | | | If "wdrpro_mode" =2, then the first |
| Image: series of the series | | | | number indicate the support strength |
| wdrpro_affect -, 0/7 When WDR Pro II. wdrpro_affect -, 0/7 When WDR Pro or WDR Enhanced is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. aespeed:disabled:, value. The affected functions are list here. aespeed:disabled:, mare:"Policy":"Value" exposurelevel:hidden:, mare:"Policy":"Value" exposurelevel:fixed: <x>, "Policy" can be categorized into following groups: <xx,< td=""> -, (disabled): UI turns grey and users can't select it. <xx: integer<="" nonnegative="" td=""> -, (unchanged): UI keeps the status as before and user can't change it. dep -, (fixed): UI is fixed to one selection or value. ent -, (ranged): UI is fixed to multiple selections or values. > selections or values. with means blc exposure window is disabled. API name can be one word as well, such as "exposureive!fixed:6"</xx:></xx,<></x> | | | | level of WDR Pro, and the scecond |
| wdrpro_affect -, 0/7 When WDR Pro or WDR Enhanced is exposurewin.mode:fixed:au to, enabled, some features may become exposurewin.mode.blc:disab value. The affected functions are list led:, aespeed:disabled:, value. The affected functions are list exposurelevel:hidden:, The format is "Affect API exposurelevel:nixed: <xx>, name":"Policy":"Value" exposurelevel:rixed:auto following groups: <x>, (disabled) : UI turns grey and users <x>: nonnegative integer - (unchanged) : UI keeps the status as oduc before and user can't change it. t - (fixed) : UI is fixed to one selection or end - (ranged) : UI is fixed to multiple > selections or values. * "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as</x></x></xx> | | | | number indicate the support strength |
| exposurewin.mode:fixed:au to,enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. aespeed:disabled:, exposurelevel:hidden:, exposurelevel:hidden:, exposurelevel:fixed: <x>, exposurelevel:fixed:<x>, (x>, x>, (x>, (x), to the format is "Affect API name":"Policy":"Value" (x), the format is "Affect API name":"Policy":"Value" (disabled) : UI turns grey and users (disabled) : UI turns grey and users (disabled) : UI turns grey and users (disabled) : UI terns grey and users (disabled) : UI terns grey and users (disabled) : UI is fixed to one selection or value.ent- (fixed) : UI is fixed to one selection or value.ent- (ranged) : UI is fixed to multiple selections or values.>>wich means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</x></x> | | | | level of WDR Pro II. |
| to,malfunction or be forced to a given value. The affected functions are list here.aespeed:disabled:,value. The affected functions are list here.aespeed:disabled:,The format is "Affect API name":"Policy":"Value"exposurelevel:fixed: <x>,name":"Policy":"Value"exposurelevel:ranged:<x>-"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.<x>.expo<x>: nonnegative integer oduc- (nuchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden.dep end end- (fixed) : UI is fixed to one selection or value.ent >>- (ranged) : UI is fixed to multiple selections or values.>-*"Affect API name" can be described in hierarchy, such as "exposurei.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</x></x></x></x> | wdrpro_affect | -, | 0/7 | When WDR Pro or WDR Enhanced is |
| exposurewin.mode.blc:disab led:, aespeed:disabled:, exposurelevel:hidden:, exposurelevel:fixed: <x>, exposurelevel:ranged:<x>- <x>,The format is "Affect API name":"Policy":"Value" exposurelevel:ranged:<x>- <x>, <x>,"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. t t the dep end end >>dep end end >>- (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values.>Selections or values"Affect API name" can be described in hierarchy, such as "exposurei.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</x></x></x></x></x></x> | | exposurewin.mode:fixed:au | | enabled, some features may become |
| Ied:,here.aespeed:disabled:,The format is "Affect APIexposurelevel:fixed: <x>,name":"Policy":"Value"exposurelevel:fixed:<x>,"Policy" can be categorized intoexposurelevel:ranged:<x>-following groups:<x>,"Policy" can be categorized intoexposuremode:fixed:autofollowing groups:< (disabled) : UI turns grey and users</x></x></x></x> | | to, | | malfunction or be forced to a given |
| aespeed:disabled:, exposurelevel:hidden:, exposurelevel:fixed: <x>, exposurelevel:ranged:<x>- <x>,The format is "Affect API name":"Policy":"Value"<x>, exposurelevel:ranged:<x>- <x>,"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as oduc before and user can't change it. t t t t end<pr </pr end end >>- (hidden) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values.<pr </pr end >>- (ranged) : UI is fixed to multiple selections or values.<pr </pr ent >>- (ranged) : UI is fixed to multiple selections or values.<pr </pr ent >>- (ranged) : UI is fixed to multiple selections or values.<pr </pr end which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</x></x></x></x></x></x> | | exposurewin.mode.blc:disab | | value. The affected functions are list |
| exposurelevel:hidden:, exposurelevel:fixed: <x>, exposurelevel:ranged:<x>- <x>,The format is "Affect API name":"Policy":"Value"<x>, exposuremode:fixed:auto"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it.<x>: nonnegative integer oduccan't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. dep end end >>dep ent >>- (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple selections or values.>Selections or values."Affect API disabled. API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</x></x></x></x></x> | | led:, | | here. |
| exposurelevel:fixed: <x>, exposurelevel:ranged: <x>- <x>, exposuremode:fixed:auto exposuremode:fixed:auto exposuremode:fixed:auto following groups: - (disabled) : UI turns grey and users can't select it. (unchanged) : UI keeps the status as oduc before and user can't change it. t t t t t t t t t t t t t t t t t t</x></x></x> | | aespeed:disabled:, | | |
| exposurelevel:ranged: <x>- "Policy" can be categorized into <x>, "Policy" can be categorized into exposuremode:fixed:auto following groups: - (disabled) : UI turns grey and users can't select it. <x>: nonnegative integer can't select it. oduc before and user can't change it. t (fixed) : UI is hidden. (fixed) : UI is fixed to one selection or end value. (ranged) : UI is fixed to multiple selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" </x></x></x> | | exposurelevel:hidden:, | | The format is "Affect API |
| <pre></pre> | | exposurelevel:fixed: <x>,</x> | | name":"Policy":"Value" |
| exposuremode:fixed:autofollowing groups: - (disabled) : UI turns grey and users <x>: nonnegative integercan't select it.<pr< td="">- (unchanged) : UI keeps the status as oducoducbefore and user can't change it.t- (hidden) : UI is hidden.dep- (fixed) : UI is fixed to one selection or value.endvalue.ent- (ranged) : UI is fixed to multiple selections or values.>which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6"</pr<></x> | | exposurelevel:ranged: <x>-</x> | | |
| - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. t - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or value. end - (ranged) : UI is fixed to multiple selections or values. - (ranged) : UI is fixed to multiple selections or values. - (ranged) : UI is fixed to multiple selections or values. | | <x>,</x> | | "Policy" can be categorized into |
| <x>: nonnegative integercan't select it.<pr< td="">- (unchanged) : UI keeps the status asoducbefore and user can't change it.t- (hidden) : UI is hidden.dep- (fixed) : UI is fixed to one selection orendvalue.ent- (ranged) : UI is fixed to multiple>selections or values.''''''''''''''''''''''''''''''''''''</pr<></x> | | exposuremode:fixed:auto | | following groups: |
| - (unchanged) : UI keeps the status as oduc before and user can't change it. t - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or end value. - (ranged) : UI is fixed to multiple selections or values. | | | | - (disabled) : UI turns grey and users |
| oducbefore and user can't change it.t- (hidden) : UI is hidden.dep- (fixed) : UI is fixed to one selection orendvalue.ent- (ranged) : UI is fixed to multiple>selections or values."Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | <x>: nonnegative integer</x> | | can't select it. |
| t - (hidden) : UI is hidden. dep - (fixed) : UI is fixed to one selection or end value. ent - (ranged) : UI is fixed to multiple > selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | <pr< td=""><td></td><td>- (unchanged) : UI keeps the status as</td></pr<> | | - (unchanged) : UI keeps the status as |
| dep - (fixed): UI is fixed to one selection or end value. ent - (ranged): UI is fixed to multiple > selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | oduc | | before and user can't change it. |
| end value. ent - (ranged) : UI is fixed to multiple > selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | t | | - (hidden) : UI is hidden. |
| ent - (ranged) : UI is fixed to multiple > selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | dep | | - (fixed) : UI is fixed to one selection or |
| selections or values. "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | end | | value. |
| "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | ent | | - (ranged) : UI is fixed to multiple |
| hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | > | | selections or values. |
| hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | | | |
| "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | | | "Affect API name" can be described in |
| which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | | | hierarchy, such as |
| disabled. API name can be one word as well, such as "exposurelevel:fixed:6" | | | | "exposurewin.mode.blc:disabled:" |
| well, such as "exposurelevel:fixed:6" | | | | which means blc exposure window is |
| | | | | disabled. API name can be one word as |
| which means exposurelevel is fixed to | | | | well, such as "exposurelevel:fixed:6" |
| | | | | which means exposurelevel is fixed to |

| | | | level 6. |
|-------------------|----------------------------------|-----|---|
| | | | |
| | | | "Value" can be a nonnegative integer |
| | | | or NULL. |
| | | | |
| | | | "-" means no feature is affected. |
| | | | * When "wdrpro"=0 and "wdrc"=0, |
| | | | this must be "-" |
| wdrc_mode | 0, 1 | 0/7 | 0: Non-support WDR Enhanced |
| | | | 1: Support WDR Enhanced |
| wdrc_supportlevel | <positive integer=""></positive> | 0/7 | indicate the support strength level of |
| | | | WDR Enhanced. |
| wdrc_affect | -, | 0/7 | When WDR Pro or WDR Enhanced is |
| | exposurewin.mode:fixed:au | | enabled, some features may become |
| | to, | | malfunction or be forced to a given |
| | exposurewin.mode.blc:disab | | value. The affected functions are list |
| | led:, | | here. |
| | <pre>aespeed:disabled:,</pre> | | |
| | exposurelevel:hidden:, | | The format is "Affect API |
| | exposurelevel:fixed: <x>,</x> | | name":"Policy":"Value" |
| | exposurelevel:ranged: <x>-</x> | | |
| | <x>,</x> | | "Policy" can be categorized into |
| | exposuremode:fixed:auto | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | <x>: nonnegative integer</x> | | can't select it. |
| | <product dependent=""></product> | | - (unchanged) : UI keeps the status as |
| | | | before and user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection or |
| | | | value. |
| | | | - (ranged) : UI is fixed to multiple |
| | | | selections or values. |
| | | | "Affect API name" can be described in |
| | | | hierarchy, such as |
| | | | "exposurewin.mode.blc:disabled:" |
| | | | which means blc exposure window is |
| | | | disabled. API name can be one word as |
| | | | well, such as "exposurelevel:fixed:6" |
| | | | which means exposurelevel is fixed to |
| | | | • • • • • • |

| Ievel 6. "Value" can be a nonnegative integer or NULL. "-" means no feature is affected. "-" means no feature is affected. # When "wdrpro"=0 and "wdre"=0, this must be "-" "." means no feature is affected. dnr 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, noiseless, lpcparkinglot, lpcstreet 0/7 Itst all the scene mode which are supported in the camera. scenemode_visibility_affe ct -, minexposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. scenemode_visibility_affe -, or others "Policy" can be categorized into following groups: - (disabled): UI turns grey and users can't select it. - (inden): UI teeps the status as before and user can't change it. - (hidden): UI to hidden. - (fixed): UI is fixed to one selection or value. | | | T | |
|---|----------------------------------|----------------------------------|------|--|
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction elis 0,1 0/7 0: Non-support 3D digital noise reduction is scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 1Ist all the scene mode which are support scene mode scenemode_support visibility, 0/7 Ist all the scene mode which are support is 1 scenemode_visibility_affe ct -, 0/7 When scene mode is enabled, some features may become malituction or be forced to a given value. The affected functions are list here. sdnr:unchanged:, or others The format is "Affect API name": "Policy": Value" <x>: nonnegative integer -product dependent> "Policy" can be categorized into following groups: - (disabled) : UI twens grey and users can't select it ((unchanged) : UI keeps the status as before and user can't change it (hidden) : UI is hidden (fixed) : UI is hidden (fixed) : UI is hidden.</x> | | | | level 6. |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction is cenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support visibility, noiseless, 0/7 Ist all the scene mode which are support scenemode_visibility_affe . . 0/7 When scene mode is enabled, some features may become malifunction or be forced to a given value. The affected functions are list here. sdnr:unchanged:, or or others . The format is "Affect API nam | | | | |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supportspe visibility, 0/7 0: Non-support scene mode scenemode_supportspe visibility, 0/7 Iist all the scene mode which are supported in the camera. lpcparkinglot, lpcstreet * Only available when * capability_image_c <n>_ scenemode_support* is 1 scenemode_visibility_affe -, mingain:hidden:, wdrpro:unchanged;, or others 3dnr:unchanged;, or others affected functions are list here. sdnruchangedi or others "Policy" can be categorized into following groups: - (disabled) : UI twens que users can't change it. <pre>roduct dependent> "Policy" can be categorized into following groups: - (disabled) : UI keeps the status as before and <td></td><td></td><td></td><td>"Value" can be a nonnegative integer</td></pre></n> | | | | "Value" can be a nonnegative integer |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 1ist all the scene mode which are support.cd visibility, 0/7 1ist all the scene mode which are support.cd support. 0/7 Visa scenemode_support is 1 scenemode_visibility_affe -, 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. sdnr:unchanged:, or others The format is "Affect API name": "Policy": "Value" <x>: nonnegative integer -product dependent> "Policy" can be categorized into following grou</x> | | | | or NULL. |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction eis 0,1 0/7 0: Non-support 3D digital noise reduction scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 0: Non-support scene mode scenemode_support visibility, 0/7 1ist all the scene mode which are support.cd visibility, 0/7 1ist all the scene mode which are support.cd support. 0/7 Visa scenemode_support is 1 scenemode_visibility_affe -, 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. sdnr:unchanged:, or others The format is "Affect API name": "Policy": "Value" <x>: nonnegative integer -product dependent> "Policy" can be categorized into following grou</x> | | | | |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction reduction 1: Support 3D digital noise reduction els 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_supporttype visibility, noiseless, lpcparkinglot, lpcstreet 0/7 0: Non-support scene mode scenemode_visibility_affe ct r, minexposure: hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode which are support? is 1 scenemode_visibility_affe ct r, mingain:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others scenemode_visibility_affe ct -, mingain:hidden:, wdrpro:unchanged:, or others The format is "Affect API name":"Policy":"Value" <x>: nonnegative integer - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is hidden. - (fixed) : UI is hidden.</x> | | | | "-" means no feature is affected. |
| dnr 0,1 0/7 0: Non-support 3D digital noise reduction 1: Support 3D digital noise reduction eis 0,1 0/7 0: Non-support 2D digital noise reduction scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer 1: Support scene mode scenemode_supporttype visibility, noiseless, lpcparkinglot, lpcstreet 0/7 0: Non-support scene mode 1: Support scene mode scenemode_visibility_affre ct -, minseposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode is enabled, some features may become mailinction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others <product dependent=""> -, reproduct dependent> The format is "Affect API name": "Policy": Tvalue" <x>: nonnegative integer "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged it. - (unchange it. - (unchanged it. - (inchange it. - (inch</x></product> | | | | * When "wdrpro"=0 and "wdrc"=0, |
| eis 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, 0/7 0! stall the scene mode which are sproduct dependent> noiseless, 1 supported in the camera. lpcparkinglot, Ipcrarkinglot, * * lpcparkinglot, Ipcrarkinglot, * * upcrave only available when * scenemode_visibility_affe -, 0/7 When scene mode is enabled, some startunchanged:, or others minfagin:hidden:, mingain:hidden:, | | | | this must be "-" |
| eis 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, 0/7 0! stall the scene mode which are sproduct dependent> noiseless, 1 supported in the camera. lpcparkinglot, Ipcrarkinglot, * * lpcstreet * Only available when * <product dependent=""> *, 0/7 When scene mode is enabled, some ct mingain:hidden:, wdrpro:unchanged:, or others features may become malfunction or sproduct dependent> or others The for</product> | dnr | 0.1 | 0/7 | 0: Non-support 3D digital noise |
| eis 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, 0/7 1st all the scene mode which are supported in the camera. sproduct dependent> noiseless, 0/7 1st all the scene mode which are supported in the camera. scenemode_visibility_affe -, 0/7 When scene mode scene mode scene mode scene mode scene mode_support" is 1 scenemode_visibility_affe -, 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. sdnr:unchanged:, 3dnr:unchanged:, or others The format is "Affect API name": "Policy": "Value" <x>: nonnegative integer -, (disabled) : UI turns grey and users can't select it. - (disabled) : UI keeps the status as before and user can't change it. - (hidden), UI is fixed to one selection or</x> | | | 0, 1 | |
| eis 0,1 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support electronic image stabilizer scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supportype visibility, 0/7 list all the scene mode which are sproduct dependent> 0/7 list all the scene mode which are supported in the camera. lpcparkinglot, lpcstreet visibility_inage_c <n>_ scenemode_visibility_affe ct scenemode_visibility_affe ct sproduct dependent> 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others The format is "Affect API name": "Policy": "Value" <x>: nonnegative integer <product dependent=""> (disabled) : UI keeps the status as before and user can't change it. - (hidden) : UI keeps the status as before and user can't change it. - (hidden) : UI is fixed to one selection or</product></x></n> | | | | |
| scenemode_support0,10/7Stabilizerscenemode_support0,10/70: Non-support scene modescenemode_supporttypevisibility, noiseless, lpcparkinglot, lpcstreet0/7list all the scene mode which are supported in the camera. lpcparkinglot, lpcstreetscenemode_visibility_affe ct-, minaexposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others0/7When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others <x>>: nonnegative integer <, product dependent>"Policy": "Value"<x>: nonnegative integer <, product dependent>"Policy": "Value"<x>: nonnegative integer <, product dependent>"Policy": UI turns grey and users can't select it. - (unchanged): UI turns grey and users can't select it. - (unchanged): UI turns grey and users can't select it. - (unchanged): UI is hidden. - (hidden): UI is fixed to one selection or</x></x></x> | aia | 0.1 | 0/7 | |
| scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, 0/7 list all the scene mode which are scenemode_supporttype visibility, 0/7 list all the scene mode which are sproduct dependent> noiseless, upcarkinglot, upcarkinglot, lpcparkinglot, product dependent> * Only available when <product dependent=""> "capability_image_c<n>_ scenemode_visibility_affe -, 0/7 When scene mode is enabled, some features may become malfunction or sproduct dependent> minagain:hidden:, wdrpro:unchanged;, affected functions are list here. 3dnr:unchanged:, or others The format is "Affect API name":"Policy":Value" <x>: nonnegative integer "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. < product dependent> "Unchanged i:. - (unchanged i:. - (unchanged i:.</x></n></product> | eis | 0,1 | 0/7 | |
| scenemode_support 0,1 0/7 0: Non-support scene mode scenemode_supporttype visibility, 0/7 list all the scene mode which are supported in the camera. <product dependent=""> lpcparkinglot, lpcparkinglot, supported in the camera. lpcparkinglot, lpcstreet * Only available when "capability_image_<n></n></product> | | | | |
| scenemode_supporttype visibility, 0/7 list all the scene mode which are supported in the camera. <product dependent=""> lpcparkinglot, supported in the camera. lpcparkinglot, lpcparkinglot, "capability_image_c<n>_ lpcstreet * Only available when "capability_image_c<n>_ <product dependent=""> "capability_image_c<n>_ scenemode_support" is 1 scenemode_visibility_affe -, 0/7 When scene mode is enabled, some features may become malfunction or wingain:hidden:, <product dependent=""> minexposure:hidden:, affected functions are list here. 3dnr:unchanged:, or others The format is "Affect API name":"Policy":"Value" <x>: nonnegative integer - (disabled) : UI turns grey and users can't select it. <product dependent=""> "Policy" can be categorized into following groups: - (unchanged) : UI keeps the status as before and user can't change it. (hidden) : UI is hidden. (hidden) : UI is fixed to one selection or </product></x></product></n></product></n></n></product> | | | | |
| scenemode_supporttype visibility, noiseless, lpcparkinglot, lpcstreet 0/7 list all the scene mode which are supported in the camera. scenemode_visibility_affe . * Only available when "capability_image_c <n>_ scenemode_support" is 1 scenemode_visibility_affe -, minexposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode which are supported in the camera. <product dependent=""> -, minexposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. <product dependent=""> * The format is "Affect API name":"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged it. - (inden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></product></n> | scenemode_support | 0,1 | 0/7 | 0: Non-support scene mode |
| <pre><pre>cheater noiseless, lpcparkinglot, lpcstreet </pre><pre>* Only available when "capability_image_c<n>_ scenemode_visibility_affe ct minexposure:hidden:, <product dependent=""></product></n></pre> 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others</pre> The format is "Affect API name":"Policy":"Value" <x>: nonnegative integer <product dependent=""> "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></x> | | | | 1: Support scene mode |
| Ipcparkinglot, IpcstreetIpcparkinglot, Ipcstreet* Only available when "capability_image_c <n>_ scenemode_support" is 1scenemode_visibility_affe ct-, minexposure:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others0/7When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here.3dnr:unchanged:, or othersThe format is "Affect API name":"Policy":"Value"<x>: nonnegative integer <product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged): UI keeps the status as before and user can't change it. - (hidden) : UI is fixed to one selection or</product></x></n> | scenemode_supporttype | visibility, | 0/7 | list all the scene mode which are |
| Ipcstreet <product dependent="">* Only available when "capability_image_c<n>_ scenemode_support" is 1scenemode_visibility_affe ct-,0/7When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here.<product dependent="">mingain:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or othersaffected functions are list here.<d><dotsymbol{3dn:unchanged:, </dotsymbol{3dn:unchanged:, or othersThe format is "Affect API name":"Policy":"Value"<x>: nonnegative integer <product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged): UI keeps the status as before and user can't change it. - (hidden): UI is hidden. - (fixed) : UI is fixed to one selection or</product></x></d></product></n></product> | <product dependent=""></product> | noiseless, | | supported in the camera. |
| <product dependent="">"capability_image_c<n>_ scenemode_support" is 1scenemode_visibility_affe-,0/7When scene mode is enabled, some features may become malfunction or be forced to a given value. The wdrpro:unchanged:, 3dnr:unchanged:, or othersaffected functions are list here.3dnr:unchanged:, or othersThe format is "Affect API name":"Policy":"Value"<x>: nonnegative integer <product dependent="">"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></x></n></product> | | lpcparkinglot, | | |
| Image: second | | lpcstreet | | * Only available when |
| scenemode_visibility_affe ct minexposure:hidden:, <product dependent=""> 0/7 When scene mode is enabled, some features may become malfunction or be forced to a given value. The affected functions are list here. 3dnr:unchanged:, or others The format is "Affect API name":"Policy":"Value" <x>: nonnegative integer <product dependent=""> "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></x></product> | | <product dependent=""></product> | | "capability_image_c <n>_</n> |
| ctminexposure:hidden:,features may become malfunction or <product dependent="">mingain:hidden:,be forced to a given value. Thewdrpro:unchanged:,affected functions are list here.3dnr:unchanged:,or othersThe format is "Affect APIor othersmame":"Policy":"Value"<x>: nonnegative integer"Policy" can be categorized into<product dependent="">"Policy" can be categorized intofollowing groups:- (disabled) : UI turns grey and userscan't select it (unchanged) : UI keeps the status asbefore anduser can't change it (hidden) : UI is hidden (fixed) : UI is fixed to one selection or</product></x></product> | | | | scenemode_support" is 1 |
| ctminexposure:hidden:,features may become malfunction or <product dependent="">mingain:hidden:,be forced to a given value. Thewdrpro:unchanged:,affected functions are list here.3dnr:unchanged:,or othersThe format is "Affect APIor othersmame":"Policy":"Value"<x>: nonnegative integer"Policy" can be categorized into<product dependent="">"Policy" can be categorized intofollowing groups:- (disabled) : UI turns grey and userscan't select it (unchanged) : UI keeps the status asbefore anduser can't change it (hidden) : UI is hidden (fixed) : UI is fixed to one selection or</product></x></product> | scenemode visibility affe | -, | 0/7 | When scene mode is enabled, some |
| <pre><product dependent=""> mingain:hidden:, wdrpro:unchanged:, 3dnr:unchanged:, or others The format is "Affect API name":"Policy":"Value" <x>: nonnegative integer <product dependent=""> "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></x></product></pre> | | | , | |
| wdrpro:unchanged:, 3dnr:unchanged:, or othersaffected functions are list here./////////////////////////////////// | | - | | |
| 3dnr:unchanged:, The format is "Affect API or others The format is "Affect API <x>: nonnegative integer "Policy":"Value" <product dependent=""> "Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. . (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</product></x> | | | | |
| or othersThe format is "Affect API name": "Policy": "Value" <x>: nonnegative integer"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or</x> | | | | unceded functions are list field. |
| <x>: nonnegative integername":"Policy":"Value"<product dependent="">"Policy" can be categorized intofollowing groups:following groups:- (disabled) : UI turns grey and userscan't select it (unchanged) : UI keeps the status asbefore anduser can't change it (hidden) : UI is hidden (fixed) : UI is fixed to one selection or</product></x> | | | | The formet is "Affect ADI |
| <pre><x>: nonnegative integer <pre>/product dependent></pre> <pre>"Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it (unchanged) : UI keeps the status as before and user can't change it (hidden) : UI is hidden (fixed) : UI is fixed to one selection or</pre></x></pre> | | or others | | |
| <pre><pre><pre><pre><pre>Policy" can be categorized into following groups: - (disabled) : UI turns grey and users can't select it (unchanged) : UI keeps the status as before and user can't change it (hidden) : UI is hidden (fixed) : UI is fixed to one selection or</pre></pre></pre></pre></pre> | | | | name":"Policy":"Value" |
| following groups: - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | |
| - (disabled) : UI turns grey and users can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | <product dependent=""></product> | | "Policy" can be categorized into |
| can't select it. - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | following groups: |
| - (unchanged) : UI keeps the status as before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | - (disabled) : UI turns grey and users |
| before and user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | can't select it. |
| user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | - (unchanged) : UI keeps the status as |
| - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | before and |
| - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or | | | | user can't change it. |
| - (fixed) : UI is fixed to one selection or | | | | - (hidden) : UI is hidden. |
| | | | | |
| | | | | value. |

| | | | - (ranged) : UI is fixed to multiple |
|----------------------------------|----------------------------------|-----|---|
| | | | selections or values. |
| | | | |
| | | | "Affect API name" can be described in |
| | | | hierarchy, such as |
| | | | "exposurewin.mode.blc:disabled:" |
| | | | which means blc exposure window is |
| | | | disabled. API name can be one word as |
| | | | well, such as "exposurelevel:fixed:6" |
| | | | which means exposurelevel is fixed to |
| | | | level 6. |
| | | | "Value" can be a nonnegative integer |
| | | | or NULL. |
| | | | "-" means no feature is affected. |
| | | | * Only available when visibility is listed |
| | | | in "capability_image_c <n>_</n> |
| | | | scenemode_supporttype" and |
| | | | "capability_image_c <n>_</n> |
| | | | scenemode_support" is 1 |
| scenemode_noiseless_aff | -, | 0/7 | When scene mode is enabled, some |
| ect | minexposure:hidden:, | | features may become malfunction or |
| <product dependent=""></product> | mingain:hidden:, | | be forced to a given value. The |
| | wdrpro:unchanged:, | | affected functions are list here. |
| | 3dnr:unchanged:, | | |
| | or others | | The format is "Affect API |
| | | | name":"Policy":"Value" |
| | <x>: nonnegative integer</x> | | |
| | <product dependent=""></product> | | "Policy" can be categorized into |
| | | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | | | can't select it. |
| | | | - (unchanged) : UI keeps the status as |
| | | | before and |
| | | | user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection or |
| | | | value. |
| | | | - (ranged) : UI is fixed to multiple |

| | | | selections or values. |
|----------------------------------|----------------------------------|-----|--|
| | | | |
| | | | "Affect API name" can be described in |
| | | | hierarchy, such as |
| | | | "exposurewin.mode.blc:disabled:" |
| | | | which means blc exposure window is |
| | | | disabled. API name can be one word as |
| | | | well, such as "exposurelevel:fixed:6" |
| | | | which means exposurelevel is fixed to |
| | | | level 6. |
| | | | "Value" can be a nonnegative integer |
| | | | or NULL. |
| | | | |
| | | | "-" means no feature is affected. |
| | | | * Only available when visibility is listed |
| | | | in "capability_image_c <n>_</n> |
| | | | scenemode_supporttype " and |
| | | | "capability_image_c <n>_</n> |
| | | | scenemode_support" is 1 |
| scenemode_lpcparkinglot | -, | 0/7 | When scene mode is enabled, some |
| _affect | minexposure:hidden:, | | features may become malfunction or |
| <product dependent=""></product> | mingain:hidden:, | | be forced to a given value. The |
| | wdrpro:unchanged:, | | affected functions are list here. |
| | 3dnr:unchanged:, | | |
| | or others | | The format is "Affect API |
| | | | name":"Policy":"Value" |
| | <x>: nonnegative integer</x> | | |
| | <product dependent=""></product> | | "Policy" can be categorized into |
| | | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | | | can't select it. |
| | | | - (unchanged) : UI keeps the status as |
| | | | before and |
| | | | user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection or |
| | | | value. |
| | | | - (ranged) : UI is fixed to multiple |
| | | | selections or values. |
| | | | user can't change it. - (hidden) : UI is hidden. - (fixed) : UI is fixed to one selection or value. - (ranged) : UI is fixed to multiple |

| | | | "Affect API name" can be described in hierarchy, such as "exposurewin.mode.blc:disabled:" which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6. |
|----------------------------------|----------------------------------|-----|--|
| | | | "Value" can be a nonnegative integer or NULL. |
| | | | <pre>"-" means no feature is affected. * Only available when visibility is listed in "capability_image_c<n>_ scenemode_supporttype " and "capability_image_c<n>_ scenemode_support" is 1</n></n></pre> |
| scenemode_lpcstreet_aff | _ | 0/7 | When scene mode is enabled, some |
| | -, | 0/7 | |
| ect | minexposure:hidden:, | | features may become malfunction or |
| <product dependent=""></product> | mingain:hidden:, | | be forced to a given value. The |
| | wdrpro:unchanged:, | | affected functions are list here. |
| | 3dnr:unchanged:,or others | | |
| | | | The format is "Affect API |
| | <x>: nonnegative integer</x> | | name":"Policy":"Value" |
| | <product dependent=""></product> | | |
| | | | "Policy" can be categorized into |
| | | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | | | can't select it. |
| | | | - (unchanged) : UI keeps the status as |
| | | | before and |
| | | | user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection or |
| | | | value. |
| | | | - (ranged) : UI is fixed to multiple |
| | | | selections or values. |
| | | | |
| | 1 | 1 | |

| *Affect API name" can be described in hierarchy, such as "exposurewin.mode.bit:disabled." which means bite exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means bite exposure window is level 6.*Value" can be a nonnegative integer or NULL."Value" can be a nonnegative integer or NULL.**" means no feature is affected. * Only available when visibility is listed in "capability_image_c <n>_ scenemode_supportype " and "capability_image_c<n>_ scenemode_supportype " and "capability_image_c<n>_ scenemode_support" is 1wbmodeauto, manual, rbgain, - visibility is listed in "capability_image_c<n>_ scenemode_support" is 1instypepiris, rbgain, - visibility is listed in rbgain, - visibility is listed in rbgain, - visibility is listed in rbgain, - visibility is listed in rbgain, - visibility is listed in rcapability_image_c<n>_ scenemode_support" is 1wbmodeauto, manual, rbgain, - visibility is listed in rbgain, regen risi in rbgain, - visibility is listed in rbgain, regen visibility is listed in rister in the blance is not supported.instypepiris, regen piris, P-Inis risting in risting in</n></n></n></n></n> | | | | |
|--|---------------------|---------|-----|---------------------------------------|
| Image: series of the series | | | | "Affect API name" can be described in |
| which means blc exposure window is disabled. API name can be one word as well, such as "exposurelevel:fixed:6" which means exposurelevel is fixed to level 6.'Value" can be a nonnegative integer or NULL.'''' means no feature is affected. * Only available when visibility is listed in "capability_image_c <n>_ scenemode_support" is 1wbmodeauto, manual, rbgain, - regain, - in0/7Available white balance mode. *"" means white balance mode. *"" means white balance mode. *"" is no Inis control support 's inis diris, '-'''' is in chris control support *" is no inis control support *" is no inis control support *"" is no inis control support *" is no inis control support *" is is voeice control. *" is is supported. *" is no inis control support *" is no inis control. *" is support exposure control. *" is support exposure control. *" is support exposure control. *" is support exposure control. *" is no inis control. *" is support exposure control. *" is no inis control.<br< td=""><td></td><td></td><td></td><td>hierarchy, such as</td></br<></n> | | | | hierarchy, such as |
| Image: series of the series | | | | "exposurewin.mode.blc:disabled:" |
| well, such as "exposurelevel: fixed: 6" which means exposurelevel is fixed to level 6."Value" can be a nonnegative integer or NULL."-" means no feature is affected. " Only available when visibility is listed in "capability_image_c <n>_ scenemode_supporttype " and "capability_image_c<n>_ scenemode_supporttype " and "capability_image_c<n>_ scenemode_support rypain, regain,<b< td=""><td></td><td></td><td></td><td>which means blc exposure window is</td></b<></n></n></n> | | | | which means blc exposure window is |
| kinkkinkwhich means exposurelevel is fixed to level 6."Value" can be a nonnegative integer or NULL."." means no feature is affected. * Only available when visibility is listed in "capability_image_c <n>_ scenemode_support reaposurelevel is 1wbmodeauto, manual, rbgain, -0/7Available white balance is not supported.irstypepiris, dciris, -0/7Indicate iris type. ""indicate iris type. ""indicate iris type.iristypepiris, dciris, -0/7Indicate iris type. ""indicate iris type. "piris": P.Iris "dciris": DC-Iris """: No Iris control supportexposure_mode0,10/70. Nor-support exposure control. 1: Support exposure control. 1: Videoin_c<n>_exposure_mode"=0, this must be set to "."</n></n> | | | | disabled. API name can be one word as |
| Image: series of the series | | | | well, such as "exposurelevel:fixed:6" |
| Image: series of the series | | | | which means exposurelevel is fixed to |
| Image: series of the series | | | | level 6. |
| Image: series of the series | | | | "Value" can be a nonnegative integer |
| Image: series of the series | | | | or NULL. |
| Image: series of the series | | | | "-" means no feature is affected. |
| Image: series of the series | | | | * Only available when |
| Image: series of the series | | | | visibility is listed in |
| Image: series of the series | | | | "capability_image_c <n>_</n> |
| Image: series of the series | | | | scenemode_supporttype " |
| Image: sequence of the sequenc | | | | and |
| wbmodeauto, manual, rbgain, -0/7Available white balance mode. "-" means white balance is not supported. "-" means white balance is not supported.iristypepiris, dciris, - - -0/7Indicate iris type. "piris": P-Iris "dciris": DC-Iris "-": No Iris control support * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 2: When "exposure_mode"=0, this must be set to "-". | | | | "capability_image_c <n>_</n> |
| nanual, rbgain, -"-" means white balance is not supported.iristypepiris, dciris, - - - / dciris, - - - -0/7Indicate iris type. "piris": P-Iris "dciris": DC-Iris "-": No Iris control support * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 2: Support exposur | | | | scenemode_support" is 1 |
| rbgan, -supported.iristypepiris, dciris, - -0/7Indicate iris type. "piris": P-Iris "dciris": DC-Iris "-": No Iris control supportexposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 2: Support exposure control | wbmode | auto, | 0/7 | Available white balance mode. |
| iristypepiris, dciris, - - - - - - -0/7Indicate iris type. "piris": P-Iris "dciris": DC-Iris "-": No Iris control support * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 2: when "exposure_mode"=0, this must be set to "-". | | manual, | | "-" means white balance is not |
| dciris, - - - -"piris": P-Iris "dciris": DC-Iris "-": No Iris control support * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 1: Support exposure control. 1: Support exposure control. 1: Support exposure level" * When "exposure_level" * When "exposure_level" | | rbgain, | | supported. |
| dciris, - - - -"piris": P-Iris "dciris": DC-Iris "-": No Iris control support * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 1: Support exposure control. 1: Support exposure control. 1: Support exposure level" * When "exposure_level" * When "exposure_level" | | - | | |
| <th< td=""><td>iristype</td><td>piris,</td><td>0/7</td><td>Indicate iris type.</td></th<> | iristype | piris, | 0/7 | Indicate iris type. |
| Image: series of the series | | dciris, | | "piris": P-Iris |
| * Note: For some cameras, this value may be varied depending on mounted lens.exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control. 1: Support exposure control.exposure_levelrange-, "0,12"0/7Available range for "videoin_c <n>_exposurelevel" * When "exposure_mode"=0, this must be set to "-".</n> | | - | | "dciris": DC-Iris |
| Image: series of the series | | | | "-": No Iris control support |
| Image: series of the series | | | | * Note: For some cameras, this value |
| exposure_mode0,10/70: Non-support exposure control. 1: Support exposure control.exposure_levelrange-, "0,12"0/7Available range for "videoin_c <n>_exposurelevel" * When "exposure_mode"=0, this must be set to "-".</n> | | | | may be varied depending on mounted |
| exposure_levelrange -, 0/7 Available range for "0,12" "videoin_c <n>_exposurelevel" * When "exposure_mode"=0, this must be set to "-".</n> | | | | lens. |
| exposure_levelrange -, 0/7 Available range for "0,12" "videoin_c <n>_exposurelevel" * When "exposure_mode"=0, this must be set to "-".</n> | exposure_mode | 0,1 | 0/7 | 0: Non-support exposure control. |
| "0,12" "videoin_c <n>_exposurelevel" * When "exposure_mode"=0, this must be set to "-".</n> | | | | 1: Support exposure control. |
| * When "exposure_mode"=0, this must be set to "-". | exposure_levelrange | -, | 0/7 | Available range for |
| must be set to "-". | | "0,12" | | "videoin_c <n>_exposurelevel"</n> |
| | | | | * When "exposure_mode"=0, this |
| exposure_winmode auto, 0/7 Available options for | | | | must be set to "-". |
| | exposure_winmode | auto, | 0/7 | Available options for |

| custom, bic, "exposurewin_c <n>_mode" bic, - """ means group: exposurewin is not supported. exposure_wintype inclusive, 0/7 The supported exposure window is the target area of exposure window is the target area of exposure control. exposure_windomain qvga, px, std, - 0/7 The domain to set an exposure window is the target area of exposure control. exposure_windomain qvga, px, std, - 0/7 The domain to set an exposure window is to mitted by exposure control. exposure_windomain qvga, px, std, - 0/7 The domain to set an exposure window. exposure_windomain qvga, px, std, - 0/7 The domain to set an exposure window. exposure_windomain qvga, px, std, - 0/7 Indicate the number of custom exitow window. exposure_window qvga, px, std, - 0/7 Indicate the number of custom exitow windows. exposure_window qvga, px, std, - 0/7 Indicate the number of custom exitow window. exposure_window qvsaitable total range for NTSC analog output * 0/19 available total range for NTSC analog output * exposure_mine_mine_mine_mine_mine_mine_mine_min</n> | 1 | | | 1 |
|--|--------------------------|--|-----|---|
| | | custom, | | "exposurewin_c <n>_mode"</n> |
| supported. * When exposure_mode="0", this must be set to "-".exposure_wintypeinclusive, exclusive, - - -0/7The supported exposure window type. inclusive: The image inside a window is the target area of exposure control. exclusive: The image inside a window is omitted by exposure control. - > Not supported.exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -> Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. in o " custom" is listed in "exposure_windows.exposure_minter_mi</positive> | | blc, | | |
| exposure_wintypeinclusive, exclusive, - exclusive, - wintypeinclusive, exclusive, - wintype0/7 The supported exposure window type, inclusive: The image inside a window is omitted by exposure control. exclusive: The image inside a window is omitted by exposure control. -: Not supported.exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. + If no " custom" is listed in "exposure_windows. + If no</positive> | | - | | * "-" means group: exposurewin is not |
| Indext in the set to "-".Indusive, exclusive, - -Indusive, exclusive, - -Indusive, exclusive, - -Indusive, exclusive: The image inside a window is the target area of exposure control. exclusive: The image inside a window is contited by exposure control. - - -Indusive: The image inside a window is the target area of exposure control. exclusive: The image inside a window is contited by exposure control. - - - -exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. -: Not supported.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output - 0niy available when [httpwersion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output - 0niy available when [httpwersion] >= 0301aexposure_maxrange"1,32000", - , - , -</positive></positive></positive> | | | | supported. |
| exposure_wintypeinclusive, exclusive, -0/7The supported exposure window type. inclusive: The image inside a window is the target area of exposure control. exclusive: The image inside a window is omitted by exposure control. -: Not supported.exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_notsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", ", o rothers ", 1,32000", ", ", o rothers <pre>0/7Available total range for TSL analog output * Only available when [httpversion] >= 0301a</pre></positive></positive> | | | | * When exposure_mode="0", this |
| exclusive, -inclusive: The image inside a window is the target area of exposure control. exclusive: The image inside a window is omitted by exposure control. -: Not supported.exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", ", ", ", ", ", ", ", ", ", ", ", ", "</positive></positive> | | | | must be set to "-". |
| the target area of exposure control. exclusive: The image inside a window is omitted by exposure control. -: Not supported.exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", , or others erpoduct dependent>0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", , , or others erpoduct dependent>0/7Available total range for PAL analog output * Only available when [httpversion] >= 15 ~ 1/320005 "1,8000" => 15 ~ 1/32005 "1,8000" => 15 ~ 1/32005</positive></positive></positive> | exposure_wintype | inclusive, | 0/7 | The supported exposure window type. |
| exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", ", ", ", ", ", ", ", ", ", ", ", ", "</positive></positive> | | exclusive, | | inclusive: The image inside a window is |
| exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion]>= 0301aexposure_naxrange"1,32000", ", Sto00", ", Sto00",<br< td=""><td></td><td>-</td><td></td><td>the target area of exposure control.</td></br<></positive></positive> | | - | | the target area of exposure control. |
| exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_windows. * If no " custom" is listed in "exposure_windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion]>= 0301aexposure_naxrange"1,32000", ", Sto00", ", Sto00",<br< td=""><td></td><td></td><td></td><td>exclusive: The image inside a window</td></br<></positive></positive> | | | | exclusive: The image inside a window |
| exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_winmode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion]>= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion]>= 0301aexposure_maxrange"1,32000", ", ", ", ", ", ", ", ", ", ", ", ", ", "</positive></positive></positive> | | | | _ |
| exposure_windomainqvga, px, std, -0/7The domain to set an exposure window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure_windows. * If no " custom" is listed in "exposure_winmode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", -, or others <pre>"1,8000" => 1s ~ 1/32000s * 1,8000" => 1s ~ 1/3200s * 1,8000" => 1s ~ 1/3200s</pre></positive></positive></positive> | | | | |
| window.window.qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows.exposure_minsc_totalrange0, <positive integer="">0/7Indicate the number of custom exposure_winnode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", -, or others < _r, or others < _r, or others < _r, or others0/7Available range for * 1,32000" => 1s ~ 1/32000s * 1,8000" => 1s ~ 1/3200s * 1,8000" => 1s ~ 1/3200s</positive></positive></positive></positive> | exposure windomain | gvga, px. std | 0/7 | |
| Image: space s | | | -,- | |
| kte whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows.exposure_minnum0, <positive integer="">0/7Indicate the number of custom exposure windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", , , , , , , , , , , , , , , , , , ,</positive></positive></positive></positive> | | | | |
| Image: space s | | | | |
| Image: series of the series | | | | _ |
| Image: stat: A normalized 0~9999 range. : Not supported.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows.# If no " custom" is listed in "exposure_winmode", this should be 0.* If no " custom" is listed in "exposure_winmode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", "1,800", ", or others erso0/7Available total range for "1,32000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s</positive></positive></positive> | | | | |
| exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows.exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", "1,8000", ", o others0/7Available range for "Videoin_c<n>_ maxexposure" "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/8000s etc.</n></positive></positive></positive></positive> | | | | |
| exposure_winnum0, <positive integer="">0/7Indicate the number of custom exposure windows. * If no " custom" is listed in "exposure_winmode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", r, or others ergoduct dependent>0/7Available range for * 1,8000" => 1s ~ 1/32000s * 1,8000" => 1s ~ 1/32000s * 1,8000s * etc.</positive></positive></positive> | | | | _ |
| LineLineLineexposure windows.exposure_windows.* If no " custom" is listed in "exposure_winmode", this should be 0.exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", ", , , , , , , , , , , , , , , , , , ,</positive></positive> | | 2 D 111 D 1 | | |
| Image: series of the series | exposure_winnum | 0, <positive integer=""></positive> | 0/7 | |
| exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for "1,8000", -, r,<br <="" td=""/><td></td><td></td><td></td><td>exposure windows.</td></positive></positive></positive> | | | | exposure windows. |
| exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for "1,8000", -, r,<br <="" td=""/><td></td><td></td><td></td><td></td></positive></br></positive></positive> | | | | |
| Image: construct of the served of the serv | | | | |
| exposure_ntsc_totalrangeA list of <positive integer="">0/7Available total range for NTSC analog output * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available total range for vulgavailable when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for "videoin_c<n>_maxexposure" "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/8000s etc.</n></br></positive></positive> | | | | |
| A list of <positive integer="">0/7Available total range for PAL analog outputexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog outputexposure_maxrange"1,32000",101101exposure_maxrange"1,32000",0/7Available range for''', '''''''11,32000",''''-, ''''''''''''11,32000'''or others'''''''''''''-, ''''''''''''or others''''''''''-, '''''''''''''''-, '''''''''''''''''or others'''''''''''''''-, ''''''''''''''''''''''''''''''''''''''</positive></positive> | | | | |
| * Only available when [httpversion] >= 0301aexposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for "videoin_c<n>_maxexposure" "1,8000", -, or others or others <pre>0/7Available range for "videoin_c<n>_maxexposure" "1,8000" => 1s ~ 1/32000s "1,8000s etc.</n></pre></n></positive> | exposure_ntsc_totalrange | A list of <positive integer=""></positive> | 0/7 | Available total range for NTSC analog |
| Image: sposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for "videoin_c<n>_maxexposure" "1,8000",-, or others-, or others0/7Available range for "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/8000s etc.</n></positive> | | | | output |
| exposure_pal_totalrangeA list of <positive integer="">0/7Available total range for PAL analog output * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000", "1,8000", -, or others <product dependent="">0/7Available range for "videoin_c<n>_maxexposure" "1,32000" => 1s ~ 1/32000s it available when "1,8000" => 1s ~ 1/8000s etc.</n></product></positive> | | | | * Only available when |
| exposure_maxrange"1,32000",0/7Available range for"1,8000","'iteoin_c <n>_maxexposure"-,"1,32000","'iteoin_c<n>_maxexposure"or othersor others"1,8000" => 1s ~ 1/32000sor othersetc.</n></n> | | | | [httpversion] >= 0301a |
| * Only available when [httpversion] >= 0301aexposure_maxrange"1,32000",0/7Available range for"1,8000","videoin_c <n>_maxexposure"-,-,"1,32000" => 1s ~ 1/32000sor othersor others"1,8000" => 1s ~ 1/8000s<product dependent="">etc.</product></n> | exposure_pal_totalrange | A list of <positive integer=""></positive> | 0/7 | Available total range for PAL analog |
| Image Image <th< td=""><td></td><td></td><td></td><td>output</td></th<> | | | | output |
| exposure_maxrange "1,32000", 0/7 Available range for "1,8000", "videoin_c <n>_maxexposure" -, "1,32000" => 1s ~ 1/32000s or others "1,8000" => 1s ~ 1/8000s <product dependent=""> etc.</product></n> | | | | * Only available when |
| "1,8000", "videoin_c <n>_maxexposure" -, "1,32000" => 1s ~ 1/32000s or others "1,8000" => 1s ~ 1/8000s <product dependent=""> etc.</product></n> | | | | [httpversion] >= 0301a |
| -, "1,32000" => 1s ~ 1/32000s or others "1,8000" => 1s ~ 1/8000s <product dependent=""> etc.</product> | exposure_maxrange | "1,32000", | 0/7 | Available range for |
| or others"1,8000" => 1s ~ 1/8000s <product dependent="">etc.</product> | | "1,8000", | | "videoin_c <n>_maxexposure"</n> |
| <product dependent=""> etc.</product> | | -, | | "1,32000" => 1s ~ 1/32000s |
| | | or others | | "1,8000" => 1s ~ 1/8000s |
| | | <product dependent=""></product> | | etc. |
| | | | | "-" means maximum exposure time is |

| exposure_minrange"1,32000", "1,8000", or others cproduct dependent>0/7Available range for "videoin_c <n>_ mix be set to ".".exposure_minrange"1,8000", or others cproduct dependent>0/7Available range for "videoin_c<n>_ means minimum exposure" "1,8000" => 1s ~ 1/8000s etc. " "means minimum exposure time is not available.privacymask_wintyperectangle, polygon0/7The supported window type. polygon shape. rectangle: The motion window is a polygon shape. rectangle: The motion window is a rectangle: The motion window is a rectangle: Shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", *0/7Available range for "videoin_c<n>_ means "videoin_c<n>_ maxgain" is not available.agc_mingain"0,100", *0/7Available range for "videoin_c<n>_ mingain" is not available.filckerless0,10/7Available range for "videoin_c<n>_ maxgain" is not available.filckerless0,10/7Windible range for "videoin_c<n>_ means "videoin_c<n>_ maxgain" is not available.</n></n></n></n></n></n></n></n> | | | | not available. |
|---|-----------------------|----------------------------------|-----|------------------------------------|
| Image: series in the series | | | | |
| exposure_minrange"1,32000", "1,8000", -, or others0/7Available range for "videoin_c <n>_minexposure" "1,32000" => 1s ~ 1/32000s 1,8000" => 1s ~ 1/32000s etc. "-, means minimum exposure time is not available. " When "exposure_mode"=0, this must be set to "-".privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle shape.privacymask_windomainqvga, px, std, -0/7The supported window type. polygon shape. rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" "0,100", "-"gic_mingain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" is not available.agc_mingain0,100", "-"0/7Available range for "videoin_c<n>_maxgain" is not available.flickerless0,10/70/100 percent "-" "sideoin_c<n>_mangain" is not available.flickerless0,10/70/100 percent "-" "sideoin_c<n>_mangain" is not available.</n></n></n></n></n></n> | | | | * When "exposure_mode"=0, this |
| "1,8000", ., or others"Videoin_<< ., or others"Videoin_<<<<>> ., means minimum exposure" "1,8000" => 1s ~ 1/32000s etc. "" means minimum exposure time is not available. # When "exposure_mode"=0, this must be set to "-".privacymask_wintyperectangle, polygon polygon0/7The supported window type. polygon; The motion window is a rectangle The motion window is a rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. (qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "."0/7Available range for "videoin_< "." means "wideoin_< <s>maxgain" "0,100", "."agc_mingain"0,100", "."0/7Available range for "videoin_<<s>maxgain" "0,100" => 0-100 percent "." means "videoin_<<s>maxgain" "0,100" => 0-100 percent "." me</s></s></s></s></s></s></s></s></s></s></s></s></s></s></s></s> | | | | must be set to "-". |
| -, or others <product dependent="">-, or others <product dependent="">-, i,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s "1,8000" => 1s ~ 1/32000s etc. "," means minimum exposure time is not available. * When "exposure_mode"=0, this must be set to ".".privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle: The motion window is a rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "."0/7Available range for "." means "videoin_c<n>_maxgain" "0,100" => 0-100 percent "." means "videoin_c<n>_mingain" " not available.flickerless0,10/7Available range for "videoin_c<n>_mingain" is not available.flickerless0,10/7Videoin_c<n>_mingain" " not available.flickerless0,10/7Videoin_c<n>_mingain" is not available.</n></n></n></n></n></n></n></n></n></n></n></product></product> | exposure_minrange | "1,32000", | 0/7 | Available range for |
| or others <product dependent="">"1,8000" => 1s ~ 1/8000s etc. "-" means minimum exposure time is not available. * When "exposure_mode"=0, this must be set to "-".privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle: The motion window is a rectangle: The motion window is a rectangle: The motion window. qvga: a 320x240 range to represent the whole image. px: Locate a window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" '0,100" => 0~100 percent "-" "wideoin_c<n>_maxgain" '0,100" => 0~100 percent "-" "wideoin_c<n>_maxgain" '0,100" => 0,100 percent "-" "images "videoin_c<n>_maxgain" '0,100" => 0,100 percent "-" "wideoin_c<n>_maxgain" '0,100" => 0,100 percent "-" "means "videoin_c<n>_mingain" '0,100" => 0,100 percent "-" means "videoin_c<n>_mingain" '0,100" => 0,100 percent "-" "means "videoin_c<n>_mingain" '1,010" => 0,100 percent '-" means "videoin_c<n>_mingain" ''." means "videoin_c<n>_mingain ''." mea</n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></product> | | "1,8000", | | "videoin_c <n>_minexposure"</n> |
| ercduct dependent>erc. "-" means minimum exposure time is not available. * When "exposure_mode"=0, this must be set to "-".privacymask_wintyperectangle, polygon0/7The supported window type. polygon shape. rectangle: The motion window is a polygon shape. rectangle: The motion window is a rectangle: The motion window is a rectangle | | -, | | "1,32000" => 1s ~ 1/32000s |
| Image: series of the series | | or others | | "1,8000" => 1s ~ 1/8000s |
| Image: series of the series | | <product dependent=""></product> | | etc. |
| Image: series of the series | | | | "-" means minimum exposure time is |
| Image: set to "-".Image: set to "-".privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c <n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_mingain" is not available.flickerless0,10/7Available range for "videoin_c<n>_mingain" ion tavailable.flickerless0,10/7O/7flickerless0,10/70: Non-support flickerless i: Support flickerless is enabled, some</n></n></n> | | | | not available. |
| Image: set to "-".Image: set to "-".privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c <n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_mingain" is not available.flickerless0,10/7Available range for "videoin_c<n>_mingain" ion tavailable.flickerless0,10/7O/7flickerless0,10/70: Non-support flickerless i: Support flickerless is enabled, some</n></n></n> | | | | * When "exposure_mode"=0, this |
| privacymask_wintyperectangle, polygon0/7The supported window type. polygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle shape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "."0/7Available range for "videoin_c <n>maxgain" "0,100", "."goc_mingain"0,100", "."0/7Available range for "videoin_c<n>maxgain" "0,100" => 0~100 percent "." means "videoin_c<n>maxgain" "0,100" => 0.100 percent "." means "videoin_c<n>maxgain" "0,100" => 0.100 percent "." means "videoin_c<n>maxgain" "0,100" => 0.100 percent "." means "videoin_c<n>mingain" "0,100" => 0.100 percent "." means "videoin_c<n>mingain" "0,100" => 0.100 percent "." means "videoin_c<n>mingain" "0,100" => 0.100 percent "." means "videoin_c<n>mingain" "Suidouin_c<n>mingain" "Suidouin_c<n>mingain" "Suidouin_c<n>mingain" "Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain" Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n>mingain Suidouin_c<n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n></n> | | | | must be set to "-". |
| polygonpolygonpolygon: The motion window is a polygon shape. rectangle: The motion window is a rectangle: The motion window. qreat a stape.privacymask_windomainqvga, px, std, -0/7The domain to set an window. qreat: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "."0/7Available range for "videoin_c <n>_maxgain" "0,100", => 0~100 percent "." means "videoin_c<n>_maxgain" "0,100" => 0/100 percent "." means "videoin_c<n>_maxgain" "0,100" => 0/100 percent "." means "videoin_c<n>_mingain" "0,100" => 0/100 percent "." means "videoin_c<n>_mingain" "." in the available.flickerless0,10/70.100 recent "." means "videoin_c<n>_mingain" "." in the available.flickerless0,10/70.100 recent "." in the available.</n></n></n></n></n></n></n></n></n></n> | privacymask_wintype | rectangle, | 0/7 | |
| Image: Second | | | | |
| Image: set of the | | | | |
| Image: section of the section of th | | | | |
| privacymask_windomainqvga, px, std, -0/7The domain to set an window. qvga: a 320x240 range to represent the whole image. px: Locate a window in the image with pixels. std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c <n>_maxgain" "0,100", solution "-" means "videoin_c<n>_maxgain" "0,100", "-"agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" "0,100" => 0~100 percent "-" means "videoin_c<n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_mingain" "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" " \$0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some</n></n></n></n></n></n></n></n></n></n></n></n></n> | | | | - |
| And and a seriesand a seri | privacymask windomain | gyga, px, std, - | 0/7 | |
| Image: Series of the series | | | | gvga: a 320x240 range to represent |
| Image: Series of the series | | | | |
| pixels.pixels.agc_maxgain"0,100",0/7Available range for "videoin_c <n>_maxgain" "0,100" => 0~100 percent "o,100" => 0~100 percent "-" means "videoin_c<n>_maxgain" is not available.agc_mingain"0,100",0/7Available range for "videoin_c<n>_maxgain" is not available.agc_mingain"0,100",0/7Available range for "videoin_c<n>_mingain" in available.flickerless0,10/7Ivaniable range for "videoin_c<n>_mingain" in available.flickerless0,10/7Ivaniable.flickerless0,10/7Ven flickerless i support flickerless i support flickerless</n></n></n></n></n></n></n></n></n> | | | | _ |
| std: A normalized 0~9999 range. -: Not supported.agc_maxgain"0,100", "-"0/7Available range for "videoin_c <n>_maxgain" "0,100" => 0~100 percent "-" means "videoin_c<n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" is not available.flickerless0,10/7O/7O: Non-support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some</n></n></n> | | | | |
| Image in the second s | | | | |
| agc_maxgain"0,100", "-"0/7Available range for "videoin_c <n>_maxgain" "0,100" => 0~100 percent "-" means "videoin_c<n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_maxgain" is not available.agc_mingain"0,100", "-"0/7Available range for "videoin_c<n>_mingain" "o,100" => 0~100 percent "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerless 1: Support flickerless is enabled, some</n></n></n></n></n> | | | | - |
| "-""videoin_c <n>_maxgain" "0,100" => 0~100 percent "-" means "videoin_c<n>_maxgain" is not available.agc_mingain"0,100",0/7Available range for "videoin_c<n>_mingain" "0,100" => 0~100 percent "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" io,100" => 0~100 percent "-" means "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some</n></n></n></n></n></n></n></n></n> | agc maxgain | "0,100", | 0/7 | |
| hereSector< | | | | - |
| Image: Section of the section of th | | | | |
| agc_mingain"0,100", "-"0/7Available range for "videoin_c <n>_mingain" "0,100" => 0~100 percent "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerless 1: Support flickerless is enabled, some</n></n> | | | | |
| "-""videoin_c <n>_mingain" "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some</n></n> | | | | not available. |
| "-""videoin_c <n>_mingain" "0,100" => 0~100 percent "-" means "videoin_c<n>_mingain" is not available.flickerless0,10/70: Non-support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some</n></n> | agc_mingain | "0,100", | 0/7 | |
| herehe | | | | - |
| flickerless0,10/70: Non-support flickerless 1: Support flickerlessflickerlessaffect-,0/7When flickerless is enabled, some | | | | |
| Image: model Image: model Image: model flickerless 0,1 0/7 0: Non-support flickerless flickerlessaffect -, 0/7 When flickerless is enabled, some | | | | |
| flickerless 0,1 0/7 0: Non-support flickerless flickerlessaffect -, 0/7 When flickerless is enabled, some | | | | |
| flickerlessaffect -, 0/7 When flickerless is enabled, some | flickerless | 0,1 | 0/7 | |
| flickerlessaffect -, 0/7 When flickerless is enabled, some | | | -, | |
| | flickerlessaffect | -, | 0/7 | |
| | | , minexposure:hidden:, | -,- | features may become malfunction or |

| | mingain:hidden:, | | be forced to a given value. The |
|----------------|----------------------------------|-----|---|
| | or others | | affected functions are list here. |
| | <x>: nonnegative integer</x> | | The format is "Affect API |
| | <product dependent=""></product> | | name":"Policy":"Value" |
| | | | |
| | | | "Policy" can be categorized into |
| | | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | | | can't select it. |
| | | | - (unchanged) : UI keeps the status as |
| | | | before and |
| | | | user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection of |
| | | | value. |
| | | | - (ranged) : UI is fixed to multiple |
| | | | selections or values. |
| | | | "Affect API name" can be described ir |
| | | | hierarchy, such as |
| | | | "exposurewin.mode.blc:disabled:" |
| | | | which means blc exposure window is |
| | | | disabled. API name can be one word as |
| | | | well, such as "exposurelevel:fixed:6" |
| | | | which means exposurelevel is fixed to |
| | | | level 6. |
| | | | "Value" can be a nonnegative integer |
| | | | or NULL. |
| | | | |
| | | | "-" means no feature is affected. |
| | | | * When "flickerless" = 0, this must be |
| | | | n_n |
| defog_mode | 0,1 | 0/7 | 0: Non-support defog |
| | | | 1: Support defog |
| defog_strength | 0, 1 | 0/7 | 0: Non-support tuning strength of |
| | | | defog |
| | | | 1: Support tuning strength of defog |

| | | | * If |
|--------------------|----------------------------------|-----|--|
| | | | |
| | | | "capability_image_c <n>_defog_mode</n> |
| | | | "=1, this may be either 0 or 1. |
| defog_supportlevel | <positive integer=""></positive> | 0/7 | The value indicate the support |
| | | | strength level of defog. |
| defog_affect | -, | 0/7 | When defog is enabled, some features |
| | wdrpro:unchanged:, | | may become malfunction or be forced |
| | or others | | to a given value. The affected |
| | | | functions are list here. |
| | <x>: nonnegative integer</x> | | |
| | <product dependent=""></product> | | The format is "Affect API |
| | | | name":"Policy":"Value" |
| | | | "Policy" can be categorized into |
| | | | following groups: |
| | | | - (disabled) : UI turns grey and users |
| | | | can't select it. |
| | | | |
| | | | - (unchanged) : UI keeps the status as before and |
| | | | |
| | | | user can't change it. |
| | | | - (hidden) : UI is hidden. |
| | | | - (fixed) : UI is fixed to one selection or value. |
| | | | - (ranged) : UI is fixed to multiple |
| | | | selections or values. |
| | | | "Affect API name" can be described in |
| | | | hierarchy, such as |
| | | | "exposurewin.mode.blc:disabled:" |
| | | | which means blc exposure window is |
| | | | disabled. API name can be one word as |
| | | | |
| | | | well, such as "exposurelevel:fixed:6" |
| | | | which means exposurelevel is fixed to |
| | | | level 6. |
| | | | "Value" can be a nonnegative integer |
| | | | or NULL. |
| | | | "-" means no feature is affected. |
| | | | - means no reature is affected. |

| | | | * When "defog" = 0, this must be "-" |
|---------------------------|----------------------------------|-----|---|
| aespeed | 0,1 | 0/7 | 0: Non-support AE speed |
| | | | 1: Support AE speed |
| aespeedsupportlevel | <positive integer=""></positive> | 0/7 | The value indicate the support |
| | | | strength level of aespeed. |
| | | | * Only available when |
| | | | "capability_image_c <n>_aespeed" is</n> |
| | | | 1. |
| gammacurve | 0,1 | 0/7 | 0: Non-support tuning Gamma curve |
| | | | 1: Support tuning Gamma curve |
| lowlightmode | -,0,1 | 0/7 | -: Internal parameter, must not open |
| | | | to user. |
| | | | 0: Non-support low light mode |
| | | | 1: Support low light mode |
| backfocus | 0,1 | 0/7 | 0: Non-support back focus |
| | | | 1: Support back focus |
| focusassist | 0,1 | 0/7 | 0: Non-support focus assist |
| | | | 1: Support focus assist |
| remotefocus | 0,1 | 0/7 | 0: Non-support remote focus |
| | | | 1: Support remote focus |
| focuswindomain | qvga, px, std, - | 0/7 | The domain to set an focus window. |
| | | | qvga: a 320x240 range to represent |
| | | | the whole image. |
| | | | px: Locate a window in the image with |
| | | | pixels. |
| | | | std: A normalized 0~9999 range. |
| | | | -: Not supported. |
| lensconfiguration_support | 0,1 | 0/7 | Indicate whether to support different |
| | | | image library configuration files for |
| | | | specific exchangeable lens. |

7.25 Customized event script

Group: event_customtaskfile_i<0~2>

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-----------|--------------|-----------|---|
| | | (get/set) | |
| name | string[40] | 6/6 | Custom script identification of this entry. |
| date | string[4~20] | 6/6 | Date of custom script. |
| time | string[4~20] | 6/6 | Time of custom script. |

7.26 Event setting

Group: event_i<0~2>

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|---------------|-------------------------------------|-----------|--|
| | | (get/set) | |
| name | string[40] | 6/6 | Identification of this entry. |
| enable | 0, 1 | 6/6 | Enable or disable this event. |
| priority | 0, 1, 2 | 6/6 | Indicate the priority of this event: |
| | | | "0"= low priority |
| | | | "1″= normal priority |
| | | | ``2″= high priority |
| delay | 1~999 | 6/6 | Delay in seconds before detecting the next |
| | | | event. |
| trigger | boot, | 6/6 | Indicate the trigger condition: |
| | di, | | "boot" = System boot |
| | pir, | | "di"= Digital input |
| | motion, | | "pir"= PIR detection |
| | seq, | | "motion" = Video motion detection |
| | recnotify, | | "seq" = Periodic condition |
| | tampering, | | "visignal" = Video input signal loss. |
| | vi, | | "recnotify" = Recording notification. |
| | volalarm, | | "tampering" = Tamper detection. |
| | visignal, | | "vi"= Virtual input (Manual trigger) |
| | vadp | | "volalarm"= Audio detection |
| | <product dependent=""></product> | | |
| triggerstatus | string[40] | 6/6 | The status for event trigger |
| di | 0, <positive integer=""></positive> | 6/6 | Indicate the source id of di trigger. |
| | | | This field is required when trigger condition is |
| | | | "di". |
| | | | One bit represents one digital input. The LSB |
| | | | indicates DI 0. |

| | | | - II I I I I I I I I I I I I I I I I I |
|----------------------------------|-------------------------------------|-----|---|
| mdwin | 0, <positive integer=""></positive> | 6/6 | Indicate the source window id of motion |
| | | | detection. |
| | | | This field is required when trigger condition is |
| | | | "md″. |
| | | | One bit represents one window. |
| | | | The LSB indicates the 1^{st} window. |
| | | | For example, to detect the 1^{st} and 3^{rd} windows, |
| | | | set mdwin as 5. |
| mdwin0 | 0, <positive integer=""></positive> | 6/6 | Similar to mdwin. The parameter takes effect |
| | | | when profile 1 of motion detection is enabled. |
| vi | 0, <positive integer=""></positive> | 6/6 | Indicate the source id of vi trigger. |
| | | | This field is required when trigger condition is |
| | | | "vi″. |
| | | | One bit represents one digital input. The LSB |
| | | | indicates VI 0. |
| vadp | 0, <positive integer=""></positive> | 6/6 | Indicate the source id of vadp event notification. |
| <product dependent=""></product> | | | Each bit corresponds to one vadp source, and |
| | | | the LSB indicates source id 0. |
| | | | For example, to detect event from any one of |
| | | | source id 0, 1 and 3, set vadp to 11. |
| | | | * Only available when vadp is listed in |
| | | | "capability_supporttriggertypes" |
| valevel | 0,1 | 6/6 | Select audio detection event. |
| | | | 0: not select |
| | | | 1: select |
| valevel0 | 0,1 | 6/6 | Select audio detection profile event. |
| | , | , - | 0: not select |
| | | | 1: select |
| inter | 1~999 | 6/6 | Interval of snapshots in minutes. |
| | | | This field is used when trigger condition is "seq". |

| weekday | 0~127 | 6/6 | Indicate which weekday is scheduled. |
|----------------------------------|-----------------------|------|---|
| | | -, - | One bit represents one weekday. |
| | | | bit0 (LSB) = Saturday |
| | | | bit1 = Friday |
| | | | bit2 = Thursday |
| | | | bit3 = Wednesday |
| | | | bit4 = Tuesday |
| | | | bit5 = Monday |
| | | | bit6 = Sunday |
| | | | For example, to detect events on Friday and |
| | | | Sunday, set weekday as 66. |
| begintime | hh:mm | 6/6 | Begin time of the weekly schedule. |
| | | | |
| endtime | hh:mm | 6/6 | End time of the weekly schedule. |
| | | | $(00:00 \sim 24:00 \text{ sets schedule as always on})$ |
| lowlightcondition | 0, 1 | 6/6 | Switch on white light LED in low light condition |
| <product dependent=""></product> | | | 0 => Do action at all times |
| | | | 1 => Do action in low-light conditions |
| action_do_i<0~(ndo-1)>_e | e <boolean></boolean> | 6/6 | Enable or disable trigger digital output. |
| nable | | | * Only available when "capability_ndo" > 0 |
| action_do_i<0~(ndo-1)>_ | 1~999 | 6/6 | Duration of the digital output trigger in seconds. |
| duration | | | * Only available when "capability_ndo" > 0 |
| action_cf_enable | <boolean></boolean> | 6/6 | Enable or disable sending media to SD card. |
| action_cf_folder | string[128] | 6/6 | Path to store media. |
| action_cf_media | NULL, 0~4,101 | 6/6 | Index of the attached media. |
| | | | 101 means "Recording Notify" |
| action_cf_datefolder | <boolean></boolean> | 6/6 | Enable this to create folders by date, time, and |
| | | | hour automatically. |
| action_cf_backup | <boolean></boolean> | 6/6 | Enable or disable the function that send media to |
| | | | SD card for backup if network is disconnected. |
| action_server_i<0~4>_ena | <boolean></boolean> | 6/6 | Enable or disable this server action. |
| ble | | | |
| action_server_i<0~4>_me | NULL, 0~4,101 | 6/6 | Index of the attached media. |
| dia | | | 101 means "Recording Notify" |
| action_server_i<0~4>_dat | <boolean></boolean> | 6/6 | Enable this to create folders by date, time, and |
| efolder | | | hour automatically. |
| action_goto_enable | <boolean></boolean> | 6/6 | Enable/disable ptz goto preset position on event |
| <product dependent=""></product> | | | triggered. |
| | | | * Only available when capability_ptzenabled > |
| | 1 | | |

| action_goto_name | string[40] | 6/6 | Specify the preset name that ptz goto on event |
|----------------------------------|------------|-----|--|
| <product dependent=""></product> | | | triggered. |
| | | | * Only available when capability_ptzenabled > |
| | | | 0. |

7.27 Server setting for event action

Group: server_i<0~4>

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|----------------------|---------------------|-----------|--|
| | | (get/set) | |
| name | string[40] | 6/6 | Identification of this entry |
| type | email, | 6/6 | Indicate the server type: |
| | ftp, | | "email" = email server |
| | http, | | "ftp" = FTP server |
| | ns | | "http" = HTTP server |
| | | | "ns" = network storage |
| http_url | string[128] | 6/6 | URL of the HTTP server to upload. |
| http_username | string[64] | 6/6 | Username to log in to the server. |
| http_passwd | string[64] | 6/6 | Password of the user. |
| ftp_address | string[128] | 6/6 | FTP server address. |
| ftp_username | string[64] | 6/6 | Username to log in to the server. |
| ftp_passwd | string[64] | 6/6 | Password of the user. |
| ftp_port | 0~65535 | 6/6 | Port to connect to the server. |
| ftp_location | string[128] | 6/6 | Location to upload or store the media. |
| ftp_passive | <boolean></boolean> | 6/6 | Enable or disable passive mode. |
| | | | 0 = disable passive mode |
| | | | 1 = enable passive mode |
| email_address | string[128] | 6/6 | Email server address. |
| email_sslmode | <boolean></boolean> | 6/6 | Enable support SSL. |
| email_port | 0~65535 | 6/6 | Port to connect to the server. |
| email_username | string[64] | 6/6 | Username to log in to the server. |
| email_passwd | string[64] | 6/6 | Password of the user. |
| email_senderemail | string[128] | 6/6 | Email address of the sender. |
| email_recipientemail | string[640] | 6/6 | Email address of the recipient. |
| ns_location | string[128] | 6/6 | Location to upload or store the media. |

| ns_username | string[64] | 6/6 | Username to log in to the server. |
|--------------|------------|-----|-----------------------------------|
| ns_passwd | string[64] | 6/6 | Password of the user. |
| ns_workgroup | string[64] | 6/6 | Workgroup for network storage. |

7.28 Media setting for event action

Group: media_i<0~4>

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|---------------------|---------------------------------|-----------|---------------------------------------|
| | | (get/set) | |
| name | string[40] | 6/6 | Identification of this entry |
| type | snapshot, | 6/6 | Media type to send to the server or |
| | systemlog, | | store on the server. |
| | videoclip, | | |
| | recordmsg | | |
| snapshot_source | 0~"capability_nmediastream -1" | 6/6 | Indicate the source of media stream. |
| | | | 0 means the first stream. |
| | | | 1 means the second stream and etc. |
| | | | 2 means the third stream and etc. |
| | | | 3 means the fourth stream and etc. |
| snapshot_prefix | string[16] | 6/6 | Indicate the prefix of the filename. |
| | | | media_i0=> Snapshot1_ |
| | | | media_i1=> Snapshot2_ |
| | | | media_i2=> Snapshot3_ |
| | | | media_i3=> Snapshot4_ |
| | | | media_i4=> Snapshot5_ |
| snapshot_datesuffix | 0, 1 | 6/6 | Add date and time suffix to filename: |
| | | | 1 = Add date and time suffix. |
| | | | 0 = Do not add. |
| snapshot_preevent | 0~" | 6/6 | Indicates the number of pre-event |
| | capability_media_snapshot_maxpr | | images. |
| | eevent" | | |
| snapshot_postevent | 0~" | 6/6 | Indicates the number of post-event |
| | capability_media_snapshot_maxpo | | images. |
| | stevent" | | |
| videoclip_source | 0~"capability_nmediastream -1" | 6/6 | Indicate the source of media stream. |
| | | | 0 means the first stream. |
| | | | 1 means the second stream and etc. |
| | | | 2 means the third stream and etc. |
| | | | 3 means the fourth stream and etc. |

| videoclip_prefix | string[16] | 6/6 | Indicate the prefix of the filename. |
|-----------------------|-----------------------------------|-----|--|
| videoclip_preevent | 0 ~ " | 6/6 | Indicates the time for pre-event |
| | capability_media_videoclip_maxpre | | recording in seconds. |
| | event" | | |
| videoclip_maxduration | 1 ~ " | 6/6 | Maximum duration of one video clip in |
| | capability_media_videoclip_maxlen | | seconds. |
| | gth" | | |
| videoclip_maxsize | 50 ~ " | 6/6 | Maximum size of one video clip file in |
| | capability_media_videoclip_maxsiz | | Kbytes. |
| | e" | | |

7.29 Recording

Group: recording_i<0~1>

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-----------|-------------------------------|-----------|--|
| | | (get/set) | |
| name | string[40] | 6/6 | Identification of this entry. |
| trigger | schedule, | 6/6 | The event trigger type |
| | networkfail | | schedule: The event is triggered by schedule |
| | | | networkfail: The event is triggered by the |
| | | | failure of network connection. |
| enable | <boolean></boolean> | 6/6 | Enable or disable this recording. |
| priority | 0, 1, 2 | 6/6 | Indicate the priority of this recording: |
| | | | "0" indicates low priority. |
| | | | "1" indicates normal priority. |
| | | | "2" indicates high priority. |
| source | 0~"capability_nmediastream-1" | 6/6 | Indicate the source of media stream. |
| | | | 0 means the first stream. |
| | | | 1 means the second stream and so on. |

| maxretentiontime | <string></string> | 6/6 | To specify the expired time for automatic clean |
|------------------|---------------------|-----|---|
| | 5 | , | up, and it only takes effect for video clip |
| | | | generated by recording_i <0~1>. |
| | | | Format is |
| | | | "`P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S' |
| | | | , similar with ISO8601 with symbols P |
| | | | Ex. P7D, it means 7 days. P1DT10H, it means |
| | | | 1 days and 10 hours. |
| | | | The parameter takes effect when |
| | | | autocleanup_ |
| | | | maxretentiontime_recording_enabled is |
| | | | enabled. |
| limitsize | <boolean></boolean> | 6/6 | 0: Entire free space mechanism |
| | | | 1: Limit recording size mechanism |
| cyclic | <boolean></boolean> | 6/6 | 0: Disable cyclic recording |
| | | | 1: Enable cyclic recording |
| notify | <boolean></boolean> | 6/6 | 0: Disable recording notification |
| | | | 1: Enable recording notification |
| notifyserver | 0~31 | 6/6 | Indicate which notification server is |
| | | | scheduled. |
| | | | One bit represents one application server |
| | | | (server_i0~i4). |
| | | | bit0 (LSB) = server_i0. |
| | | | bit1 = server_i1. |
| | | | bit2 = server_i2. |
| | | | bit3 = server_i3. |
| | | | bit4 = server_i4. |
| | | | For example, enable server_i0, server_i2, and |
| | | | server_i4 as notification servers; the |
| | | | notifyserver value is 21. |

| weekday | 0~127 | 6/6 | Indicate which weekday is scheduled. |
|--------------------|---------------------|-----|--|
| | | | One bit represents one weekday. |
| | | | bit0 (LSB) = Saturday |
| | | | bit1 = Friday |
| | | | bit2 = Thursday |
| | | | bit3 = Wednesday |
| | | | bit4 = Tuesday |
| | | | bit5 = Monday |
| | | | bit6 = Sunday |
| | | | For example, to detect events on Friday and |
| | | | Sunday, set weekday as 66. |
| begintime | hh:mm | 6/6 | Start time of the weekly schedule. |
| endtime | hh:mm | 6/6 | End time of the weekly schedule. |
| | | | (00:00~24:00 indicates schedule always on) |
| prefix | string[16] | 6/6 | Indicate the prefix of the filename. |
| cyclesize | 100~ | 6/6 | The maximum size for cycle recording in |
| | | | Kbytes when choosing to limit recording size. |
| reserveamount | 0~1500000 | 6/6 | The reserved amount in Mbytes when |
| | | | choosing cyclic recording mechanism. |
| dest | cf, | 6/6 | The destination to store the recorded data. |
| | 0~4 | | "cf" means local storage (CF or SD card). |
| | | | "0" means the index of the network storage. |
| cffolder | string[128] | 6/6 | Folder name. |
| maxsize | 100~2000 | 6/6 | Unit: Mega bytes. |
| | | | When this condition is reached, recording file |
| | | | is truncated. |
| maxduration | 60~3600 | 6/6 | Unit: Second |
| | | | When this condition is reached, recording file |
| | | | is truncated. |
| adaptive_enable | <boolean></boolean> | 6/6 | Indicate whether the adaptive recording is |
| | | | enabled |
| adaptive_preevent | 0~9 | 6/6 | Indicate when is the adaptive recording |
| | | | started before the event trigger point |
| | | | (seconds) |
| adaptive_postevent | 0~10 | 6/6 | Indicate when is the adaptive recording |
| | | | stopped after the event trigger point |
| | | | (seconds) |

7.30 HTTPS

Group: **https** (capability.protocol.https > 0)

| NAME | VALUE | SECURITY (get/set) | DESCRIPTION |
|---------------------|---------------------|-----------------------|---|
| enable | <boolean></boolean> | 6/6 | To enable or disable secure HTTP. |
| policy | <boolean></boolean> | 6/6 | If the value is 1, it will force HTTP connection |
| | | | redirect to HTTPS connection |
| method | auto, | 6/6 | auto =>Create self-signed certificate |
| | manual, | | automatically. |
| | install | | manual =>Create self-signed certificate |
| | | | manually. |
| | | | install =>Create certificate request and install. |
| status | -3 ~ 1 | 6/6 | Specify the https status. |
| | | | -3= Certificate not installed |
| | | | -2 = Invalid public key |
| | | | -1 = Waiting for certificate |
| | | | 0= Not installed |
| | | | 1 = Active |
| countryname | string[2] | 6/6 | Country name in the certificate information. |
| stateorprovincename | string[128] | 6/6 | State or province name in the certificate |
| | | | information. |
| localityname | string[128] | 6/6 | The locality name in thecertificate information. |
| organizationname | string[64] | 6/6 | Organization name in the certificate |
| | VIVOTEK Inc. | | information. |
| unit | string[64] | 6/6 | Organizational unit name in thecertificate |
| | VIVOTEK Inc. | | information. |
| commonname | string[64] | 6/6 | Common name in the certificate information. |
| | www.vivotek.com | | |
| validdays | 0 ~ 3650 | 6/6 | Valid period for the certification. |

7.31 Storage management setting

Group: **disk_i<0~(n-1)>** n is the total number of storage devices. (capability.storage.dbenabled > 0)

| PARAMETER | VALUE | | DESCRIPTION |
|---|----------------------------------|-----------|--|
| | | (get/set) | |
| cyclic_enabled | <boolean></boolean> | 6/6 | Enable cyclic storage method. |
| autocleanup_enabled | <boolean></boolean> | 6/6 | Enable automatic clean up method. |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>Expired and not locked media files will be</td></not> | | | Expired and not locked media files will be |
| this> | | | deleted. |
| | | | * For forward compatibility reservations, but |
| | | | only group disk_i0_autocleanup is effective. |
| | | | * Not recommended to use this. Please refers |
| | | | "autocleanup" group. |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or greater |
| | | | than 0400a. |
| autocleanup_maxage | <positive integer=""></positive> | 6/6 | To specify the expired days for automatic clean |
| <not recommended="" td="" to="" use<=""><td></td><td></td><td>up.</td></not> | | | up. |
| this> | | | * For forward compatibility reservations, but |
| | | | only group disk_i0_autocleanup is effective. |
| | | | * Not recommended to use this. Please refers |
| | | | "autocleanup" group. |
| | | | * This parameter will not be used after the |
| | | | version number (httpversion) is equal or greater |
| | | | than 0400a. |

Currently it's only for local storage (SD, CF card), so n is equal to 1.

Group: **autocleanup** (capability.localstorage.supportedge > 0)

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|---------------------------|---------------------|-----------|--|
| | | (get/set) | |
| enabled | <boolean></boolean> | 6/6 | Enable automatic clean up method. |
| | | | Expired and not locked media files will be |
| | | | deleted. |
| maxretentiontime_recordin | <boolean></boolean> | 6/6 | Enable automatic clean up method for video |
| g_enabled | | | clip generated by recording task. |
| | | | The parameter takes effect when |
| | | | autocleanup_enabled is enabled. |

| maxretentiontime_recordin | <string></string> | 6/6 | To specify the expired time for automatic clean |
|---------------------------|---------------------|-----|--|
| g_i <0~1>_maxage | | | up, and it only takes effect for video clip |
| | | | generated by recording_i <0~1>. |
| | | | |
| | | | Format is |
| | | | ```P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S' |
| | | | , similar with ISO8601 with symbols P |
| | | | Ex. P7D, it means 7 days. P1DT10H, it means 1 |
| | | | days and 10 hours. |
| | | | The parameter takes effect when autocleanup_ |
| | | | maxretentiontime_recording_enabled is |
| | | | enabled. |
| maxretentiontime_others_e | <boolean></boolean> | 6/6 | Enable automatic clean up method for all |
| nabled | | | media files except media files generated by |
| | | | recording task. |
| | | | The parameter takes effect when |
| | | | autocleanup_enabled is enabled. |
| | <string></string> | 6/6 | To specify the expired time for automatic clean |
| maxage | | | up, and it takes effect for all media files except |
| | | | media files generated by recording task. |
| | | | Format is |
| | | | "``P[Y]Y[MM]M[DDD]DT[hh]H[mm]M[ss]S' |
| | | | , similar with ISO8601 with symbols P |
| | | | Ex. P7D, it means 7 days. P1DT10H, it means 1 |
| | | | days and 10 hours. |
| | | | |
| | | | The parameter takes effect when |
| | | | autocleanup_maxretentiontime_others_enabl |
| | | | ed is enabled. |

7.32 Region of interest

Group: **roi_c<0~(n-1)>** for n channel product. (capability.eptz > 0)

m denotes the value of "capability_nmediastream".

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|--------------------|----------------------------------|-----------|---|
| | | (get/set) | |
| s<0~(m-2)>_home | <w,h></w,h> | 1/6 | ROI left-top corner coordinate.* If the minimal |
| | <product dependent=""></product> | | window size is 64x64, then the |
| | | | "win_i0_home"=(0~resolution_W-64, |
| | | | 0~resolution_H-64), which the resolution is the |
| | | | value in current stream. |
| s<0~(m-2)>_size | <wxh></wxh> | 1/6 | ROI width and height. The width value must be |
| | <product dependent=""></product> | | multiples of 16 and the height value must be |
| | | | multiples of 8* The minimal window size is |
| | | | 64x64 |
| s <m-1>_home</m-1> | <w,h></w,h> | 1/7 | ROI left-top corner coordinate.* If the minimal |
| | <product dependent=""></product> | | window size is 64x64, then the |
| | | | "win_i0_home"=(0~resolution_W-64, |
| | | | 0~resolution_H-64), which the resolution is the |
| | | | value in current stream. |
| s <m-1>_size</m-1> | <wxh></wxh> | 1/7 | ROI width and height. The width value must be |
| | <product dependent=""></product> | | multiples of 16 and the height value must be |
| | | | multiples of 8* The minimal window size is |
| | | | 64x64 |

7.33 ePTZ setting

Group: **eptz_c<0~(n-1)>** for n channel product. (capability.eptz > 0)

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|-----------|---------------------|-----------|--|
| | | (get/set) | |
| osdzoom | <boolean></boolean> | 1/4 | Indicates multiple of zoom in is "on-screen |
| | | | display″ or not |
| smooth | <boolean></boolean> | 1/4 | Enable the ePTZ "move smoothly" feature |
| tiltspeed | -5 ~ 5 | 1/7 | Tilt speed |
| | | | (It should be set by eCamCtrl.cgi rather than by |
| | | | setparam.cgi.) |

| panspeed | -5 ~ 5 | 1/7 | Pan speed |
|-----------|--------|-----|--|
| | | | (It should be set by eCamCtrl.cgi rather than by |
| | | | setparam.cgi.) |
| zoomspeed | -5 ~ 5 | 1/7 | Zoom speed |
| | | | (It should be set by eCamCtrl.cgi rather than by |
| | | | setparam.cgi.) |
| autospeed | 1 ~ 5 | 1/7 | Auto pan/patrol speed |
| | | | (It should be set by eCamCtrl.cgi rather than by |
| | | | setparam.cgi.) |

Group: **eptz_c<0~(n-1)>_s<0~(m-1)>** for n channel product and m is the number of streams which support ePTZ. (capability.eptz > 0)

| | | CECUDITY | DECODIDITION |
|---------------------|----------------------------------|-----------|---|
| PARAMETER | VALUE | SECORITY | DESCRIPTION |
| | | (get/set) | |
| patrolseq | string[120] | 1/4 | The patrol sequence of ePTZ. All the patrol |
| | | | position indexes will be separated by "," |
| patroldwelling | string[160] | 1/4 | The dwelling time (unit: second) of each patrol |
| | | | point, separated by ",". |
| preset_i<0~19>_name | string[40] | 1/7 | Name of ePTZ preset. |
| | | | (It should be set by ePreset.cgi rather than by |
| | | | setparam.cgi.) |
| preset_i<0~19>_pos | <w,h></w,h> | 1/7 | Left-top corner coordinate of the preset. |
| | <product dependent=""></product> | | (It should be set by ePreset.cgi rather than by |
| | | | setparam.cgi.) |
| preset_i<0~19>_size | <wxh></wxh> | 1/7 | Width and height of the preset. |
| | <product dependent=""></product> | | (It should be set by ePreset.cgi rather than by |
| | | | setparam.cgi.) |

7.34 Focus Window setting

Group: focuswindow_c<0~(n-1)> for n channel products

n denotes the value of "capability_nvideoin".

(capability_image_c<0~(n-1)>_backfocus=1 or capability_image_c<0~(n-1)>_remotefocus=1)

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|---------------|----------------------------------|-----------|---|
| | | (get/set) | |
| win_i0_enable | <boolean></boolean> | 4/4 | Enable or disable the window. |
| win_i0_home | <w,h></w,h> | 4/4 | Left-top corner coordinate of the window. |
| | <product dependent=""></product> | | * If the minimal window size is 192x144, then |
| | | | the "win_i0_home"=(0~resolution_W-192, |
| | | | 0~resolution_H-144), which the resolution is |
| | | | the value in current stream. |
| win_i0_size | <wxh></wxh> | 4/4 | Width and height of the window. |
| | <product dependent=""></product> | | * The minimal window size is 192x144 |

7.35 Seamless recording setting

Group: **seamlessrecording** (capability.localstorage.seamless> 0)

| PARAMETER | VALUE | SECURITY | DESCRIPTION |
|------------------|---------------------|-----------|---|
| | | (get/set) | |
| diskmode | seamless, | 1/6 | "seamless" indicates enable seamless recording. |
| | manageable | | "manageable" indicates disable seamless |
| | | | recording. |
| maxconnection | 3 | 1/7 | Maximum number of connected seamless |
| | | | streaming. |
| enable | <boolean></boolean> | 1/7 | Indicate whether seamless recording is |
| | | | recording to local storage or not at present. |
| | | | (Read only) |
| guid<0~2>_id | string[127] | 1/7 | The connected seamless streaming ID. |
| | | | (Read only) |
| guid<0~2>_number | 0~3 | 1/7 | Number of connected seamless streaming with |
| | | | guid<0~2>_id. |
| | | | (Read only) |

7.36 VIVOTEK Application Development Platformsetting

Group: vadp

| NAME | VALUE | SECURITY (get/set) | DESCRIPTION |
|------------------------|-------------------------------------|-----------------------|---|
| version | <string></string> | 6/7 | Indicate the VADP version. |
| resource_total_memory | 0, <positive integer=""></positive> | 6/7 | Indicate total available memory size for VADP |
| | | | modules. |
| resource_total_storage | 0, <positive integer=""></positive> | 6/7 | Indicate total size of the internal storage |
| | | | space for storing VADP modules. |
| resource_free_memory | 0, <positive integer=""></positive> | 6/7 | Indicate free memory size for VADP modules. |
| resource_free_storage | 0, <positive integer=""></positive> | 6/7 | Indicate current free storage size for |
| | | | uploading VADP modules. |
| module_number | 0, <positive integer=""></positive> | 6/7 | Record the total module number that already |
| | | | stored in the system. |
| module_order | string[40] | 6/6 | The execution order of the enabled modules. |
| module_save2sd | <boolean></boolean> | 6/6 | Indicate if the module should be saved to SD |
| | | | card when user want to upload it. |
| | | | If the value is false, save module to the |
| | | | internal storage space and it will occupy |
| | | | storage size. |
| number | string[128] | 6/7 | This number is used to register license key for |
| | | | VADP application. |

Group: vadp_module_i<0~(n-1)> for n VADP package number (capability_vadp_npackage > 0)

n denotes the value of "capability_vadp_npackage".

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------------|---------------------|-----------|---|
| | | (get/set) | |
| enable | <boolean></boolean> | 6/6 | Indicate if the module is enabled or not. |
| | | | If yes, also add the index of this module to the |
| | | | module_order. |
| name | string[40] | 6/6 | Module name |
| extendedname | string[40] | 6/6 | Extended module name. If this value is not |
| | | | blank, it will be shown on the VADP UI first |
| | | | instead of vadp_module_i <n>_name.</n> |
| url | string[120] | 6/6 | Define the URL string after the IP address if the |
| | | | module provides it own web page. |
| vendor | string[40] | 6/6 | The provider of the module. |

| | 1 | | |
|----------------|-------------|-----|---|
| vendorurl | string[120] | 6/6 | URL of the vendor. |
| version | string[40] | 6/6 | Version of the module. |
| license | string[40] | 6/6 | Indicate the license status of the module. |
| licmsg | string[128] | 6/6 | Indicate the message that will be show on |
| | | | license status when mouse over. |
| path | string[40] | 6/6 | Record the storage path of the module. |
| initscr | string[40] | 6/6 | The script that will handle operation |
| | | | commands from the system. |
| status | string[40] | 6/6 | Indicate the running status of the module. |
| statmsg | string[128] | 6/6 | Indicate the message that will be show on the |
| | | | running status when mouse over. |
| vvtklicensemec | string[40] | 6/7 | Indicate the module use VIVOTEK license |
| | | | mechanism |

Group: vadp_event

| NAME | VALUE | SECURITY | DESCRIPTION |
|---------------------------|-------------------------------------|-----------|--|
| | | (get/set) | |
| ntrigger | 0, <positive integer=""></positive> | 6/7 | Indicate the number of topics to be transferred |
| | | | to event manager for trigger. |
| triggerlist_i<0~(n-1)>_to | string[256] | 6/6 | Indicate the event notification with this topic |
| pic | | | will be transferred to event manager as trigger. |
| | | | n is equal to ntrigger above. |

7.37 camera PTZ control

Group: camctrl

| NAME | VALUE | SECURITY | DESCRIPTION |
|------------------|---------------------|-----------|--|
| | | (get/set) | |
| enablehttptunnel | <boolean></boolean> | 1/4 | Enable HTTP tunnel for camera control. |
| | | | * Only available when |
| | | | capability_camctrl_httptunnel > 0 |
| enableptztunnel | <boolean></boolean> | 1/4 | Enable PTZ tunnel for camera control. |
| | | | * Only available when |
| | | | capability_ptzenabled > 0 |

Group: camctrl_c<0~(n-1)> for n channel products (capability.ptzenabled > 0)

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY (get/set) | DESCRIPTION |
|---|-----------------------|-----------------------|--|
| panspeed | -5 ~ 5 | 1/4 | Pan speed |
| tiltspeed | -5 ~ 5 | 1/4 | Tilt speed |
| zoomspeed | -5 ~ 5 | 1/4 | Zoom speed |
| focusspeed | -5 ~ 5 | 1/4 | Auto focus speed |
| patrolseq | string[120] | 1/4 | (For external device) The indexes of patrol points, separated by "," |
| patroldwelling | string[160] | 1/4 | (For external device) The dwelling time of each patrol point, separated by "," |
| preset_i<0~(capability_n preset -1)>_name | string[40] | 1/4 | Name of the preset location. |
| preset_i<0~(capability_n preset -1)>_ dwelling | 0 ~ 999 | 1/4 | The dwelling time of each preset location |
| uart | 0 ~ | 1/4 | Select corresponding uart |
| | (capability_nuart -1) | | (capability.nuart>0). |
| cameraid | 0~255 | 1/4 | Camera ID controlling external PTZ camera. |
| isptz | 0 ~ 2 | 1/4 | 0: disable PTZ commands. |
| | | | 1: enable PTZ commands with PTZ driver. |
| | | | 2: enable PTZ commands with UART tunnel. |
| | | | * Only available when |
| | | | bit7 of |

| | | | capability_ptzenable d is 1 |
|----------------|---------------------|-----|--|
| disablemdonptz | <boolean></boolean> | 1/4 | Disable motion detection on PTZ operation. |

7.38 UART control

Group: **uart** (capability.nuart > 0 and capability.fisheye = 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------------------|---------------------|-----------|---|
| | | (get/set) | |
| ptzdrivers_i<0~19, | string[40] | 1/4 | Name of the PTZ driver. |
| 127>_name | | | |
| ptzdrivers_i<0~19, | string[128] | 1/4 | Full path of the PTZ driver. |
| 127>_location | | | |
| enablehttptunnel | <boolean></boolean> | 1/4 | Enable HTTP tunnel channel to control UART. |

Group: **uart_i<0~(n-1)>** n is uart port count (capability.nuart > 0 and capability.fisheye = 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-----------------------|-------------------|-----------|--|
| | | (get/set) | |
| baudrate | 110,300,600,1200, | 4/4 | Set baud rate of COM port. |
| | 2400,3600,4800,72 | | |
| | 00,9600,19200,384 | | |
| | 00,57600,115200 | | |
| databit | 5,6,7,8 | 4/4 | Data bits in a character frame. |
| paritybit | none, | 4/4 | For error checking. |
| | odd, | | |
| | even | | |
| stopbit | 1,2 | 4/4 | 1 |
| | | | 2-1.5 , data bit is 5 |
| | | | 2-2 |
| uartmode | rs485, | 4/4 | RS485 or RS232. |
| | rs232 | | |
| customdrvcmd_i<0~9> | string[128] | 1/4 | PTZ command for custom camera. |
| speedlink_i<0~4>_name | string[40] | 1/4 | Additional PTZ command name. |
| speedlink_i<0~4>_cmd | string[40] | 1/4 | Additional PTZ command list. |
| ptzdriver | 0~19, | 1/4 | The PTZ driver is used by this COM port. |
| | 127 (custom), | | |
| | 128 (no driver) | | |

7.39 Lens configuration

Group: **lens** (capability.image.c<0~n-1>.lensconfiguration.support = 1) for n channel products

n denotes the value of "capability_nvideoin"

| NAME | VALUE | SECURITY | DESCRIPTION |
|----------|-------------------------------------|-----------|---|
| | | (get/set) | |
| selected | 0, <positive integer=""></positive> | 6/7 | Current selected lens profile. |
| | | | If the "lens_selected" is equal or greater than |
| | | | "lens_default_numbers", it means the lens |
| | | | profile is selected from "lens_user_len< |
| | | | lens_selected - lens_default_numbers>" |
| | | | profile. |

Group: lens_default

| NAME | VALUE | SECURITY | DESCRIPTION |
|---------|-------------------------------------|-----------|---|
| | | (get/set) | |
| numbers | 0, <positive integer=""></positive> | 6/7 | Totoal support number of the default lens |
| | | | profiles |

Group: lens_user

| NAME | VALUE | SECURITY | DESCRIPTION |
|---------|-------------------------------------|-----------|--|
| | | (get/set) | |
| numbers | 0, <positive integer=""></positive> | 6/7 | Totoal number of the user lens profiles |
| max | 0, <positive integer=""></positive> | 6/7 | Maximum number of the user lens profiles |

Group: lens_default_len<0~(n-1)> n is lens_default_numbers

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|-------------------|-----------|-------------------|
| | | (get/set) | |
| name | <string></string> | 6/7 | Default lens name |
| type | <string></string> | 6/7 | Default lens type |

Group: lens_user_len<0~(n-1)> n is lens_user_numbers

| NAME | VALUE | SECURITY | DESCRIPTION |
|------|-------------------|-----------|------------------------|
| | | (get/set) | |
| name | <string></string> | 6/7 | User-defined lens name |
| type | <string></string> | 6/7 | User-defined lens type |

7.40 Fisheye info

Group: **fisheyeinfo** (capability.fisheye > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|-------------------|---|-----------|-----------------------------------|
| | | (get/set) | |
| revisedcenteraxis | <coordinate></coordinate> | 6/7 | The actual center axis coordinate |
| radius | 0, <positive< td=""><td>6/7</td><td>The actual center radius</td></positive<> | 6/7 | The actual center radius |
| | integer> | | |

7.41 Fisheye local dewarp setting

Group: **fisheyedewarp_c<0~(n-1)>** (capability_fisheyelocaldewarp_c<0~(capability_nvideoin)-1>> 0)

| n denotes the value of ' | "canability nyideoin" | " m denotes the val | lue of "canability | nmodiastroam" |
|--------------------------|-----------------------|----------------------|--------------------|--------------------|
| If denotes the value of | capability_liviueoili | , in denotes the var | iue or capability_ | _iiiiieuiastieaiii |

| NAME | VALUE | SECURITY | DESCRIPTION |
|------------------------|---------------------|-----------|--|
| | | (get/set) | |
| panspeed | -5 ~ 5 | 1/4 | Pan speed of regional view |
| | <integer></integer> | | |
| tiltspeed | -5 ~ 5 | 1/4 | Tilt speed of regional view |
| | <integer></integer> | | |
| zoomspeed | -5 ~ 5 | 1/4 | Zoom speed of regional |
| | <integer></integer> | | |
| s<0~(m-2)>_panorama_ | 0~359 | 1/4 | Initial pan position of panorama view. |
| panstart | <integer></integer> | | (only available for 1P and 2P mode at ceiling or |
| | | | floor mount) |
| s<0~(m-2)>_region_pan | -90~359 | 1/4 | Pan home angle of regional view |
| | <integer></integer> | | Pan range of ceiling/floor mount is [0~359]. |
| | | | Pan range of wall mount is $[-90 \sim 90]$. |
| s<0~(m-2)>_region_tilt | -90~90 | 1/4 | Tilt home angle of regional view |
| | <integer></integer> | | Tilt range of ceiling/floor mount is $[0 \sim 90]$. |
| | | | Tilt range of wall mount is [-90~90]. |
| s<0~(m-2)>_region_zoo | 100~300 | 1/4 | Zoom home ratio of regional view |
| m | <integer></integer> | | |

7.42 PIR behavior define

Group: **pir** (capability.npir > 0)

| NAME | VALUE | SECURITY | DESCRIPTION |
|--------|---------------------|-----------|--------------------|
| | | (get/set) | |
| enable | <boolean></boolean> | 1/1 | Enable/disable PIR |

8. Useful Functions

8.1 Drive the Digital Output (capability.ndo > 0)

Note: This request requires Viewer privileges. **Method:** GET/POST

| Syntax: |
|---|
| http://< <i>servername</i> >/cgi-bin/dido/setdo.cgi?do1=< <i>state</i> >[&do2= <state>]</state> |
| [&do3= <state>][&do4=<state>]</state></state> |

Where state is 0 or 1; "0" means inactive or normal state, while "1" means active or triggered state.

| PARAMETER | VALUE | DESCRIPTION |
|----------------|-------|-----------------------------|
| do <num></num> | 0, 1 | 0 – Inactive, normal state |
| | | 1 – Active, triggered state |

Example: Drive the digital output 1 to triggered state and redirect to an empty page.

http://myserver/cgi-bin/dido/setdo.cgi?do1=1

8.2 Query Status of the Digital Input(capability.ndi > 0)

Note: This request requires Viewer privileges

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/dido/getdi.cgi?[di0][&di1][&di2][&di3]

If no parameter is specified, all of the digital input statuses will be returned.

Return:

| HTTP/1.0 200 OK\r\n |
|---------------------------------------|
| Content-Type: text/plain\r\n |
| Content-Length: < <i>length</i> >\r\n |
| \r\n |
| [di0= <state>]\r\n</state> |
| [di1= <state>]\r\n</state> |
| [di2= <state>]\r\n</state> |
| [di3= <state>]\r\n</state> |

where <*state*> can be 0 or 1.

Example: Query the status of digital input 1 . Request: http://myserver/cgi-bin/dido/getdi.cgi?di1 Response: HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: 7\r\n \r\n di1=1\r\n

8.3 Query Status of the Digital Output (capability.ndo > 0)

Note: This request requires Viewer privileges

Method: GET/POST

Syntax:

http://<servername>/cgi-bin/dido/getdo.cgi?[do0][&do1][&do2][&do3]

If no parameter is specified, all the digital output statuses will be returned.

Return: HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: <*length*>\r\n \r\n [do0=<state>]\r\n [do1=<state>]\r\n [do2=<state>]\r\n [do3=<state>]\r\n

where <*state*> can be 0 or 1.

Example: Query the status of digital output 1.

Request: http://myserver/cgi-bin/dido/getdo.cgi?do1 Response:

HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: 7\r\n

8.4 Capture Single Snapshot

Note: This request requires Normal User privileges.

Method: GET/POST

Syntax:

```
http://<servername>/cgi-bin/viewer/video.jpg?[channel=<value>][&resolution=<value>]
[&quality=<value>][&streamid=<value>]
```

If the user requests a size larger than all stream settings on the server, this request will fail.

| PARAMETER | VALUE | DEFA | DESCRIPTION |
|------------|----------------------|------|---|
| | | ULT | |
| channel | 0~(n-1) | 0 | The channel number of the video source. |
| resolution | IP8165: | 0 | The resolution of the image. |
| | (160~640, 120~360) | | |
| | IP8155: | | |
| | (160~1280, 120~1024) | | |
| quality | 1~5 | 3 | The quality of the image. |
| streamid | 0~(m-1) | 2 | The stream number. |

The server will return the most up-to-date snapshot of the selected channel and stream in JPEG format. The size and quality of the image will be set according to the video settings on the server.

Return:

HTTP/1.0 200 OK\r\n Content-Type: image/jpeg\r\n [Content-Length: <image size>\r\n] <binary JPEG image data>

8.5 Account Management

Note: This request requires Administrator privileges. Method: GET/POST

Syntax:

http://<servername>/cgi-bin/admin/editaccount.cgi?

method=<value>&username=<name>[&userpass=<value>][&privilege=<value>]

[&privilege=<value>][...][&return=<return page>]

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---------------------------|--|
| method | Add | Add an account to the server. When using this method, the "username" |
| | | field is necessary. It will use the default value of other fields if not |
| | | specified. |
| | Delete | Remove an account from the server. When using this method, the |
| | | "username" field is necessary, and others are ignored. |
| | edit | Modify the account password and privilege. When using this method, |
| | | the "username" field is necessary, and other fields are optional. If not |
| | | specified, it will keep the original settings. |
| username | <name></name> | The name of the user to add, delete, or edit. |
| userpass | <value></value> | The password of the new user to add or that of the old user to modify. |
| | | The default value is an empty string. |
| Privilege | <value></value> | The privilege of the user to add or to modify. |
| | viewer | Viewer privilege. |
| | operator | Operator privilege. |
| | admin | Administrator privilege. |
| Return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The < <i>return page</i> >can be a full URL path or relative path according to |
| | | the current path. If you omit this parameter, it will redirect to an |
| | | empty page. |

8.6 System Logs

Note: This request require Administrator privileges. **Method:** GET/POST

Syntax:

http://<servername>/cgi-bin/admin/syslog.cgi

Server will return the most up-to-date system log.

Return: HTTP/1.0 200 OK\r\n Content-Type: text/plain\r\n Content-Length: <syslog length>\r\n \r\n <system log information>\r\n

8.7 Upgrade Firmware

Note: This request requires Administrator privileges. Method: POST

Syntax:

http://<servername>/cgi-bin/admin/upgrade.cgi

Post data:

fimage=<file name>[&return=<return page>]\r\n \r\n <multipart encoded form data>

Server will accept the file named <file name> to upgrade the firmware and return with <return page> if indicated.

8.8 ePTZ Camera Control (capability.eptz > 0 and

capability_fisheye = 0)

Note: This request requires camctrl privileges. **Method:** GET/POST

Syntax:

| http://< <i>servername</i> >/cgi-bin/camctrl/eCamCtrl.cgi?channel= <value>&stream=<value></value></value> |
|--|
| [&move= <value>] – Move home, up, down, left, right</value> |
| [&auto= <value>] - Auto pan, patrol</value> |
| [&zoom= <value>] -Zoom in, out</value> |
| [&zooming= <value>&zs=<value>] -Zoom without stopping, used for joystick</value></value> |
| [&x= <value>&y=<value>&w=<value>&h=<value>&resolution=<value>] - Zoom in, out on a specific area</value></value></value></value></value> |
| [&vx= <value>&vy=<value>&vs=<value>] - Shift without stopping, used for joystick</value></value></value> |
| [&x= <value>&y=<value>&videosize=<value>&resolution=<value>&stretch=<value>] -Click on image</value></value></value></value></value> |
| (Move the center of image to the coordination (x,y) based on resolution or videosize.) |
| [[&speedpan= <value>][&speedtilt=<value>][&speedzoom=<value>][&speedapp=<value>]] - Set speeds</value></value></value></value> |
| [&return= <return page="">]</return> |

Example:

| http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=0&move=right |
|--|
| http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=1&vx=2&vy=2&vz=2 |
| http://myserver/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=1&x=100&y=100& |
| videosize=640x480&resolution=640x480&stretch=0 |

In zoom operation, there are two ways to control it, scale zoom and area zoom.

1. [Scale zoom]: contains two control method, relative movement and continuous movement

a. relative movement -

If you trigger a relative movement, it will only zoom certain ratio and stop by itself.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=tele

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=wide

The zoom ratio to move by relative movement is according to the setting of speedzoom [-5~5].

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&speedzoom=5

b. continuous movement -

If you trigger a continuous movement, you have to handle the stop time by yourself.

A continuous movement is convenient to integrate a joystick control.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zooming=tele&zs=1

<u>http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zooming=wide&zs=5</u> zooming is used to indicate the moving direction, and zs is used to indicate the speed. To stop a continuous movement, you have to use the command as below: <u>http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?stream=0&zoom=stop&zs=0</u>

2. [Area zoom]: it means to zoom in on a specific area, here is an example for a directly moving

[x, y] is the desired coordinate, and it will be the center after movement

[w, h] is the scaled area size

[resolution] is the base range of this coordinate system

The example shows [w, h] = [864, 488], which means to zoom in to ratio x2.2 based on [1920x1080].

Pay attention to that [x, y, w, h] are essential parameters in an area zoom case, and the stream index is counted from 0 as the first stream.

http://IPAddr/cgi-bin/camctrl/eCamCtrl.cgi?channel=0&stream=0&x=912&y=297&w=864&h=488&resolution=1920x1080

| PARAMETER | VALUE | DESCRIPTION |
|------------|---------------------------|--|
| channel | <0~(n-1)> | Channel of video source. |
| stream | <0~(m-1)> | Stream. |
| move | home | Move to home ROI. |
| | up | Move up. |
| | down | Move down. |
| | left | Move left. |
| | right | Move right. |
| auto | pan | Auto pan. |
| | patrol | Auto patrol. |
| | stop | Stop auto pan/patrol. |
| zoom | wide | Zoom larger view with current speed. |
| | tele | Zoom further with current speed. |
| zooming | wide or tele | Zoom without stopping for larger view or further view with zs speed, |
| | | used for joystick control. |
| zs | 0 ~ 6 | Set the speed of zooming, "0" means stop. |
| х | <integer></integer> | The desired coordinate, and it will be the center after movement |
| у | <integer></integer> | |
| w | <integer></integer> | The scaled area size |
| h | <integer></integer> | |
| resolution | <window size=""></window> | The resolution of streaming. |

| vx | <integer></integer> | The direction of movement, used for joystick control. |
|------------|---------------------------|---|
| vy | <integer></integer> | |
| vs | 0 ~ 7 | Set the speed of movement, "0" means stop. |
| x | <integer></integer> | x-coordinate clicked by user. |
| | | It will be the x-coordinate of center after movement. |
| у | <integer></integer> | y-coordinate clicked by user. |
| | | It will be the y-coordinate of center after movement. |
| videosize | <window size=""></window> | The size of plug-in (ActiveX)window in web page |
| resolution | <window size=""></window> | The resolution of streaming. |
| stretch | <boolean></boolean> | 0 indicates that it uses resolution (streaming size) as the range of the |
| | | coordinate system. |
| | | 1 indicates that it uses videosize (plug-in size) as the range of the |
| | | coordinate system. |
| speedpan | -5 ~ 5 | Set the pan speed. |
| speedtilt | -5 ~ 5 | Set the tilt speed. |
| speedzoom | -5 ~ 5 | Set the zoom speed. |
| speedapp | 1 ~ 5 | Set the auto pan/patrol speed. |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The < <i>return page</i> >can be a full URL path or relative path according to |
| | | the current path. |
| | | |

8.9 ePTZ Recall (capability.eptz > 0 and capability_fisheye = 0)

Note: This request requires camctrl privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/camctrl/eRecall.cgi?channel=<value>&stream=<value>& recall=<value>[&return=<*return page*>]

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---------------------------|--|
| channel | <0~(n-1)> | Channel of the video source. |
| stream | <0~(m-1)> | Stream. |
| recall | Text string less than 40 | One of the present positions to recall. |
| | characters | |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The < <i>return page</i> >can be a full URL path or relative path according to |
| | | the current path. |

8.10 ePTZ Preset Locations(capability.eptz > 0 and

capability_fisheye = 0)

Note: This request requires Operator privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/operator/ePreset.cgi?channel=<value>&stream=<value>

```
[&addpos=<value>][&delpos=<value>][&return=<return page>]
```

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---|--|
| channel | <0~(n-1)> | Channel of the video source. |
| stream | <0~(m-1)> | Stream. |
| addpos | <text less="" string="" td="" than<=""><td>Add one preset location to the preset list.</td></text> | Add one preset location to the preset list. |
| | 40 characters> | |
| delpos | <text less="" string="" td="" than<=""><td>Delete preset location from the preset list.</td></text> | Delete preset location from the preset list. |
| | 40 characters> | |

| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
|--------|---------------------------|--|
| | | The < <i>return page</i> >can be a full URL path or relative path according to |
| | | the current path. |

8.11 IP Filtering

Note: This request requires Administrator access privileges.

Method: GET/POST

Syntax: <product dependent>

http://<*servername*>/cgi-bin/admin/ipfilter.cgi?type[=<value>]

http://<*servername*>/cgi-bin/admin/ipfilter.cgi?method=add<v4/v6>&ip=*<ipaddress*>[&index=<value>][&ret urn=*<return page*>]

http://<*servername*>/cgi-bin/admin/ipfilter.cgi?method=del<v4/v6>&index=<value>[&return=<*return page*>]

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---------------------------|---|
| type | NULL | Get IP filter type |
| | allow, deny | Set IP filter type |
| method | addv4 | Add IPv4 address into access list. |
| | addv6 | Add IPv6 address into access list. |
| | delv4 | Delete IPv4 address from access list. |
| | delv6 | Delete IPv6 address from access list. |
| ip | <ip address=""></ip> | Single address: <ip address=""></ip> |
| | | Network address: <ip address="" mask="" network=""></ip> |
| | | Range address: <start -="" address="" end="" ip=""></start> |
| index | <value></value> | The start position to add or to delete. |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The <i><return page=""></return></i> can be a full URL path or relative path according to |
| | | the current path. If you omit this parameter, it will redirect to an |
| | | empty page. |

8.12 IP Filtering for ONVIF

Syntax: < product dependent >

| http://< <i>servername</i> >/cgi-bin/admin/ipfilter.cgi?type[= <value>]</value> | | |
|---|---------------------------|---|
| http://< <i>servername</i> >/cgi-bin/admin/ipfilter.cgi?method=add <v4 v6="">&ip=<<i>ipaddress</i>>[&index=<value>][&ret</value></v4> | | |
| urn=< <i>return pa</i> | age>] | |
| http://< <i>serveri</i> | name>/cgi-bin/admin/i | ipfilter.cgi?method=del <v4 v6="">&index=<value>[&return=<<i>return page</i>>]</value></v4> |
| PARAMETER | VALUE | DESCRIPTION |
| type | NULL | Get IP filter type |
| | allow, deny | Set IP filter type |
| method | addv4 | Add IPv4 address into access list. |
| | addv6 | Add IPv6 address into access list. |
| | delv4 | Delete IPv4 address from access list. |
| | delv6 | Delete IPv6 address from access list. |
| ip | <ip address=""></ip> | Single address: <ip address=""></ip> |
| | | Network address: <ip address="" mask="" network=""></ip> |
| | | Range address: <start -="" address="" end="" ip=""></start> |
| index | <value></value> | The start position to add or to delete. |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the parameter is assigned. |
| | | The < <i>return page</i> >can be a full URL path or relative path according to |
| | | the current path. If you omit this parameter, it will redirect to an |
| | | empty page. |

8.13 UART HTTP Tunnel Channel (capability.nuart > 0)

Note: This request requires Operator privileges. **Method:** GET and POST

Syntax:

POST /cgi-bin/operator/uartchannel.cgi x-sessioncookie: string[22] content-type: application/x-vvtk-tunnelled pragma : no-cache cache-control : no-cache content-length: 32767 expires: Sun, 9 Jam 1972 00:00:00 GMT

User must use GET and POST to establish two channels for downstream and upstream. The x-sessioncookie in GET and POST should be the same to be recognized as a pair for one session. The contents of upstream should be base64 encoded to be able to pass through a proxy server.

This channel will help to transfer the raw data of UART over the network. Please see UART tunnel spec for detail information

| PARAMETER | VALUE | DESCRIPTION |
|-----------|-----------|-----------------------------|
| channel | 0 ~ (n-1) | The channel number of UART. |

8.14 Event/Control HTTP Tunnel Channel (capability.

evctrlchannel > 0)

Note: This request requires Administrator privileges. **Method:** GET and POST

Syntax:

| http://< <i>servername</i> >/cgi-bin/admin/ct | rlevent.cgi | |
|---|-------------|--|
| GET /cgi-bin/admin/ctrlevent.cgi | | |
| x-sessioncookie: string[22] | | |
| accept: application/x-vvtk-tunnelled | | |
| pragma: no-cache | | |
| cache-control: no-cache | | |
| | | |
| POST /cgi-bin/admin/ ctrlevent.cgi | | |
| x-sessioncookie: string[22] | | |
| content-type: application/x-vvtk-tunnel | led | |
| pragma : no-cache | | |
| cache-control : no-cache | | |

content-length: 32767 expires: Sun, 9 Jam 1972 00:00:00 GMT

User must use GET and POST to establish two channels for downstream and upstream. The x-sessioncookie in GET and POST should be the same to be recognized as a pair for one session. The contents of upstream should be base64 encoded to be able to pass through the proxy server.

This channel will help perform real-time event subscription and notification as well as camera control more efficiently. The event and control formats are described in another document.

See Event/control tunnel spec for detail information

8.15 Get SDP of Streams

Note: This request requires Viewer access privileges. **Method:** GET/POST

Syntax:

http://<servername>/<network_rtsp_s<0~m-1>_accessname>

"m" is the stream number.

"network_accessname_<0~(m-1)>" is the accessname for stream "1" to stream "m". Please refer to the "subgroup of network: rtsp" for setting the accessname of SDP.

You can get the SDP by HTTP GET.

When using scalable multicast, Get SDP file which contains the multicast information via HTTP.

8.16 Open the Network Stream

Note: This request requires Viewer access privileges.

Syntax:

For HTTP push server (MJPEG):

http://<servername>/<network_http_s<0~m-1>_accessname>

For RTSP (MP4), the user needs to input theURL below into an RTSP compatible player.

rtsp://<servername>/<network_rtsp_s<0~m-1>_accessname>

"m" is the stream number.

For details on streaming protocol, please refer to the "control signaling" and "data format" documents.

8.17 Senddata (capability.nuart > 0)

Note: This request requires Viewer privileges.

Method: GET/POST

Syntax:

http://<*servername*>/cgi-bin/viewer/senddata.cgi? [com=<value>][&data=<value>][&flush=<value>] [&wait=<value>] [&read=<value>]

| PARAMETER | VALUE | DESCRIPTION |
|-----------|--|--|
| com | 1 ~ <max. com="" port<="" td=""><td>The target COM/RS485 port number.</td></max.> | The target COM/RS485 port number. |
| | number> | |
| data | <hex decimal<="" td=""><td>The <hex data="" decimal=""> is a series of digits from 0 \sim 9, A \sim F. Each</hex></td></hex> | The <hex data="" decimal=""> is a series of digits from 0 \sim 9, A \sim F. Each</hex> |
| | data>[, <hex decimal<="" td=""><td>comma separates the commands by 200 milliseconds.</td></hex> | comma separates the commands by 200 milliseconds. |
| | data>] | |
| flush | yes,no | yes: Receive data buffer of the COM port will be cleared before read. |
| | | no: Do not clear the receive data buffer. |
| wait | 1 ~ 65535 | Wait time in milliseconds before read data. |
| read | 1 ~ 128 | The data length in bytes to read. The read data will be in the return |
| | | page. |

Return:

| HTTP/1.0 200 OK\r\n | |
|------------------------------|--|
| Content-Type: text/plain\r\n | |

Content-Length: <system information length>\r\n \r\n

<hex decimal data>\r\n

Where hexadecimal data is digits from 0 \sim 9, A \sim F.

8.18 Storage managements (capability.storage.dbenabled > 0)

Note: This request requires administrator privileges.

Method: GET and POST

Syntax:

http://<*servername*>/cgi-bin/admin/lsctrl.cgi?cmd=<cmd_type>[&<parameter>=<value>...]

The commands usage and their input arguments are as follows.

| PARAMETER | VALUE | DESCRIPTION |
|-----------|-------------------|---|
| cmd_type | <string></string> | Required. |
| | | Command to be executed, including search, insert, delete, update, |
| | | and <i>queryStatus</i> . |

Command: search

| PARAMETER | VALUE | DESCRIPTION |
|-------------|---------------------------------------|---|
| label | <integer key="" primary=""></integer> | Optional. |
| | | The integer primary key column will automatically be assigned a |
| | | unique integer. |
| triggerType | <text></text> | Optional. |
| | | Indicate the event trigger type. |
| | | Please embrace your input value with single quotes. |
| | | Ex. mediaType='motion' |
| | | Support trigger types are product dependent. |
| mediaType | <text></text> | Optional. |
| | | Indicate the file media type. |
| | | Please embrace your input value with single quotes. |
| | | Ex. mediaType='videoclip' |
| | | Support trigger types are product dependent. |
| destPath | <text></text> | Optional. |
| | | Indicate the file location in camera. |
| | | Please embrace your input value with single quotes. |
| | | Ex. destPath ='/mnt/auto/CF/NCMF/abc.mp4' |
| resolution | <text></text> | Optional. |

| | | Indicate the media file resolution. |
|-------------|----------------------------------|---|
| | | Please embrace your input value with single quotes. |
| | | Ex. resolution='800x600' |
| isLocked | <boolean></boolean> | Optional. |
| | | Indicate if the file is locked or not. |
| | | 0: file is not locked. |
| | | 1: file is locked. |
| | | A locked file would not be removed from UI or cyclic storage. |
| triggerTime | <text></text> | Optional. |
| | | Indicate the event trigger time. (not the file created time) |
| | | Format is "YYYY-MM-DD HH:MM:SS" |
| | | Please embrace your input value with single quotes. |
| | | Ex. triggerTime='2008-01-01 00:00:00' |
| | | If you want to search for a time period, please apply "TO" |
| | | operation. |
| | | Ex. triggerTime='2008-01-01 00:00:00'+TO+'2008-01-01 |
| | | 23:59:59' is to search for records from the start of Jan 1 st 2008to |
| | | the end of Jan 1 st 2008. |
| limit | <positive integer=""></positive> | Optional. |
| | | Limit the maximum number of returned search records. |
| offset | <positive integer=""></positive> | Optional. |
| | | Specifies how many rows to skip at the beginning of the matched |
| | | records. |
| | | Note that the offset keyword is used after limit keyword. |

To increase the flexibility of search command, you may use "OR" connectors for logical "OR" search operations. Moreover, to search for a specific time period, you can use "TO" connector.

Ex. To search records triggered by motion or di or sequential and also triggered between 2008-01-01 00:00:00 and 2008-01-01 23:59:59.

http://<*servername*>/cgi-bin/admin/lsctrl.cgi?cmd=search&triggerType='motion'+OR+'di'+OR+'seq'&triggerTi me='2008-01-01 00:00:00'+TO+'2008-01-01 23:59:59'

Command: delete

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---------------------------------------|---------------------------------|
| label | <integer key="" primary=""></integer> | Required. |
| | | Identify the designated record. |
| | | Ex. label=1 |

Ex. Delete records whose key numbers are 1, 4, and 8.

http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=delete&label=1&label=4&label=8

Command: update

| PARAMETER | VALUE | DESCRIPTION |
|-----------|---------------------------------------|--|
| label | <integer key="" primary=""></integer> | Required. |
| | | Identify the designated record. |
| | | Ex. label=1 |
| isLocked | <boolean></boolean> | Required. |
| | | Indicate if the file is locked or not. |

Ex. Update records whose key numbers are 1 and 5 to be locked status.

http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=update&isLocked=1&label=1&label=5

Ex. Update records whose key numbers are 2 and 3 to be unlocked status.

http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=update&isLocked=0&label=2&label=3

Command: queryStatus

| PARAMETER | VALUE | DESCRIPTION |
|-----------|-------------------|--|
| retType | xml or javascript | Optional. |
| | | Ex. retype=javascript |
| | | The default return message is in XML format. |

Ex. Query local storage status and call for javascript format return message.

http://<servername>/cgi-bin/admin/lsctrl.cgi?cmd=queryStatus&retType=javascript

8.19 Virtual input (capability.nvi > 0)

Note: Change virtual input (manual trigger) status. Method: GET

Syntax:

http://<servername>/cgi-bin/admin/setvi.cgi?vi0=<value>[&vi1=<value>][&vi2=<value>] [&return=<return page>]

| PARAMETER | VALUE | DESCRIPTION |
|----------------|----------------------------|---|
| vi <num></num> | state[(duration)nstate] | Ex: vi0=1 |
| | | Setting virtual input 0 to trigger state |
| | Where "state" is 0, 1. "0" | |
| | means inactive or normal | Ex: vi0=0(200)1 |
| | state while "1" means | Setting virtual input 0 to normal state, waiting 200 |
| | active or triggered state. | milliseconds, setting it to trigger state. |
| | Where "nstate" is next | Note that when the virtual input is waiting for next state, it |
| | state after duration. | cannot accept new requests. |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> >after the request is |
| | | completely assigned. The <return page="">can be a full URL</return> |
| | | path or relative path according the current path. If you omit |
| | | this parameter, it will redirect to an empty page. |

| Return Code | Description |
|-------------|---|
| 200 | The request is successfully executed. |
| 400 | The request cannot be assigned, ex. incorrect parameters. |
| | Examples: |
| | setvi.cgi?vi0=0(10000)1(15000)0(20000)1 |
| | No multiple duration. |
| | setvi.cgi?vi3=0 |
| | VI index is out of range. |
| | setvi.cgi?vi=1 |
| | No VI index is specified. |
| 503 | The resource is unavailable, ex. Virtual input is waiting for next state. |
| | Examples: |
| | setvi.cgi?vi0=0(15000)1 |
| | setvi.cgi?vi0=1 |
| | Request 2 will not be accepted during the execution time(15 seconds). |

8.20 Open Timeshift Stream (capability.timeshift > 0,

timeshift_enable=1, timeshift_c<n>_s<m>_allow=1)

Note: This request requires Viewer access privileges.

Syntax:

For HTTP push server (MJPEG):

http://<servername>/<network_http_s<m>_accessname>?maxsft=<value>[&tsmode=<value>&reftime=<v alue>&forcechk&minsft=<value>]

For RTSP (MP4 and H264), the user needs to input theURL below into an RTSP compatible player.

```
rtsp://<servername>/<network_rtsp_s<m>_accessname>?maxsft=<value>[&tsmode=<value>&reftime=<va
lue>&forcechk&minsft=<value>]
```

"n" is the channel index.

"m" is the timeshift stream index.

For details on timeshift stream, please refer to the "TimeshiftCaching" documents.

| PARAMETER | VALUE | DEFAULT | DESCRIPTION |
|-----------|---|-----------------|---|
| maxsft | <positive< td=""><td>0</td><td>Request cached stream at most how many seconds ago.</td></positive<> | 0 | Request cached stream at most how many seconds ago. |
| | integer> | | |
| tsmode | normal, | normal | Streaming mode: |
| | adaptive | | normal => Full FPS all the time. |
| | | | adaptive => Default send only I-frame for MP4 and H.264, and |
| | | | send 1 FPS for MJPEG. If DI or motion window are triggered, the |
| | | | streaming is changed to send full FPS for 10 seconds. |
| | | | (*Note: this parameter also works on non-timeshift streams.) |
| reftime | mm:ss | The time | Reference time for maxsft and minsft. |
| | | camera receives | (This provides more precise time control to eliminate the |
| | | the request. | inaccuracy due to network latency.) |
| | | | Ex: Request the streaming from 12:20 |
| | | | rtsp://10.0.0.1/live.sdp?maxsft=10&reftime=12:30 |
| forcechk | N/A | N/A | Check if the requested stream enables timeshift, feature and |
| | | | if minsft is achievable. |
| | | | If false, return "415 Unsupported Media Type". |
| minsft | <positive< td=""><td>0</td><td>How many seconds of cached stream client can accept at least.</td></positive<> | 0 | How many seconds of cached stream client can accept at least. |
| | integer> | | (Used by forcechk) |

| | Return Code | Description |
|--|-------------|-------------|
|--|-------------|-------------|

| 400 Bad Request | Request is rejected because some parameter values are illegal. |
|----------------------------|---|
| 415 Unsupported Media Type | Returned, if forcechk appears, when minsft is not achievable or the timeshift |
| | feature of the target stream is not enabled. |

8.21 Remote Focus

Note: This request requires Administrator privileges. **Method:** GET/POST

Syntax:

http://<*servername*>/cgi-bin/admin/remotefocus.cgi?function=<value>[&direction=<value>] [&position=<value>][&steps=<value>][&iris]

| PARAMETER | VALUE | DESCRIPTION |
|-----------|--------------|---|
| function | focus, | Function type |
| | auto, | focus – Move focus motor |
| | scan, | auto – Perform auto focus |
| | stop, | scan – Perform focus scan |
| | positioning, | stop – Stop current operation |
| | irisopen, | positioning – Position the motors |
| | irisenable, | irisopen – Open iris. It will maintain this status until sending irisenable |
| | resetfocus, | cgi. |
| | getstatus | irisenable – Not open iris |
| | | resetfocus – reset focus motor to default valuegetstatus-Information |
| | | of motors, return value as below: |
| | | remote_focus_focus_motor_max: Maximum steps of focus motor |
| | | remote_focus_focus_motor_start: Start point of effective focal length |
| | | remote_focus_focus_motor_end: End point of effective focal length |
| | | remote_focus_focus_motor: Current position of focus motor |
| | | remote_focus_focus_enable: Current function of focus motor |
| | | remote_focus_value_mode: Source of focus value. 0: ISP, 1: Edge. |
| | | remote_focus_iris_open: The current status of iris. 0: irisenable, 1: |
| | | irisopen |
| direction | direct, | Motor's moving direction. |
| | forward, | It works only if function= focus. |
| | backward | |

| position | 0~ <motor_max></motor_max> | Motor's position. | |
|----------|-----------------------------|--|--|
| | | It works only if function=zoom focus and direction=direct. | |
| | | <motor_max> is refer to remote_focus_focus_motor_max which</motor_max> | |
| | | replied from "function=getstatus" | |
| steps | 1 ~ <motor_max></motor_max> | Motor's moving steps. | |
| | | It works only if function = focus and direction = forward backward. | |
| | | <motor_max> is refer to remote_focus_focus_motor_max which</motor_max> | |
| | | replied from "function=getstatus" | |
| iris | N/A | Open iris or not. | |
| | | It works only if function=auto scan. | |

8.22 Export Files

Note: This request requires Administrator privileges.

Method: GET

Syntax:

For daylight saving time configuration file:

http://<servername>/cgi-bin/admin/exportDst.cgi

For language file:

http://<*servername*>/cgi-bin/admin/export_language.cgi?currentlanguage=<value>

| PARAMETER | VALUE | DESCRIPTION | |
|-----------------|-------|---|--|
| currentlanguage | 0~20 | Available language lists. | |
| | | Please refer to: | |
| | | system_info_language_i0 ~ system_info_language_i19. | |

For setting backup file:

http://<*servername*>/cgi-bin/admin/export_backup.cgi?backup

8.23 Upload Files

Note: This request requires Administrator privileges. Method: POST

Syntax:

For daylight saving time configuration file:

http://<servername>/cgi-bin/admin/upload_dst.cgi

Post data:

filename =<file name>\r\n

\r\n

<multipart encoded form data>

For language file:

http://<*servername*>/cgi-bin/admin/upload_lan.cgi

Post data:

filename =<file name>\r\n

\r\n

<multipart encoded form data>

For setting backup file:

http://<servername>/cgi-bin/admin/upload_backup.cgi

Post data:

filename =<file name>\r\n \r\n <multipart encoded form data>

Server will accept the file named <file name> to upload this one to camera.

8.24 Update Lens Configuration

Note: This request requires Administrator privileges. **Method:** GET

Syntax:

For choose selected lens configuration:

http://<servername>/cgi-bin/admin/update_lens.cgi?choose_lens=<value>

For delete selected lens configuration:

http://<servername>/cgi-bin/admin/update_lens.cgi?delete_lens=<value>

| PARAMETER | VALUE | DESCRIPTION |
|-----------|-------|--|
| value | 0~10 | Available lens lists. |
| | | Please refer to: |
| | | lens_default_len0 ~ lens_default_len10 |
| | | lens_user_len0 ~ lens_user_len10 |

Method: POST

Syntax:

For upload user-defined lens configuration:

http://<servername>/cgi-bin/admin/update_lens.cgi?upload_lens

Post data:

upload_lens_profile_input = <file name>\r\n \r\n <multipart encoded form data>

Server will accept the file named <file name> to upload the lens profile to camera.

8.25 Media on demand (capability.localstorage.modnum > 0)

Media on demand allows users to select and receive/watch/listen to metadata/video/audio contents on demand. **Note:** This request requires Viewer access privileges.

Syntax:

rtsp://<servername>/mod.sdp?[&stime=<value>][&etime=<value>][&length =<value>][&loctime =<value>][&file=<value>][&tsmode=<value>]

| PARAMETER | VALUE | DEFAULT | DESCRIPTION |
|-----------|---|---------|---|
| stime | <yyyymmdd_hhmmss.mmm></yyyymmdd_hhmmss.mmm> | N/A | Start time. |
| etime | <yyyymmdd_hhmmss.mmm></yyyymmdd_hhmmss.mmm> | N/A | End time. |
| length | <positive integer=""></positive> | N/A | The length of media of interest. |
| | | | The unit is second. |
| loctime | <boolean></boolean> | 0 | Specify if start/end time is local time format. |
| | | | 1 for local time, 0 for UTC+0 |
| file | <string></string> | N/A | The media file to be played. |
| tsmode | <positive integer=""></positive> | N/A | Timeshift mode, the unit is second. |

Ex.

| stime | etime | length | file | Description |
|-------|-------|--------|------|---|
| v | v | х | x | Play recordings between stime and etime |
| | | | | rtsp://10.10.1.2/mod.sdp?stime=20110312_040400.000&etime= |
| | | | | 2011_0312_040510.000 |
| V | x | ν | x | Play recordings for <code>length</code> seconds which start from <code>stime</code> |
| | | | | rtsp://10.10.1.2/mod.sdp?stime=20110312_040400.000&length |
| | | | | =120 |
| x | V | v | x | Play recordings for length seconds which ends at etime |
| | | | | rtsp://10.10.1.2/mod.sdp?etime=20110312_040400.000&length |
| | | | | =120 |
| x | x | X | V | Play file file |
| | | | | <pre>rtsp://10.10.1.2/mod.sdp?filename=/mnt/link0/</pre> |

8.26 Fisheye local dewarp camera control (capability.fisheye > 0 and capability.fisheyelocaldewarp.c0 > 0, only support in 1R mode)

Note: This request requires camctrl privileges. **Method:** GET/POST

Syntax:

http://<servername>/cgi-bin/camctrl/fdCamCtrl.cgi?channel=<value>&stream=<value>
[&move=<value>] - Move home, up, down, left, right
[&zoom=<value>] - Zoom wide, tele
[[&speedpan=<value>][&speedtilt=<value>][&speedzoom=<value>]] - Set speeds
[&zooming=<value>&zs=<value>] - Zoom without stopping, used for joystick
[&vx=<value>&vy=<value>&vs=<value>] - Shift without stopping, used for joystick
[&x=<value>&y=<value>&videosize=<value>&resolution=<value>&stretch=<value>] - Click on image (Move
the center of image to the coordination (x,y) based on resolution or videosize of 10 mode.)
[&return=<return page>]

Example:

http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&move=right http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&zoom=tele http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&move=top&speedtilt=-1 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&zooming=tele&zs=2 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&vx=5&vy=3&vs=2 http://myserver/cgi-bin/camctrl/fdCamCtrl.cgi?channel=0&stream=0&x=700&y=700&videosize=1920x1920&r esolution=1920x1920&stretch=1

| PARAMETER | VALUE | DESCRIPTION |
|-----------|-----------|--------------------------|
| channel | <0~(n-1)> | Channel of video source. |
| stream | <0~(m-1)> | Stream. |
| move | home | Move to home position. |
| | up | Move up. |
| | down | Move down. |
| | left | Move left. |
| | right | Move right. |

| zoom | wide | Zoom larger view with current speed. |
|------------|---------------------------|---|
| | tele | Zoom further with current speed. |
| speedpan | -5 ~ 5 | Set the pan speed of current command. |
| speedtilt | -5 ~ 5 | Set the tilt speed of current command. |
| speedzoom | -5 ~ 5 | Set the zoom speed of current command. |
| zooming | wide or tele | Zoom without stopping for larger view or further view with zs speed, used for joystick control. |
| zs | 0 ~ 6 | Set the speed of zooming, "0" means stop. |
| vx | -6 ~ 6 | The direction of movement, used for joystick control. |
| vy | -6 ~ 6 | |
| vs | 0 ~ 7 | Set the speed of movement, "0" means stop. |
| х | <integer></integer> | x-coordinate clicked by user. |
| | | It will be the x-coordinate of center after movement. |
| у | <integer></integer> | y-coordinate clicked by user. |
| | | It will be the y-coordinate of center after movement. |
| videosize | <window size=""></window> | The size of plug-in (ActiveX) window in web page of 10 content. |
| resolution | <window size=""></window> | The resolution of streaming of 10 content. |
| stretch | <boolean></boolean> | 0 indicates that it uses resolution (streaming size) as the range of |
| | | the coordinate system. |
| | | 1 indicates that it uses videosize (plug-in size) as the range of the |
| | | coordinate system. |
| return | <return page=""></return> | Redirect to the page < <i>return page</i> > after the parameter is assigned. |
| | | The <i><return page=""></return></i> can be a full URL path or relative path according to |
| | | the current path. If you omit this parameter, it will redirect to an |
| | | empty page. |

<End of document>

Technical Specifications

| Model CC8370-HV Interface 108ase-T/100BaseTX Ethernet (R-4S) "It is highly recommended to use star cables which are compliant with the 3 cables which are compliant with the 3 cables which are compliant with the 3 cables which are compliant with the 3 CPU CPU Multimedia SoC (System-on-Chip) ONVIF Supported, specification available at 0 intelligent Video Flash 128 MB Intelligent Video Intelligent Video RAM 256 MB Video Motion Detection Five-window video motion detection Image Sensor 1/3 Progressive CMOS Alarm and Event Alarm Triggers Video motion detection, manual trigg system boot, recording notification, cald detection Maximum Resolution 2048x1536 Alarm Events Event notification using HTTP, SMTP, FTP, NATP Card File upload via HTTP, SMTP, FTP, NATP Card File upload via HTTP, SMTP, FTP, NATP File upload via HTTP, SMTP, FTP, NATP Card File upload via HTTP, SMTP, FTP, NATP Card File upload via HTTP, SMTP, FTP, NATP Card File upload via HTTP, SMTP, FTP, NATP Card Card Streme and Status indicator Field of View 180° (horizontal) 180° (dagonal) LED Indicator System power and status indicator Image Sensor 180° (dagonal) 180° (dagonal) IEEE 802.3 af POE Class 1 | P/ETL standard. |
|---|--------------------------|
| System Information ONVIF Supported, specification available at a constraint of the specification availabl | |
| Flash 128 M8 RAM 256 M8 Camera Features Video Motion Detection Image Sensor 1/3 Progressive CMOS Maximum Resolution 2048x1536 Maximum Resolution 2048x1536 Frocal Length 1.6 mm Focal Length 1.6 mm Field of View 180° (horizontal) 130' (derizontal) 130' (vertical) | |
| RAM 256 MB Video Motion Detection Five-window video motion detection Camera Features Alarm and Event Image Sensor 1/3 Progressive CMOS Alarm Triggers Video motion detection, manual trigg system boot, recording notification, co detection, audio detection Maximum Resolution 2048x1536 Alarm Events Event notification using HTTP, SMTP, ITP, Cater Coll Icens Type Fixed-focal General Event notification using HTTP, SMTP, FTP, NAS Focal Length 1.6 mm General Itel of View 180' (horizontal) 130' (vertical) 130' (vertical) 130' (vertical) 130' (vertical) 130' (vertical) 130' (vertical) LED Indicator System power and status indicator | |
| Camera Features Alarm and Event Image Sensor 1/3 Progressive CMOS Maximum Resolution 2048x1536 Lens Type Fixed-focal Focal Length 1.6 mm Aperture F2.0 Field of View 180' (horizontal) 130' (vertical) 130' (vertical) | |
| Image Sensor 1/3 Progressive CMOS Alarm Triggers Video motion detection, manual trigg system boot, recording notification, addection, addection, addedection, addedection, addedection, addedection, addedection Maximum Resolution 2048x1536 Alarm Events Event notification using HTTP, SMTP, FTP, NAS Lens Type Fixed-focal General Event notification Card Aperture F2.0 Connectors RJ-45 for Network/PoE connection Field of View 180' (horizontal) 130' (vertical) LED Indicator System power and status indicator | |
| Maximum Resolution 2048x1536 Alarm Events Event notification using HTTP, SMTP, I Card File upload via HTTP, SMTP, I Card File upload via HTTP, SMTP, FTP, NAS Focal Length 1.6 mm General Aperture F2.0 Connectors RJ-45 for Network/PoE connection Field of View 180' (horizontal) 130' (vertical) South Connectors System power and status indicator | er, periodical trigger, |
| Lens Type Fixed-focal Focal Length 1.6 mm Aperture F2.0 Field of View 180' (horizontal) 130' (vertical) 130' (vertical) 130' (vertical) Field of View 180' (horizontal) 130' (vertical) LED Indicator System power and status indicator | amera tampering |
| Focal Length 1.6 mm General Aperture F2.0 Connectors RJ-45 for Network/PoE connection Field of View 180' (horizontal) 130' (vertical) 130' (vertical) 130' (diagonal) LED Indicator System power and status indicator | |
| Aperture F2.0 Connectors RJ-45 for Network/PoE connection Field of View 180' (horizontal) 130' (vertical) 130' (original) LED Indicator System power and status indicator | erver and SD card |
| Field of View 180° (horizontal) LED Indicator System power and status indicator 130° (vertical) 180° (diagonal) EXEMPTION EXEMPTION EXEMPTION | |
| 130' (vertical) 180' (diagonal) | |
| Power Input IEEE 802.3af PoE Class 1 | |
| Shutter Time 1/5 sec. to 1/32,000 sec. | |
| WDR Technology WDR Pro Poil Max. 4.9 W | |
| Dimensions 115 (D) x 65 (W) x 59 (H) mm Minimum Illumination 0.05 Lux @ F2.0 (Color) mm | |
| Pan/tilt/zoom Functionalities ePTZ: 4x dioital zoom lE pluq-in Casing IP66, IK10 | |
| | |
| On-board Storage MicroSD/SDHC/SDXC card slot Safety Certifications CE, LVD, FCC Class B, VCCI, C-Tick, UL Video Operating Temperature Starting Temperature Starting Temperature | |
| Working Temperature: -10°C ~ 50°C (1- | ~ 122 F) \$'F~ 122'F) |
| Compression H.264 & MJPEG Warranty 24 months | |
| Maximum Frame Rate 30fps @ 2048x1536 System Requirements Maximum Streams 3 simultaneous streams System Requirements | |
| Maximum Sureams 3 simulateous sureams Operating System Microsoft Windows 8/7/Vista/XP/200 S/N Ratio 58.8 dB |) |
| Dynamic Range 100 dB Web Browser Mozilla Firefox 7-10 (streaming only) Internet Explorer 7/8/9/10 | |
| Video Streaming Adjustable resolution, quality and bitrate Other Players VLC: 1.1.11 or above Quicktime: 7 or above | |
| Image Settings Adjustable Image size, quality and bit rate; Time stamp, Included Accessories | |
| text overlay, flip & mirror & rotate; Configurable brightness, contrast, saturates, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings | d, mounting bracket, |
| Scheduled profile settings screw pack | |
| Audio Capability Audio input Dimensions | |
| Compression G.711, G.726 | |
| Interface Built-In Microphone 115 mm 59 mm | |
| Effective Range 5 meters | |
| Network | |
| Users Live viewing for up to 10 clients | 65 mm |
| Protocols IP-4, IP-6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, ICMP, SMTTP, FTP, DHCP, NTTP, DHS, DDNS, PPPPe, CoS, QoS, SNMP, 802, IX, UDP, ICMP | |

All specifications are subject to change without notice. Copyright © VIVOTEK INC. All rights reserved.



VIVOTEK INC. 6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, 235, Taiwan, R.O.C. T: +886-282455282 F: +886-2-82455532 E: sales@vivotek.com

VIVOTEK USA 2050 Ringwood Avenue, San Jose, CA 95131 T: 408-773-8686 F: 408-773-8298 E: salesusa@vivotek.com

VIVOTEK Europe Randstad 22-133, 1316BW Almere, The Netherlands T: +31(0)36-5298-434 E: saleseurope@vivotek.com

VIVOTEK India 602, Best sky Tower, Plot No. F-5, Netaji Subhash Place, Pitam Pura, Delhi-110 034 T: 491-11-45137465 E: salesindia@vivotek.com

Ver. 7

Technology License Notice

AMR-NB Standard

THIS PRODUCT IS LICENSED UNDER THE AMR-NB STANDARD PATENT LICENSE AGREEMENT. WITH RESPECT TO THE USE OF THIS PRODUCT, THE FOLLOWING LICENSORS' PATENTS MAY APPLY:

TELEFONAKIEBOLAGET ERICSSON AB: US PAT. 6192335; 6275798; 6029125; 6424938; 6058359. NOKIA CORPORATION: US PAT. 5946651; 6199035. VOICEAGE CORPORATION: AT PAT. 0516621; BE PAT. 0516621; CA PAT. 2010830; CH PAT. 0516621; DE PAT. 0516621; DK PAT. 0516621; ES PAT. 0516621; FR PAT. 0516621; GB PAT. 0516621; GR PAT. 0516621; IT PAT. 0516621; LI PAT. 0516621; LU PAT. 0516621; NL PAT. 0516621; SE PAT 0516621; US PAT 5444816; AT PAT. 819303/AT E 198805T1; AU PAT. 697256; BE PAT. 819303; BR PAT. 9604838-7; CA PAT. 2216315; CH PAT. 819303; CN PAT. ZL96193827.7; DE PAT. 819303/DE69611607T2; DK PAT. 819303; ES PAT. 819303; EP PAT. 819303; FR PAT. 819303; GB PAT. 819303; IT PAT. 819303; JP PAT. APP. 8-529817; NL PAT. 819303; SE PAT. 819303; US PAT. 5664053. THE LIST MAY BE UPDATED FROM TIME TO TIME BY LICENSORS AND A CURRENT VERSION OF WHICH IS AVAILABLE ON LICENSOR'S WEBSITE AT HTTP://WWW.VOICEAGE.COM.

Electromagnetic Compatibility (EMC)

FCC Statement

This device compiles with FCC Rules Part 15. Operation is subject to the following two conditions.

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a partial installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Shielded interface cables must be used in order to comply with emission limits.

CE Mark Warning

This is a Class B product. In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

VCCI Warning

この装置は、情報処理装置等電波障害自主規制協議会(VCCI)の基準にづくクラスB情報技術装置 です。この装置は、家庭環境で使用することを目的としていますが、この装置がラジオやテレビジョン 受信機に近接して使用されると、受信障害を引き起こすことがあります。

取扱説明書に従って正しい取り扱いをして下さい

Liability

VIVOTEK Inc. cannot be held responsible for any technical or typographical errors and reserves the right to make changes to the product and manuals without prior notice. VIVOTEK Inc. makes no warranty of any kind with regard to the material contained within this document, including, but not limited to, the implied warranties of merchantability and fitness for any particular purpose.